1

MicroD

National Library
of Canada

Bibliothèque nationale
du Canada

Canadian Theses Service

Service des thèses canadiennes

Ottawa, Canada
K1A 0N4

NOTICE

The quality of this microform is heavily dependent upon the quality of the original thesis submitted for microfilming. Every effort has been made to ensure the highest quality of reproduction possible.

If pages are missing, contact the university which granted the degree.

Some pages may have indistinct print especially if the original pages were typed with a poor typewriter ribbon or if the university sent us an inferior photocopy.

Previously copyrighted materials (journal articles, published tests, etc.) are not filmed.

Reproduction in full or in part of this microform is governed by the Canadian Copyright Act, R.S.C. 1970, c. C-30

AVIS

La qualité de cette microforme dépend grandement de la qualité de la thèse soumise au microfilmage. Nous avons tout fait pour assurer une qualité supérieure de reproduction.

S'il manque des pages, veuillez communiquer avec l'université qui a conféré le grade.

La qualité d'impression de certaines pages peut laisser à désirer, surtout si les pages originales ont été dactylographiées à l'aide d'un ruban usé ou si l'université nous a fait parvenir une photocopie de qualité inférieure.

Les documents qui font déjà l'objet d'un droit d'auteur (articles de revue, tests publiés, etc.) ne sont pas microfilmés.

La reproduction, même partielle, de cette microforme est soumise à la Loi canadienne sur le droit d'auteur, SRC 1970, c. C-30.

ANALYSIS OF WINTER ICE USING DIGITAL STAR-1 SAR IMAGERY
OF MOULD BAY, N.W.T.

© M.A. Cameron

December 1986

Copyright 1986, M.A. Cameron

Carleton University

Permission has been granted to the National Library of Canada to microfilm this thesis and to lend or sell copies of the film.

The author (copyright owner) has reserved other publication rights, and neither the thesis nor extensive extracts from it may be printed or otherwise reproduced without his/her written permission.

L'autorisation a été accordée à la Bibliothèque nationale du Canada de microfilmer cette thèse et de prêter ou de vendre des exemplaires du film.

L'auteur (titulaire du droit d'auteur) se réserve les autres droits de publication; ni la thèse ni de longs extraits de celle-ci ne doivent être imprimés ou autrement reproduits sans son autorisation écrite.

ISBN 0-315-46239-6

Carleton University
Ottawa, Canada K1S 5B6

Thesis contains coloured
photographs & explanatory tables
which when microfilmed lose their
significance. The hardcopy of the
thesis is available upon request
from Carleton University Library.

The undersigned recommend to the Faculty of Graduate
Studies and Research acceptance of the thesis

ANALYSIS OF WINTER ICE USING DIGITAL STAR-1 SAR IMAGERY
OF MOULD BAY, N.W.T.

submitted by Murray Allan Cameron
B.A. Honours Carleton University
in partial fulfillment of the requirements for
the degree of Master of Arts.

THESIS SUPERVISOR

CHAIRMAN, DEPARTMENT OF GEOGRAPHY

Carleton University

ABSTRACT

On March 3rd 1984, Intera Technologies Limited flew their STAR-1 Synthetic Aperture Radar over Mould Bay N.W.T. in support of the joint Atmospheric Environment/ National Research Council experiments conducted between mid-March and April. Part of the experimental objectives was to conduct one of the first detailed field validations in support of the STAR-1 imagery. The field work was followed by an analysis of the digital radar data generated from the STAR-1 flight. This work was carried out using a DIPIX image analysis system located at Environment Canada's Ice Centre in Ottawa. The sizes of ice targets and the separation distances between them were determined on a pixel-by-pixel basis and standard analysis filters were applied to the data to determine enhancement value. The digital data was also degraded to resolutions simulating other operational systems to determine relative loss of ice feature detail.

(iii)

ACKNOWLEDGEMENTS

I would like to take this opportunity to extend my thanks to Dr. R. O. Ramseier of Ice, Research and Development, Atmospheric Environment Service, Environment Canada. Dr. Ramseier provided me with the opportunity to experience the Canadian Arctic, which then led to the development of this thesis. His encouragement and criticism along with those of Michael Fox, my faculty advisor, are highly valued and appreciated.

I would also like to thank the following people who also assisted in the completion of this thesis; Mr. M. Kirby of Intera Technologies Limited who provided the digital SAR data; Mr. D. Lapp of Norland Science and Engineering Limited who provided the field observations; Mr. J. Faulkingham, Ice Centre, AES Ottawa who allowed me unlimited access to the Centre's DIPIX Image Analysis System. I also wish to acknowledge B. Ramsay, S. Thompson and D. Henderson of Ice Centre, AES Ottawa who all provided assistance during the digital analysis; and Karen Burton and Laura Darling who both assisted me in typing and correcting the manuscript. Finally, I cannot help but wonder what my family and friends are going to talk about in the future, since their favorite topic of discussion during the last few months has been the status of this thesis.

M. Cameron
Ottawa, December 1986

TABLE OF/CONTENTS

	<u>PAGE</u>
ABSTRACT	iii
ACKNOWLEDGEMENTS	iv
TABLE OF CONTENTS	v
LIST OF TABLES	vii
LIST OF FIGURES	viii
LIST OF PLATES	x
CHAPTER	
0. INTRODUCTION	1
0.1 Background	3
0.2 Thesis Objectives	5
1. SEA-ICE AS A MATERIAL	7
1.1 Growth of Sea-Ice	9
1.2 Crystal Structure	17
1.3 Salinity	20
2. STUDY AREA AND DATA COLLECTION	25
2.1 Description of Study Area	25
2.1.1 Ice Conditions	26
2.2 Field Work	29
2.2.1 Field Data Collection	31
2.2.2 Physical Properties of Sea-Ice	34
2.2.3 Mapping of Ice Features	38
2.3 Remote Sensing Data	38
2.3.1 Active Microwave	41
2.3.1.1 Variables Affecting Radar Return	50
2.3.1.2 Backscatter Coefficient	56
2.3.1.3 Scatterometry	57
2.3.2 STAR-1 SAR System	62
3. INVESTIGATIVE TECHNIQUES	65
3.1 Analysis System	65
3.2 Preliminary Work	67
3.2.1 Orthogonal Passes	67
3.2.2 Image Registration	69
3.2.3 Selection of Subscenes	70

TABLE OF CONTENTS (CONT'D)

	<u>PAGE</u>
3.3 Image Analysis Procedures	72
3.3.1 Enhancements	75
3.3.1.1 Local Operations	75
3.3.1.2 Point Operations	80
3.3.2 Classifications	83
4. RESULTS OF ANALYSIS	85
4.1 Analysis of Results from Procedures ..	88
4.1.1 Local Operation Enhancements ..	89
4.1.1.1 Filters	89
4.1.1.2 Convolution Filtering ..	92
4.1.1.3 Texture Measure Filtering	96
4.1.2 Point Operations	98
4.1.2.1 Stretches	98
4.1.2.2 Arithmetic Functions ..	106
4.1.3 Classifications	109
4.1.3.1 Unsupervised	109
4.1.3.2 Density Slicing	111
4.2 Verification of Mapped Ice Features ..	113
4.2.1 Point Targets	118
4.2.2 Floe Targets	123
4.2.3 Triangulation	127
5. CONCLUSIONS	131
5.1 Summary	131
5.2 Limitations	132
5.3 Evaluation	132
5.4 Further Work	136
APPENDIX A: DIPIX IMAGE ANALYSIS SYSTEM	137
BIBLIOGRAPHY	142

LIST OF TABLES

<u>TABLE</u>		<u>PAGE</u>
1.1	Sea-Ice Development and Thickness Range	16
2.1	Ice Surface and Physical Property Data Collected at Target Stations	35
2.2	STAR-1 SAR Specifications	63
4.1	Results from Image Analysis Procedures	90
4.2	Comparison of SAR Imageries with Topographic map Measurements	117
4.3	Point Target Characteristics	119
4.4	Comparison of Target Dimensions	122
4.5	Characteristics of Targets within KA Floe	126
4.6	Comparison of Target Separation Distances	128

LIST OF FIGURES

<u>FIGURE</u>		<u>PAGE</u>
0-1	Location of Mould Bay Study Area in Arctic Canada	4
1-1	Structure of Ice	10
1-2	Growth Sequence of an Ice Crystal	11
1-3	Orientation of the C-axes of Sea-Ice Crystals from Different Depths Below the Surface of an Ice Sheet	18
1-4	Histograms Showing the Relative Percentage of Different C-axis Orientations	19
1-5	First-year Ice Salinity Profiles from Eclipse Sound N.W.T., 1977-78	22
1-6	Multi-year Ice Salinity Profiles	24
2-1	Aging Process of Sea-Ice at Mould Bay, N.W.T, October 1981 to June 84	27
2-2	Mould Bay Sampling Sites 1984	32
2-3	The Electromagnetic Spectrum	39
2-4	Real Aperture SLAR Geometry and Resolved Surface Area	42
2-5	Illustration of Advantage of Synthetic Aperture in a Space Application	43
2-6	Real Aperture SLAR Technique	47
2-7	Band Designation of the Radio Spectrum and the Letter Designation of the Microwave Portion	51
2-8	Radar Displacement of Elevated Objects	53

LIST OF FIGURES (Cont'd)

<u>FIGURE</u>		<u>PAGE</u>
2-9	Range Resolution Deterioration in SLAR	55
2-10	Theoretical Backscatter for Multi-year and First-year Ice	60
2-11	Theoretical Angular Variations of Backscatter for Multi-year and First-year Ice	61
3-1	Orientation of SAR Flight Paths Flown Over Mould Bay on March 3, 1984	68
3-2	Subscenes Created for DIPIX Image Analysis	71
3-3	Digital Image Representation	73
3-4	Principle of Contrast Stretch Enhancement	81
4-1	Primary Ordering of Image Elements	86
4-2	Histogram From Plate 4-10	102
4-3	Histogram Resulting from Piecewise Linear Stretch Shown in Plate 4-11	103
4-4	Histogram Resulting from Histogram Equalized Stretch Shown in Plate 4-12 ..	103
4-5	Histogram Resulting from Logarithmic Transformation	104
4-6	Histogram Resulting from Exponential Transformation	104
4-7	Histogram Showing Density Slices Chosen for Plate 4-17	114
4-8	Location of Control Points for Distortion Calculation	116

LIST OF PLATES

<u>PLATE</u>		<u>PAGE</u>
1-1	Grease Ice in Lancaster Sound, September 1984	12
1-2	Formation of Pancake Ice in Lancaster Sound, October 1984	14
1-3	Pancake Ice in Lancaster Sound, October 1984	15
1-4	Vertical Thin Section of Sea-Ice	21
2-1	Intera STAR-1 SAR Image of Mould Bay, March 3, 1984. East/West Pass	28
2-2	Enlargement of Lake Sites from the East/West Image Pass	37
2-3	AES SLAR Image of Mould Bay, 1984	46
3-1	AES Ice Centre, DIPIX Workstation	66
4-1	Intera STAR-1 SAR Image of Mould Bay, March 3, 1984. North/South Pass	87
4-2	Raw SAR Data, North/South Pass	91
4-3	Median Filtered SAR Data, North/South Pass	91
4-4	6m Median Filtered SAR Data, North/South Pass	93
4-5	18m Median Filtered SAR Data, North/South Pass	94
4-6	30m Median Filtered SAR Data, North/South Pass	94
4-7	Homogeneity Texture Filter, East/West Pass	97
4-8	Contrast Texture Filter, East/West Pass	97
4-9	False Colour Combination of Contrast Texture Filter with Original SAR Data, East/West Pass	99

LIST OF PLATES

<u>PLATE</u>		<u>PAGE</u>
4-10	Subsection of Original East/West SAR Image Showing KA Floe	101
4-11	Results of Linear Stretch Applied to Plate 4-10	105
4-12	Results of Histogram Equalized Stretch Applied to Plate 4-10	107
4-13	Ratio of East/West to North/South Passes	108
4-14	Subtraction of East/West and North/South Passes	108
4-15	Unsupervised Classification of the North/South Image Pass	110
4-16	Median Filtered SAR Data, North/South Pass	112
4-17	Resulting Density Slice From Plate 4-16	112
4-18	Central Rubble Pile from Target J2	121
4-19	Ice Feature Located on Target J4	121
4-20	Flat Profile of Ridge on KA Floe	125
4-21	Large Ridge Target on Norland Floe	125

CHAPTER 0

INTRODUCTION

During the past 10 years, the search for hydrocarbons in the Beaufort Sea and eastern Arctic, along with navigation in Canada's northern waterways, has increased to the point where methods to extend operating seasons are being vigorously pursued. In operational terms, this means that detailed, near-real-time ice information is needed during the entire season while ships operate in ice-frequented waters. As activities in arctic waterways increase, the demand for timely information on sea-ice increases so that efficient transit of the area travelled can be achieved. In order to attain this, high resolution data-gathering systems that can operate regardless of light or weather conditions are needed. Early studies indicated the usefulness of side-looking airborne radar (SLAR) as a tool for mapping and identifying sea-ice (Anderson, 1966; Johnson and Farmer, 1971; Page and Ramseier, 1975). Remote sensing systems using visible and infrared energy have been utilized in the analysis and monitoring of sea-ice. Imaging radars have proven to be the most useful

in terms of operational support of Arctic activities (Sneyd and Luce, 1984). However, recent studies have shown higher resolution synthetic aperture radar (SAR) to be highly reliable for sea-ice reconnaissance (Gray et al., 1982; Rossiter et al., 1984; Nicols et al., 1984). High resolution passive microwave systems are also being developed for ice reconnaissance purposes (Hollinger et al., 1984).

Imaging radars presently used in an operational environment include both SARs and SLARs. The SLAR system is the mainstay of the Atmospheric Environment Service (AES) Ice Reconnaissance Branch which provides ice information services for the whole of Canada's ice-frequented waterways and has been used extensively in the mapping and monitoring of sea-ice in Canada's arctic. However, the system's resolution, in the order of 30 metres, has prevented acquisition of images with fine detail. To this end, SARs are becoming the preferred imaging system for detailed ice reconnaissance requirements given their synthesized resolutions of between 6 and 12 m.

In November 1983, Intera Technologies' Sea Ice and Terrain Assessment Radar (STAR-1) began operational

support of Dome Petroleum's activities in the Beaufort Sea. It has since been demonstrated that this system is able to provide detailed ice information for drilling activities and marine transportation (Nichols et al., 1984). Even as early as 1979 the usefulness of SAR imagery in helping to extend the drilling season of a Dome Petroleum subsidiary operating in the Beaufort Sea had been demonstrated (McAvoy et al., 1985).

0.1 Background

This thesis analyses Intra STAR-1 SAR data collected in support of the joint Atmospheric Environment Service National Research Council (NRC) sea-ice experiments conducted between mid-March and mid-April 1984. Data consist of digital SAR data, SLAR imagery and field observations collected at the Mould Bay, Prince Patrick Island experiment site (76 14' N, 119 21' W), shown in Figure 0-1.

The thesis forms a distinct and separate portion of a study carried out for the Ice Research and Development Division, Atmospheric Environment Service,

FIGURE 0-1
LOCATION OF MOULD BAY STUDY AREA
IN ARCTIC CANADA

Environment Canada. This study, the first official field verification of the STAR-1 SAR imagery, was concerned with an investigation of ice types at Mould Bay and Isachsen N.W.T.

0.2 Thesis Objectives

The main objective of this thesis is to analyse, using digital analysis techniques, the STAR-1 SAR data and to compare visually the results to those obtained in the field. The work utilizes the DIPIX image analysis system located at the AES Ice Centre, Ottawa. A secondary objective is to investigate the application of system software and digital analysis techniques to the STAR-1 SAR data. The thesis work was conducted by the execution of the following specific tasks:

1. application of available DIPIX software to achieve optimal enhancement of the SAR data.
2. determine the size and distance between targets on pixel-by-pixel basis for comparison with field-measured distances.
3. degrade imagery resolution to approach that of operational radars to determine relative loss of detail.

The purpose of these procedures was to determine the utility of the available DIPIX software in enhancing the ice features present on the imagery. Once the first task was completed the best enhancement could be utilized during the comparison of target measurements, signatures and detail present on the imagery. All measurements taken from the digital data were determined on a picture element or pixel basis described in Section 3.3. This study presents an application of remote sensing to the field of sea-ice studies which is of practical value to Arctic marine transportation and oil/energy development.

CHAPTER 1

SEA-ICE AS A MATERIAL

Arctic sea-ice occupies five percent of the earth's oceans during the northern winter months (Ramseier, 1985), posing an operational deterrent and hazard to activities in ice-frequented waters. As shown below, the Arctic winter ice cover is one and a half times greater than the continental expanse of Canada.

ARCTIC ICE COVERAGE VS WORLD'S OCEANS AND CANADA'S AREAL EXPANSE

ARCTIC ICE

WINTER	$15.1 \times 10^6 \text{ km}^2$
SUMMER	$7.0 \times 10^6 \text{ km}^2$
DIFFERENCE	$8.1 \times 10^6 \text{ km}^2$

WORLD'S OCEANS

TOTAL OCEANS	$361 \times 10^6 \text{ km}^2$
--------------	--------------------------------

CANADA

TOTAL AREA	$10 \times 10^6 \text{ km}^2$
------------	-------------------------------

(after Ramseier, 1985)

The sea-ice cover in the Arctic consists of a variety of ice types having different physical and mechanical

properties (Weeks and Ackley, 1982). Physical properties refer to those variables which characterize ice growth, while mechanical properties refer to the behaviour of ice under various loading conditions. The thicker, stronger types, including old ice, which have survived a few melt seasons, and glacial ice, pose the most dangerous threats to navigation in Arctic waters. It is the age, thickness, and type of ice that restricts the movement of traffic through the Arctic as laid out in the Arctic Shipping Pollution Prevention Regulations of Transport Canada (1970a; 1970b).

2 The term "sea-ice" encompasses all types of ice formed from the freezing of seawater, with type being determined by the environmental conditions under which it forms. For a detailed description of the internal structure and bulk properties of sea-ice the reader is referred to Doronin and Kheisin (1977) and Weeks and Ackley (1982), but a general understanding of these parameters is helpful. The next section will discuss the growth of sea-ice along with techniques used in sea-ice research as they affect the interpretation of remote sensing imagery.

1.1 Growth of Sea-Ice

Initially the freezing of seawater parallels that of fresh water with the first crystals growing in the a-axis or basal plane as shown in Figure 1-1. Once the initial grain is formed it grows into a dendritic star illustrated in Figure 1-2. During this process the ability of the crystal to dissipate heat is increased and the disc-to-star growth occurs rapidly (Weeks and Ackley, 1982). As the crystals continue to grow on the water surface they overlap and freeze together forming an ice "skim". Under ideal calm conditions the crystals would be aligned in one direction on the sea surface. However, in open water, wave or wind action occurs resulting in turbulence during ice formation. This turbulence sometimes causes the ice crystals to be stirred up to the depth of several metres (Martin and Kaufman, 1981). Ice crystals called frazil, formed in supercooled water, coagulate to form ice termed grease ice. As shown in Plate 1-1, grease ice is characterized by its dull appearance. Grease ice accumulations can reach a depth of 1m under turbulent conditions compared to 0.01 to 0.1m when calm conditions are experienced (Weeks and Ackley, 1982). This initial layer is often referred to as primary

Figure 1-1 - Structure of Ice

(Weeks and Ackley, .1982).

Figure 1-2 - Growth Sequence of an Ice Crystal

(Weeks and Ackley, 1982)

Plate 1-1 - Ground view of Limestone Quarry, September 1964.

ice. Generally speaking, all first-year ice in navigable waters has a consolidated frazil ice layer at the top of the ice cover.

Pancake ice shown in Plate 1-2 forms from frazil ice during periods of wave action. This wave action causes the frazil crystals to contact each other repeatedly, thereby forming the pancake shape. Once a complete layer of joined pancakes forms (Plate 1-3) sheet ice begins to grow beneath the pancake layer. From this point on, various classes of first-year ice listed in Table 1.1 are determined by the thickness of the ice as it continues to grow.

The next stage in sea-ice development is the transition to old ice which occurs once an ice sheet has survived one or more summer melts. Second-year ice develops after one summer's melt while multi-year ice is the term used for ice having survived two or more melt seasons. The differences between old ice and other ice classes include its smooth hummocky surface, crystalline structure, and salinity profile.

Figure 1-4 - Photograph of the interior of the instrument shown in Figure 1-3.

Plate 1-3 - Pancake Ice in Lancaster Sound, October 1994.

TABLE 1.1

SEA-ICE DEVELOPMENT AND THICKNESS RANGE

<u>ELEMENT</u>	<u>THICKNESS RANGE</u>
New ice	---
Nilas, ice rind	10 cm
Young ice	10-30 cm
Grey ice	10-15 cm
Grey white ice	15-30 cm
First-year ice	30 cm
Thin first-year ice	30-70 cm
Medium first-year ice	70-120 cm
Thick first-year ice	over 120 cm
Old ice	2m or more

(adapted from MANICE, 1980)

1.2 Crystal Structure

Once initial downward growth begins in the region termed secondary ice, crystals oriented most favorably with the horizontal c-axis begin to grow and cut off those crystals not aligned in the preferred growth direction. This region of orientation, termed the transition layer, is usually completed 5-10cm into the region of secondary growth. Figures 1-3 and 1-4 illustrate the elimination of the majority of the vertically-oriented crystals by the 5cm level in the ice sheet. The Schmidt diagrams presented in Figure 1-3 graphically represent the spatial orientation of the optical axes of the ice crystals. Once the axes have assumed a non-random clustering a preferred orientation of the ice crystals has been attained (Ramseier, 1983).

The region of secondary ice also includes the columnar zone, so called because of its similarity to the columnar zone in metal ingots (Weeks and Ackley, 1982). Since the majority of the changes in crystal orientation occur in the thin upper transition layer within the columnar zone, the changes occurring below the transition layer are more subtle. The most evident change is the

0.0-0.5 CM 17 MAX

0.5-1.0 CM 9 MAX

1.0-1.5 CM 6 MAX

2.5-3.0 CM 8 MAX

3.5-4.0 CM 10 MAX

5.0-5.5 CM 13 MAX

10.0-10.5 CM 13 MAX

Figure 1-3 - Orientations of the C-axes of Sea-Ice Crystals from Different Depths Below the Surface of an Ice Sheet

(Weeks and Ackley, 1982)

Figure 1-4 - Histograms Showing the Relative Percentage of Different C-axis Orientations

(Weeks and Ackley, 1982)

increase in grain size as a function of depth. Plate 1-4 illustrates that after the transition zone has completed its selective ordering, the size of the grains in the columnar zone increases with depth. The columnar zone, or secondary ice layer, also depicts the layering inherent in old ice forms, and can provide some clues as to the environmental influences that occurred at each layer representing one year of growth (Bjerkelund et al., 1984; Weeks and Ackley, 1982).

1.3 Salinity

Salinity profiles of first-year and old ice vary markedly. Studies have shown that for first-year ice the salinity profile shows high salinity content in the upper and lower-most layers, resulting in profiles having a distinctive C-shape (Nakamo and Sinha, 1981; Lopp et al., 1984; Bjerkelund et al., 1984). Figure 1-5 illustrates first-year ice profiles collected at Eclipse Sound, N.W.T., showing a decrease in salinity during the period after initial freezing. Salinity values stabilize at this point and decrease slowly throughout the growth season (Nakamo and Sinha, 1981). The profiles for old ice show

21

31

Figure 1-5 - First-year Ice Salinity Profiles
(Nakawo and Sinha, 1981).

near zero salinity in the upper ice layer with a gradual increase towards the bottom. Figure 1-6 illustrates a salinity profile for old ice. The lower values when compared to first-year ice are due to the migration of meltwater through the brine channels during the melt season and the metamorphosis of the ice crystals over time. Salinity profiles are useful in determining the type and age of ice as well as the conditions of growth and environmental effects experienced during ice formation (Nakamo and Sinha, 1981; Weeks and Ackley, 1982; Bjerkelund et al., 1985).

This introductory chapter has listed the objectives of the research and described the growth and formation of sea-ice. The next chapter describes the area investigated, the instrument used, and the interaction between microwave pulses and ice.

Figure 1-6 - Multi-year Ice Salinity Profile
(Weeks and Ackley, 1982)

CHAPTER 2

STUDY AREA AND DATA COLLECTION

The data presented in this thesis were collected during March and April 1984 at Mould Bay, N.W.T. The experiment represented the fourth in a series of sea-ice experiments based at Mould Bay to investigate the aging of sea-ice in terms of its physical and mechanical properties, including the active and passive microwave signatures of the ice.

2.1 Description of Study Area

The Mould Bay area provides a unique opportunity for field work because of the presence of an AES high Arctic weather station which operates as base camp. Logistically this factor is invaluable since the main camp is ready for occupation and the study site, being a short distance away, is easily accessible. The Mould Bay site also offers the opportunity to study, at their various stages of growth, a diversity of ice types characteristic of high Arctic coastal environments.

2.1.1 Ice Conditions

The series of sea-ice experiments at Mould Bay was initiated in 1981 when a new ice cover was documented to have formed (Digby, 1982). The following yearly experiments were thus dependent upon the ice cover remaining in the bay during each successive melt season. This situation occurred during 1982 and provided the opportunity to study documented second-year ice during spring 1983. However during August 1983 the ice in Mould Bay was forced out of the Bay due to strong winds, thereby removing the possibility of studying a true third-year ice cover the following year. Figure 2-1 illustrates the formation process occurring over part of the life of the experiments conducted at Mould Bay. The melting of the ice in the summer of 1983 almost resulted in the cancellation of the 1984 experiment. However, prior to the ice reforming, a matrix of old ice floes moved into the southern part of the bay. The presence of this ice provided the opportunity to study the properties of old ice and the 1984 experiment took place.

Plate 2-1 is a SAR image showing ice conditions as they existed during the 1984 experiment. This particular

Figure 2-1 - Aging Process of Sea-Ice at Mould Bay, N.W.T., October 1981 to June 1984

(adapted from Bjerkelund et al., 1985)

Plate 2-1 - INTERA STAR-1 SAR Image of Mould Bay,
March 3, 1984. East/West Pass.

image was taken along the east-west pass flown by the Intera STAR-1 SAR. The bay at this time was totally ice-covered with a layer of snow varying in thickness from one to seven centimetres (Bjerkelund et al., 1984). To the south of the bay there were several large old ice floes set in a matrix of first-year ice. The old ice stands out from the first-year ice due to its much brighter signature. The remainder of the bay to the north consisted of a predominant first-year ice cover in dark tones with a few old ice, ridge, and rubble features standing out as lighter tones.

2.2 Field Work

The 1984 experiment and field data collection exercises were conducted at Mould Bay from March 15 to April 16. The general objective of the experiment was to continue the documentation of the physical properties of the ice cover while the more specific objective of the field data collection program was to acquire ice surface data for the evaluation of the Intera STAR-1 SAR imagery (Bjerkelund et al., 1984). The experiment had two objectives as did the field data collection program.

The experiment program objectives as described in Bjerkelund et al. (1984) included:

1. establishing a barrel line across the bay with 10 stations and measuring the ice physical properties and structure.
2. conducting a detailed field study of the physical properties and structure of selected old ice floes.

As in previous years an east-west data collection line was established in 1984 with 10 stations at which ice physical properties were measured. Physical property measurements were also conducted on specific old ice floes scattered throughout the bay. These floes were selected based on their identification on the Intera STAR-1 SAR imagery.

The objectives of the field data collection program (Lapp and Bjerkelund, 1984) were also two-fold:

1. to determine the minimum size/height of targets which were detected by the radar and to observe their relationship to the surrounding ice cover.
2. to acquire visual observations and photography of specific areas on the imagery containing different signatures.

Targets were selected for field analysis by choosing from a wide range of signatures from the STAR-1 SAR imagery. Image signatures were compared with field observations and detailed field measurements of the chosen ice targets were made. Analysis, subsequent to the field exercise, compared field and image measurements with mapped distances. Despite a time difference between the image date (March 3) and collection of field data (March 15 to April 16) the two data sets are comparable because the ice cover remained stable throughout the period (March 3 to April 16).

2.2.1 Field Data Collection

Several floes and point targets for detailed field analysis were selected from the SAR imagery both at its original scale and at two times enlargement. Four fresh water lakes were also investigated and subsequent analysis has been carried out by R. Williams (1985).

From all the original imagery, enlargements were made to 5X and 10X to aid detailed analysis of specific targets. Figure 2-2 shows the location of sites chosen for field observation. The following variables were

measured at these sites:

- target diameter
- separation distances between targets
- specific distinguishing features (ie. rubble and ridges)
- physical ice properties

The first two measurements were used to determine the geometric fidelity of the imagery and formed the basis for comparing those determined by both manual and digital methods. The final two variables were used to assess the morphology of ice targets as depicted on the SAR imagery.

The STAR-1 imagery made available to the experiment team proved invaluable to the efficient operation of the field observation program. The high resolution allowed the identification of small-scale ice features such as a one metre ridge evident on the east-west image and point targets less than 6m in width, as well as larger floes present in the southern portion of the bay. The imagery documented discontinuities in some sites such as a dark signature on one large old ice floe which was subsequently identified as a meltpond (Lapp and Bjerkelund, 1984). Old ice floes surrounded by first-year

ice and covered by snow could be located with the use of the SAR imagery even though these targets were not visible to the naked eye. The imagery also aided on-ice navigation for all experiment activities.

Field data collection involved measuring distances using a 50m survey tape supported by odometer readings from the bombardier used during on-ice travel. Triangulation measurements were also taken for specific targets selected for analysis. Table 2.1 lists the targets analysed with the corresponding data collected for each site.

2.2.2 Physical Properties of Sea-Ice

On an image of Mould Bay that has been used in the present work (Plate 2-1), ice types range from first-year and old sea-ice to the fresh water ice present in the lakes imaged on Prince Patrick Island. Table 2.1 lists the physical properties and ice surface data collected at each sample site. As shown, physical property data were collected at the old ice and lake sites along with selected point targets. Ice cores were taken

TABLE 2.1

ICE SURFACE AND PHYSICAL PROPERTY DATA COLLECTED AT TARGET STATIONS

TARGETS	ICE TYPE	SALINITY	DENSITY	SURFACE ROUGHNESS	CRYSTAL ORIENTATION	ICE TEMP.	ICE STRUCTURE	ICE THICKNESS	SNOW DEPTH	ICE FREEBOARD	FEATURE SIZE/HEIGHT	FEATURE SEPARATIONS	35 mm PHOTOGRAPHY
4-peg Floe	Old ice	X	-	-	-	X	X	X	X	X	X	X	X
Coast Guard Floe	Old ice	X	-	-	-	-	X	X	X	X	X	X	X
KA Floe	Old ice	X	X	-	-	X	X	X	X	X	X	X	X
Norland Floe	Old ice	X	X	-	-	X	X	X	X	X	X	X	X
Nirmals Floe	Old ice	X	-	-	-	-	X	X	X	X	-	-	X
Barrel Line	First-year	X	Some	-	Some	Some	Some	X	X	X	-	-	X
Barrel Floe	-	-	-	-	-	-	-	-	X	-	X	X	X
Speck Floe	-	-	-	-	-	-	-	-	X	-	X	X	X
A-Floe	-	-	-	-	-	-	-	-	X	-	-	-	-
Dot Floe	-	-	-	-	-	-	-	-	X	-	-	-	-
RT Targets	-	-	-	-	-	-	-	-	X	-	-	-	X
JA Targets	-	-	-	-	Some	-	Some	Some	X	Some	X	X	X
Foothills	-	-	-	-	-	-	-	-	X	-	-	X	X
Twin Targets	-	-	-	-	-	-	-	-	X	-	-	X	X
ACID Rock	-	-	-	-	-	-	-	-	X	-	-	X	X
ACIR Jungle	-	-	-	-	-	-	-	-	X	-	-	-	X
MC Lake	Fresh Water	X	X	-	X	X	X	X	X	X	-	-	X
RN Lake	Fresh Water	X	X	-	X	X	X	X	X	X	-	-	X
LS Lake	Fresh Water	X	X	-	X	X	X	X	X	X	-	X	X
ACID Lake	Fresh Water	X	-	-	X	X	X	X	-	X	-	-	X

to determine the internal structure through the subsequent creation of thin sections in the laboratory. Salinity of the ice was measured as was the density of the snow cover. In-situ snow and ice cover thickness measurements were also taken.

Physical property measurements confirmed the identity of selected first-year and old ice sites as shown in Table 2.1. However, for the fresh-water lakes shown in Plate 2-2 the physical property measurements were used to account for the apparent variations in SAR signatures between each target. Both R. Williams (1985) and Lapp and Bjerkelund (1984) determined that these differences were due to the depth of ice present. Areas of high radar return, evident in MC and ACIC lakes, were related to the ice cover not extending to the lake bottom while areas of low speckled return evident in MC and LS lakes were related to the ice cover being frozen to the lake bottom. Thus the presence of an ice/water interface and bubbles in the ice caused a bright return for RW and ACIC lakes while the presence of an ice/soil interface in MC and LS lakes absorbed the majority of the incident radiation (Weeks et al., 1981; R. Williams, 1985). The speckled return in MC and LS lakes was due to the presence of bubbles in the ice.

Plate 2-2 - Enlargement of Lake Sites from the East/West Pass.

2.2.3 Mapping of Ice Features

Based upon the high resolution of the STAR-1 SAR imagery, both point targets and several floes were selected for field analysis. Due to time constraints in the field only representative sites were chosen. Using the SAR imagery as a site map, the selected targets were identified in the field and mapped relative to the location of other targets chosen. Figure 2-2 showed all sites chosen with each corresponding site identifier. During field data collection a 2X enlargement of the original oriented north/south pass was used to verify the identity of targets. Both passes were analysed digitally.

2.3 Remote Sensing Data

Over the past 15 years both satellite and airborne remote sensing in the Arctic has used visible, infrared and active and passive microwave sensors (Weeks et al., 1981; Kim et al., 1984; Hollinger et al., 1984). Figure 2-3 shows where these remotely sensed regions lie in the electromagnetic spectrum. Each sensor, depending

Figure 2-3 - The Electromagnetic Spectrum

(Ulaby et al., 1981)

on frequency, provides differing information about sea-ice at varying resolutions, scales, and presentation formats. All of these sensors have been applied to various aspects of studying the following sea-ice characteristics which are of importance in operational and research areas (Weeks, 1981). The parameters are:

- Ice extent
- Ice type
- Ice thickness
- Ice drift
- Internal ice stress
- Ice physical and chemical properties
- Ice roughness
- Ice growth and melt
- Snow cover

The analysis of these characteristics requires the interpretation of imagery generated through the scattering or emission of electromagnetic waves from the sensed target material. Each method has its own inherent difficulties and errors associated with it (Carsey, 1982). There follows a description of active microwave or radar remote sensing and its application in sea-ice studies. The reader is referred to Weeks (1981) and Carsey (1982) for a description and discussion of the other sensors' utility in sea-ice sensing.

2.3.1. Active Microwave

Active microwave sensing of sea-ice includes radar altimetry, scatterometry, imaging radar and land-based radar (Page and Ramseier, 1975; Carsey, 1982; Weeks, 1981). The most frequently used sensors are scatterometers and imaging radars. Radars are termed active since they supply their own source of illumination for features being sensed. Also microwaves, at certain frequencies, are little affected by the atmosphere and weather. Imaging radars include side-looking airborne radar (SLAR) and synthetic aperture radar (SAR). Figures 2-4 and 2-5 illustrate the geometry of the two systems.

The simplest of the two types is the SLAR, termed a real-aperture system in which the along-track resolution is determined by the along-track beamwidth of the antenna (Ulaby et al., 1981; Page and Ramseier, 1975). The narrowest along-track beamwidth is obtained by using the longest antenna possible. The cross-track resolution is determined by the length of the transmitted microwave pulses; therefore a frequency is chosen so as to retain a cross-track resolution approximating that in the along-track direction (Ulaby et al., 1981; Page and

Figure 2-4. - Real Aperture SLAR Geometry and Resolved Surface Area

(Ulaby et al., 1981)

Figure 2-5 - Illustration of Advantage of Synthetic Aperture in a Space Application

(Ulaby et al., 1981)

Ramseier, 1975). As shown in Figure 2-4 the pixel size of the real aperture system is determined by the antenna beamwidth:

$$B_h \cong \lambda / \ell \quad \text{radians} \quad (2.1)$$

Where;

B_h is the beamwidth
 λ is the wavelength
 ℓ is the horizontal antenna length

The along-track resolution resulting from 2.1 is:

$$r_a = B_h R \quad (2.2)$$

Where;

R is the slant range

therefore resolution along-track is a function of range and varies across the image. In the across-track dimension resolution is given by:

$$r_p = \frac{c \pi}{2 \sin \phi} \quad (2.2a)$$

Where:

r_p is the pixel dimension
 c is the velocity of light
 π is the pulse duration
 ϕ is the angle from vertical

Both the across-track and along-track dimensions are a function of distance from the sensor which results in pixel shape being elongated across-track in the near range and along-track in the far range (Ulaby et. al., 1981; Skolnik, 1962). Inherent in SLAR there is also a linear degradation in the across-track resolution away from the transmitter due to the angular spread of the antenna beam (Page and Ramseier, 1975). An example of this resolution drop off is illustrated in Plate 2-3.

As shown in Figure 2-6 a SLAR image is created by motion of the sensor past the object being imaged. An electromagnetic pulse is swept line by line on an image tube or film by receiving transmitted pulses whose strength is a measure of several variables including system geometry, the dielectric constant and surface roughness and relief. These variables are discussed later in Sections 2.3.1.1 and 2.3.1.3. The time delay associated with the received signal gives the distance between the target and radar and hence the position of the target on the image (LaPrade, 1976).

The second type of radar, the SAR, attains much higher resolutions than SLAR because of the along-track

Figure 2-2 - The Black Image of World War. 1944.

Figure 2-6 - Real Aperture SLAR Technique

(Ulaby et al., 1981)

direction being independent of altitude flown (Ulaby et al., 1981). To achieve high resolutions SLAR requires very long antennas while SAR systems synthesize a long antenna by taking advantage of the motion of the imaging platform. The cross-track resolution in SAR is also independent of distance to the imaged target and high resolution can be achieved (Page and Ramseier, 1975). To produce a SAR image the received signals from each surface target are observed along the plane's flight path while the feature imaged remains in the radar beam reflecting a series of microwave pulses. The location of each feature in the radar beam is used to synthesize a much larger antenna than is physically present. Through signal processing a much narrower beamwidth is achieved and a corresponding higher resolution is attained (LaPrade, 1976; Page and Ramseier, 1975). Thus a SAR system can achieve much higher resolutions than a SLAR.

Theoretically along-track resolution in a SAR can be as small as:

$$r_a = \ell / 2 \quad (2.3)$$

Where;

ℓ is the along-track antenna length. In across-track the SAR pixel dimension is:

$$r_p = \frac{C}{2B \sin \phi} \quad (2.4)$$

Where;

B is the bandwidth

Figure 2-5 illustrated the advantages in the SAR antenna beam formation over a real aperture SLAR system.

The SLAR system has proven valuable for ice reconnaissance over the past 8 years and is still in operational use at this time. SAR have primarily been used in their developmental stage; however, STAR-1 has just completed its second year of commercial operation in the Arctic and has demonstrated its utility as an ice reconnaissance tool. To date there has been only one deployment of a SAR in a satellite. The SEASAT SAR launched in 1978, failed after 100 days of operation due to a power breakdown, and much of the data collected during this time is still being analysed (Fu and Holt, 1982; Pravdo et al., 1983).

2.3.1.1 Variables Affecting Radar Return

One of the main considerations in an imaging radar is the geometry of the system and the wavelength at which the system operates. Radar frequencies reside in the microwave portion of the electromagnetic spectrum and are divided into letter designations as shown in Figure 2-7. Most remote sensing radars use the X-band frequency. In general, ice detail is better resolved at greater frequencies (Page and Ramseier, 1975; Carsey, 1982). X-band (5.75 to 10.9 GHz) and L-band (0.3 to 1.55 GHz) have been demonstrated to be complementary in terms of sea-ice imaging (Gray et al., 1982) while C-band (3.9 to 5.75 GHz) has been chosen as the frequency for Canada's RADARSAT SAR (Shaw et al., 1984). Other variables that influence the return of the radar signal include the complex dielectric constant and surface relief and roughness.

The dielectric constant, a measurement of the electrical properties of a material, affects radar return since it strongly influences absorption and propagation of electromagnetic waves into the surface sensed. The two parts of the complex dielectric constant include; the

Figure 2-7 - Band Designation of the Radio Spectrum and Letter Designation of the Microwave Portion

(Ulaby et al., 1981)

real part, referring to the permittivity of a material, and the imaginary part, which refers to a material's conductivity (Ulaby et al., 1981). Both parts are dependent upon the liquid content of the surface imaged and the frequency of energy used. Sea-ice is regarded as relatively lossless in the microwave spectrum, with a resulting low dielectric constant, because it exists for part of the year at temperatures below freezing with an absence of liquid water. However the dielectric constant does vary due to salinity, temperature and ice type and does affect the backscatter coefficient discussed in section 2.3.1.2 (Kim et al., 1984).

Surface relief affects radar returns by causing both radar shadow and radar layover. Radar shadow occurs when electromagnetic energy strikes a high relief feature resulting in a lack of return (shadow) from the slope facing away from the radar beam. This can cause problems along landfast ice zones by masking ice that may be present. Radar layover is a function of the distance of an object to the radar. As shown in Figure 2-8 the image of the hilltop (A) is laid over the image of the base of the hill (C) resulting in different terrain features appearing at the same point on the image. A similar

Figure 2-8 - Radar Displacement of Elevated Objects

problem occurs with real-aperture radars in their far range. Figure 2-9 illustrates two objects being imaged as individuals in the near range and becoming one in the far range. This is due to the radar beam fanning out across the track and being wider at the far range than in the near. This results in a deterioration of resolution with range as is shown in Plate 2-3.

The dominant factor in determining the tone of radar images lies in the interaction of the electromagnetic energy in a diffuse or specular fashion with the imaged surface. Specular reflection refers to interaction with a smooth surface while diffuse reflection occurs on rough surfaces. But it is not simply the roughness of a surface that determines the type of reflection. Reflectivity is also a function of the wavelength of the system and the angle of incidence of the emitted energy when it strikes the surface. Therefore a surface may appear rough at a high frequency while being smooth at a low frequency (Jensen et al., 1977; Simonett and Davies, 1983). Surface roughness is a critical variable in the interpretation of sea-ice types. This measure of image

Figure 2-9 - Range Resolution Deterioration in SLAR

(Jensen et al., 1977)

roughness is also termed backscatter and can influence the tone of targets on a radar image, and hence its interpretability.

2.3.1.2 Backscatter Coefficient

Imaging radars are recognized as the primary remote sensing tool in the operation and research sides of sea-ice studies (Johnson and Farmer, 1971; Gray et al., 1977; Weeks, et al., 1981; Carsey, 1982). However, these radars have yet to be optimized for frequency of operation, viewing angle, antenna polarization and resolution (Onstott and Gogineni, 1985; Gogineni et al., 1984). In order to optimize radar parameters, an understanding of the interaction between the microwave pulse and sea-ice is necessary. This return, termed the scattering coefficient, or backscatter, has been extensively measured (Gray et al., 1977, 1982; Onstott et al., 1982; Onstott, 1984; Gogineni et al., 1984; Onstott and Gogineni, 1985).

Backscatter is affected both by the parameters of the sensing radar and the physical parameters of the

imaged scene. Radar parameters include frequency, viewing angle and antenna polarization while scene parameters include location and size of imaged target, surface characteristics and permittivity (Kim et al., 1984; Onstott and Gogineni, 1985). However, because ice properties are influenced by season, it is necessary to collect backscatter data under different situations in different seasons (Carsey, 1982; Kim et al., 1984; Onstott and Gogineni, 1985). The backscatter coefficient is further discussed in the following section.

2.3.1.3 Scatterometry

The scatterometer radar has been used extensively in backscatter research. A scatterometer is a calibrated radar that measures the backscatter coefficient of the imaged surface. Analysis of data from calibrated scatterometers has proven to be a ~~fundamental step~~ in the understanding of radar systems (Ulaby et al., 1981). The differing frequencies measured by Gray et al. (1982) and Onstott et al. (1979), and the multi-frequency approach taken by Onstott and Gogineni (1985) and Gogineni (1984), have demonstrated the backscatter difference between

various ice forms are at their greatest during winter and spring. Summer investigations by Gray et al. (1982) and Onstott and Gogineni (1985) have shown that there are variations between summer and winter microwave responses to sea-ice. Onstott and Gogineni (1985) conclude that the well-documented winter and spring microwave responses for cold conditions cannot be extended into the summer season. It is only through a thorough understanding of the seasonal variation in the backscatter coefficient that a truly optimized imaging radar can be built.

As described in Chapter 1, sea-ice is a very dynamic medium continually growing and changing under a variety of environmental conditions. Ice properties such as salinity, temperature, dielectric constant, volume scattering and surface roughness all affect the backscatter of ice types and thus their appearance on radar imagery (Vant et al., 1974, 1979; Onstott et al., 1979, 1982, 1984; Kim et al., 1984).

The backscatter coefficient is measured in decibels (dB) with the relationship between backscatter and sea-ice having been extensively reviewed and reported on by Kim et al. (1984). Variations of up to 2 to 3 dB

have been found as temperature and salinity in first-year ice changes since the dielectric constant is affected by these fluctuations. In the case of multi-year ice these changes can cause variations of up to 6 dB (Kim et al., 1984). Surface roughness has also been found to play a role in determining the backscatter of first-year and multi-year ice (Onstott et al., 1982, 1984; Gray et al., 1982). Volume scattering in multi-year ice, due to the presence of air bubbles and its density, has been shown to affect the backscatter coefficient by up to 10 dB.

Figure 2-10 illustrates the relationship between backscatter and imaging frequency. As mentioned in Section 2.3.1.1, backscatter is also a function of the wavelength of the imaging system and the angle of incidence of the radar energy with the surface sensed. In the case of Figure 2-11 the backscatter of rough and smooth first-year ice and that of medium tough and rough multi-year ice surfaces are plotted against frequency. Overlap can be seen in the return of the first-year and multi-year ice types up to 17 GHz. Therefore high frequencies are better in the discrimination of ice types (Kim et al., 1984). Figure 2-11 shows the range of backscatter response for 5 and 13 GHz plotted against

Figure 2-10 - Theoretical Backscatter for Multi-year and First-year Ice
(Kim et al., 1984) /

Figure 2-11 - Theoretical Angular Variations of Backscatter for Multi-year and First-year Ice

(Kim et al., 1981)

incidence angle. In both cases incidence angles above 30 degrees show the best discrimination between first-year and multi-year ice. Therefore as concluded by Kim et al. (1984), the best frequencies for sea-ice discrimination are at X-band and higher with an optimum imaging incidence angle of 30-40 degrees. The STAR-1 SAR system described next images at X-band with a range of incidence angles of about 30 degrees.

2.3.2 STAR-1 SAR System

The STAR-1 system is a new generation of SAR designed as a commercially viable radar providing high resolution SAR imagery to commercial users (Lowry, 1985; OILWEEK, 1985). The system operates at a nominal altitude of 10km which is above turbulence levels that cause motion compensation problems with SAR. For sea-ice studies STAR-1 imagery can be used to discriminate between first-year and old ice types. The system also provides improved resolution over currently operational ice reconnaissance radars along with variable radiometric and spatial control. Table 2.2 lists the STAR-1 SAR specifications. STAR-1 also has the ability to transmit

TABLE 2.2STAR-1 SPECIFICATIONS

Nominal Operating Altitude	10 km (33,000 ft.)
Wavelength	X-band (3.2 cm)
Polarization	HH
Viewing direction	Left or right
Sensitivity	Better than -30 dB approximately across swath
Processing	Real-time digital
Recording	Full-bandwidth recording of image data on High Density Digital Recorder at 1.4 Mbps
Downlink	Full bandwidth downlink to ground receiver station with display and tape recorder. Range 150 miles at 30,000 ft. altitude
Display	High resolution laser beam recorder on aircraft recording on heat processed paper. High resolution wet chemically processed display on ground

<u>MODES</u>	<u>HIGH RESOLUTION</u>	or	<u>WIDE SWATH</u>
Swath width	23 km		46 km
Range resolution	6 m		12 m
Azimuth resolution	6 m		6 m
Number of looks per pixel.	7		7

data to surface receiving stations for real-time analysis. Imagery is output in hardcopy on the aircraft and the data are recorded on tape for subsequent analyses. Due to processing of the STAR-1 data resulting in a resolution of 6m, and the excellent radiometric and spatial control inherent in the system, the output imagery resembles a black and white photograph that is easily visually interpreted. In addition to ice reconnaissance its value extends to geological, oceanographic and marine transportation applications. The radar's high resolution, variable swath and uniform image quality all lend themselves to real-time support of drilling platforms and navigating vessels in ice-and iceberg-frequented waters. The imagery has already had an impact upon the extension of operating seasons for these activities in the Arctic (Offshore Resources, 1985).

CHAPTER 3

INVESTIGATIVE TECHNIQUES

The method of approach used in this work involved the visual interpretation of the STAR-1 SAR imagery and the application of DIPIX image analysis system software to the digital data. The aim was to enhance the images as much as was reasonably possible for ice feature detail and compare the collected field measurements to those calculated in the visual and digital analyses.

3.1 Analysis System

The digital analysis of the Mould Bay SAR data was carried out on a VAX 11/750 based DIPIX Aries-II image analysis system located at the AES Ice Centre in Ottawa. This system was purchased in 1984 to investigate the digital enhancement of NOAA weather satellite imagery used in operational ice forecasting (Ramsay and Zieger, 1986). As shown in Plate 3-1 the DIPIX workstation consists of VAX based computer terminal, high resolution graphics monitor, bit pad, and printer. The system is capable of

loading digital remotely sensed imagery, providing it has been formatted properly, and performing image analysis tasks on the data. A detailed description of DIPIX use appears in Appendix A. The basic steps in image analysis include: data acquisition and input; image display; image manipulation; and data output. Section 3.2 describes the preliminary work involved in preparing the SAR data for analysis.

3.2 Preliminary Work

The Mould Bay STAR-1 SAR data was received on a computer compatible tape (CCT) from Intera Technologies Limited. The data was provided at 1600 characters per inch (CPI), 9 track, with 4096 8 bit pixels per line compatible with the DIPIX system. The data have a resolution of 6m from the nominal altitude of 10km.

3.2.1 Orthogonal Passes

Mould Bay was imaged on two separate passes as shown in Figure 3-1. These passes provide an orthogonal

Figure 3-1 - Orientation of SAR Flight Paths Flown Over Mould Bay on March 3, 1984

view of the ice cover resulting in the ability to highlight relief characteristics by emphasizing the different orientations of features present. Therefore by combining both passes, differences between them can be highlighted, providing more information about features than if only one pass had been imaged. The repeat view of the ice cover is only available for the Bay itself since the acquired CCT data did not extend past the meteorological station for the east/west image line.

3.2.2 Image Registration

Prior to analysis of the digital data sets, the two images had to be registered to one another. The Aries-II software provides an image registration package which uses operator-defined ground control points to calculate a polynomial transformation which is then used to position the two passes together. The process involves the selection of ground control points from features that were clearly definable on both passes. Sixteen ground control points were selected resulting in the successful registration of both images. In the case of radar images, past studies such as Kirby (1980) have determined that it

is difficult to select ground control points which are common to more than one radar image because of the varying appearance of imaged ice features. This was not so in this case since the STAR-1 images were easily registered using 16 land-based ground control points.

3.2.3 Selection of Subscenes

Each digital SAR image occupied far more frame space than the graphics terminal could accommodate. This necessitated dividing each imaged pass into two subscenes for analysis. The criterion followed for subscene creation was to keep the point targets investigated on one scene and the old ice field on the other. This method was employed since the point targets were analysed separately from the floe targets. Along with creation of the subscenes, extraneous land data were removed in order to reduce the size of the data files and the time required to process the data. Figure 3-2 shows the area occupied by each subscene.

Figure 3-2 - Subscenes Created for DIPIX Image Analysis

3.3 Image Analysis Procedures

The intent of digital image processing was to optimize the identification of ice features. The main limitation of the available software for use with the SAR data was its multispectral (MSS) data analysis design. MSS data files, such as those created by Landsat, differ from the Intera STAR-1 SAR data in that the former record at four different wavelengths, or bands for each scene while the latter is imaged at only one frequency, or band. Each Landsat band is capable of emphasizing different features of the area imaged due to the differing wavelengths employed (Lillesand and Kiefer, 1979). The single frequency SAR data cannot be manipulated by software designed for four channel data. However, the SAR data were acquired in two passes. These orthogonal views can be used in much the same way as the Landsat MSS data for some specific applications (Piowar, 1984; Kirby, 1980).

The Landsat and STAR-1 SAR data are termed digital since the acquired data are imaged as an array of pixels (Lillesand and Kiefer, 1979). As shown in Figure 3-3 the data are scanned in horizontal rows of pixels termed scan lines. Thus a specific point on the image can be

Figure 3-3 - Digital Image Representation

(Colwell, 1983)

referenced by row (scan line) and pixel number. Each pixel has a unique grey level intensity in the range of 0-255 which results from the backscatter of the radar energy from the target sensed.

The procedures used in this study were selected on the basis of their success in other studies (Kirby, 1980; Blom and Daily, 1982; Daily, 1983; Curlander et al., 1985; Lowry, 1985). Lowry (1985) claimed that classification techniques designed for multispectral data do not work with SAR data while Kirby (1980) and Blom and Daily (1982) recommended median filters as a useful tool in reducing the speckle associated with SAR imagery. Daily (1983) and Lowry (1985) also recommended the use of low pass filters in the reduction of radar speckle. Other techniques including density slicing, texture measure filtering and convolution filtering were also applied to the SAR data.

The main procedures applied to the SAR data were enhancements and classifications. A classification is the end result of the interpretive process in which data, once analysed and interpreted, are converted into sets of specific classes providing specific information whereas in

an enhancement procedure the data are transformed into a more meaningful form and it is only once this transformation has taken place that the data are analysed.

3.3.1 Enhancements

According to Lillesand and Kiefer (1979) most enhancement techniques can be characterized as point or local operations. Point operations modify pixel values independently while local operations modify pixels in the context of the values of pixels surrounding them. Local operations employed here used filters while point operations included stretches and arithmetic functions.

3.3.1.1 Local Operations

SAR imagery contains a high degree of speckle which is related to the scattering of incident radiation that occurs from each resolvable object on the imaged surface. The end result is variable intensities across the radar image. Local operations such as filters are utilized to emphasize or de-emphasize large variations in

pixel values. Filters help to smooth the speckle in SAR imagery thereby altering the textural appearance of the imagery. Filters that de-emphasize high pixel values are referred to as low pass filters while filters that exaggerate pixel values are termed high pass filters.

The simplest form of low pass filter utilizes a 3X3 "window". As shown below, the filter replaces such pixel at the center of the window with the mean value computed within its neighbourhood.

C = 1 1 1 = mean value filter

1 1 1
1 1 1

Since the radar speckle or image noise is smoothed out by reducing the high values present, the filter is termed a smoothing operation (Lillesand and Kiefer, 1979).

High pass filters are useful with noise or speckle-free data since they exaggerate image values. These filters make bright pixels brighter and dark pixels darker by doubling the value of each pixel and subtracting the

windowed pixel average. High pass filters are also termed edge enhancement filters. Unfortunately they are not useful in analysing SAR imagery because of the high degree of speckle in the data.

Another filter that is useful in removing radar speckle is the median filter. The difference between the low pass and median filters is that the latter preserves edge definition of features much better than the low pass filter. Operationally the median filter functions like a low pass filter, except that it replaces the pixel at the centre of its neighbourhood with the median value of the whole window.

Two other filters that function best once the radar speckle has been removed are the convolution and texture measure filters. Convolution filtering is used to enhance or suppress spatial features such as edges, lines, and homogeneous areas. By selecting an appropriate convolution window, features may be enhanced or suppressed. Therefore, for example, by selecting a 5X5 window, the original 6m SAR data can be "degraded" to about a 30m resolution. Once the desired convolution

window is chosen it is overlain on the image and each pixel is summed and multiplied as follows:

where C is the convolution window

I is the image

and O is the output image

if C is a 3×3 window

$$C = \begin{matrix} 1 & 2 & 3 \\ 4 & 5 & 6 \\ 7 & 8 & 9 \end{matrix}$$

input image $I = \begin{matrix} 1 & 2 & 3 & 4 & 5 & 6 & 7 & 8 \\ 9 & 10 & 11 & 12 & 13 & 14 & 15 & 16 \\ 17 & 18 & 19 & 20 & 21 & 22 & 23 & 24 \\ 25 & 26 & 27 & 28 & 29 & 30 & 31 & 32 \\ 33 & 34 & 35 & 36 & 37 & 38 & 39 & 40 \end{matrix}$

compute the output image at line 2 pixel 2 (line 2 pixel 2 is centre point of overlain filter) as:

$$\begin{aligned} O(2,2) = & \begin{matrix} 1*1 & + & 2*2 & + & 3*3 & & \text{row 1} \\ + & 9*4 & + & 10*5 & + & 11*6 & \text{row 2} \\ + & 17*7 & + & 18*8 & + & 19*9 & \text{row 3} \end{matrix} \end{aligned}$$

Texture measure filtering requires that all radar speckle be removed prior to calculation. This filter

characterizes the grey level variability within an image. It measures the degree to which grey levels of each pixel in a defined window are similar, termed homogeneity, or the degree to which they are different, termed contrast. The formulae for determining homogeneity and contrast texture measurements as defined by D. Williams (1985) are:

$$\text{homogeneity: } SF * (\text{SUM } ((1.0 / (1.0 + (I_i - I_j)))) / NP)$$

$$\text{contrast: } SF * (\text{SUM } ((I_i - I_j)^2)) / NP$$

where i is indexed over all pixels in the filter

j is indexed over the neighbours of pixel i

I_i is the intensity of pixel i

I_j is the intensity of pixel j

NP is the total neighbouring pixel pair count*

* therefore if i is indexed at 1 to N and j from 1 to M then:

$$NP = N * M$$

SF is the scale factor

The texture filter is placed over each pixel in the image and homogeneity or contrast are evaluated for that pixel at the centre of the pixel window.

3.3.1.2 Point Operations

The point operations include both stretches and arithmetic functions. These functions will not be discussed in detail here. The reader is referred to Lillesand and Kiefer (1979) and Colwell (1983) for in-depth descriptions. The contrast stretch and its variations including linear stretch, histogram-equalized stretch, logarithmic transformation, and exponent transformation are all used to expand the range of pixel values over the full scale of 0-255 intensity levels. Typically, SAR data occupies a small range of the available 256 grey levels resulting in a low contrast display. As illustrated in Figure 3-4 these grey levels can be manipulated to fill the dynamic range of the histogram so that features having slightly different but similar pixel intensities in the original image may now be distinguished due to the stretching of pixel values over the full range of the histogram.

Figure 3-4 - Principle of Contrast Stretch Enhancement
(Lillesand and Kiefer, 1977)

Arithmetic functions include ratioing, sum, product, difference and difference over sum. With one band SAR data these functions may not be applied, but given two registered passes the same band may be used to highlight spectral differences. Utilizing these arithmetic functions, subtle differences between passes not evident by visual analysis may be highlighted.

Arithmetic functions available on the DIPIX include:

ratio $F = F(1)/F(2)$

product $F = F(1)*F(2)$

sum $F = F(1)+F(2)$

difference $F = (F(1)-F(2))/(F(1)+F(2))$

difference/sum $F = (F(1)-F(2))/(F(1)+F(2))$

where F = the output files and F(1) and F(2) are the input files

Once these functions are executed values exceeding the 0-255 intensity range may be calculated. These out-of-range data are then clipped from the data set.

3.3.2 Classifications

Image classification procedures make use of the spectral distribution of pixel intensities to identify features of interest. The two approaches to classification include supervised and unsupervised methods. In the supervised approach the analyst chooses features or categories (training sites) on the image he wishes to analyse and then based on statistics derived from the training sites instructs the computer to select all other areas on the image with similar characteristics. In the unsupervised approach algorithms are used to divide the image data set into classes based upon the natural variability of image values. One difference between the two approaches is that all pixels in the unsupervised approach are used to create image classes while pixels may be excluded during training in the supervised approach (Lillesand and Kiefer, 1979; Kirby, 1980). The unsupervised approach has the advantage that the analyst is not required to have a detailed knowledge of image data to perform a classification (Kirby, 1980).

A much simpler approach to image classification is density slicing. Density slicing is based upon slicing a

2 of/de 2

feature's intensity range from the rest of the distribution in a one dimensional histogram. This technique assumes each feature of interest occupies a unique intensity level within the histogram. The analyst identifies pixel intensities for each feature desired and then slices these regions by assigning varying colour or grey levels to each sliced region.

This chapter has presented the various DIPIX image analysis techniques available for the analysis of digital data. The results obtained by applying techniques utilized during the study are presented in the following chapter.

CHAPTER 4

RESULTS OF ANALYSIS

The analysis of the STAR-1 data was executed in two steps. The first step involved investigating the available image analysis software to determine its utility in enhancing the SAR data. The second step involved applying digital analysis techniques to the data to aid in the verification of the collected field measurements. Prior to these analyses the STAR-1 imagery was visually interpreted for ice features present. Because the high resolution STAR-1 SAR image appears like a photograph the principles of radar image interpretation are similar to those in aerial photographic interpretation. These elements of appearance of features on an image include those ordered in Figure 4-1.

Referring to Plate 4-1 first-year ice is visible in the upper portion of the image as a dark grey tone with white veins of rafted ice providing texture. Along the shore adjacent to the meteorological station a broken lead of landfast ice is represented by the smooth black tone.

Figure 4-1 - Primary Ordering of Image Elements
(Colwell, 1983)

Plate 4-1 - INTERA STAR-1 SAR Image of Mould Bay.
March 3, 1984. North/South Pass.

The majority of the old ice occupies the southern portion of the bay and it appears in a bright mottled grey signature caused by upturned ice blocks and weathered ridges within the floes. The extent and boundaries of old ice floes can be determined due to the contrast between the old ice and surrounding first-year ice. The same distinction can be applied to the difference between the ice cover and surrounding land features. Plate 4-1 represents the north/south pass and was the image used for field work during the Mould Bay experiment.

4.1 Analysis of Results from Procedures

Both enhancements and classifications were applied to the digital SAR data using the DIPIX image analysis system. The utility of each technique applied was considered in terms of ice detail revealed. In this section the results of the digital analysis are discussed.

To conserve computer resources and unnecessary duplication of effort, subareas, rather than whole scenes,

were analysed to determine the effect of applied software. Table 4.1 lists the enhancements and classifications applied to the SAR data and the results obtained. Each procedure is evaluated in terms of its effect on the digital data. A listing of the Plates included for each procedure and on which the various effects can be noted is given.

4.1.1 Local Operation Enhancements

4.1.1.1 Filters

Of the three filters applied to the SAR data to remove inherent speckle, the median filter best retained image contrast. The high pass filter exaggerated high pixel values rendering the image washed out, but the low pass filter, while removing radar speckle, did not retain image contrast and feature edge detail as well as the median filter. Plates 4-2 and 4-3 show the raw SAR data and the median filtered image from the north/south pass. As can be seen, the radar speckle has been removed and smoothed while retaining edge definition for the bright old ice targets. Texture within the first-year ice cover

TABLE 4.1 - RESULTS FROM IMAGE ANALYSIS PROCEDURES

EFFECT	ENHANCEMENT PROCEDURES				CLASSIFICATION PROCEDURES			
	LOCAL OPERATIONS		POINT OPERATIONS		STRETCHES		ARITHMETIC FUNCTIONS	
	LOW PASS	HIGH PASS	MEDIUM	CONVOLUTION	TEXTURE	LINEAR	HISTOGRAM	RATIO DIFFERENCE
	yes	no	yes	N/A*	N/A*	N/A*	N/A*	N/A*
Radar								
Speckle Reduction	yes	no	yes	N/A*	N/A*	N/A*	N/A*	N/A*
Overall	good	poor	excellent	excellent	excellent	good	fair	good
Image contrast	good	poor	excellent	excellent	excellent	good	fair	good
Overall	good	poor	excellent	excellent	excellent	good	fair	good
Image texture/detail	good	poor	excellent	excellent	excellent	good	fair	good
First-year/old ice contrast	good	fair	excellent	excellent	excellent	good	good	good
Ice/land contrast	good	fair	excellent	excellent	excellent	good	good	good
First-year/ice texture/detail	good	poor	excellent	excellent	excellent	good	good	good
Old ice texture/detail	fair	poor	excellent	excellent	excellent	good	good	good
Results of Procedures	Radar speckle reduction with values of some out contrast image and detail in old ice floes.	Exaggeration of high pixel values washing out contrast image.	Medium filtered image degraded to 18 & 30m resolutions. Predictable loss of detail and changing application due to degradation.	Homogeneity and contrast filters applied to median filtered data. Results of filter combined in false colour to give excellent representation of texture present.	Existing tones on image expanded so light tones lighter & dark tones darker.	Contrast Ratio- ing smoothed the detail in floes the difficult spectral to interpretations between them produced in pseudo 3-D effect around edges of features common to both passes.	The EW/ NS passes were subtracted and enhanced to emphasize signatures. spectral Texture differ- ences. ice floes lost.	Great deal of manual classification of feature intensities selected by operator. Able to highlight PY and OI types.
Plate References	None	None	4-4, 4-5, 4-6	4-7, 4-8, 4-9	4-11	4-12	4-13	4-14, 4-15, 4-17
Presented in Plates	None	None	N-S Pass	E-W Pass	Enlarge- ment of floe on linear E-W Pass	Same as linear	Both passes	Both passes

is more apparent on the filtered image and detail within old ice floes can also be seen. The fact that edge definition is preserved is extremely important for image interpretation in the spatial domain, especially where little contrast exists between a target and its surrounding matrix as shown by the detail apparent within the old ice floes. Because of its usefulness in the reduction of the radar speckle without much loss in contrast and feature edge detail, the median filter was applied to both image passes prior to further analysis since speckle can interfere with statistical calculations by introducing a large number of saturated pixel intensities into the image calculations.

4.1.1.2 Convolution Filtering

This filter was applied to the SAR data since it can suppress spatial features. It was used to permit comparison of 6m STAR-1 SAR data with other operational SLARS of lower resolution, allowing a qualitative assessment of each systems usefulness. Plates 4-4, 4-5 and 4-6 show the raw median filtered data with the 18m (3X3 windowed) and 30m (5X5 windowed) degradations. These

PLATE 4-3 - THE TOWER, BOSTON, MASS., NORTH SIDE VIEW

examples demonstrate the relative differences between 6, 18 and 30m resolution formats. The different resolutions result in decreased ice feature detail with the smoothing out of point targets and ice texture. As the degradation increases from 6 to 18m, edge definition around old ice targets becomes less defined and texture in the first-year ice cover and on land becomes smoothed over. Progressing to 30m the first-year landfast lead along the eastern shoreline merges into a continuous feature whereas on the 6 and 18m images more detail can be discerned within individual leads. The most apparent difference, however, is the complete removal of the three old ice point targets visible on both the 6 and 18m imagery. This degradation process provides a clear indication of the value of each level of resolution for specific applications. Both the 18 and 30m images are useful for determining ice type extent while the 6m image is best for determining ice feature and texture detail. In terms of operational marine navigation the loss of detail on the 30m image is significant since such targets do pose a hazard to navigation. Therefore the potential application of each image lies in the amount of detail provided.

4.1.1.3 Texture Measuring Filtering

According to Ulaby et al. (1986), texture may be more useful in interpreting radar images than image tone. Texture refers to the frequency of tonal change in an image due to the shape, size, pattern and shadow associated with individual image features. Plates 4-7 and 4-8 show the results of the homogeneity (similarity between pixels) and contrast (difference between pixels) texture filters for the east/west pass. The east/west pass was used in this case since it was determined visually that more texture within the ice cover was present on this pass as evidenced by the east/west ridge running across the bay. Plate 4-7, the homogeneity filter, demonstrates little correspondence in similarity between image pixels while Plate 4-8 illustrates the amount of contrast that is present on the image. In both cases, if all pixels had been similar or contrasting, the resulting image would have been white. Referring to Plate 4-7, the area in white to the left of Feature 1 on the homogeneity filter corresponds to an area of radar shadow where all pixels have a similar intensity. By combining the results obtained from filtering with the original data, contrast or homogeneity may be highlighted. For

Plate 4-7 - Homogeneity Texture Filter, East/West Pass.

Plate 4-8 - Homogeneity Texture Filter, East/West Pass.

example, Plate 4-9 shows the results of the contrast texture filter from Plate 4-8 highlighted with the original east/west data in a false colour image created on the DIPIX system. The white colour within floes and point targets illustrates the similarity in texture for the east/west image while the light blue emphasizes the contrasting texture present. By utilizing the colour guns on the image analysis system, areas of high contrast (or most texture) can be overlaid on the original image. With these colour combinations the analyst can determine areas of texture not readily visually apparent on the original image. By using the colour guns one can quickly determine texture within floes and first-year ice cover more so than using grey levels since it is easier for the eye to discern colour differences than changing grey level variations. The result is a more interpretable image than is present with grey tones alone.

4.1.2 Point Operations

4.1.2.1 Stretches

The types of contrast stretches applied to the

original SAR data included piecewise linear stretch and histogram equalization. Logarithm and exponent transformations were also applied to the image but did not add substantially to the interpretability of the SAR data. A subsection of the original east/west pass SAR image appears in Plate 4-10 with its corresponding histogram of grey level intensities shown in Figure 4-2. The resulting histograms from the applied stretches are presented in Figures 4-3 to 4-6. These histograms illustrate the effect of expanding the range of pixel values so that they are displayed over a fuller range of grey levels. The original image of the old ice floe was quite dark with a few bright signatures identified as upturned ice blocks and ice ridges. It was found that both the linear and histogram equalized stretches best enhanced the ice features present. As shown in Plate 4-11, the linear stretch expanded the existing tones over the full range of grey levels, brightening the light tones, which represented rough rubbled areas, and darkening the darker, smoother areas. The histogram equalized stretch resulted in a more smoothed image than the linear stretched image. This was due to the histogram function displaying pixel values on the basis of their occurrence. Therefore the less frequently occurring values of 0 to 15 and 65 to 120

Plate 4-10 - Subsection of Original East/West 200 image
showing EA Fine.

2

Figure 4-2 - Histogram from Plate 4-10

Figure 4-3 - Histogram Resulting from Piecewise Linear Stretch Shown in Plate 4-11

Figure 4-4 - Histogram Resulting from Histogram Equalized Stretch Shown in Plate 4-12

Figure 4-5 - Histogram Resulting from Logarithmic Transformation

Figure 4-6 - Histogram Resulting from Exponential Transformation

Plate 4-11 - Results of Linear Stretch Applied to
Plate 4-10.

were pushed to the extremes on the display histogram, while the more frequently occurring values were displayed over the majority of grey levels in between. This resulted in lower contrast on the image. As shown in Plate 4-12, however, more detail in the smooth ice surrounding the old ice floe can be discerned simply because the recurring high pixel values that were previously hidden by lower return values are now being highlighted. Both the linear and histogram equalized stretches were the most effective in accentuating the intensity contrast on the single band SAR data.

4.1.2.2 Arithmetic Functions

Arithmetic functions are used to provide contrast between different bands of image data. These techniques are not useful with one band SAR data, but when two different but registered views of the same area are available, spectral contrast between bands may be determined. Both ratioing the return signal between passes and subtracting the return signal of one pass from the other were undertaken to emphasize differences between passes. As shown in Plates 4-13 and 4-14 both functions

Figure 4-10 - Comparison of the two methods of
failure.

resulted in features common to both passes being highlighted. Edges of old ice pieces and texture within the first-year ice cover are more prominent than on the individual images. There is, however, a loss of contrast when compared to the original images which could hinder the identification of ice types present.

4.1.3 Classifications

4.1.3.1 Unsupervised

Of the two types of classifications termed supervised and unsupervised only the unsupervised approach was taken. The supervised approach was not attempted since it requires the operator to select pixel intensity classes that are then used by the computer to classify the image. As described by Kirby (1980) this approach can result in data gaps because all intensities not included in the original classification selection procedure are left out of the final classification. The unsupervised approach, on the other hand, relies on the computer to classify all pixel values present. From the results of the unsupervised classification presented in Plate 4-15 it was apparent that a procedure like this does not lend

Plate 4-15 - Unsupervised Classification of the
North/South Image Pass.

itself well to single frequency/band radar data. As can be seen, signatures of land and old ice floes are quite similar in terms of their tones. As a result of the unsupervised procedure, texture within the old floes and on land is lost. The procedure does have a use, however, in that pixels are grouped according to spectral groupings in grey value intensities. The value of radar imagery is that old ice and first-year ice are at the extreme ends of grey levels present, old ice being quite bright while first-year is much darker. Thus the computer can serve as a tool in ice type identification once the influence of land signatures are removed, since the primary ice types and their extent can be easily determined.

4.1.3.2 Density Slicing

A simpler way to classify an image is to perform a density slice of the data. In this procedure the analyst determines from the histogram the intensity values of pixels that represent the various classes of features. These classes are then sliced from the data set and each is assigned a visually distinctive colour or grey level. Plates 4-16 and 4-17 show the median filtered image and

Plate 4-16 - Median Filtered Sea Data, North/South Pass.

Plate 4-17 - Resampled Version of Data from Plate 4-16.

the resulting density slice. By referring back to Plate 4-15 it is evident that more texture within old ice floes is shown in the density slice than on the unsupervised classification. By slicing out classes of pixel intensities a much more easily interpreted classification is obtained. Figure 4-7 shows the selected slices of the histogram that were used for the image in Plate 4-17. Again as in the unsupervised case there is overlap between old ice and land classes which cannot be removed from the SAR imagery. The utility of this type of classification is that it is based on histogram intensities and can be used to highlight certain features within the original image. Therefore older ice types may be distinguished from younger ice based upon their differing signature intensities using a distinctive colour scheme.

4.2 Verification of Mapped Ice Features

The verification of ice features was accomplished by identifying the selected ice targets mapped in the field using both visual and DIPIX image analysis techniques. Application of the median filter to the digital data resulted in a reduction of radar speckle and

Figure 4-7 - Histogram Showing Density Slices
Chosen for Plate 4-17

increased feature contrast and edge definition. By utilizing the median filtered images of both passes the verification of mapped ice features was facilitated. The comparison of mapped ice features was made between field measurements collected with those calculated visually and digitally from the SAR data. All digital data measurements were conducted on a pixel-by-pixel basis. Distortion in the SAR data was determined by comparing points identified on both a 1:50000 scale topographic map and on the original 1:125000 scale imagery used in the field. Figure 4-8 shows the location of the control points selected for analysis while Table 4.2 lists the distortions calculated. Overall the distortion in the along-track direction was greater than in the across-track direction on both the hard copy imagery and digital data for the north/south pass. Only three measurements could be obtained from the east/west data since the supplied digital tape was cut off at the juncture of the land and ice cover on the east side of the bay. However the measurements that were taken showed distortion in the along-track direction again being greater than across-track. The differences between the distortions calculated for along-and across-track in both pass directions could

Figure 4-8 - Location of Control Points for Distortion Calculation

TABLE 4.2

COMPARISON OF SAR IMAGERIES WITH TOPOGRAPHIC MAP MEASUREMENTS

MEASUREMENT SITES	IMAGERY		NS PASS DIGITAL		EW PASS DIGITAL		*MAP MEASUREMENT	
	SCALE 1:125,000	Dist km	SCALE 1:90,000	Error %	SCALE 1:90,000	Dist km	SCALE 1:50,000	Dist km
1 = A-B	6.8	4.6	8.1	21	7.7	12.3	6.5	
2 = B-D	8.6	2.4	9.3	10.7	7.8	7.1	8.4	
3 = A-C	9.0	0.0	10	14.1	---	---	9.0	
4 = C-D	4.0	5.1	4.4	16	---	---	3.8	
5 = A-D	7.3	2.8	6.6	7	6.0	15.5	7.1	
6 = B-C	7.3	1.4	6.8	5.5	---	---	7.2	
Average %	2.71 ± 1.92		11.9 ± 5.8		---			
Across Track								
Distortion	2.1		6.3					
Along Track								
Distortion	2.6		18.5					

be accounted for by a difference in azimuth and range dimensions of the pixels, with azimuth being greater. Shadow effects in the SAR data could also be contributing to the distortion calculated by increasing the difficulty in accurately locating measurement control points.

The next three sections describe the verification procedures conducted for targets analysed during the 1984 experiment. Each feature was analysed for its size, location and proximity to other targets.

4.2.1 Point Targets

The point targets analysed were located in the first-year ice cover adjacent to the Mould Bay field site (Figure 2-2). All targets appeared as bright dots of varying sizes on the SAR imagery. Only targets J1, J2, J3 and J4 are discussed here since J6 and J7 were not used as extensively during field measurements due to time constraints.

Table 4.3 lists the characteristics of point targets analysed. All targets had flat profiles with a central ice feature. In the case of J1, J2 and J4 there

TABLE 4.3
POINT TARGET CHARACTERISTICS

POINT TARGET	LENGTH (m)	WIDTH (m)	HEIGHT (m)	DESCRIPTION
J1	131.6	91.7	2.0	Flat profile, central rubble pile. Rubble pieces along perimeter.
J2	40.5	40.4	2.0	Rubbled profile, hard snow cover. Rubble piles in centre. Plate 4-18.
J3	101.6	101.2	1.0	Flat. Large tabular piece in centre. Longitudinal snow drifts. Ice rafting along perimeter.
J4	10.0	8.0	2.0	3 rubble pieces. Smallest target. Plate 4-19.
J6	48.1	53.1	4.0	Hard snow cover, snow drifts, series rubble piles in centre, rafted ice along perimeter.
J7	37.9	27.8	3.0	Snow covered rubble piles. Rafted ice between J6 and J7.

(Adapted from Lapp and Bjerkelund, 1984)

was rubbled ice two metres in height while J3 had a low tabular ice piece one metre in height. Each target also had rafting of ice around its perimeter which defined the targets limits. Plate 4-18 illustrates the central rubble pile of target J2 while Plate 4-19 shows the ice feature from J4. All J targets had a cover of hard-packed granular snow and were distinguishable from the surrounding ice cover by their 2 to 4 metre rubbled ice centres. J3 was the exception because its low profile made it difficult to distinguish in the field.

Table 4.4 presents the results of the point target measurements from the field compared to both the visual and digital analyses of the image. It is evident that the SAR was detecting individual targets approaching its 6m resolution as shown by the J4 target. Also, the length measurement which is perpendicular to the plane's east/west flight path had lower errors calculated than determined for the width measurement. This effect due to the orientation of the SAR when imaging was also evident when comparing the distortion calculated between the two passes (Table 4.2). Therefore errors were greatest along the plane's flight path than in the SAR's look direction. The greatest differences between the digital, visual and

Photo 8-25 - Two Pictures Taken at Target J4.

TABLE 4.4
COMPARISON OF TARGET DIMENSIONS

TARGET	TARGET LENGTH (m) (North-South Measurement)				TARGET WIDTH (m) (East-West Measurement)			
	Field Measure- ment	EW Pass Image Measure- ment	Digital Measurement		Field Measure- ment	EW Pass Image Measure- ment	Digital Measurement	
			EW (m)	Pass Error%			EW (m)	Pass Err
J1	132	80	78	40.9	92	100	66	28.
J2	41	29	42	2.4	40	34	30	25
J3	102	102	114	11.8	101	97	72	28.
J4	10	15	-	-	8	12	-	-
J6	-	-	60	-	-	-	36	-
J7	-	-	30	-	35	34	24	31.
SPECK FLOE	28	27	36	14.3	35	34	24	31.
FOOTHILLS	-	-	228	-	-	-	150	-
BARREL FLOE	91	112	120	5.5	78	71	66	15.
4 PEG FLOE	90	83	96	6.7	78	71	72	7.
COAST GUARD FLOE	89	83	108	21.3	162	151	126	22.
NORLAND FLOE	-	1036	1416	-	-	940	888	-
KA FLOE	-	1700	2592	-	-	1780	1752	-

field measurements came with targets over 100m in size. One of the reasons for the differences is that the orientation of the field measurement and the judgement of the target boundary in the field were difficult because of the snow cover present and the low profiles of some targets. In most cases small targets on the imagery had saturated signatures resulting in ill-defined boundaries. Features within these targets could not be easily identified because of signature blooming. Therefore in some cases it was difficult to relate the location of selected targets in the field to their corresponding signatures on the image. This coupled with pacing distances between ill-defined target boundaries during the field exercise resulted in suspect field measurements. However, as shown by Table 4.3, only three measurements of length and one of width taken in the field and from the imagery differed by more than 10m.

4.2.2 Floe Targets

All floes except for KA and Norland were situated in the first-year ice cover as shown in Plates 2-2 and 4-1. KA and Norland were part of the old ice field in the southern part of Mould Bay. All old ice floes analysed in

the field were identified based upon their thickness, salinity, and the presence of several growth interfaces in the vertical ice structure (Lapp and Bjerkelund, 1984). The differences between the signatures of Norland and KA floes were related to the surface relief present. As shown by Plate 4-20, KA's lower return was due to its being flatter and with fewer upturned ice blocks than on the Norland floe. Plate 4-21 shows the large ridge target from Norland floe. Also, darker areas which had little or no mottled texture, and which were evident in both floes, signified the presence of meltpond areas. Table 4.5 presents a comparison between the field, manual and digital measurements of targets within KA floe. As shown by targets KA-3 to KA-6 their sizes determined in the field were consistently less than those calculated both manually and digitally. All of these targets were less than 30m in size and were identified as block ice features. These differences in size calculation between techniques reflects the difficulty in determining target dimensions and edges in the field due to the snow cover present and the lack of distinguishing target features. Target KA-8, which approached 70m in size, was the only

TABLE 4.5

CHARACTERISTICS OF TARGETS WITHIN KA FLOE

TARGET	LENGTH (m)		DIGITAL		WIDTH (m)		DIGITAL		HEIGHT FIELD	COMMENTS
	FIELD	MANUAL	EW	NS	FIELD	MANUAL	EW	NS		
KA-1	--	30	--	--	--	22	--	--	2	Block
KA-2	--	--	24	18	--	--	24	24	2.4	Block
KA-3	2.5	9	12	12	2	9	12	12	1.5	Block
KA-4	5	18	18	--	2	18	12	--	1.5	Block
KA-5	7.5	26	24	*	7.5	20	18	*	1.8	Block
KA-6	17	33	30	*	7.5	23	18	*	2	Hummock
KA-7	--	21	24	--	--	12	18	--	2	Block
KA-8	70	78	72	72	15	48	36	30	3.8	Ridge
T-1	--	--	36	--	6.5	33	30	--	3.5	Block
T-2	12	27	12	--	--	--	12	--	5	Block

* Targets blended together.

observed target to have been determined to be larger in the field than in subsequent analysis. This target was a ridge and stood out as a distinct feature on the floor.

4.2.3 Triangulation

The field triangulation exercise was performed to chain distances between targets identified on the SAR imagery for later correlation with both manual and digital interpretations. Table 4.6 presents the measurements made in the field along with corresponding manual and digital measurements. Chained distances matched well with both manual and digitally calculated distances. The largest percentage error estimates occurred between the shortest chained distances. The effect due to the orientation of the radar while imaging, or the radar's aspect angle on the surface sensed, was apparent with most measured distances being normal to the north/south pass resulting in a smaller calculated error than for the east/west pass. However, the size of the error estimates reflect the difficulties with the field measurements. These measurements were taken over long distances using a survey tape and odometer on a tracked vehicle. Problems included difficulty in maintaining a straight line between point

TABLE 4.6

COMPARISON OF TARGET SEPARATION DISTANCES

TARGET	NS PASS:		NS PASS:		DIGITAL DATA		DIGITAL DATA		FIELD MEASUREMENT (km)
	ORIGINAL	ENLARGEMENT	EW PASS	NS PASS	Dist km	error%	Dist km	error%	
	Scale 1:125,000	Scale 1:62,200							
	Dist km	error%	Dist km	error%	Dist km	error%	Dist km	error%	
J1 to J2	1.44	2.7	1.42	1.4	2.008	43.4	2.02	44.3	1.4
J2 to J6	1.45	2	1.05	29.1	1.692	14.3	1.668	12.7	1.48
J6 to J7	0.0875	19	0.0933	13.6	0.156	44.4	0.144	33.3	0.108
J6 to Barrel Floe	1.21	17.7	1.19	19.1	1.571	6.8	1.554	5.7	1.47
Barrel Floe to J2	0.5	0.4	0.491	2.2	0.566	12.7	0.572	13.9	0.502
J2 to J3	0.35	5.1	0.323	12.5	0.424	14.9	0.424	14.9	0.369
J3 to Foothills	2.5	2	2.55	0	3.601	41.2	2.008	21.2	2.55
Coast Guard to Foothills	0.663	11.6	0.752	0.3	0.985	31.3	0.963	28.4	0.750
Coast Guard to Norland	0.375	25	0.368	22.8	0.588	17.6	0.486	2.8	0.5
4 Peg to Barrel	0.962	0.2	0.989	2.1	1.163	21.1	1.171	21.9	0.96
Barrel to Speck	0.338	39.6	0.355	36.6	0.485	13.3	0.485	13.3	0.56
KA to Twin Targets	0.175	60.7	0.323	27.4	0.255	42.7	0.241	45.8	0.445
ACID to Twin Targets	0.275	27.6	0.479	26.1	0.422	11.1	0.421	10.8	0.380
Width J6	0.0563	2.4	0.0559	1.6	0.036	34.5	0.048	12.7	0.055
Width Dead Zone	1.25	2.3	1.24	3.1	---	---	---	---	1.28
Average error %	14.6 ± 17.6	13.9 ± 12.9	24.95 ± 13.92	20.12 ± 13.32					

targets which sometimes were several kilometers apart. Also, floe and point target boundaries were not always apparent in the field and therefore could not be matched in later analysis since it was difficult to determine start and end measurement locations.

The limitations that became apparent during the visual analysis were also re-emphasized by the digital analysis. These were the probable inaccuracy of the chained field distances since there was no way to fix position accurately on the ice surface with the location of the target on the imagery. Also, some target signatures were saturated on the imagery due to a large amount of rubble ice. This caused them to appear larger than they actually were in the field since their edge locations could not be determined. However these limitations did not hinder the location of selected ice targets. The inaccurate measurements only affected the chaining of distances between them. Each feature identified on the imagery was matched to its location in the field and the comparison of ice types to imaged target signature was conducted.

The difficulty in the field verification lay in the limitations of the field measurements collected. The locating and verification of ice types to target signatures was not a problem; however, there were inaccuracies in determining measurement start and end points in analysis subsequent to field data collection. The next chapter discusses the problems raised by these limitations and presents the conclusions reached as a result of this work.

CHAPTER 5

CONCLUSIONS

5.1 Summary

This thesis analysed Intera STAR-1 SAR imagery collected in support of a joint AES/NRC sea-ice experiment conducted in early 1984. The main objective of this thesis was to analyse, using digital analysis techniques, the STAR-1 SAR data and to compare the results to those obtained in the field. A secondary objective was to investigate the application of digital analysis techniques to the SAR data. The objectives of this thesis were met through the execution of the following specific tasks:

1. application of available DIPIX software to achieve optimal enhancement of the SAR data
2. determine the size and distance between targets on a pixel-by-pixel basis for comparison with field measured distances
3. degrade imagery resolution to approach that of operational radars to determine relative loss of detail.

This study presented an application of remote sensing to the field of sea-ice studies of practical value to Arctic marine transportation and oil/energy development.

5.2 Limitations

The saturation of targets on the SAR imagery was an effect that could not be removed from the data. Measurement technique problems as described in Section 4.2.3 included the difficulty of relating positions on the ice cover to the corresponding positions on the imagery in both the manual and digital analyses. Field measurements were also suspect since one could not determine in hindsight how measurements in the field were oriented with respect to the boundaries of the targets analysed both visually and digitally.

5.3 Evaluation

This study demonstrated the usefulness of DIPIX image analysis techniques in the digital analysis of SAR imagery as opposed to the more common application with

multi-band data. Image analysis techniques were applied to the SAR data to enhance ice features. This exercise has shown that a combination of median and texture measure filtering yield the best results in terms of feature edge definition and speckle (noise) reduction. Both histogram equalized and linear stretches were effective in highlighting contrast present in the SAR data, while arithmetic functions highlighted features common to the orthogonal passes. Classification techniques did not yield useful results because of the requirement of multi channel data which were not available from the SAR data collected. However simple density slice techniques provided information not readily apparent on the median filtered radar image. Degradation of the SAR imagery to 18 and 30m resolutions demonstrated the loss of detail inherent in these systems. The 6m data was best for determining ice feature detail and texture while both the 18 and 30m resolutions were useful in ice type extent determination.

The comparisons between the field, manual and digitally calculated target sizes and distances between targets demonstrated the aspect angle effect inherent in

the imagery. Calculation of distortion showed the along-track distortion to be greater than the across-track in both the digital and hard copy imagery. Estimates of the error in both the manual and digital methods based on the calculated field distance measurements, and in the size measurements of targets investigated, were lowest between targets oriented with the radar look direction in the across-track direction. The largest percentage error estimates occurred between the smallest measured separation distances, while the greatest difference between field, manual and digital measurements of target size occurred with targets over 100m.

The SAR imagery proved to be a valuable tool in on-ice navigation during the 1984 experiment. The imagery provided an excellent representation of the ice cover with discrimination between first-year and multi-year ice targets being easily facilitated. The application of DIPIX image analysis software to the SAR data has demonstrated the use of such techniques in the enhancement of SAR ice data. The use of these techniques, many of which were developed for MSS data, has shown that SAR data can be successfully analysed. In terms of operations in

ice-frequented waters the findings of this thesis have demonstrated that techniques are available to manipulate SAR data in real-time, highlighting ice features of interest. Distortion inherent in the data has been shown to be consistent in orientation.

Synthetic Aperture Radar is a one channel imaging system, the implication being that one cannot clarify with absolute certainty the exact types of ice present when signatures overlap, an example of this being the similarity in backscatter between rough first-year ice and multi-year ice shown in Figure 2-11. In such cases the naked eye is needed to assist in the identification of ice types. Recent advances in the use of multi-channel systems such as passive microwave radiometers holds great promise in the distinguishing of ice types since multi-frequencies can identify more ice types than a single frequency. However, the main limitation with multi-frequency radiometers is that resolution is only high enough for ice navigation at close range applications. The distinct advantage of SAR lies in both its excellent resolution and its applicability from both airborne and spaceborne platforms.

5.4 Further Work

The increasing availability of SAR imagery has resulted in developments being made in techniques designed specifically for digital SAR analysis. As demonstrated earlier, tonal classifiers designed for MSS data give poor results when applied to SAR data. It is the development and application of analysis techniques such as texture filtering, as discussed by Ulaby et al., (1986) and Lowry (1984), that hold the most promise for the analysis of digital SAR data.

APPENDIX A

DIPIX IMAGE ANALYSIS SYSTEM

The digital analysis of the Mould Bay SAR data was carried out on a VAX 11/750 based DIPIX Aries-II image analysis system located at the AES Ice Centre in Ottawa. This system was purchased in 1984 to investigate the digital enhancement of NOAA weather satellite imagery used in operational ice forecasting (Ramsay and Zeiger, 1985). The DIPIX workstation consists of a VAX based computer terminal, high resolution graphics monitor, bit pad, and printer. It is from this workstation that the operator instructs the computer on how to analyse digital data. The user is prompted by the computer terminal, which is the focus of the user-system interaction (Piwawar, 1984). The printer records important events such as file creation/deletion and error messages while the colour monitor displays the imagery being analysed. The bit pad is used to manipulate the imagery on the colour monitor. An external tape drive loads data into the computer system.

and makes back-up copies of selected files. A system for obtaining screen output in the form of slides and prints is also provided.

The DIPIX Aries-II is a fully integrated image analysis system providing digital data processing capability based upon Aries application software. All Aries software is menu driven and executed through a series of prompts and questions. Each program, termed a task, is initiated and run from the Operator Interaction Sequence (OIS). Each Aries analysis task is designed by a two letter mnemonic, with program execution requiring the entry of a task identifier to begin running. All tasks execute once the program has been invoked and all parameters necessary to run the task entered. After program execution the system automatically returns to OIS. Table A.1 lists all the tasks available to run on the Ica Centre DIPIX system, along with a short summary of each tasks function. For a detailed description of the tasks listed the reader is referred to DIPIX (1984).

TABLE A.1SUMMARY OF DIPIX TASKS

<u>TASK</u>	<u>FUNCTION</u>
AG	- Annotation generation program.
AJ	- ACT-2 Ink Jet Plotter Image Data Recording Task.
AR	- Polynomial transform generation for arbitrary scale change and rotation.
AU	- Inter - signature distance calculation.
BC	- Convolution Filtering of Images.
BS	- Statistical Filtering.
BU	- Backup/Restore Utility.
CA	- Parallelepiped Classification Task.
CC	- Earth curvature correction.
CT	- Tabular summary of classifications.
CU	- Post classification filterer (clusterer).
DF	- File copy.
DP	- Fast classification program.
DRC	- Interactive Contour Drawing Program.
DS	- Destripe.
FCO	- Directory manipulation.
GC	- Image registration.
GG	- Grid-generation.
ID	- Image display.

TABLE A.1 (Continued)

<u>TASK</u>	<u>FUNCTION</u>
IE	- Image enhancement.
IT	- Interactive training area and signature generation.
IV	- Horizontal and Vertical image transposition.
LR	- Dropped line replacement.
LT	- Look-up table manipulation.
MD	- Median Filter.
ML	- Maximum likelihood classification.
MT	- Manual Theme File Generation.
NCT	- NOAA Infrared Temperature Conversion Program.
NO	- Arithmetic operations on feature files.
PD	- Pixel dump.
PP	- Printer hardcopy of theme file.
QD	- QCR image record.
RS	- Resampling program.
RT	- Lists and restores image files from BU or BR.
SLR	- AES SLAR image tape read program.
TC	- Comparison of two classifications.
TI	- Tape input (used to bring images off tape on to disk).

TABLE A.1 (Continued)

<u>TASK</u>	<u>FUNCTION</u>
TO	- LGSOWG Format Magnetic Tape Creation Program.
TPS	- Tape format characteristics acquisition.
TS	- Training area Statistics Generation and Display.
TX	- Texture measure filtering.
UC	- Unsupervised classifications.

BIBLIOGRAPHY

- Anderson, V.H. (1966). "High Altitude, Side-Looking Radar Images of Sea Ice in the Arctic", Proceedings of the Fourth Symposium on Remote Sensing of Environment, University of Michigan, Ann Arbor, pp. 845-857.
- Aviation Week and Space Technology (1984). "Airborne Radar Maps Canadian Ice Field", January 16.
- Bercha and Associates Limited (1982). "Quantification and Analysis of Ice Radar Signature Characteristics", Report Prepared for Atmospheric Environment Service, Environment Canada, Ottawa.
- Bjerkelund, C.A., D.J. Lapp and S. Prashker (1984). "An Investigation and Report on the Definition of the Physical Properties of Ice Types at Mould Bay and Isachsen, N.W.T., April 1984, Volume I: Field Data Results", report prepared by Norland Science and Engineering Limited for Ice Research and Development, Atmospheric Environment Service, Ottawa.
- Bjerkelund, C.A., D.J. Lapp, R.O. Ramseier and N.K. Sinha (1985). "The Texture and Fabric of the Second Year Ice Cover at Mould Bay, Prince Patrick Island, N.W.T., April 1983", Proceedings of the 1985 International Geoscience and Remote Sensing Symposium, October 7-9, University of Massachusetts, Amherst, pp. 426-431.
- Blom, R.G. and M. Daily (1982). "Radar Image Processing for Rock Type Discrimination", IEEE Transactions on Geoscience and Remote Sensing, Vol. GE-20, No. 3, pp. 343-351.
- Bregha, F. (1982). "Arctic Pilot Project: CARC's Memorandum to Cabinet", Northern Perspectives, Vol. 10, No. 3.
- Bullock, B. and M.E. Kirby (1982). "Technology Transfer at Work", GEOS, Vol. 11, No. 1, pp. 5-9.
- Campbell, W.J., P. Gloersen, H.J. Zwally, R.O. Ramseier and C. Elachi (1977). "Simultaneous Passive and Active Microwave Observations of Near-Shore Beaufort Sea Ice", Proceedings of the 9th Offshore Technology Conference, Houston, pp. 287-294.

- Carsey, F.D. (1982). "Remote Sensing as a Research Tool", in Air-Sea-Ice Interaction, edited by N. Untersteiner.
- Colwell, R.N. (ed.) (1983). "Manual of Remote Sensing, Volume I", American Society of Photogrammetry, Falls Church, Virginia.
- Curlander, J.C., B. Holt and K. Hussey (1985). "Determination of Sea Ice Motion Using Digital SAR Imagery", Journal of Oceanic Engineering, Vol. OE-10, No. 4, pp. 358-367.
- Cutrona, L.J. (1970). "Synthetic Aperture Radar", in Radar Handbook, M. Skolnik (ed.), Chapter 23.
- Daily, M. (1983). "Hue-Saturation-Intensity Split-Spectrum Processing of SEASAT Radar Imagery", Photogrammetric Engineering and Remote Sensing, Vol. 49, No. 3, pp. 349-355.
- Dey, B.B. (1981). "Shipping Routes, Ice Cover and Year-Round Navigation in the Canadian Arctic", Polar Record, Vol. 20, No. 129, pp. 549-559.
- Digby, S.A. (1982). "Mould Bay Sea Ice Experiment I, Summary and Surface Characteristics Report", RADARSAT Report 82-15.
- DIPIX Systems Ltd. (1984). "Aries II V-Stream Application Software Package User's Manual", Ottawa, Ontario.
- Doronin, Y.P. and D.E. Kheisin (1977). "Sea Ice", Amerind Publishing Company Limited, New York.
- Dotto, L. (1980). "Prospectors in the Sky", Canadian Business, April.
- Fox, M.F. (1979). "Introduction to Environmental Remote Sensing", Carleton University Teaching Manual.
- Fu, L.L. and B. Holt (1982). "Seasat Views Oceans and Sea Ice with Synthetic Aperture Radar", Jet Propulsion Laboratory, Publication 81-120, Pasadena.

Glorsen, P., W. Nordberg, T.J. Schmugge, T.T. Wilheit and W.J. Campbell (1973). "Microwave Signatures of First-Year and Multi-Year Sea Ice", Journal of Geophysical Research, Vol. 78, No. 18, pp. 3564-3572.

Gogineni, S., R.G. Onstott, R.K. Moore and J. Chancellor (1984). "Intermediate Results of Radar Backscatter Measurements from Summer Sea Ice", Remote Sensing Laboratory Technical Report 331-2, University of Kansas Centre for Research Incorporated, Lawrence Kansas.

Goodenough, D.G., K.J. O'Neill, L.A. Gordon, J. Yan, T. Fisher, C.L. MacDonald and A. DesRochers (1979). "Standard Format for the Transfer of Geocoded Polygon Data", CCRS Research Report 79-3.

Government of Canada (1982). "Canada in Space".

Government of Canada (1977). "Satellites and Sovereignty".

Gray, A.L., R.K. Hawkins, C.E. Livingstone, L.D. Arsenault, and W.M. Johnstone (1982). "Simultaneous Scatterometer and Radiometer Measurements of Sea-Ice Microwave Signatures", IEEE Journal of Oceanic Engineering, Vol. OE-7, No. 1, pp. 20-32.

Gray, A.L., R.O. Ramseier and W.J. Campbell (1977). "Scatterometer and SLAR Results Obtained Over Arctic Sea-Ice and Their Relevance to the Problems of Arctic Ice Reconnaissance", Proceedings of the 4th Canadian Symposium on Remote Sensing, Quebec City, pp. 424-443.

Guindon, B. and D.G. Goodenough (1982). "Spectral-Spatial Analysis of X and L Band SAR Imagery of Arctic Sea-Ice", Proceedings of Advances in Instrumentation for Processing and Analysis of Photogrammetric and Remotely Sensed Data, August 30 - September 3, Ottawa, pp. 506-521.

Harvie, J.M., J. Cihlar and C. Goodfellow (1982). "Surface Cover Mapping in the Arctic Through Satellite Remote Sensing", CCRS User's Manual 82-1.

- Hollinger, J.P., B.E. Troy, Jr., R.O. Ramseier, K.W. Asmus, M.F. Hartman, and C.A. Luther (1984). "Microwave Emission from High Arctic Sea Ice During Freeze-up", Journal of Geophysical Research, Vol. 89, No. C5, pp. 8104-8122.
- Holmes, Q.A., D.R. Nuesch and R.A. Schuchman (1984). "Textural Analysis and Real-Time Classification of Sea-Ice Types Using Digital SAR Data", IEEE Transactions on Geoscience and Remote Sensing, Vol. GE-22, No. 2, pp. 113-120.
- Holt, B. and S.A. Digby (1984). "Processes and Imagery of Fast First Year Sea Ice During the Melt Season", Journal of Geophysical Research, Vol. 90, No. C3, pp. 5045-5062.
- Intera Technologies Limited (1984). "STAR System", Promotional Brochure, Calgary.
- Jensen, H., D.C. Graham, L.J. Porcello and E.N. Leith (1977). "Side-looking Airborne Radar", Scientific American, 237, pp. 84-95.
- Johns, H.O. (1985). "Tailor-made Technology for Each Area as North America Arctic Energy Flows", Offshore Resources, Vol. 3, No. 1, pp. 8-13.
- Johnson, J.D. and L.D. Farmer (1971). "Use of Side-Looking Airborne Radar for Sea-Ice Identification", Journal of Geophysical Research, Vol. 76, No. 9, pp. 2138-2155.
- Ketchum Jr., R.D. and L.D. Farmer (1980). "Eastern Arctic SURSAT SAR Ice Experiment: Radar Signatures of Sea Ice Features", Proceedings of the Final SURSAT Ice Workshop, R.O. Ramseier and D.J. Lapp eds., Section 5.2.
- Kim, Y.S., R.K. Moore and R.G. Onstott (1984). "Theoretical and Experimental Study of Radar Backscatter from Sea Ice", Remote Sensing Laboratory Technical Report 331-37, University of Kansas Centre for Research Incorporated, Lawrence Kansas.

- Kirby, M.E. (1980). "Digital Image Analysis of SAR Imagery for the Detection of Icebergs", Proceedings of the Final SURSAT Ice Workshop, Atmospheric Environment Service, Toronto, June 23-27, Section 5.14.
- Kovacs, A. and R.M. Morey (1979). "Anisotropic Properties of Sea Ice in the 50 to 150 MHz Range", Journal of Geophysical Research, Vol. 84, No. C9, pp. 5749-5759.
- Lapp, D.J. and C. Bjerkelund (1984). "An Investigation and Report on the Definition of the Physical Properties of Ice Types at Mould Bay and Isachsen, N.W.T., April 1984, Volume II - Ground Truth Data and Manual Analysis of STAR-1 SAR Imagery", report prepared by Norland Science and Engineering Limited for Ice Research and Development, Atmospheric Environment Service, Ottawa.
- Lapp, D.J., C. Bjerkelund and S. Prashker (1984). "Investigation and Documentation of Second Year and First Year Ice Characteristics at Mould Bay, N.W.T., Phase I - Field Data Report", report prepared by Norland Science and Engineering Limited for Ice Research and Development, Atmospheric Environment Service, Ottawa.
- LaParade, G.L. (1976). "Basic Concepts of Synthetic Aperture, Side-Looking Radar", Goodyear Aerospace Corporation, Report 61B-9167.
- Leberl, F., M.L. Bryan, C. Elachi, T. Farr, and W.J. Campbell (1979). "Mapping of Sea Ice and Measurement of Its Drift Using Aircraft Synthetic Aperture Radar Images", Journal of Geophysical Research, Vol. 84, pp. 1827-1835.
- Li, F.K. and M. Leonard Bryan (1983). "Tradeoffs Among Several Synthetic Aperture Radar Image Quality Parameters: Results of a User Survey Study", Photogrammetric Engineering and Remote Sensing, Vol. 49, No. 6, pp. 791-803.
- Lillesand, T.M. and R.W. Kiefer (1979). "Remote Sensing and Image Interpretation", John Wiley and Sons, New York.

- Livingstone, C.E., R.K. Hawkins, A.L. Gray, L.D. Arsenault, K. Akamoto, T.L. Wilkinson, and D. Pearson (1983). "The CCRS/SURSAT Active-Passive Experiment 1978-1980 - The Microwave Signatures of Sea-Ice Types and Features and Their Implications for Remote Sensing", CCRS Report, June.
- Livingstone, C.E., D. Hudson, J.D. Lyden, C.L. Liskow, R.A. Shuchman and R.T. Lowry (1983). "Gain Compression Effects in SAR Imagery", Proceedings of the Seventeenth International Symposium on Remote Sensing of Environment, Vol. III, May 9-13, Ann Arbor, pp. 1109-1116.
- Livingstone, C.E., R.G. Onstott, R.K. Hawkins, L.D. Arsenault, A.L. Gray, and K.P. Singh (1985). "Microwave Sea Ice Signatures Near the Onset of Melt", submitted to IEEE Journal of Geoscience and Remote Sensing.
- Lowry, R.T., D.R. Inkster and M.E. Kirby (1979). "Ice and Iceberg Studies using State-of-the-art Remote Sensing", presented at the Port and Ocean Engineering under Arctic Conditions, Norwegian Institute of Technology.
- Lowry, R.T., S. Shlien and D.G. Goodenough (1978). "A CCRS Systems for Synthetic Aperture Radar Imagery Analysis", Proceedings of the 5th Canadian Symposium on Remote Sensing, Victoria, pp. 363-371.
- Lowry, R.T., G.W. Wessels and D.R. Inkster (1984). "Optimizing Image Quality for SAR", Proceedings of IGARSS Symposium, August 27-30, Strasbourg.
- Lowry, R.T. (1985). Course Notes; Short Course on Snow and Ice Studies, Alberta Remote Sensing Centre, May 5-9.
- MANICE (1980). "Manual of Standard Procedures and Practices for Observing and Reporting Sea Ice Conditions," Fifth Edition, Environment Canada, Toronto.
- Martin, S. and P. Kaufman (1981). "A Field and Laboratory Study of Wave Damping by Grease Ice, "Journal of Glaciology, Vol. 27, No. 96.

- McAvoy, J. and R.T. Lowry (1985). "A Shipboard Ice Navigation System", Proceedings of the Radarsat Workshop, June 10, Ottawa, pp. 3-1 - 3-10.
- Nakawo, M. and N.K. Sinha (1981). "Growth Rate and Salinity Profile of First-Year Sea Ice in the High Arctic", Journal of Glaciology, Vol. 27, No. 96, pp. 315-330.
- Nichols, A., T. Gaffield, J. Wilhelm, R. Inkster and S. Leung (1984). "A SAR for Real-Time Ice Reconnaissance", Proceedings of IGARSS Symposium, August 27-30, Strasbourg.
- Offshore Resources (1985). "Enhanced Marine Radar being used to Extend Arctic Shipping Season", Vol. 3, No. 1, pp. 20.
- Offshore Resources (1984). "Advanced Radar Gives Sharp Image", Vol. 2, No. 2, pp. 62-63.
- OILWEEK (1985). "Airborne Radar Proving up a Worldwide Market", Vol. 35, No. 52, pp. 14-15.
- Onstott, R.G. (1984). "1983 Marginal Ice Zone Experiment", Remote Sensing Laboratory Technical Report 331-32, University of Kansas Centre for Research Incorporated, Lawrence Kansas.
- Onstott, R.G. and S.P. Gogineni (1985). "Active Microwave Measurements of Arctic Sea-Ice under Summer Conditions", Journal of Geophysical Research, Vol. 90, No. C3, pp. 5035-5044.
- Onstott, R.G., and R.K. Moore (1984). "Active Microwave Measurements of Sea Ice in the Marginal Ice Under Summer Conditions", Proceedings of IGARSS '84 Symposium, Strasbourg, 27-30 August, pp. 359-363.
- Onstott, R.G. R.K. Moore, S. Gogineni, and C. Delker (1982). "Four Years of Low Altitude Sea-Ice Broadband Backscatter Measurements", IEEE Journal of Oceanic Engineering, Vol. OE-7, January, pp. 44-50.

- Onstott, R.G. R.K. Moore, and W.F. Weeks (1979).
"Surface-Based Scatterometer Results of Arctic Sea Ice", IEEE Transactions, Vol. GE-17, No. 3, pp. 78-85.
- Page, D.F. and R.O. Ramseier (1975). "Applications of Radar Techniques to Ice and Snow Studies", Journal of Glaciology, Vol. 15, No. 73, pp. 171-191.
- Piwowar, J.M. (1984). "Aries II Image Analysis System User's Guide", University of Waterloo, Waterloo, Ontario.
- Pravdo, S.H., B. Honeycutt, B.M. Holt and D.N. Held (1983). "Seasat Synthetic Aperture Radar Data User's Manual", Jet Propulsion Laboratory, Publication 82-90, Pasadena.
- Ramsay, B. and M. Zieger (1986). "Enhancement of NOAA AVHR Digital Data for Sea Ice Analysis in an Operational Environment", Proceedings of the Canadian East Coast Workshop on Sea-Ice, January 7-9, pp. 495-508.
- Ramseier, R.O. (1985). Course Notes, Short Course on Snow and Ice, Alberta Remote Sensing Centre, May 5-9.
- Ramseier, R.O. (1983). "Classification of River and Lake Ice Based on its Genesis Structure and Texture, and Methods of Sample Preparation and Evaluation", Atmospheric Environment Service, Lecture Notes for Course 45:536, Department of Geography, Carleton University.
- Raney, R.K. (1982). "RADARSAT - Canada's National Radar Satellite Program", IEEE Geoscience and Remote Sensing Newsletter, March, pp. 5-9.
- Rossiter, J.R., L.D. Arsenault, A.L. Gray, E.V. Guy, D.J. Lapp, R.O. Ramseier and E. Wedler (1984). "Detection of Icebergs by Airborne Imaging Radars", Proceedings of the 9th Canadian Symposium on Remote Sensing, St. John's, pp. 39-48.

- Shaw, E., R.K. Raney, E.J. Langham, and W.M. Strome (1984). "Radarsat - Canada's Remote Sensing Satellite Program", Proceedings of the 9th Canadian Symposium on Remote Sensing, St. Johns, pp. 1-8.
- Shroeder, L.C., W.L. Jones, P.R. Schaffner and J.L. Mitchell (1984). "Flight Measurement and Analysis of AAFE RADSCAT Wind Speed Signature of the Ocean", NASA Technical Memorandum 85646.
- Skolnik, M. (1962). "Introduction to Radar Systems", McGraw-Hill Book Company, New York.
- Skolnik, M. (1970). "Radar Handbook", McGraw-Hill Book Company, New York.
- Sneyd, A.R. and M.P. Luce (1984). "SLAR as a Tactical Aid to Navigation in Ice", Proceedings of the 9th Canadian Symposium on Remote Sensing, August 14-17, St. Johns, pp. 49-56.
- Simonett, D.S. and R.E. Davies (1983). "Image Analysis-Active Microwave", in Manual of Remote Sensing, Volume I, R.N. Colwell (ed.), Chapter 25.
- Teillet, P.M. (1978). "Digital Analysis of Multi-Channel Radar Data at CCRS", in Surveillance of Environmental Pollution and Resources by Electromagnetic Waves, D. Reidel Publishing Company, Dordrecht, Holland, pp. 381-385.
- Tezeki, P.G., W.J. Campbell, R.O. Ramseier and D. Ross (1979). "The Offshore Environment: A Perspective from Seasat-1 SAR Data", proceedings of the 11th Offshore Technology Conference, Houston Texas, April 30 - May 3, pp. 215-224.
- Transport Canada (1970a). "Arctic Waters Pollution Prevention Act", Arctic Shipping Pollution Prevention Regulations, Chapter 353.
- Transport Canada (1970b). "Shipping Safety Control Zones Order", Arctic Shipping Pollution Prevention Regulations, Chapter 356.

- Ulaby, F.T., R.K. Moore and A.K. Fung (1981). "Microwave Remote Sensing: Active and Passive - Volume I Microwave Remote Sensing Fundamentals and Radiometry", Addison-Wesley Publishing Company, Reading, Massachusetts..
- Ulaby, F.T., R.K. Moore and A.K. Fung (1982). "Microwave Remote Sensing: Active and Passive - Volume II Radar Remote Sensing and Surface Scattering and Emission Theory", Addison-Wesley Publishing Company, Reading, Massachusetts.
- Ulaby, F.T., F. Kouyate, B. Brisco and T.H. Lee Williams (1986). "Textural Information in SAR Images", IEEE Transactions on Geoscience and Remote Sensing, Vol. GE-24, No. 2, pp. 235-245.
- Van de Lindt, W.J. (1977). "Digital Technique for Generating Synthetic Aperture Radar Images", IBM Journal of Research and Development, September, pp. 415-432.
- Vant, M.R., R.B. Gray, R.O. Ramseier and V. Makios (1974). "Dielectric Properties of Fresh and Sea Ice at 10 and 35 GHz", Journal of Applied Physics, Vol. 45, No. 11, pp. 4712-4717.
- Vant, M.R., R.W. Herring and E. Shaw (1979). "Digital Processing Techniques for Satellite-Borne Synthetic Aperture Radars", Canadian Journal of Remote Sensing Vol. 5, No. 1, pp. 67-73.
- Vant, M.R., R.O. Ramseier and V. Makios (1978). "The Complex Dielectric Constant of Sea Ice at Frequencies in the Range 0.1 - 40 GHz", Journal of Applied Physics, Vol. 49, pp. 1264-1280.
- Weeks, W.F. (1981). "Sea-Ice: The Potential of Remote Sensing", Oceanus, Vol. 24, No. 3, pp. 39-47.
- Weeks, W.F. and S.F. Ackley (1982). "The Growth, Structure, and Properties of Sea Ice", CRREL Monograph 82-1.

- Weeks, W.F., A.G. Fountain, M.C. Bryan and C. Elachi (1978). "Differences in Radar Return from Ice-Covered North Slope Lakes", Journal of Geophysical Research, Vol. 83, No. C8, pp. 4069-4073.
- Weeks, W.F. and A.J. Gow (1980). "Crystal Alignment in the Fast Ice of Arctic Alaska", Journal of Geophysical Research, Vol. 84, No. C10, pp. 1137-1146.
- Weeks, W.F., A.J. Gow and R.J. Schertler (1981). "Ground-truth Observations of Ice-Covered North Slope Lakes Imaged by Radar", CRREL Report 81-19.
- Weeks W.F., P. Sellmann and W.J. Campbell (1977). "Interesting Features of Radar Imagery of Ice-Covered North Slope Lakes", Journal of Glaciology, Vol. 18, No. 78, pp. 129-136.
- Weller, G., F. Carsey, B. Holt, D.A. Rothrock and W.F. Weeks (1983). "Science Program for an Imaging Radar Receiving Station in Alaska", California Institute of Technology, Pasadena, California.
- Williams, R. (1985). "Radar Imaging of Lake Ice at Mould Bay, N.W.T.", unpublished paper, Carleton University Geography Department, course 45:536.
- Williams, D. (1985). "Texture measure Filtering Program", Software prepared by DMR and Associates for Ice Branch, Atmospheric Environment Service, Ottawa.
- Wu, C. (1976). "A Digital System to Produce Imagery from SAR Data", Jet Propulsion Laboratory, Report 76-968, Pasadena, California.

END

29/06/89

FIN