1

MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS
STANDARD REFERENCE MATERIAL 1010a
(ANSI and ISO TEST CHART No 2)

National Library
of Canada

Bibliothèque nationale
du Canada

Canadian Theses Service Service des thèses canadiennes

Ottawa, Canada
K1A 0N4

NOTICE

The quality of this microform is heavily dependent upon the quality of the original thesis submitted for microfilming. Every effort has been made to ensure the highest quality of reproduction possible.

If pages are missing, contact the university which granted the degree.

Some pages may have indistinct print especially if the original pages were typed with a poor typewriter ribbon or if the university sent us an inferior photocopy.

Reproduction in full or in part of this microform is governed by the Canadian Copyright Act, R.S.C. 1970, c. C-30, and subsequent amendments.

AVIS

La qualité de cette microforme dépend grandement de la qualité de la thèse soumise au microfilmage. Nous avons tout fait pour assurer une qualité supérieure de reproduction.

S'il manque des pages, veuillez communiquer avec l'université qui a conféré le grade.

La qualité d'impression de certaines pages peut laisser à désirer, surtout si les pages originales ont été dactylographiées à l'aide d'un ruban usé ou si l'université nous a fait parvenir une photocopie de qualité inférieure.

La reproduction, même partielle, de cette microforme est soumise à la Loi canadienne sur le droit d'auteur, SRC 1970, c. C-30, et ses amendements subséquents.

Deformations and Stresses in Pipelines Buried in Freezing Ground

by

Ketan R. Shah, B.Tech.(Civil)
Indian Institute of Technology, Bombay, 1988

A thesis submitted to
The Faculty of Graduate Studies and Research
in partial fulfillment of the requirements
for the degree of
Master of Engineering

**Department of Civil Engineering
Carleton University, Ottawa
Ontario, Canada
August, 1990**

©copyright
1990, K. R. Shah

National Library
of Canada

Bibliothèque nationale
du Canada

Canadian Theses Service Service des thèses canadiennes

Ottawa, Canada
K1A 0N4

NOTICE

The quality of this microform is heavily dependent upon the quality of the original thesis submitted for microfilming. Every effort has been made to ensure the highest quality of reproduction possible.

If pages are missing, contact the university which granted the degree.

Some pages may have indistinct print especially if the original pages were typed with a poor typewriter ribbon or if the university sent us an inferior photocopy.

Reproduction in full or in part of this microform is governed by the Canadian Copyright Act, R.S.C. 1970, c. C-30, and subsequent amendments.

AVIS

La qualité de cette microforme dépend grandement de la qualité de la thèse soumise au microfilmage. Nous avons tout fait pour assurer une qualité supérieure de reproduction.

S'il manque des pages, veuillez communiquer avec l'université qui a conféré le grade.

La qualité d'impression de certaines pages peut laisser à désirer, surtout si les pages originales ont été dactylographiées à l'aide d'un ruban usé ou si l'université nous a fait parvenir une photocopie de qualité inférieure.

La reproduction, même partielle, de cette microforme est soumise à la Loi canadienne sur le droit d'auteur, SRC 1970, c. C-30, et ses amendements subséquents.

ISBN 0-315-60457-3

The undersigned hereby recommend to the Faculty of Graduate Studies and Research acceptance of the thesis,

**"Deformations and Stresses in Pipelines
Buried in Freezing Ground"**

submitted by
Ketan R. Shah, B. Tech.

in partial fulfillment of the requirements for
for the degree of *Master of Engineering*

(Dr. A. G. Razaqpur)

Thesis Supervisor

(Dr. J. L. Humar)

Professor and Chairman

Department of Civil Engineering

Carleton University

Ottawa

August, 1990

To My Parents

Abstract

When a buried pipeline carrying chilled gas passes through unfrozen ground, freezing around the pipeline causes heave. The present study is aimed at evaluating the deformation and stresses in the pipeline and surrounding soil caused by the process of heaving. The Rigid-Ice model of frost heave (RIM) is adopted to achieve this objective. This model is one of the most comprehensive frost heave models, but in its present form it cannot be applied to two or three-dimensional cases, a situation that exists around actual buried pipelines. A two-dimensional form of the model is proposed and applied to the freezing around chilled gas pipelines. The nonlinear partial differential equations governing the heat and moisture transfer phenomenon and regelation process are solved using the finite element method in conjunction with an iterative time-marching scheme. The solution involves a large amount of computation and hence a simple procedure is proposed to reduce the computational time without significantly altering the final magnitude of heave.

The RIM in its existing form assumes soil grains to be incompressible. To date models which include the effect of the compressibility of soil grains couple the stress analysis with the heat and moisture transfer during the freezing process. It is shown here that an uncoupled elasto-plastic stress analysis of freezing soil can be carried out to obtain an accurate estimate of the magnitude of heave and of soil and pipeline stresses. The study highlights the significance of a quasi-consolidation process, caused by a reduction in the soil pore pressure, on the magnitude of heave. An interface element is included in the analysis to account for the effect of loss of contact between the pipe and surrounding soil. Two computer programs are developed, the first of which deals with heat and moisture transfer analysis and the second with the nonlinear stress analysis. For verification of the computer programs developed, several one-dimensional and two-dimensional numerical examples are

solved and the results are compared with available analytical and experimental data, with reasonable agreement between them.

Acknowledgments

The author wishes to express his gratitude to Prof. A. G. Razaqpur, under whose supervision this research-work was carried out, for his able guidance, advice, encouragement and useful suggestions.

The author also thanks Prof. P. J. Williams and Dr. O. J. Svec for providing several useful discussions on frost heave. Thanks are also due to Dr. Kevin O'Neill for his fruitful suggestions on frost heave modelling.

I am grateful to my parents and to my sister for their continuous love and support. I would like to thank my friends and colleagues for their help.

The scholarships provided by Department of Civil Engineering, Carleton University are gratefully acknowledged.

Table of Contents

Abstract	iv
Acknowledgments	vi
Table of Contents	vii
Notation	x
List of Figures	xviii
List of Tables	xxi
1 Introduction	1
1.1 General	1
1.2 Frost Heave Mechanism	3
1.2.1 <i>Moisture Migration</i>	3
1.2.2 <i>Freezing Fringe</i>	4
1.2.3 <i>Capillary Theory</i>	5
1.2.4 <i>Clausius-Clapeyron Equation</i>	7
1.2.5 <i>Overburden Pressure and Shut-off Pressure</i>	9
1.2.6 <i>Stress Partition Factors</i>	9
1.2.7 <i>Frost Heaving and Ice-lens Formation Criteria</i>	11
1.2.8 <i>Segregation Potential Concept</i>	12
1.2.9 <i>Regelation</i>	13
1.3 Frost Heave Models	15
1.4 Limitation of Present Frost Heave Models	21

1.5	Frost Heave and Pipelines	22
1.6	Objective and Scope	23
1.7	Structure of Thesis	24
2	2-D Rigid-Ice Model	28
2.1	General	28
2.2	Phase Equilibrium	29
2.3	Transport Equations	31
2.3.1	<i>Mass Transport Equation</i>	31
2.3.2	<i>Energy Transport Equation</i>	34
2.4	Calculation of Ice Velocity	35
2.5	Boundary Conditions	36
2.6	Lens Initiation	38
2.7	Variation of Physical Parameters in Transport Equations	39
2.8	Finite Element Formulation	41
3	Numerical Solution Strategies	52
3.1	General	52
3.2	8-Noded Isoparametric Element	53
3.3	Numerical Integration and Surface Normals	54
3.4	Evaluation of The Direction of Ice-Velocity	56
3.5	Stability and Oscillation	56
3.6	Thermal Properties of Frozen Region	57
3.7	Convergence and Time-Step Adjustments	57

	ix
3.8 Solution Procedure	58
4 Stress Analysis	65
4.1 General	65
4.2 The Constitutive Equations	66
4.3 Constitutive Models	69
4.4 Interface Element	73
4.5 Mechanical Properties of Frozen Soil	75
4.6 Finite Element Implementation	76
4.7 Tangential Stiffness Method	78
5 Results and Discussion	82
5.1 General	82
5.2 One-Dimensional Examples	84
5.2.1 <i>Example I</i>	84
5.2.2 <i>Example II</i>	87
5.3 Two-Dimensional Example	88
6 Summary, Conclusions and Recommendations	114
6.1 Summary and Conclusions	114
6.2 Recommendations For Future Work	116
References	120
Appendix A	127

Notation

The following symbols are used here. All the matrices are represented by bold-faced symbols. All the vectors are either represented by bold-faced symbols or are enclosed in { }.

A	= pressure difference, ϕ_{iw} per unit water pressure
A_{el}	= area of a finite element
A_i	= area of an ice-lens over an element, Fig. 4
$\mathbf{A}_k$	= vector of constant coefficients to be obtained by curve fitting unfrozen water content data
$\mathbf{a}$	= derivative of yield function with stress vector
$\mathbf{a}_1$	= a coefficient vector given by Eq. (4.17a)
$\mathbf{a}_2$	= a coefficient vector given by Eq. (4.17b)
$\mathbf{a}_3$	= a coefficient vector given by Eq. (4.17c)
a_g	= an arbitrary function in Eq. (2.36)
B	= pressure difference, ϕ_w per unit temperature
B_1	= a coefficient given by Eq. (2.34a)
B_2	= a coefficient given by Eq. (2.34b)
B_3	= a coefficient given by Eq. (2.34c)
B_4	= a coefficient given by Eq. (2.34d)
B'	= strain-displacement relationship matrix
$\mathbf{b}$	= body forces
b_1, b_2	= empirical constants in Eq. (4.29)
b_3, b_4, l	= empirical constants in Eq. (4.30)
b_5, b_6	= empirical constants in Eq. (4.31)
C	= cohesion in soil
C_1	= a constant given by Eq. (4.19a) or (4.21a)
C_2	= a constant given by Eq. (4.19b) or (4.21b)

C_3	= a constant given by Eq. (4.19c) or (4.21c)
C_a	= volumetric heat capacity of soil
C_{eff}	= effective heat capacity
C_f	= apparent heat capacity of frozen soil
C_i	= volumetric heat capacity of ice
C_w	= volumetric heat capacity of water
c_1	= arbitrary weight function in eq. (2.35)
c_2	= arbitrary weight function in eq. (2.35)
c_i	= specific heat capacity of ice
c_s	= specific heat capacity of soil grains
c_w	= specific heat capacity of water
D_e	= elasticity matrix
D_{ep}	= tangential elasto-plastic matrix
d_1	= arbitrary weight function in eq. (2.35)
d_2	= arbitrary weight function in eq. (2.35)
d_3	= arbitrary weight function in eq. (2.35)
d_D	= $D_e a$
E	= modulus of elasticity
E_i	= initial elastic modulus
E_T	= tangential elastic modulus
F	= yield surface
F'	= curvature of a capillary pore
F_1	= a load vector due to external forces
F_n	= a load vector due to the change in neutral pressure
F'_n	= force in the tangential spring at interface
F_p	= a load vector due to the volumetric strains in the soil grains caused by the change in neutral pressure
F_T	= a load vector due to the thermal strains
F_v	= a load vector due to the volumetric strains caused by freezing
f_1	= a water flux vector in Eq. (2.43a)

$\mathbf{f}_2$	= a heat flux vector in Eq. (2.43b)
G	= volumetric grain content
g	= gravitational acceleration
$grad h$	= gradient of height from datum
$grad P_w$	= gradient of water pressure
$grad T$	= gradient of temperature in the freezing fringe
h_w	= depth of the warm end from water table
I	= volumetric ice content
I_t	= total thickness of ice-lenses in any direction
I'	= derivative of ice content with the pressure difference ϕ_{iw}
i	= x, y, z
$ \mathbf{J} $	= determinant of the Jacobian of integration
$\mathbf{JP}$	= heat flux per unit rate of change of water pressure
$\mathbf{JT}$	= heat flux per unit rate of change of temperature
J_s	= determinant of the Jacobian of the line integration
$\mathbf{K}$	= permeability matrix of soil
$\mathbf{K}_{ep}$	= tangential elastoplastic stiffness matrix
K_s	= bulk modulus of soil grains
k_d	= permeability of soil in any direction
$\mathbf{K}'$	= stiffness matrix of interface element in local directions
$\mathbf{K}'_1$	= stiffness matrix of the interface in global directions
$\mathbf{K}'_2$	= stiffness matrix of the interface element
L	= latent heat of fusion of water
M	= number of Gauss points
$\mathbf{MP}$	= water flux per unit rate of change of water pressure
$\mathbf{MT}$	= water flux per unit rate of change of temperature
$\mathbf{m}'$	= equal to unity for the normal stress components and zero for shear stress components
$\mathbf{N}$	= shape function matrix
$\mathbf{N}'$	= a matrix of shape functions for the stress analysis

N_k	= k th shape function
n	= porosity of soil
n_{11}	= X -component of a normal to the surface
n_{12}	= Y -component of a normal to the surface
$\mathbf{n}_1$	= a normal to S_1 going away from R_1
$\mathbf{n}_2$	= an outward normal to S_2
$\mathbf{n}_g$	= a normal to surface S
$\mathbf{n}_v$	= unit vector normal to the warmest ice-lens
n_{v1}	= horizontal scalar components of the unit normal vector $\mathbf{n}_v$
n_{v2}	= vertical scalar components of the unit normal vector $\mathbf{n}_v$
$\mathbf{n}'$	= a normal to surface S' passing through the given point
nn	= number of nodes in a finite element
$\mathbf{P}$	= boundary tractions
P_1	= given by Eq. (2.33a)
P_2	= given by Eq. (2.33b)
P_3	= given by Eq. (2.33c)
P_i	= ice pressure
P_w	= water pressure
$\mathbf{P}_w^s$	= vector containing nodal values of water pressure
$(\mathbf{P}_w^s)_m$	= vector of nodal water pressures at the beginning of m th time step
$(\mathbf{P}_w^s)_{m+1}$	= vector of nodal water pressures at the end of m th time step
$(\mathbf{P}_w^s)^*$	= water pressure vector at which dependent parameters are evaluated
q_2	= specified moisture flow on boundary S_2
q_h	= heat flux due to conduction
q_{h1}	= heat flow in R_2 at boundary S_1
q_{h2}	= specified heat flow on boundary S_2
q_{h2}	= specified heat flow on boundary S_3
q_{hg}	= specified heat flow on boundary S
R_1	= lens-free region

R_2	= frozen region
R_a	= domain of a problem
R_f	= a constant (less than 1) in Eq. (4.23)
R'	= a region of an arbitrary body
RP	= heat flux per unit water pressure
RT	= heat flux per unit temperature
r_{iw}	= radius of the ice-water interface
S_1	= surface made by the warmest ice-lens
S_2	= external boundary of lens-free zone
S_3	= internal boundary of frozen zone
S_a	= boundary of a problem
S_I	= rate of freezing
S_w	= rate of change of the unfrozen water mass
S'	= surface of region R'
SP	= water flux per unit water pressure
SP_o	= segregation potential
ST	= water flux per unit temperature
T	= temperature of soil in celsius
T_1	= temperature in the frozen region in celsius
T_{il}	= temperature of the warmest ice-lens
T_o	= freezing point of water at reference pressures in Kelvin
T^s	= vector containing nodal values of temperature
$(\mathbf{T}^s)_m$	= vector of nodal temperatures at the beginning of m th time step
$(\mathbf{T}^s)_{m+1}$	= vector of nodal temperatures at the end of m th time step
T'	= changed freezing point of water under pressure in Kelvin
$(\mathbf{T}_1^s)_m$	= vector of nodal temperatures at the beginning of m th time step in the frozen region
$(\mathbf{T}_1^s)_{m+1}$	= vector of nodal temperatures at the end of m th time step in the frozen region
T_t	= a transformation matrix given by Eq. (4.26)

T_{t1}	= a transformation matrix given by Eq. (4.28)
T_{sf}	= a new ice-lens forms at this temperature
T_{sm}	= when the warmest ice-lens reaches this temperature, new ice-lens forms
$(T^s)^*$	= temperature vector at which dependent parameters are evaluated
t_{m+1}	= time at the beginning of m th time-step
t_m	= time at the end of m th time-step
u	= vector of displacements
u^s	= a vector of nodal displacements
u_r^s	= nodal displacements at the end of the r th iteration
u_{r-1}^s	= nodal displacements at the end of the $(r - 1)$ th iteration
V_I	= ice velocity
$ V_I $	= magnitude of ice velocity
V_o	= water intake at the formation of final ice-lens
v_i	= volumetric ice flux per unit area of soil
v_w	= volumetric water flux per unit area of soil
W	= volumetric unfrozen water content
W_i	= weight factor of the i th Gauss point
W_j	= weight factor of the j th Gauss point
X_1	= a vector containing X -coordinates of nodes of an element
XT	= heat flux per unit rate of change of temperature in frozen region
Y_1	= a vector containing Y -coordinates of nodes of an element
YT	= heat flux per unit temperature in frozen region
ZT	= heat flux vector
α	= a constant between 0 and 1 in Eq. (2.47)
β	= coefficient of thermal expansion of soil grains
β_s	= coefficient of thermal expansion of structure
χ	= stress partition factor
Δf	= a finite load increment
$\Delta \rho$	= difference between the density of ice and water

Δt_m	= m th time step = $t_{m+1} - t_m$
Δu_n	= relative displacement in normal direction of interface
Δu_t	= relative displacement in tangential direction of interface
Δu_r^s	= the incremental displacements for the r th iteration
$\Delta\{\psi_r\}$	= residual forces for the r th iteration
$\Delta\{\psi_{r-1}\}$	= residual forces for the $(r - 1)$ th iteration
$\Delta\{\psi_1\}$	= residual forces at the beginning of any load-step
$\{\epsilon\}$	= total strain vector in the soil
ϵ_{ii}	= total normal strains
$\{\epsilon_p\}$	= volumetric strains due to the neutral pressure
$\{\epsilon_T\}$	= thermal strain vector
$\{\epsilon_v\}$	= volumetric strains due to the freezing
η	= natural coordinate varying from -1 to 1
η_c	= a constant value of η
η_j	= j th Gauss point coordinate
γ	= empirical constant in Eq. (2.29)
k_h	= thermal conductivity matrix of soil
k_{hd}	= thermal conductivity of soil in any direction
k_{hi}	= thermal conductivity of ice
k_{hs}	= thermal conductivity of soil grains
k_{hw}	= thermal conductivity of water
μ	= a constant between 0 and 1 in Eq. (2.45)
μ_1	= a constant between 0 and 1 in Eq. (2.49)
μ'	= friction coefficient between soil and structure
ν	= Poisson's ratio
ω	= dummy variable of the integration in Eq. (1.10)
π	= osmotic pressure of water
ϕ	= friction angle of soil
$\{\phi'\}$	= an arbitrary function in Eq. (2.36)
ϕ_{iw}	= $P_i - P_w$

ρ_i	= density of ice
ρ_s	= dry density of soil
ρ_w	= density of water
σ	= total stress
σ'_1	= maximum principal effective stress
σ'_3	= minimum principal effective stress
σ_e	= effective stress
σ'_{ii}	= effective normal stresses
σ_{ii}	= total normal stresses
σ_{iw}	= surface tension at ice-water interface
σ_n	= neutral or pore pressure
σ_{n_1}	= total stress normal to the warmest ice-lens
$\{\sigma_t\}$	= total stress vector
σ_Y	= uniaxial yield stress
$\{\sigma'\}$	= effective stress vector
σ^o_{ii}	= deviatoric stresses
τ_{xy}	= shear stress
θ	= given by Eq. (4.20)
ζ	= natural coordinate varying from -1 to 1
ζ_i	= ith Gauss point coordinate

List of Figures

Figure	Description	Page
1.1	Variation of unfrozen water content with temperature for freezing soils. After Burt and Williams (1985)	25
1.2	Soil-moisture characteristic curves for unfrozen soils. After Williams (1989)	26
1.3	Permeability of frozen soils as a function of temperature. After Burt and Williams (1985)	27
2.1	A continuous and intricate body of ice in freezing fringe. After O'Neill and Miller (1985)	50
2.2	Freezing soil divided into lens-free and frozen regions	51
3.1	8-noded isoparametric element	61
3.2	Direction of ice-velocity in a two-dimensional space	61
3.3	Formation of new ice-lens segment in two-dimensional case	62
3.4	Variation of water pressure, ice pressure and neutral pressure in freezing fringe at the formation of new ice-lens	63
3.5	Unfrozen water content and permeability variation and their linearized estimate	64
4.1	A segment of ice-lens over a finite element	80
4.2	Interface displacements between soil and structure	80
4.3	Load-displacement relationship for interface element in (a) normal direction (b) tangential direction	81
5.1	Soil column subjected to freezing for Example I	94
5.2	Heave and water intake for Example I	95
5.3	Variation of heave rate for Example I	95
5.4	Heat extraction at the warmest ice-lens for Example I	96

5.5	Variation of the thickness of freezing fringe with time for Example I	96
5.6	Variation of temperature gradient in freezing fringe with time for Example I	97
5.7	Global ice segregation ratio verses time for Example I	97
5.8	Thickness of individual ice-lenses for Example I	98
5.9	Time interval between the formation of two consecutive ice-lenses for Example I	99
5.10	Loading and boundary conditions for Example I	100
5.11	Variation of effective stress and neutral pressure for Example I	101
5.12	Unfrozen water content for Example II	102
5.13	Heave variation for Example II	103
5.14	Water intake for Example II	103
5.15	Heave rate variation with time for Example II	104
5.16	Warmest ice-lens temperature variation with time for Example II	104
5.17	Schematic diagram of Caen-experiment: (a) longitudinal section of trough and (b) cross-section of trough. After Dallimore et al. (1984)	105
5.18	Unfrozen water content curves for Caen silt and SNEC sand. After Dallimore et al. (1984)	106
5.19	Boundary conditions for the Caen-experiment	107
5.20	Variation of heave and water intake for SNEC sand	108
5.21	Finite element mesh for lens-free region in two-dimensional example	109
5.22	Heave rate variation with time for Caen silt in the two-dimensional example	110
5.23	Total thickness of ice-lenses for Caen silt in the two-dimensional example	110
5.24	Volume of ice-lenses and water intake for Caen silt in the two-dimensional example	111

5.25	Heat extraction rate under the pipeline for Caen silt	111
5.26	Variation of neutral pressure under the pipeline for Caen silt	112
5.27	Principal effective stress under the pipeline for Caen silt	112
5.28	Configuration of the interface between the soil and pipeline at the end of simulation	113
A.1	Flow of major subroutines for the program 2D-RIGICE	147
A.2	Flow chart for the program 2D-RIGICE	148
A.3	Flow of major subroutines for the program FROSTRA	149
A.4	Flow chart for the program FROSTRA	150

List of Tables

Table	Description	Page
5.1	Thermal and hydraulic properties of Caen silt and SNEC sand	90

CHAPTER 1

Introduction

1.1 General

Ground water freezes and expands in winter, a phenomenon known as frost heave, which causes the ground and structures lying on it to move upward. Melting of ice in the frozen ground in summer causes both the ground and structures on it to move downward. This thawing of ground produces an excess of water and of pore pressure in soil which reduce the bearing capacity of soil. This process is called thaw weakening of soils. Uniform movement of underlying soils due to those two processes does not cause any stresses in structures. Thus, uniform movements are not of much interest to design engineers as long as their magnitude is not larger than the serviceability requirements. Large differential movements, on the other hand, can cause large stresses in structures.

Differential movement in ground may be caused by either freezing, thawing or both, depending upon the ground and the atmospheric conditions. A continuous permafrost region remains at sub-zero temperatures most of the year round. Differential movement in this region is normally caused by the thawing of part of the ground due to the artificial heat sources, e.g. oil pipelines, heat from houses and other similar structures. Various techniques are being used in permafrost regions to

prevent the transfer of heat from the structures to the frozen ground. A discontinuous permafrost region has patches of unfrozen regions in between the frozen ground where either the freezing of the unfrozen region due to the artificial heat sink (e.g. chilled gas pipelines) or the thawing of the frozen region due to the artificial heat source, may cause differential movement. For engineering design purposes, it is required to predict the above ground movements in terms of measurable parameters of the ground and the atmosphere. A clear understanding of the mechanism of freezing and thawing would enable us to devise effective ways to mitigate the above differential movements. In the present review, frost heave, its mechanism and the various models to predict its magnitude are considered. For the details of thawing, the reader is referred to other sources (Ladanyi and Shen, 1989).

For the frost heave to be significant, the following three conditions should be present: (i) sub-zero temperature, (ii) frost susceptible soil and (iii) availability of water. Frost susceptibility of any soil is measured by its capacity to facilitate migration of water. Gravels and sands are least frost susceptible whereas silts are the most frost susceptible. Clays cause larger suction for water migration, but the amount of water migration is limited by their low permeability. Hence, clays are less frost susceptible than silts, but can lift much higher external loads.

There are a large number of lab tests and empirical relations available to predict the magnitude of frost heave (Chamberlain, 1981). It is, however, difficult to simulate the actual field conditions in the lab and it would be uneconomical and cumbersome to carry out lab tests for all the possible variations in the ground and atmospheric conditions. Empirical relations either do not reflect the importance of all the relevant parameters or are not universally applicable. There are numerous (Chamberlain, 1981) criteria to classify soils according to their frost susceptibility. While these criteria give an idea to design engineers about the order of magnitude of the heave for various types of soils, they are in fact generally valid for a few limited conditions. The above deficiencies make it necessary to develop a numerical model representing all the relevant processes involved in the frost heave. In the

last two decades extensive research effort have been devoted to the understanding of the basic principles of the frost heave process and to their application in numerical frost heave models. Our better understanding of the physics and thermodynamics of the frost heave process has made present models more detailed and complex. There have been reviews of the existing frost heave models in papers by O'Neill(1983), Ladany and Shen(1989) and Loch(1980), in a textbook style treatment by Miller(1980) and in a book by Williams and Smith(1989). In the following sections a brief review of our present understanding of the frost heave mechanism is presented and the capabilities and limitations of the existing frost heave models are discussed, but for more details the reader is referred to the above reviews and to the proceedings of the First(1978), Second(1980), Third(1982), Fourth(1985) and Fifth(1988) International Symposia on Ground Freezing.

1.2 Frost Heave Mechanism

1.2.1 Moisture Migration

Experimentally measured heave magnitudes suggest that the frost heave is not caused only by freezing and expansion of in-situ water but also by the water and vapour migrating towards the freezing front. In the saturated soils migration occurs only in the form of water while in the unsaturated soil, vapour diffusion is also possible. Many investigators (Evgin and Svec, 1988; Jackson, 1965; Hilel, 1971) have reported the variation of the diffusivity of water and vapour with the total water content in the unsaturated soils. They have observed that the overall diffusivity increases with the total water content, but this is mainly due to the increase in the water diffusivity. The diffusivity of vapour was found to be significant only at very low water content (less than 5% by weight). In his computer simulation, Outcalt(1979) found considerable vapour diffusion near the freezing front. Recent evidence presented by Nakano et al.(1983, 1984) suggests that the vapour diffusivity in the frozen soil is very low. This is expected because the presence of pore ice in frozen soils hinders the vapour flow but the water flow continues through the

adsorbed films around the grains. From the magnitude of the diffusivities, Williams and Smith(1989) have shown that the vapour diffusion is several orders of magnitudes less than the water flow. Thus, for all practical purposes it may be neglected (Dirkson and Miller, 1966).

1.2.2 Freezing Fringe

It is well recognized that the freezing of soil causes the formation of segregated ice, known as ice-lenses. Ice-lenses have been found to initiate at several tenths of degree below the normal freezing point of water (0°C). Ice below the warmest ice-lens is in the form of pore ice and is in equilibrium with the unfrozen water. The presence of unfrozen water at several degrees below 0°C has been confirmed by many investigators (Anderson and Tice, 1972). The nucleation temperature required for pore ice to form is below 0°C because of the effect of the surface adsorption and capillary forces. The difference between the nucleation temperature and the normal freezing point of water is defined as the freezing point depression. The magnitude of freezing point depression depends upon the type of soil. Its magnitude would be higher for finer soils, e.g. clay. Miller(1970) defined the region from the base of the warmest ice-lens to the freezing front (0°C isotherm) as a freezing fringe. Ice content in the freezing fringe varies from 0% at the freezing front to the 100% at the base of the warmest ice-lens. Water from the unfrozen region transports through the freezing fringe to the base of the warmest ice-lens where it freezes. The thickness of freezing fringe depends upon the type of soil and the external overburden pressure. It increases as the fineness of soil is increased and as the overburden pressure is increased. It may be zero for some cases such as sand with zero overburden pressure.

The variation of unfrozen water content in the freezing soil is a very important parameter of any numerical frost heave model. Many investigators have reported the variation of unfrozen water with temperature (Williams and Smith, 1989; Horiguchi and Miller, 1980), Fig. 1.1. It can be seen that the unfrozen water content in coarse-grained soils reduces more rapidly with negative temperature. Variation

of water content with suction in unsaturated unfrozen soils is well established in soil mechanics, known as soil-moisture characteristic curves, Fig. 1.2. Large variations of suction pressures in the freezing soils make it necessary to consider the variation of unfrozen water content with both water pressure and temperature. Unfrozen water in the partially frozen soils is found in the adsorbed water layers around the grains and in capillary pores. Williams(1964) showed that its variation with temperature for any soil does not depend upon the total water content in its unfrozen state. The water in the vicinity of the grains and in capillary pores remains unfrozen due to the surface adsorption forces and capillary forces, respectively. These forces depend upon the type of grains and their distribution. Hence the unfrozen water content by weight would not depend upon the total water content in its unfrozen state. It would certainly depend upon the porosity of soil because that affects the grain distribution.

The presence of pore ice in the freezing fringe hinders the flow from the unfrozen soil to the base of the warmest ice-lens. Since the pore ice content increases as we approach to the base of the warmest ice-lens, permeability of the water reduces in that direction. Burt and Williams(1976) measured the permeability of various types of frozen soils in their permeameter for the range of temperatures, -8°C - 0°C . Permeability at -1°C is 3 to 4 orders of magnitude less than the corresponding value of the unfrozen soil, Fig. 1.3. Cary and Mayland(1972) proposed that the permeability of frozen soil be considered to be same as that of soil above the freezing point of water when unsaturated and when it has the same water content as the frozen soil. The presence of ice-lenses in frozen soil makes this analogy invalid but it can be used for freezing fringe.

1.2.3 Capillary Theory

Capillary theory has been used by many investigators to explain the large suction pressures and the consequent moisture migration in the freezing fringe. According to this theory the pressure jump between the ice and water at their interface is given by

$$P_i - P_w = \frac{2\sigma_{iw}}{r_{iw}} \quad (1.1)$$

where

- P_i = ice pressure
- P_w = water pressure
- σ_{iw} = surface tension of ice-water interface
- r_{iw} = radius of the ice-water interface

In the above ice and water are assumed to have a macroscopically isotropic stress state. O'Neill(1983) has discussed the limitations and validity of this assumption. A thin adsorbed film around the grain in the freezing soil pulls the water from one side and pushes the ice on the other side (Miller, 1978; Gilpin, 1979). This would not be possible without the anisotropic and complex state of stress in the water and the ice. Pore ice, being solid, can support the anisotropic stress state and stress concentrations. Gilpin(1979) gave the theoretical expressions for the ice pressure and water pressure in the thin film around a wire embedded in ice in terms of the temperature and the film thickness. He also showed that for small wire velocities, the change in the film thickness around the wire is negligible. If we extend these concepts to the frost heave process, then we can neglect the pressure variations around a grain due to the variations in film thickness since the frost heave process is slow and grain velocities are small. If we consider a macroscopic unit consisting of a few grains, water, ice and air, the temperature within it may be assumed to be constant and hence the macroscopic ice and water stresses can be considered to be the same in all directions.

Many investigators have assumed that the mean ice-water interface curvature is some macroscopic function of the unfrozen water content. That is,

$$P_i - P_w = 2\sigma_{iw}F'(W) \quad (1.2)$$

where

- $F'(W)$ = curvature of the ice-water interface

W = volumetric unfrozen water content

A frost heave model which assumes that the driving force for moisture migration is only the capillary force is called the capillary heave model or the primary heave model. Koopmans and Miller(1966) assumed that the mean curvature function, $F'(W)$, is the same for the unsaturated unfrozen soil and the saturated frozen soil. If water pressure is atmospheric in both cases, then using the capillary equation for the mean air-water interface and Eq. (1.2) gives

$$\frac{P_i}{P_a} = \frac{\sigma_{iw}}{\sigma_{aw}} \quad (1.3)$$

where P_a is the air pressure and σ_{aw} is the surface tension at air-water interface. They measured the ratio of ice pressure and air pressure for the granular soils at the same water content. They got the value of 0.45, in agreement with the ratio on the right hand side of Eq. (1.3) measured by other techniques. But for clays the ratio of ice pressure and air pressure was unity. This shows that the value of ice pressure has a much larger value than the capillary model can predict. Capillary model applies only to non-colloidal materials, e.g. sand, glass beads etc.

1.2.4 Clausius-Clapeyron Equation

It is well known that the freezing point of water depends upon the applied pressure. The change in the freezing point due to pressure is given by the Clausius-Clapeyron equation,

$$\ln\left(\frac{T'}{T_o}\right) = \frac{1}{L} \left[\frac{P_w - \pi}{\rho_w} - \frac{P_i}{\rho_i} \right] \quad (1.4)$$

where

- L = latent heat of fusion of water
- T_o = freezing point of water at reference pressures, in Kelvin
- T' = changed freezing point of water under pressure, in Kelvin
- π = osmotic pressure of water

ρ_w = density of water

ρ_i = density of ice

If $T' - T_o$ is very small then the above equation can be simplified to

$$L \frac{T' - T_o}{T_o} = \left[\frac{P_w - \pi}{\rho_w} - \frac{P_i}{\rho_i} \right] \quad (1.5)$$

The Clausius-Clapeyron equation has been verified experimentally by many investigators. Hopke(1980) has summarized the available evidence. Vignes and Dijkema(1974) and Biermens, Dijkema and de Vries(1978) verified this equation when only ice and water were present. Radd and Oertle(1973) found the required overburden pressure, which is equal to ice pressure at an ice-lens, to prevent the heave completely in clays. They assumed the water pressure to be zero at an ice-lens and measured its temperature and found that the above equation is in good agreement at temperatures as low as $-15^\circ C$.

Unfrozen water has been found to be present at several degrees below $0^\circ C$. From the Clausius-Clapeyron equation it can be concluded that the large difference between the ice pressure and water pressure must exist and that it would keep on increasing as the temperature is lowered (it is of the order of 1.2 MPa at $-1^\circ C$). This pressure differential can be caused by very high ice pressure or by very small water pressure or by both. Maximum ice pressure is restricted by the overburden pressure at an ice-lens. Hence large suction develops in the freezing soils which may draw large amount of water to the freezing fringe. This water flow is restricted by the low permeability of the frozen soils and by the presence of impermeable ice-lenses. The Clausius-Clapeyron equation explains the presence of large suction pressures and the overall freezing process very well. That has led many recent researchers to use the concept of ice pressure and this equation in their models. It is to be noted that this equation is valid only when ice and water are present simultaneously.

1.2.5 Overburden Pressure and Shut-off Pressure

Penner and Ueda(1977) showed experimentally that the magnitude of heave decreases as the external overburden pressure is increased on the heaving soils. They found that at very high overburden pressures water from the freezing fringe exudes for a certain time and then reverses its direction of flow. Some other researchers have suggested that for any soil there exists an overburden pressure at which the heaving of soil would be prevented completely. This overburden pressure is defined as shut-off pressure. Konrad and Morgenstern(1982a) calculated the theoretical values of shut-off pressure from the Clausius-Clapeyron equation assuming the no flow condition, i.e. $P_w = 0$. But Penner and Ueda (1977) showed that any overburden pressure just delayed the process of water intake and hence there always would be some amount of heave given sufficient time.

As the overburden pressure is increased, the ice pressure in the frozen soil increases since ice pressure at an ice-lens is equal to the the overburden pressure. From the Clausius-Clapeyron equation it can be concluded that the suction pressures would be reduced in the freezing soils at any temperature. It would reduce the water intake and the magnitude of heave. At very high overburden pressures the consolidation effect dominates over the water intake and hence we find the water expulsion. But the consolidation pressure decreases exponentially with time whereas the average suction in the freezing fringe increases with time and hence there would always be reversal of flow. If the time required for the flow to reverse and to nullify the expulsion effect is larger than the period over which freezing takes place under certain overburden pressure, then it could be regarded as the shut-off pressure.

1.2.6 Stress Partition Factors

Bishop and Blight(1963) and Miller(1978) suggested applying Terzaghi's concept of effective stress and pore pressure for frozen soils. Water and ice normally coexist in the frozen soils and are generally at different pressures. They used the

stress partition factor, χ , to determine the total pore pressure in frozen soils. Accordingly

$$\sigma = \sigma_e - \sigma_n \quad (1.6a)$$

$$\sigma_n = (1 - \chi)P_i + \chi P_w \quad (1.6b)$$

where

- σ = total stress
- σ_e = effective stress
- σ_n = neutral or pore pressure

The stress partition factor mainly depends upon the ice content, unfrozen water content and porosity of soil. There are experimental results and empirical formulas available for predicting that factor. As the ice content increases, we expect the contribution of ice pressure to the neutral stress to increase, which means that the stress partition factor must decrease. Hopke(1980) assumed the χ for unsaturated soils to be

$$\chi = \frac{n - I}{n} \quad (1.7)$$

where

- n = porosity of soil
- I = volumetric ice content

His formula for saturated frozen soils reduces to

$$\chi = \frac{W}{n} \quad (1.8)$$

O'Neill and Miller(1982) used the following expression for χ based on the experimental observations:

$$\chi = \left(\frac{W}{n} \right)^{1.5} \quad (1.9)$$

Snyder and Miller(1985) obtained the approximate formula for χ by using the Aitchison's (1961) suggested expression. They modified that expression by multiplying it by 0.5 and by assuming zero effective stress. Accordingly,

$$\chi(W) = \frac{0.5}{n} \left[W - \frac{0.3}{\phi_{iw}(W)} \int_W^n \phi_{iw}(\omega) d\omega \right] \quad (1.10)$$

where

$$\begin{aligned} \phi_{iw} &= P_i - P_w \\ \omega &= \text{dummy variable of the integration} \end{aligned}$$

The quantity ϕ_{iw} is a function of unfrozen water content given by Eq. (1.2). O'Neill and Miller(1985) used Eq. (1.10) in their model.

Some other approaches to calculate the neutral pressure are summarized by Ladanyi and Shen(1989). Groonvelt and Kay(1977) suggested a different approach to the stress partition but their equation requires the determination of two empirical coefficients, namely load factor and frost factor. Ladanyi(1985) considered only mechanical effects and gave a formula for computing the increase in the pore matrix stress per unit increase in the external pressure.

1.2.7 Frost Heaving and Ice-lens Formation Criteria

There are various criteria to determine when and where would the excess ice would be allowed to form an ice-lens and for heave to occur. Most of the frost heave models monitor the ice content in the freezing fringe and when it exceeds the critical ice content, it is allowed to heave. Taylor and Luthin(1978) and Dirkson and Miller(1966) assumed the critical ice content to be 85% of the porosity. Others assumed that if the ice content is equal to or greater than the porosity minus the unfrozen water then heave would occur. Outcalt(1980) assumed that when the heat flux divergence becomes greater than the heat required to freeze all the water arriving in the freezing fringe, heaving would occur. The above heave criteria assume soil to be a continuum and their prediction is not in accord with

experimentally observed formation of ice-lenses. An ice-lens is a discontinuity in the soil and represents a nearly impermeable barrier to water flow; therefore, the freezing region needs to be divided into two distinct regions: (i) the frozen region above the warmest ice-lens and (ii) the lens-free region below the warmest ice-lens. There are several criteria for determining when and where a new ice-lens forms in lens-free region. Konrad and Morgenstern (1980) assumed that when the existing warmest ice-lens reaches a certain temperature, T_{sm} , a new ice-lens forms where the temperature is T_{sf} . The magnitudes of both T_{sm} and T_{sf} were less than zero and T_{sm} was less than T_{sf} . This criterion means that an ice-lens initiates at temperature T_{sf} and develops till its temperature reaches T_{sm} . O'Neill and Miller (1983) assumed that when and where the effective stress in the soil goes to zero, i.e, the neutral pressure in the soil surpasses the overburden pressure, a new ice-lens will form. They used the stress partition factor to determine the neutral pressure. Soil grains in freezing soils are surrounded by a thin layer of water and hence there is no direct contact between grains, this makes the validity of their criterion dubious. Ladanyi and Shen(1989) have stated that the numerical results of the magnitudes of heave are not significantly influenced by the heaving criterion.

1.2.8 Segregation Potential Concept

Konrad and Morgenstern(1980) introduced the concept of segregation potential relating the mass flow and temperature gradient in freezing soils. They carried out a simple linear analysis assuming that; (a) the Clausius-Clapeyron equation is valid at the base of an ice-lens, (b) water flow across the freezing fringe is continuous, i.e, all the water accumulates at the base of the warmest ice-lens, (c) the freezing fringe is characterized by an overall permeability, (d) the temperature varies linearly in the fringe and (e) the external overburden pressure and the ice pressure in the fringe are zero. From analyses based on these assumptions they concluded that during the freezing of soil columns under the same warm-side temperatures but different cold-side temperatures, water intake flux is proportional to the temperature gradient in the fringe during the formation of the final ice-lens, i.e at the steady state.

Accordingly,

$$V_o = SP_o grad T \quad (1.11)$$

where

V_o = water intake during the formation of final ice-lens

SP_o = segregation potential

$grad T$ = gradient of temperature in the freezing fringe

They verified this equation experimentally and found that (a) the segregation potential is constant if the suction at the freezing front is constant, (b) it is maximum when the suction is zero and decreases as the suction increases. Later they (Konrad and Morgenstern, 1982a and 1982b) provided the variation of segregation potential with the rate of cooling in the fringe and with applied overburden pressure. The latter makes it possible to predict water intake flux for a more general case of transient freezing with external overburden pressure. It has been stated that (Nixon, 1982) the segregation potential is a very useful parameter for predicting heave in field from the laboratory test data.

1.2.9 Regelation

It has been observed that a solid particle embedded in ice moves under conditions of temperature and pressure gradient (Gilpin, 1979; Romkens and Miller, 1973). This phenomenon is known as regelation. Koopmans and Miller (1966) showed that for non-colloidal soils, suction in the freezing fringe is much higher than the capillary equation can predict. Based on that observation, they noted that there must be some other driving force or some other mode of transport in freezing soils. They postulated that ice moves through regelation around the soil grains during freezing. Water is more strongly attracted to a solid particle and hence a thin layer of water exists around it (Gilpin, 1979). It is believed that ice melts at the warmer side or at the lower suction side of the solid particle and the resulting water is transported around it through the thin liquid (water) layer to

the cooler side or to the higher suction side and freezes there. This process causes the uneven thickness of the adsorbed film but the centripetal surface adsorption forces try to centre the grain or solid particle. Consequently, the grain moves to even warmer or high suction environment inducing further regelation.

Gilpin(1980) derived the equation for the movement of single spherical or cylindrical object in ice under conditions of temperature or pressure gradient using basic thermodynamics and mechanics. He found that if the difference between the conductivities of the foreign object and the ice is not very high, then the regelation velocity of the object is very small. In that case the change in the thickness of the film around the object is negligible and the relevant expressions of pressure and temperature in the film are simplified. Philip(1980) has used the same simplified equations for a cylindrical object and derived the equation for temperature field and for stream lines for regular arrays of such objects. If the soil is assumed to consist of a regular array of grains, then his equations can be extended to predict ice-transport through regelation during freezing. He also derived the theoretical expression for the apparent hydraulic conductivity, i.e, the ice velocity per unit hydraulic gradient. He obtained the value of $2.7 \times 10^{-11} m/s$ for 50% porosity assuming the ratio of the conductivities of the object and ice is 1.5.

Horiguchi and Miller(1980) in their ice sandwich experiment obtained the experimental magnitude of the apparent hydraulic conductivity in the temperature range of $-0.15^{\circ}C$ to $0^{\circ}C$. They used the ice-sandwich permeameter with phase barriers and supercooled water and measured the flow through it under the application of pressure gradient. They experimentally disproved the notion that all the flow takes place either through the polycrystalline ice or at the edges. They therefore concluded that the only possible flow mechanism is the melting of ice at the outflow side and the freezing of the supercooled water at the inflow side, i.e. regelation. They found that the apparent hydraulic conductivity decreases as the temperature is reduced and it shows hysteretic behaviour. Ohrai and Yamamoto(1985) observed that a number of ice-lenses develop simultaneously and many small ice-lenses dis-

appear at very low temperatures. He proposed that the flow mechanism for the above behaviour is regelation. This mass transport between the existing ice-lenses in the frozen region is known as regelation transport. Mageau and Morgenstern (1980) observed the moisture redistribution during freezing in a laboratory test of a soil column and found that the frozen soil above an ice-lens has little or no effect on the rate of water intake and heave rate.

1.3 Frost Heave Models

A large amount of latent heat is released when the water in the ground freezes. Any sensible frost heave model must take into account this release of heat in some approximate manner. If the phase change boundary is assumed to be a concentrated macroscopic discontinuity, then the ground freezing problem reduces to the Stefan problem. This problem has been solved analytically for simple boundary conditions and numerically for more general cases (Crank, 1981). Various numerical methods, e.g. isotherm migration, moving mesh and body-fitted curvilinear coordinates maintain the phase change boundary at the element edges and take into account the change in the thermal properties on either side of the phase change front. A large amount of heat release in the thin infinitesimal phase change zone causes discontinuity in the heat flow. It is numerically difficult to deal with this moving discontinuity. To avoid this, various methods, e.g. apparent heat capacity method and enthalpy method, spread the latent heat release over a macroscopic step. None of the above methods include the mass transport and hence predict only in-situ freezing of water. Their understanding, however, is essential because they form an important part of any frost heave model.

One of the first and simplest frost heave models which included both heat and mass transfer was proposed by Harlan(1973). The freezing fringe was taken care of by using the soil-moisture characteristic curve and the empirical relationship between permeability and the pressure head. The soil was assumed to be a continuous medium and the concept of ice pressure, capillary relations or Clausius-Clapeyron equation was not used. His model did not consider the heaving of soil and predicted

only the temperature profile, ice content and unfrozen water content variations in space and time. Jame and Norum(1980) used essentially the same heat and mass transport equations except that the diffusivity concept was used, i.e. it was assumed that the flow was driven by the gradient in the moisture content. All the thermal and mass transport coefficients were assumed to vary throughout the soil. Unfrozen water content was assumed to depend upon temperature only and the empirical relation between the diffusivity and the moisture content was used. Their results were in good agreement with experimental results for the temperature and the unfrozen water content variation provided the diffusivity magnitudes were increased by an impedance factor. This impedance factor was found to reach as high as 1000. They gave the expression for impedance factor in term of ice content, but theoretically could not justify their proposed impedance factor. Their model did not include the heaving and did not predict the heave magnitudes. Taylor and Luthin(1978) used the same equations but they include the heaving. When the ice content at any point exceeded the 85% of porosity, then heaving was assumed to occur. They also assumed the unfrozen water content to be a function of temperature only and used the diffusivity concept. To match the calculated heave magnitudes with the experimental values, they found it necessary to increase the diffusivity magnitudes by the impedance factor similar to Jame and Norum(1980).

Outcalt(1980) and Dudek and Holden(1979) considered the simple heat conduction above and below the step freezing front. It was assumed that when the heat flux divergence in the freezing front was more than the heat required to freeze all the water coming into the freezing front, the front would advance or else it would heave. In Outcalt's model flow was driven by the pressure gradient caused by the constant suction value at the front. The segregation temperature was assumed to be constant and the fringe was represented by an overall permeability. Neither the capillary relationship nor the Clausius-Clapeyron equation was used and the results were not compared with experimental data. Dudek and Holden(1979) used the capillary relationship and the Clausius-Clapeyron equation but took the ice pressure to be zero everywhere. The concept of critical pore radius was used to

determine whether the given deficit would result in heave and the permeability was assumed to be a function of suction alone. Konrad and Morgenstern(1980) also assumed the ice pressure to be zero and used the Clausius-Clapeyron equation to determine the suction pressures in the fringe. The fringe was characterized by an overall permeability and the temperature was assumed to vary linearly across it. Ice-lenses were assumed to form at the predefined segregation temperature, T_{sf} , when the existing warmest ice-lens reached a certain temperature, T_{sm} .

All the above models are simple but none considers the effect of ice pressure and overburden pressure nor gives results which are in good agreement with experimental data without ad hoc adjustment of certain parameters. Berg et al(1980) were one of the first to take into account the effect of overburden pressure. They used the capillary model and assumed the ice pressure to be equal to the overburden pressure throughout the freezing fringe. The equivalent critical pore radius was determined from the soil-moisture characteristic curve for unsaturated unfrozen soils. They arbitrarily doubled the effect of water pressure in the capillary relationship at the ice-water interface according to Penner's(1959) suggestion and evaluated the suction at the segregation front using the critical pore-radius. The unfrozen water content and the permeability were assumed to vary only with the pressure head. All the water available for freezing was assumed to freeze at a predefined freezing point depression and heaving was assumed to occur when the saturation of voids exceed 90%. Their model showed the reduction in the heave with increasing overburden pressures but did not predict the expulsion of water at high overburden pressure. Their assumptions of isothermal freezing, adjustment in capillary equation and ice-pressure variation were not supported by experiments and were too simple to be true. Shen and Ladanyi(1988) considered the influence of overburden pressure by assuming ice pressure variation. Ice pressure was assumed to be zero at the freezing front, equal to overburden pressure at the segregation front and linear in between. They used the Clausius-Clapeyron equation with the above ice-pressure variation to get the suction variation with temperature in the fringe. They assumed the unfrozen water content to vary with temperature only and did not predict water

expulsion at a high external overburden pressure.

None of the above models predicted expulsion of water at high overburden pressure and except for Outcalt(1980) and Konrad and Morgenstern(1980), they did not include the effect of discontinuous ice-lenses. Outcalt(1980) assumed a layer of ice growing on top of some unfrozen soil, i.e. the thickness of the freezing fringe was assumed to be zero. O'Neill and Miller (1985) defined this mode of heave as primary heave mode in which ice does not penetrate the remaining unfrozen soil. In the secondary heave mode, the presence of freezing fringe allows development of large suction and ice pressures, resulting in the ability of soil to lift heavy loads. The secondary heave mode is of the greater importance to engineers. Lewis and Sze(1988) assumed that the flow in the fringe is driven by the gradients in the moisture and temperature and the diffusivity magnitudes are constant throughout the simulation. They neglected the regelation and took the phase conversion factor (ratio of ice content to the combined ice content and water content) constant. They used the capillary relationship and the Clausius-Clapeyron equation and stress partition factor for the ice-lens formation. Their model showed the reduction in heave with increasing overburden pressure and predicted rhythmic ice-lens formation but not the expulsion of water at high overburden pressure.

Hopke(1980) used the capillary model for unsaturated soils considering the effect of overburden pressure. He used the Clausius-Clapeyron equation with the same assumed variation of ice-pressure as Shen and Ladanyi(1988) except the ice pressure was assumed to be equal to zero when pores were not completely filled with water and ice. The unfrozen water content and hydraulic permeability were assumed to depend upon the difference of ice pressure and water pressure. His assumed ice pressure variation caused a discontinuity of the water content at the freezing front and convergence problems, except when the ratio of ice-water surface tension to the air-water surface tension was set equal to unity. He showed the reduction in heave with increasing overburden pressures and the expulsion of water at high overburden pressures. Ice-lens was assumed to form when and where ice pressure exceeded the

overburden stress. His model predicted too much heave at low overburden pressure and too much heave at high temperature gradients. He believed that the minimum fringe thickness or an additional effective overburden pressure is required to match the experimental data.

Gilpin(1980) found the secondary heave model of Miller(1978) intractably complex and so he made some simplifying assumptions. Based on his earlier research on regelation (Gilpin, 1979), he explained the drive for migration by the special form of Clausius-Clapeyron equation. Flow of water is driven by both the ice pressure gradient and the temperature gradient. He assumed the permeability to be a function of temperature alone and that all the water available for freezing freezes either at the freezing front or at an ice-lens. He neglected the heat capacity of soil and assumed overall hydraulic and thermal coefficients for frozen, unfrozen and partially frozen zones. He defined the separation pressure as that ice pressure which is required to form the ice-lens, and whenever and wherever the ice pressure exceeded this value, ice-lens was assumed to form. He predicted the rhythmic formation of ice-lenses, their growth, consequent redistribution in the system and the effects of overburden pressure, but found that the magnitude of heave rates was similar to experimental data only if the radius of the spheres was basically equal to the size of the finest 10% of soil particles.

All of the above models neglect ice transport around soil grains due to regelation in the freezing fringe. Considering ice transport due to regelation, O'Neill and Miller(1982a) proposed the rigid-ice model. They assumed the pore ice in the fringe and the warmest ice-lens to be inter-connected and to be forming an intricate body. This body of ice was assumed to be rigid and was considered to move with the same velocity everywhere. In the mathematical formulation, they used both the capillary relationship and the Clausius-Clapeyron equation but neglected mass transport beyond the warmest ice-lens. They utilized an empirical stress partition factor to determine the neutral pressure which determined when and where the new ice-lens would form. The unfrozen water content and permeability were varied with

both temperature and water pressure. Their results showed most of the expected trends like ice-lens spacing, their thickness, the formation of ice-lenses somewhat behind the freezing front and the effect of overburden pressure. In the present form their model is applicable to the saturated soils only. Unfortunately, their assumption of rigid-ice and the results of their model have not been yet verified by experimental observations. Their model is the most comprehensive model to date and embodies most of the known physics and thermodynamics pertinent to the frost heave process.

Numerical implementation of the rigid-ice model is quite complex and a lot of computing time is wasted in the determination of the initial, very closely spaced and extremely thin ice-lenses. That has led researchers to simplify the rigid-ice model (Gilpin, 1980; Holden et al, 1985; Black and Miller, 1985). Holden et al.(1985) assumed quasi-static profiles for the water pressure and temperature in the rigid-ice model and simplified the computation. They assumed a linear variation of temperature for both the frozen and partially frozen region, linear variation of water pressure for unfrozen region and quartic variation of water pressure for partially frozen region. He showed that the computation time decreased due to the above assumptions, but his results of heave were not in good agreement with the experimental values. Black and Miller(1985) treated the soil as a continuous medium and suggested that (a) the lensing zone (freezing fringe) be treated in a way that its response to current boundary conditions matches those of a corresponding zone in a 'steady state' system, i.e. one involving an endless succession of identical ice-lensing cycles, and (b) throughout the life history of the lens formed during each cycle, heat and mass fluxes are to be assumed constant through the boundaries of the lensing zone. Their model predicted much higher heaving pressures than those observed experimentally.

The stress analysis of soils during freezing is very important for predicting the stability of soils and structures in cold regions. Many of the models described above consider the effect of overburden pressures but fail to take into account the

compressibility of soil grains. Blanchard and Tremond(1985) were the pioneers in coupling the mechanical field with the thermal and hydraulic fields. Their model treated the soil as a continuum and did not predict the segregation of ice. They did not use the capillary relationship or the Clausius-Clapeyron equation in their model. Shen and Ladanyi(1988) showed the simpler way of coupling the stress field. They used the Clausius-Clapeyron equation and the concept of heaving. They also used the power creep law to take into consideration the highly time-dependent behaviour of frozen soils. They used the total stress concept for soil and hence did not include the effect of compressibility of soil grains.

Stochastic frost heave models (Chamberlain, 1980) have been proposed to take into account the consequences of our ignorance of various parameters. However, the mechanism of frost heave process has to be understood to decide which parameters have to be statistically varied. Results of these models would depend upon the frost heave mechanism utilized. These models would certainly be useful in limiting the errors produced by using the empirical values of the various coefficients.

1.4 Limitation of Present Frost Heave Models

There are still many aspects of frost heave process which have been completely ignored or superficially treated.

1. Properties of frozen soils vary considerably with the number of freeze-thaw cycles (Chamberlain, 1982), but none of the models have considered this hysteretic behaviour of frozen soils.
2. Most of the existing heave models are restricted to one-dimensional cases. Blanchard and Tremond's (1985) model is applicable to multi-dimensional cases, but it does not include the phenomena embodied in the capillary equation, the Clausius-Clapeyron equation and ice segregation concept.
3. Most of the models neglect mass transport beyond the warmest ice-lens. Gilpin (1980) assumed the ice pressure to be equal to overburden pressure at all the existing ice-lenses, and knowing the temperature, he evaluated the water pres-

sure using the Clausius-Clapeyron equation. He evaluated the flow between every two subsequent ice-lenses based on the calculated water pressures and the empirical permeability data. He did not show the contribution of transport beyond the warmest ice-lens to the total heave magnitudes.

4. All the models assume the soil to be solute-free and ion-free. The work of Romkens and Miller(1973) would be useful for considering the influence of solutes in water. Horiguchi(1987) proposed the osmotic model for the frost heave but numerical results have not yet been presented.
5. Most of the models assume the soil to be saturated and neglect the vapour diffusion for unsaturated cases. Hopke's(1980) model is for unsaturated soils but has convergence problems because of the assumed ice pressure variation. The rigid-ice model could be extended to unsaturated soils and work is in progress (O'Neill and Miller, 1985).
6. The effect of the compressibility of soil grains on the magnitude of heave had been neglected by most of the models. Blanchard and Fremond (1985) coupled the stress field with thermal and hydraulic fields but treated soil as a linearly elastic medium and did not report the change in the magnitude of heave due to the compressibility of grains.

1.5 Frost Heave and Pipelines

Several pipelines have been constructed to carry natural gas and oil from Arctic regions. These pipelines pass through continuous and discontinuous permafrost regions. They can be either buried in the ground or built above ground. Buried pipelines have to be kept at sub-zero temperatures to prevent thawing of the ice-rich continuous permafrost region. Cooling of oil causes problems to oil flow and hence the buried pipeline cannot be used for the oil transportation (Williams, 1986). Natural gas can be chilled below 0°C and transported through the buried pipeline. When this pipeline passes through unfrozen ground in a discontinuous permafrost region, frost heave around the pipeline causes differential movements. The process

of frost heave around a chilled gas pipeline continues as long as the gas is being transported, which may be virtually throughout the life of the pipeline. This may lead to large differential heave and large stresses in the pipeline. Slusarchuk et al.(1978) have reported the value of heave of 0.6 m in a field test in Calgary. Konrad and Morgenstern (1984) used the segregation potential concept to predict frost heave of a chilled gas pipeline buried in unfrozen ground. Their method is simple to use but their assumptions of radial heat flow and constant ambient temperatures are not valid for general cases. Svec(1981) suggested using heat cables and insulation beneath the pipeline to reduce the heave. He used the finite difference method to predict the freezing front locations, but did not predict the magnitudes of heave. Blanchard and Fremond's (1984) model can be applied to the freezing around a chilled gas pipeline but their model makes several simplifying assumptions. A large-scale experiment of freezing around chilled gas pipeline is in progress since 1981 in Caen, France under a joint Canada-France operation (Dallimore et al, 1984). The aim of the experiment is a scientific and geotechnical study of freezing of soils, investigation of stresses in pipelines and study of complex soil-structure interaction (Dallimore et al, 1984). Such large-scale experiments cannot be conducted too often and hence the observations and results of the experiment must lead to recommendation for the design of pipelines in arctic region and to reliable and accurate numerical frost heave models.

1.6 Objective and Scope

The objectives of the present thesis are as follows:

- The analysis of underground pipeline for frost heave in its general form requires a three-dimensional frost heave model. However, if we assume the ground and atmospheric conditions along the length of pipeline to be uniform, then the problem of freezing around chilled gas pipeline can be reduced to the two-dimensional case. The pertinent equations governing frost heave in two dimensions will be developed according to the theory of the Rigid-Ice model (RIM).

- An attempt will be made to reduce the amount of computational time for the RIM.
- Most existing frost heave models do not include the effect of soil stresses which suggests that the coupling of stress field with heat and mass transfer is not strong. An uncoupled elastoplastic stress analysis of the combined system of soil and pipeline will be carried out. The interface between the soil and pipeline will be modelled using a simple interface element.
- Computer programs for 2-D RIM and for the stress analysis of freezing soils will be developed. These programs would be verified by solving one-dimensional problems for which a great amount of experimental and numerical results are available. The so-called Caen-experiment will be simulated using the proposed model and the soil heave and the stresses in the pipeline will be compared with experimental data.

1.7 Structure of Thesis

The governing partial differential equations and boundary conditions for two-dimensional Rigid-Ice model are presented in Chapter 2. The finite element equations are also derived in the same chapter while aspects of their numerical implementation and solution procedures are discussed in Chapter 3. Chapter 4 deals with the derivation of governing equations for the uncoupled stress analysis of freezing soils and with the finite element formulation of those equations. The numerical results of both the one-dimensional and the two-dimensional examples are discussed in Chapter 5; the final conclusions and recommendations for future work are given in Chapter 6.

Fig. 1.1. Variation of unfrozen water content with temperature for freezing soils. After Burt and Williams (1976)

Fig. 1.2. Soil-moisture characteristic curves for unfrozen soils.
After Williams and Smith(1989)

Fig. 1.3. Permeability of frozen soils as a function of temperature.
After Burt and Williams (1976)

CHAPTER 2

2-D Rigid-Ice Model

2.1 General

As stated in the previous chapter, the present analysis is based on the Rigid-Ice model (RIM). The basic assumption behind this model is that the pore ice in the freezing fringe and the warmest ice-lens are inter-connected and form an intricate and rigid body of ice, Fig. 2.1. Although this assumption has not been experimentally verified, O'Neill and Miller (1985) provided some rational explanations to support it. They argued that it is possible to supercool wet soil by several degrees below 0°C in the absence of proper nucleation sites. In the partially frozen soils, existing ice serves as nucleation sites, hence new ice forms on already existing ice producing a continuous body of ice. Ice moves around the soil grains through regelation under conditions of applied thermal and pressure gradients. If this body is not rigid, then movement would be accommodated either by breaking it at various locations or by elastic deformations. Since an ice-lens is a discontinuity in the soil, it would bear all the external pressure and the weight of soil above it, causing compressive stresses in it. From the capillary relationship, pore ice, being in equilibrium with unfrozen water, has higher pressure than unfrozen water. Thus, it also has compressive stresses and consequently cracking or fracturing of ice is not possible.

The ice strain rate can be found assuming that the heave rate is a reasonable ice velocity and the change in the velocity takes place over some macroscopic dimension, e.g. grain diameter or pore dimension. The stresses in ice required to cause these strain rates are much higher than the stresses which are observed during freezing and hence elastic deformations in ice could not accomodate the observed heave rates. Based on the above observations it would be reasonable to assume that ice is rigid.

Based on the foregoing arguments, O'Neill and Miller(1985) developed the governing equations and boundary conditions for one-dimensional RIM and solved them using the finite element method. In the following sections their model is extended to two dimensions and the complete derivation of the partial differential equations and boundary conditions for two-dimensional RIM are presented. The reader is referred to their work for more detailed description of derivation procedures.

2.2 Phase Equilibrium

The unfrozen water in partially frozen soils is present either in the thin adsorbed films around the soil grains or in capillary pores. The unfrozen water content in the capillary pores is directly related to the curvature of pores which depends upon the difference of ice pressure and water pressure, ϕ_{iw} . When a body of ice approaches an immersed grain, the amount of water it can displace from the adsorbed film depends upon their pressure difference, ϕ_{iw} . Hence, the unfrozen water content is a function of ϕ_{iw} . For saturated soils, ice content is a complementary function of ϕ_{iw} , assuming the volumetric grain content to be constant. Accordingly

$$W(\phi_{iw}) + I(\phi_{iw}) + G = 1 \quad (2.1)$$

where

G = volumetric grain content

The Clausius-Clapeyron equation, Eq. (1.5), can be simplified as follows by taking the freezing point of water to be 273 K.

$$P_w - \frac{\rho_w}{\rho_i} P_i = \frac{\rho_w L}{273} T \quad (2.2)$$

where

$$T = \text{temperature of soil in celsius}$$

The pressure difference, ϕ_{iw} , may be expressed as a linear function of water pressure and temperature using Eq. (2.2). That is

$$\phi_{iw} = \left(\frac{\rho_i}{\rho_w} - 1 \right) P_w - \frac{\rho_i L}{273} T = AP_w + BT \quad (2.3)$$

where

$$\begin{aligned} A &= \frac{\rho_i}{\rho_w} - 1 \\ B &= -\frac{\rho_i L}{273} \end{aligned}$$

From the above equation, the unfrozen water content and ice content can be written as

$$W = W(AP_w + BT) \quad (2.4a)$$

$$I = I(AP_w + BT) \quad (2.4b)$$

Differentials dI and dW , which are required subsequently, can be written from the latter as

$$dI = \frac{\partial I}{\partial P_w} dP_w + \frac{\partial I}{\partial T} dT = AI' dP_w + BI' dT \quad (2.5a)$$

$$dW = -dI \quad (2.5b)$$

where

$$I' = \frac{dI}{d\phi_{iw}}$$

2.3 Transport Equations

The process of freezing involves both heat and moisture transfer and therefore transport equations for both of these quantities need to be obtained.

2.3.1 Mass Transport Equation

The rate of change of mass of water and ice phase in a macroscopic soil element can be written as

$$S_w = \frac{\partial}{\partial t}(\rho_w W) + \nabla \cdot (\rho_w \mathbf{v}_w) \quad (2.6a)$$

$$S_I = \frac{\partial}{\partial t}(\rho_i I) + \nabla \cdot (\rho_i \mathbf{v}_i) \quad (2.6b)$$

where

$\mathbf{v}_w$ = volumetric water flux per unit area of soil

$\mathbf{v}_i$ = volumetric ice flux per unit area of soil

S_I = rate of change of ice mass or freezing

S_w = rate of change of the unfrozen water mass

It is to be noted that if the regelation contribution to mass transport is neglected, i.e. ice is assumed to have zero velocity, then the second term on the right-hand side of Eq. (2.6b) would disappear. If the volumetric grain content is constant with time and the pores are saturated, then mass conservation over a soil element can be written as

$$S_w + S_I = 0 \quad (2.7a)$$

or

$$\frac{\partial}{\partial t}(\rho_w W + \rho_i I) + \nabla \cdot (\rho_w \mathbf{v}_w) + \nabla \cdot (\rho_i \mathbf{v}_i) = 0 \quad (2.7b)$$

If the regelation contribution is neglected and the densities of water and ice are assumed to be constant with pressure and temperature, then Eq. (2.7b) may be simplified using Eq. (2.5b) as

$$\Delta\rho\frac{\partial}{\partial t}I + \rho_w\nabla \cdot (\mathbf{v}_w) = 0 \quad (2.8)$$

where

$$\Delta\rho = \rho_i - \rho_w$$

Most of the existing frost heave models have used the above equation for mass conservation. Since the RIM accounts for regelation, we will instead use Eq. (2.7b).

Darcy's law has been used by all the existing frost heave models to account for water transport, which may be expressed as

$$\mathbf{v}_w = \frac{-\mathbf{K}}{\rho_w g} \text{grad}(P_w) - \mathbf{K} \text{grad} h \quad (2.9)$$

where

$$\begin{aligned} \mathbf{K} &= \text{permeability matrix of soil} \\ g &= \text{gravitational acceleration} \\ \text{grad} h &= \text{gradient of height from datum} \\ \text{grad} P_w &= \text{gradient of water pressure} \end{aligned}$$

The gravity term in Eq. (2.9) has negligible contribution in the small soil-columns used in laboratory tests but would be considerable in the field.

The ice flux from the rigid-ice assumption can be written as

$$\mathbf{v}_I = \mathbf{V}_I I \quad (2.10)$$

where

$$\mathbf{V}_I = \text{ice velocity}$$

The ice velocity, $\mathbf{V}_I$, has a constant magnitude in space but its direction may be different at different points in space. At any point A in space its direction is given by a normal to the warmest ice-lens passing through the same point, Fig. 2.2. Thus $\mathbf{V}_I$ may be expressed as

$$\mathbf{V_I} = |\mathbf{V_I}| \mathbf{n_v} \quad (2.11)$$

where

$$\begin{aligned} |\mathbf{V_I}| &= \text{magnitude of ice velocity} \\ \mathbf{n_v} &= \text{unit vector normal to the warmest ice-lens} \\ &\quad \text{passing through the point under consideration} \end{aligned}$$

The expressions for water flux and ice flux from Eq. (2.9) and (2.10), respectively, can be substituted in the continuity equation (Eq. (2.7b)). If we assume constant densities, then using Eq. (2.5) the continuity equation may be written as

$$\Delta \rho A I' \frac{\partial P_w}{\partial t} + \Delta \rho B I' \frac{\partial T}{\partial t} - \nabla \cdot \left[\frac{\mathbf{K}}{g} \text{grad}(P_w + \rho_w g h) \right] + \rho_i \nabla \cdot (\mathbf{V_I} I) = 0 \quad (2.12)$$

The last term $\nabla \cdot (\mathbf{V_I} I)$ in the above may be expressed as follows using Eq. (2.6)

$$\nabla \cdot (\mathbf{V_I} I) = \mathbf{V_I}^T \text{grad} I + I \nabla \cdot (\mathbf{V_I}) = \mathbf{V_I}^T A I' \text{grad}(P_w) + \mathbf{V_I}^T B I' \text{grad} T + I \nabla \cdot (\mathbf{V_I}) \quad (2.13)$$

The modulus of ice velocity, $|\mathbf{V_I}|$, is constant in space and hence $\nabla \cdot (\mathbf{V_I})$ can be simplified using Eq. (2.11)

$$\nabla \cdot (\mathbf{V_I}) = |\mathbf{V_I}| \nabla \cdot (\mathbf{n_v}) \quad (2.14)$$

Substituting Eqs. (2.13) and (2.14) into Eq. (2.12) yields

$$\begin{aligned} &\Delta \rho A I' \frac{\partial P_w}{\partial t} + \Delta \rho B I' \frac{\partial T}{\partial t} - \nabla \cdot \left[\frac{\mathbf{K}}{g} \text{grad}(P_w + \rho_w g h) \right] \\ &+ \rho_i |\mathbf{V_I}| \mathbf{n_v}^T A I' \text{grad}(P_w) + \rho_i |\mathbf{V_I}| \mathbf{n_v}^T B I' \text{grad} T + \rho_i I |\mathbf{V_I}| \nabla \cdot (\mathbf{n_v}) = 0 \end{aligned} \quad (2.15)$$

This completes the development of mass transport equation. We observe that it contains three unknowns; namely water pressure, P_w , temperature, T , and ice velocity, $\mathbf{V_I}$.

2.3.2 Energy Transport Equation

We will begin by the following form of energy conservation equation which includes the latent heat effect and heat transfer due to convection:

$$C_a \frac{\partial T}{\partial t} + \nabla \cdot (\mathbf{q}_h) - \nabla \cdot [(C_w \mathbf{v}_w + C_i \mathbf{v}_i)T] = LS_I \quad (2.16)$$

where

- C_a = volumetric heat capacity of soil
- $\mathbf{q}_h$ = heat flux vector due to conduction
- C_w = volumetric heat capacity of water
- C_i = volumetric heat capacity of ice

The right-hand side term in the latter equation reflects the latent heat due to the freezing of water. The last term on the left-hand side of the same equation is the convection term. Convection heat transfer may occur through both the moisture and ice movement. It has been found that the convection term in freezing soils is several orders of magnitude less than the conduction term (Taylor and Luthin, 1978) and hence it will be discarded. It has also been neglected in all the previous frost heave models. The heat capacity of soil, C_a , can be evaluated from the individual heat capacity of soil grains, water and ice, i.e.

$$C_a = \rho_w c_w W + \rho_i c_i I + \rho_s c_s G \quad (2.17)$$

where

- c_s = specific heat capacity of soil grains
- c_w = specific heat capacity of water
- c_i = specific heat capacity of ice
- ρ_s = dry density of soil

The Fourier heat conduction law will be used to substitute for heat flux due to conduction

$$q_h = -k_h \text{grad} T \quad (2.18)$$

where

k_h = thermal conductivity matrix of soil

Combining Eqs. (2.5), (2.6b), (2.13) and (2.18) with Eq. (2.16) and neglecting convection yield,

$$\begin{aligned} (C_a - \rho_i L B I') \frac{\partial T}{\partial t} - \rho_i L A I' \frac{\partial P_w}{\partial t} - \rho_i L |V_I| n_v^T [A I' \text{grad}(P_w) + B I' \text{grad} T] \\ - \rho_i L I |V_I| \nabla \cdot n_v - \nabla \cdot (k_h \text{grad} T) = 0 \end{aligned} \quad (2.19)$$

Note that this energy-transport equation contains the same three unknowns as the mass-transport equation.

2.4 Calculation of Ice Velocity

Equations (2.15) and (2.19) represents coupled heat and moisture transfer in freezing soils. If the regelation contribution is neglected, then these two equations with the boundary and initial conditions would be sufficient for the solution. The consideration of regelation introduces one more unknown, the ice velocity. It is necessary to obtain an independent equation in terms of water pressure and temperature to evaluate the ice velocity. This equation with Eqs. (2.15) and (2.19) and the boundary and initial conditions would complete a solution.

It is possible to construct a mass balance over the lens-free region (freezing fringe and unfrozen region) which is independent of the continuity equation, Eq. (2.15). The ice-lens moves with a velocity of constant magnitude, $|V_I|$, in the direction normal to itself and hence ice flux through boundary S_1 (Fig. 2.2) is given by $\rho_i |V_I| \int_{S_1} dS_1$. The mass flux through the warm boundary S_2 can be evaluated by integrating water flux over it. The difference in these two fluxes must

be balanced by the rate of change in the ice and water mass over the lens-free region. That is

$$\rho_i |\mathbf{V}_I| \int_{S_1} dS_1 + \rho_w \int_{S_2} \mathbf{v}_w \mathbf{n}_2 dS_2 = \frac{d}{dt} \int_{R_1} [\rho_w W + \rho_i I] dR \quad (2.20)$$

where

- S_1 = surface made by the warmest ice-lens
- S_2 = external boundary of lens-free zone
- R_1 = lens-free region
- $\mathbf{n}_2$ = outward normal to S_2

The moisture flux, $\mathbf{v}_w$, in the above equation can be replaced by using Darcy's law, Eq. (2.9). The last term in it can be simplified by taking derivative with respect to time inside the integration and then by using Eq. (2.5). That is

$$|\mathbf{V}_I| = \frac{1}{\rho_i \int_{S_1} dS_1} \left[\frac{1}{g} \int_{S_2} \mathbf{K} \text{grad}(P_w + \rho_w g h) \mathbf{n}_2 dS_2 + \Delta \rho \frac{d}{dt} \int_{R_1} I dR \right] \quad (2.21a)$$

or

$$|\mathbf{V}_I| - \frac{1}{\rho_i \int_{S_1} dS_1} \left[\frac{1}{g} \int_{S_2} \mathbf{K} \text{grad}(P_w + \rho_w g h) \mathbf{n}_2 dS_2 + \Delta \rho \frac{d}{dt} \int_{R_1} I dR \right] = 0 \quad (2.21b)$$

The system of equations (2.15), (2.19) and (2.21b) with specified boundary and initial conditions are sufficient to solve for all the three unknowns, namely water pressure, temperature and ice velocity in space and time. It is also possible to evaluate $\mathbf{V}_I$ by considering mass balance over a plane through the warmest ice-lens. O'Neill and Miller(1985) have shown that if the mass balance over this infinitesimally thin zone is used to evaluate the ice velocity, then the result might become unstable when the system tries to achieve steady state.

2.5 Boundary Conditions

The governing partial differential equations for the lens-free region, R_1 , were derived. Since, both heat and moisture transfer takes place in this region, it is

necessary to specify two boundary conditions. Boundary conditions on the warm surface, S_2 , are the input of a problem. They can be of either Dirichlet type or Neumann type for both heat and moisture flow. Boundary conditions on S_1 (surface through the warmest ice-lens) can be obtained from the existing physical conditions. An ice-lens is a macroscopic discontinuity in the soil fabric and hence the total stress due to the existing external pressure and due to the weight of soil in the direction normal to the ice-lens must be equal to ice pressure at the location of ice-lens. For the warmest ice-lens (on S_1) it can be written as

$$\sigma_{n_1} = P_i \quad (\text{On } S_1) \quad (2.22)$$

where

σ_{n_1} = total stress normal to the warmest ice-lens

The ice pressure can be expressed in terms of basic variables P_w and T by using Eq. (2.3)

$$\sigma_{n_1} = (1 + A)P_w + BT \quad (\text{On } S_1) \quad (2.23)$$

The magnitude of stress σ_{n_1} should be determined from the stress analysis of the complete region, including both frozen and lens-free regions. The above stress analysis would be carried out before beginning the heat and moisture transfer model and the total stresses obtained would be used to determine σ_{n_1} .

A second boundary condition on S_1 can be obtained by considering the continuity of heat flow. It is assumed that mass transport and the phase change (freezing) in the frozen region, R_2 , are negligible and hence it can be analyzed for heat transfer only. The governing differential equation for that region is given by

$$C_a \frac{\partial T_1}{\partial t} = \nabla \cdot (k_h \text{grad } T_1) \quad (\text{On } R_2) \quad (2.24)$$

where

T_1 = temperature in the frozen region in celsius

The above equation can be solved for temperatures in the frozen region if thermal boundary conditions on S_1 and the cold surface, S_3 , (Fig. 2.2) are known. The boundary condition on S_3 is an input parameter, whereas for S_1 it is given by,

$$T_1 = T_{il} \quad (\text{On } S_1) \quad (2.25)$$

where

T_{il} = temperature of the warmest ice-lens

It is to be noted that T_{il} may vary from one point to another on the warmest ice-lens. In the time-marching scheme, the magnitude of T_{il} will be the one obtained from the analysis of R_1 in the previous time step.

Thermal analysis of R_2 would enable us to determine the heat extracted by R_2 along its boundary S_1 . We can thus write heat balance over S_1 as

$$q_{h_1} = -\mathbf{n}_1^T (\mathbf{k}_h \text{grad } T) + \mathbf{n}_1^T L \rho_w \mathbf{v}_w \quad (\text{On } S_1) \quad (2.26)$$

where

q_{h_1} = heat flow in R_2 at boundary S_1

$\mathbf{n}_1$ = a normal to surface S_1 going away from region R_1

The first term on the right-hand side reflects the conduction heat flow in R_1 ; the second term is the latent heat generated by the freezing of moisture arriving at the base of the warmest ice-lens.

2.6 Lens Initiation

We obtained the governing differential equations and their required boundary conditions in the preceding sections. The equations can be solved to obtain the water pressure and temperature distribution in space and time. The ice pressure distribution can be obtained from Eq. (2.2). As freezing progresses, the ice pressure keeps on increasing and somewhere behind the warmest ice-lens the conditions become favourable for the formation of a new ice-lens. When this happens, the

position of the warmest ice-lens, i.e. surface S_1 , is moved to this new location and the analysis of a reduced lens-free region is continued till steady state is reached.

The various available criteria to determine when and where a new ice-lens forms were discussed in section 1.2.7. O'Neill and Miller(1985) used the concept of the stress partition factor to determine the location and the time for the formation of a new ice-lens. This criterion predicts the formation of new ice-lens somewhere behind the freezing front rather than at the freezing front. This is in agreement with experimental evidence (Penner, 1986). An ice-lens is a macroscopic discontinuity in the soil fabric and hence it can form only by moving the soil grains apart. This would be possible when grain-to-grain contact stresses, i.e. the effective stress becomes zero. The effective stress will go to zero when the neutral pressure offsets all the overburden pressure. According to the concept of the stress partition factor, neutral pressure is some weighted average of ice pressure and water pressure (Eq. 1.6b). We shall use Eq. (1.9) to determine the stress partition factor.

2.7 Variation of Physical Parameters in Transport Equations

The variation of unfrozen water content is a very important parameter for the prediction of heave magnitudes in any numerical frost heave model. It was shown earlier that this quantity is a function of $\phi_{iw} = AP_w + BT$ (Eq. 2.4a). It would be desirable to fit some smooth function to the experimental data points for computational purposes. We fit the same function as that used by O'Neill and Miller(1985). That is

$$W = \sum_{k=0}^5 A_k \left(\ln \frac{\phi_{iw}}{\omega_{iw}} \right)^k \quad (2.27)$$

where

A_k = vector of constant coefficients to be obtained by curve fitting

The functional expression for the unfrozen water content would enable us to carry

out the integration in the formula of stress partition factor, Eq. 1.10, analytically. The hydraulic permeability and thermal conductivity matrices vary with the unfrozen water content and the ice content. We will assume the soil to be isotropic and also the off-diagonal terms in the permeability and the thermal conductivity matrices to be zero. i.e.

$$\mathbf{K} = \begin{bmatrix} k_d & 0 \\ 0 & k_d \end{bmatrix} \quad (2.28a)$$

$$\mathbf{k}_h = \begin{bmatrix} k_{hd} & 0 \\ 0 & k_{hd} \end{bmatrix} \quad (2.28b)$$

where

k_d = permeability of soil in any direction

k_{hd} = thermal conductivity of soil in any direction

The permeability variation is assumed to be (O'Neill and Miller, 1985)

$$k_d(W) = k_d(n) \left(\frac{W}{n} \right)^\gamma \quad (2.29)$$

where

γ = empirical constant

The magnitude of γ was taken to be 7 by Bresler et al.(1978) and 9 by O'Neill and Miller(1985). The thermal conductivity for both the frozen and unfrozen soil was evaluated by the geometric mean formula given by Johansen(1977).

$$k_{hd} = k_{hi}^I k_{hw}^W k_{hs}^G \quad (2.30)$$

where

k_{hi} = thermal conductivity of ice

k_{hw} = thermal conductivity of water

k_{hs} = thermal conductivity of soil grains

For the unfrozen region, the ice content would be zero and the unfrozen water content would be the same as porosity, whereas for frozen or partially frozen regions

W can be calculated from Eq. (2.27) and I can be obtained by subtracting it from the porosity.

The effective or apparent heat capacity from energy transport equation, Eq. 2.19, can be written as

$$C_{eff} = \rho_w c_w W + \rho_i c_i I + \rho_s c_s G - \rho_i L B I' \quad (2.31)$$

where

$$C_{eff} = \text{effective heat capacity}$$

The derivative of the ice content, I' , can be evaluated analytically from Eq. (2.28)

$$I' = \sum_{k=0}^5 \mathbf{A}_k k \left(\ln \frac{\phi_{iw}}{\omega_{iw}} \right)^{k-1} \frac{1}{\phi_{iw}} \quad (2.32)$$

2.8 Finite Element Formulation

The governing partial differential equations and the boundary conditions at the interface of frozen and lens-free regions were obtained. We can solve these equations using a suitable numerical method if initial conditions are provided. We shall use the finite element method in space and the finite difference method in time to solve the relevant differential equations. The governing differential equations for the lens-free region, Eqs. (2.15), (2.19) and (2.21b), respectively, can be written as

$$P_1 = 0 \quad (2.33a)$$

$$P_2 = 0 \quad (2.33b)$$

$$P_3 = 0 \quad (2.33c)$$

where P_1 , P_2 and P_3 are given by the left-hand side of Eqs. (2.15), (2.19) and (2.21b), respectively. The boundary conditions for the lens-free region on surface $S = S_1 + S_2$ can be written as

$$B_1 = \sigma_{n_1} - [(1 + A)P_w + BT] = 0 \quad (\text{On } S_1) \quad (2.34a)$$

$$B_2 = q_{h_1} + \mathbf{n}_1^T (\mathbf{k}_h \text{grad } T) - \mathbf{n}_1^T L \rho_w \mathbf{v}_w = 0 \quad (\text{On } S_1) \quad (2.34b)$$

$$B_3 = q_2 + \mathbf{n}_2^T \frac{\mathbf{K}}{g} \text{grad } (P_w + \rho_w g h) = 0 \quad (\text{On } S_2) \quad (2.34c)$$

$$B_4 = q_{h_2} + \mathbf{n}_2^T (\mathbf{k}_h \text{grad } T) = 0 \quad (\text{On } S_2) \quad (2.34d)$$

where

q_2 = specified moisture flow on boundary S_2

q_{h_2} = specified heat flow on boundary S_2

The Dirichlet type boundary conditions on surface S_2 , i.e. prescribed pore pressure or temperature, can be directly applied to the final finite element equations and therefore are not considered in the latter equations. The boundary condition given by Eq. (2.34a) can be applied in a similar way to the final finite element equations and hence will not be considered in the derivation of finite element equations.

Eq. (2.33c) is used to evaluate ice velocity from the given water pressure and temperature distribution. It can be substituted in the mass and energy transport equations, Eqs. (2.33a) and (2.33b), to reduce one unknown but that destroys the banded nature of the system of finite element equations since the evaluation of ice velocity involves integration over the full lens-free region. We will therefore include it iteratively with Eqs. (2.33a) and (2.33b). The condition that Eqs. (2.33a) and (2.33b) are valid in the full lens-free region while the boundary condition implicit in Eq. (2.34) are valid on the surface, requires that

$$\int_{R_1} c_1 P_1 dR + \int_{S_2} d_1 B_3 dS = 0 \quad (2.35a)$$

$$\int_{R_1} c_2 P_2 dR + \int_{S_1} d_2 B_2 dS + \int_{S_2} d_3 B_4 dS = 0 \quad (2.35b)$$

where c_1, d_1, c_2, d_2 and d_3 are arbitrary weight functions.

The finite element method can now be applied to the above integral equations. Eqs. (2.35a) and (2.35b) contain spatial integration of the second derivatives of

$(P_w + \rho_w gh)$ and T , respectively. This necessitates the smooth distribution of these quantities in space, i.e their continuous first derivative. In order to overcome this limitation a weak form can be obtained by means of Green's Theorem. According to which for region R' with boundary S'

$$\int_{R'} a_g \nabla \cdot \{\phi'\} dR - \int_{S'} (\mathbf{n}')^T a_g \{\phi'\} dS = - \int_{R'} (\text{grad } a_g)^T \{\phi'\} dR \quad (2.36)$$

where a_g and $\{\phi'\}$ are any functions and $\mathbf{n}'$ is a normal to surface S' . Since c_1, c_2, d_1, d_2 and d_3 are arbitrary weight functions, they can be taken such that

$$c_1 = d_1 \quad (2.37a)$$

$$c_2 = d_2 = d_3 \quad (2.37b)$$

Substituting Eq. (2.37) and the expressions for P_1, P_2, B_2, B_3 and B_4 into Eq. (2.34) gives

$$\begin{aligned} & \int_{R_1} c_1 \left[\Delta \rho A I' \frac{\partial P_w}{\partial t} + \Delta \rho B I' \frac{\partial T}{\partial t} + \rho_i |\mathbf{V}_I| |\mathbf{n}_v|^T \{ A I' \text{grad}(P_w) + B I' \text{grad} T \} \right] dR \\ & - \int_{R_1} c_1 \left[\nabla \cdot \left\{ \frac{\mathbf{K}}{g} \text{grad}(P_w + \rho_w gh) \right\} \right] dR + \int_S c_1 \mathbf{n}_g^T \frac{\mathbf{K}}{g} \text{grad}(P_w + \rho_w gh) dS \\ & + \int_{R_1} c_1 \rho_i I |\mathbf{V}_I| \nabla \cdot (\mathbf{n}_v) dR + \int_{S_2} c_1 q_2 dS - \int_{S_1} c_1 \mathbf{n}_1^T \frac{\mathbf{K}}{g} \text{grad}(P_w + \rho_w gh) dS = 0 \end{aligned} \quad (2.38a)$$

$$\begin{aligned} & \int_{R_1} c_2 \left[C_{eff} \frac{\partial T}{\partial t} - \rho_i L A I' \frac{\partial P_w}{\partial t} - \rho_i L |\mathbf{V}_I| |\mathbf{n}_v|^T \{ A I' \text{grad}(P_w) + B I' \text{grad} T \} \right] dR \\ & - \int_{R_1} c_2 \nabla \cdot (\mathbf{k}_h \text{grad} T) dR + \int_S c_2 \mathbf{n}_g^T (\mathbf{k}_h \text{grad} T) dS \\ & - \rho_i L \int_{R_1} c_2 I |\mathbf{V}_I| \nabla \cdot \mathbf{n}_v dR + \int_S c_2 q_{hg} dS + \int_{S_1} c_2 \mathbf{n}_1^T L \frac{\mathbf{K}}{g} \text{grad}(P_w + \rho_w gh) dS = 0 \end{aligned} \quad (2.38b)$$

where $\mathbf{n}_g$ is a normal to surface $S = S_1 + S_2$ and q_{hg} is a specified heat flow on the boundary S . The normal $\mathbf{n}_g$ would equal $\mathbf{n}_1$ if the point under consideration is on S_1 or equal to $\mathbf{n}_2$ if it is on S_2 . The last term in Eq. (2.38a) is not necessary since we are imposing Eq. (2.34a) on S_1 . Applying Green's Theorem to the second line of Eqs. (2.38a) and (2.38b) with $\{\phi'\} = -\frac{\mathbf{K}}{g} \text{grad}(P_w + \rho_w gh)$ and $\{\phi'\} = -\mathbf{k}_h \text{grad} T$, respectively.

$$\begin{aligned} & \int_{R_1} c_1 \left[\Delta \rho A I' \frac{\partial P_w}{\partial t} + \Delta \rho B I' \frac{\partial T}{\partial t} + \rho_i |\mathbf{V}_I| |\mathbf{n}_v|^T \{ A I' \text{grad}(P_w) + B I' \text{grad} T \} \right] dR \\ & + \int_{R_1} c_1 \rho_i I |\mathbf{V}_I| |\nabla \cdot (\mathbf{n}_v)| dR + \int_{R_1} (\text{grad} c_1) \frac{\mathbf{K}}{g} \text{grad}(P_w + \rho_w gh) dR + \int_{S_2} c_1 q_2 dS = 0 \end{aligned} \quad (2.39a)$$

$$\begin{aligned} & \int_{R_1} c_2 \left[C_{eff} \frac{\partial T}{\partial t} - \rho_i L A I' \frac{\partial T}{\partial t} - \rho_i L |\mathbf{V}_I| |\mathbf{n}_v|^T \{ A I' \text{grad}(P_w) + B I' \text{grad} T \} \right] dR \\ & + \int_{R_1} (\text{grad} c_2) \mathbf{k}_h \text{grad} T dR + \int_S c_2 q_{hg} dS \\ & - \rho_i L \int_{R_1} c_2 I |\mathbf{V}_I| |\nabla \cdot \mathbf{n}_v| dR + \int_{S_1} c_2 \mathbf{n}_1^T L \frac{\mathbf{K}}{g} \text{grad}(P_w + \rho_w gh) dS = 0 \end{aligned} \quad (2.39b)$$

The finite element expressions for the variation of water pressure and temperature over an element can be applied to Eq. (2.39). We shall use the Galerkin finite element method and hence weight functions c_1 and c_2 are the same as the shape functions defining the variation of water pressure and temperature. The quantities P_w and T can be expressed as

$$P_w = \mathbf{N} \mathbf{P}_w^s \quad (2.40a)$$

$$T = \mathbf{N} \mathbf{T}^s \quad (2.40b)$$

where

$\mathbf{N}$ = shape function matrix

$\mathbf{P}_w^s$ = vector containing nodal values of water pressure

$\mathbf{T}^s$ = vector containing nodal values of temperature

and c_1 and c_2 can be written as

$$c_1 = c_2 = N_k \quad (\text{For } k = 1, nn) \quad (2.41)$$

where

N_k = k th shape function

nn = number of nodes in a finite element

If we substitute Eqs. (2.40) and (2.41) into Eq. (2.39), then we get nn equations which are given by

$$\begin{aligned} \Delta \rho A \int_{R_1} \mathbf{N}^T I' \mathbf{N} dR \frac{\partial \mathbf{P}_w^s}{\partial t} + \Delta \rho B \int_{R_1} \mathbf{N}^T I' \mathbf{N} dR \frac{\partial \mathbf{T}^s}{\partial t} + \int_{R_1} (\text{grad } \mathbf{N})^T \frac{\mathbf{K}}{g} \text{grad } \mathbf{N} dR \mathbf{P}_w^s \\ + \rho_i |\mathbf{V}_I| A \int_{R_1} \mathbf{N}^T \mathbf{n}_v^T I' \text{grad } \mathbf{N} dR \mathbf{P}_w^s + \rho_i |\mathbf{V}_I| B \int_{R_1} \mathbf{N}^T \mathbf{n}_v^T I' \text{grad } \mathbf{N} dR \mathbf{T}^s \\ + \rho_w \int_{R_1} (\text{grad } \mathbf{N})^T \mathbf{K} \text{grad } h dR + \rho_i |\mathbf{V}_I| \int_{R_1} \mathbf{N}^T I \nabla \cdot (\mathbf{n}_v) dR + \int_{S_2} \mathbf{N}^T q_2 dS = 0 \end{aligned} \quad (2.42a)$$

$$\begin{aligned} \int_{R_1} \mathbf{N}^T C_{eff} \mathbf{N} dR \frac{\partial \mathbf{T}^s}{\partial t} - \rho_i L A \int_{R_1} \mathbf{N}^T I' \mathbf{N} dR \frac{\partial \mathbf{P}_w^s}{\partial t} - \int_{R_1} (\text{grad } \mathbf{N})^T \mathbf{k}_h \text{grad } \mathbf{N} dR \mathbf{T}^s \\ - \rho_i B L |\mathbf{V}_I| \int_{R_1} \mathbf{N}^T \mathbf{n}_v^T I' \text{grad } \mathbf{N} dR \mathbf{T}^s - \rho_i A L |\mathbf{V}_I| \int_{R_1} \mathbf{N}^T \mathbf{n}_v^T I' \text{grad } \mathbf{N} dR \mathbf{P}_w^s \\ + \int_S \mathbf{N}^T q_{hg} dS + \frac{L}{g} \int_{S_1} \mathbf{N}^T \mathbf{n}_1^T \mathbf{K} \text{grad } \mathbf{N} dS \mathbf{P}_w^s + L \rho_w \int_{S_1} \mathbf{N}^T \mathbf{n}_1^T \mathbf{K} \text{grad } h dS \\ + \rho_i L \int_{R_1} \mathbf{N}^T I |\mathbf{V}_I| \nabla \cdot (\mathbf{n}_v) dR = 0 \end{aligned} \quad (2.42b)$$

Eq. (2.42) can be written in a simpler form as

$$\mathbf{M}\mathbf{P} \frac{\partial \mathbf{P}_w^s}{\partial t} + \mathbf{M}\mathbf{T} \frac{\partial \mathbf{T}^s}{\partial t} + \mathbf{S}\mathbf{P}\mathbf{P}_w^s + \mathbf{S}\mathbf{T}\mathbf{T}^s + \mathbf{f}_1 = 0 \quad (2.43a)$$

$$\mathbf{JP} \frac{\partial \mathbf{P}_w^s}{\partial t} + \mathbf{JT} \frac{\partial \mathbf{T}^s}{\partial t} + \mathbf{RPP}_w^s + \mathbf{RTT}^s + \mathbf{f}_2 = 0 \quad (2.43b)$$

where

$$\mathbf{MP} = \Delta \rho A \int_{R_1} \mathbf{N}^T I' \mathbf{N} dR$$

$$\mathbf{MT} = \Delta \rho B \int_{R_1} \mathbf{N}^T I' \mathbf{N} dR$$

$$\mathbf{SP} = \int_{R_1} (\text{grad} \mathbf{N})^T \frac{\mathbf{K}}{g} \text{grad} \mathbf{N} dR + \rho_i |\mathbf{V}_I| A \int_{R_1} \mathbf{N}^T \mathbf{n}_v^T I' \text{grad} \mathbf{N} dR$$

$$\mathbf{ST} = \rho_i |\mathbf{V}_I| B \int_{R_1} \mathbf{N}^T \mathbf{n}_v^T I' \text{grad} \mathbf{N} dR$$

$$\mathbf{f}_1 = \rho_w \int_{R_1} (\text{grad} \mathbf{N})^T \mathbf{K} \text{grad} h dR + \rho_i |\mathbf{V}_I| \int_{R_1} \mathbf{N}^T I \nabla \cdot (\mathbf{n}_v) dR + \int_{S_2} \mathbf{N}^T q_2 dS$$

$$\mathbf{JP} = -\rho_i L A \int_{R_1} \mathbf{N}^T I' \mathbf{N} dR$$

$$\mathbf{JT} = \int_{R_1} \mathbf{N}^T C_{eff} \mathbf{N} dR$$

$$\mathbf{RP} = -\rho_i A L |\mathbf{V}_I| \int_{R_1} \mathbf{N}^T \mathbf{n}_v^T I' \text{grad} \mathbf{N} dR + \frac{L}{g} \int_{S_1} \mathbf{N}^T \mathbf{n}_1^T \mathbf{K} \text{grad} \mathbf{N} dS$$

$$\mathbf{RT} = \int_{R_1} (\text{grad} \mathbf{N})^T \mathbf{k}_h \text{grad} \mathbf{N} dR - \rho_i B L |\mathbf{V}_I| \int_{R_1} \mathbf{N}^T \mathbf{n}_v^T I' \text{grad} \mathbf{N} dR$$

$$\mathbf{f}_2 = \int_S \mathbf{N}^T q_{hg} dS + L \rho_w \int_{S_1} \mathbf{N}^T \mathbf{n}_1^T \mathbf{K} \text{grad} h dS + \rho_i L \int_{R_1} \mathbf{N}^T I |\mathbf{V}_I| \nabla \cdot (\mathbf{n}_v) dR$$

A suitable time marching scheme can be applied to Eq. (2.43) to obtain the solution in time domain. We apply Eq. (2.43) at successive points in time t' , where $t_m \leq t' \leq t_{m+1}$, and t_m and t_{m+1} are the magnitude of time at the beginning and at the end of m th time step. The dependent variables $\mathbf{P}_w^s$ and $\mathbf{T}^s$ at time t' can be approximated by

$$\mathbf{P}_w^s = \mu (\mathbf{P}_w^s)_{m+1} + (1 - \mu) (\mathbf{P}_w^s)_m \quad (2.44a)$$

$$\mathbf{T}^s = \mu (\mathbf{T}^s)_{m+1} + (1 - \mu) (\mathbf{T}^s)_m \quad (2.44b)$$

where

μ = a constant between 0 and 1

$(\mathbf{P}_w^s)_m$ = vector of nodal water pressures at the beginning of m th time step

$(\mathbf{P}_w^s)_{m+1}$ = vector of nodal water pressures at the end of m th time step

$(\mathbf{T}^s)_m$ = vector of nodal temperatures at the beginning of m th time step

$(\mathbf{T}^s)_{m+1}$ = vector of nodal temperatures at the end of m th time step

The first derivatives of $\mathbf{P}_w^s$ and $\mathbf{T}^s$ with respect to time can be approximated by using finite difference expressions,

$$\frac{\partial \mathbf{P}_w^s}{\partial t} = \frac{(\mathbf{P}_w^s)_{m+1} - (\mathbf{P}_w^s)_m}{t_{m+1} - t_m} \quad (2.45a)$$

$$\frac{\partial \mathbf{T}^s}{\partial t} = \frac{(\mathbf{T}^s)_{m+1} - (\mathbf{T}^s)_m}{t_{m+1} - t_m} \quad (2.45b)$$

We can substitute Eqs. (2.44) and (2.45) into Eq. (2.43) and write it in matrix form as

$$\begin{bmatrix} \mu \mathbf{SP} + \frac{\mathbf{MP}}{\Delta t_m} & \mu \mathbf{ST} + \frac{\mathbf{MT}}{\Delta t_m} \\ \mu \mathbf{RP} + \frac{\mathbf{JP}}{\Delta t_m} & \mu \mathbf{RT} + \frac{\mathbf{JT}}{\Delta t_m} \end{bmatrix} \begin{Bmatrix} (\mathbf{P}_w^s)_{m+1} \\ (\mathbf{T}^s)_{m+1} \end{Bmatrix} = \begin{bmatrix} \frac{\mathbf{MP}}{\Delta t_m} - (1 - \mu) \mathbf{SP} & \frac{\mathbf{MT}}{\Delta t_m} - (1 - \mu) \mathbf{ST} \\ \frac{\mathbf{JP}}{\Delta t_m} - (1 - \mu) \mathbf{RP} & \frac{\mathbf{JT}}{\Delta t_m} - (1 - \mu) \mathbf{RT} \end{bmatrix} \begin{Bmatrix} (\mathbf{P}_w^s)_m \\ (\mathbf{T}^s)_m \end{Bmatrix} - \begin{Bmatrix} \mathbf{f}_1 \\ \mathbf{f}_2 \end{Bmatrix} \quad (2.46)$$

where

$$\Delta t_m = \text{size of } m\text{th time step} = t_{m+1} - t_m$$

Eq. (2.46) will provide the solution in space and time if proper boundary and initial conditions are given. The coefficient matrices in this equation contain ice velocity, water content, ice content, thermal conductivity and permeability, which are dependent upon the unknowns, water pressure and temperature. They can be evaluated iteratively at $(\mathbf{P}_w^s)^*$ and $(\mathbf{T}^s)^*$, where $(\mathbf{P}_w^s)^*$ and $(\mathbf{T}^s)^*$ are given by

$$(\mathbf{P}_w^s)^* = \alpha (\mathbf{P}_w^s)_{m+1} + (1 - \alpha) (\mathbf{P}_w^s)_m \quad (2.47a)$$

$$(\mathbf{T}^s)^* = \alpha (\mathbf{T}^s)_{m+1} + (1 - \alpha) (\mathbf{T}^s)_m \quad (2.47b)$$

α = a constant between 0 and 1

The coefficients α and μ defines the finite difference scheme ($\alpha = \mu = 1$ gives backward difference, $\alpha = \mu = 0$ gives forward difference and $\alpha = \mu = 0.5$ gives Crank-Nicholson scheme). The expression for ice velocity (Eq. 2.21) can be written in a finite element form using Eqs. (2.40) and (2.47). The time derivative in the equation can be approximated by a finite difference expression.

$$|\mathbf{V}_1| = \frac{1}{\rho_i \int_{S_1} dS_1} \left[\frac{1}{g} \int_{S_2} \mathbf{K} \text{grad} N dS (\mathbf{P}_w^s)^* + \rho_w \int_{S_2} \mathbf{K} \text{grad} h dS + \right]$$

$$\Delta\rho\left\{\frac{\left(\int_{R_1} IdR\right)_{m+1} - \left(\int_{R_1} IdR\right)_m}{\Delta t_m}\right\} \quad (2.48)$$

The complete solution can be obtained from Eq. (2.46), Eq. (2.48), initial conditions and the boundary conditions on the warmest ice-lens (Eqs. (2.34a) and (2.34b)) and the prescribed pressure and temperature boundary conditions on the remaining surface of lens-free region.

The thermal analysis of frozen zone is governed by Eq. (2.24). We can solve this equation using the finite element method. The finite element equations can be derived similarly to those of the lens-free region. The differential equation contains the second derivative of temperature in space and hence a weak form would be obtained using Green's Theorem. The final finite element equations can be written as

$$\left[\frac{\mathbf{XT}}{\Delta t_m} + \mu_1 \mathbf{YT}\right] (\mathbf{T}_1^s)_{m+1} = \left[\frac{\mathbf{XT}}{\Delta t_m} - (1 - \mu_1) \mathbf{YT}\right] (\mathbf{T}_1^s)_m - \mathbf{ZT} \quad (2.49)$$

where

- μ_1 = a constant between 0 and 1
- $\mathbf{XT}$ = $\int_{R_2} \mathbf{N}^T C_a \mathbf{N} dR$
- $\mathbf{YT}$ = $\int_{R_2} (\text{grad } \mathbf{N})^T \mathbf{k}_h \text{grad } \mathbf{N} dR$
- $\mathbf{ZT}$ = $\int_{S_3} \mathbf{N}^T q_{h3} dS$
- $(\mathbf{T}_1^s)_m$ = vector of nodal temperatures at the beginning of
mth time step in the frozen region
- $(\mathbf{T}_1^s)_{m+1}$ = vector of nodal temperatures at the end of
mth time step in the frozen region
- q_{h3} = specified heat flow on boundary S_3

We will use the same element as that is used for the analysis of lens-free region and

hence the shape functions will remain the same. Eq. (2.49) with specified thermal boundary conditions on S_3 , Eq. (2.25), and the initial conditions can be used to solve for temperature distribution in the frozen region. The latter can be used to determine the rate of the extraction of heat at the interface of frozen and lens-free region. We shall use the same time step for the analysis of both regions.

Fig. 2.1. A continuous and intricate body of ice in freezing fringe. After O'Neill and Miller (1985)

Fig. 2.2. Freezing soil divided into lens-free and frozen regions

CHAPTER 3

Numerical Solution Strategies

3.1 General

In the previous chapter, we obtained the finite element equations for the heat and moisture transfer in freezing soils. The equation for the evaluation of ice velocity, boundary conditions at the interface of the frozen and lens-free regions and the finite element equations for the frozen region were obtained in a form which can be readily solved. The scheme of solution involves a time-incremental analysis. The governing partial differential equations for the lens-free region are highly nonlinear and hence it is necessary to iterate in each time-step. The nonlinearity of these equations arises from the dependence of ice velocity, thermal conductivity, permeability and ice content on water pressure and temperature. This nonlinearity is local since these equations are reduced to a linear form in the unfrozen region. After the completion of each time-step the system is checked for the initiation of a new ice-lens. If the new ice-lens is about to form, then the finite element mesh for the lens-free region is contracted and that for the frozen region is expanded in such a way that their common boundary coincides with the location of the new warmest ice-lens. This procedure can be repeated till the system approaches a steady state, i.e the growth of final ice-lens is achieved.

The order of variation of various dependent properties is very high in the thin freezing fringe. The permeability at the base of the warmest ice-lens is 2 to 3 orders of magnitude less than at the freezing front. These large variations and the consequent nonlinearity in the extremely thin freezing fringe make it necessary to use higher order elements. The 8-noded isoparametric element with a fine mesh in the frozen fringe would be satisfactory to accomodate these large variations.

In the following sections, some important aspects of the numerical simulations are discussed.

3.2 8-Noded Isoparametric Element

The node-numbering for an 8-noded isoparametric element is shown in Fig. 3.1. Its shape functions in natural coordinates are given by (zienkwicz, 1985)

$$\mathbf{N} = \{N_1, N_2, N_3 \dots N_8\} \quad (3.1)$$

where the shape functions N_1 to N_8 are given by

$$N_5 = \frac{1}{2}(1 - \eta)(1 - \zeta^2) \quad (3.2a)$$

$$N_6 = \frac{1}{2}(1 - \eta^2)(1 + \zeta) \quad (3.2b)$$

$$N_7 = \frac{1}{2}(1 + \eta)(1 - \zeta^2) \quad (3.2c)$$

$$N_8 = \frac{1}{2}(1 - \eta^2)(1 - \zeta) \quad (3.2d)$$

$$N_1 = \frac{1}{4}(1 - \eta)(1 - \zeta) - \frac{N_5}{2} - \frac{N_8}{2} \quad (3.2e)$$

$$N_2 = \frac{1}{4}(1 - \eta)(1 + \zeta) - \frac{N_5}{2} - \frac{N_6}{2} \quad (3.2f)$$

$$N_3 = \frac{1}{4}(1 + \eta)(1 + \zeta) - \frac{N_6}{2} - \frac{N_7}{2} \quad (3.2g)$$

$$N_4 = \frac{1}{4}(1 + \eta)(1 - \zeta) - \frac{N_7}{2} - \frac{N_8}{2} \quad (3.2h)$$

where

ζ = natural coordinate varying from -1 to 1

η = natural coordinate varying from -1 to 1

The global coordinates X and Y for an isoparametric element can be written as

$$X = \sum_{i=1}^8 N_i X_i \quad (3.3a)$$

$$Y = \sum_{i=1}^8 N_i Y_i \quad (3.3b)$$

where

X_i = a vector containing X -coordinates of nodes of an element

Y_i = a vector containing Y -coordinates of nodes of an element

3.3 Numerical Integration and Surface Normals

The integrations in the coefficient matrices of Eqs. (2.45) and (2.46) will be carried out using Gaussian integration. Accordingly, area integrations of function F in two-dimensions can be written as

$$\iint F(X, Y) dX dY = \sum_{i=1}^M \sum_{j=1}^M F(\zeta_i, \eta_j) W_i W_j |J| \quad (3.4)$$

where

M = number of Gauss points

W_i = weight factor of the i th Gauss point

W_j = weight factor of the j th Gauss point

ζ_i = coordinate of i th Gauss point

η_j = coordinate of j th Gauss point

$|J|$ = determinant of the Jacobian matrix

The function F can be obtained in terms of natural coordinates by substituting for the global coordinates X and Y from Eq. (3.3). The determinant of the Jacobian is given by

$$| \mathbf{J} | = \det \begin{bmatrix} \frac{\partial X}{\partial \zeta} & \frac{\partial Y}{\partial \zeta} \\ \frac{\partial X}{\partial \eta} & \frac{\partial Y}{\partial \eta} \end{bmatrix} \quad (3.5)$$

The derivatives of X and Y in the above equation can be evaluated by using Eq. (3.3).

The line integration of any function F_1 can be similarly written as

$$\int F_1(X, Y) dS = \sum_{i=1}^M F(\zeta_i, \eta_c) W_i J_s \quad (3.6)$$

where

η_c = a constant value of η

J_s = determinant of the Jacobian for the line integration

On any surface, either ζ or η would have a constant value. If we assumed η to have a constant value of η_c , the Jacobian of line integration for this case can be written as

$$J_s = \sqrt{\left(\frac{\partial X}{\partial \zeta}\right)^2 + \left(\frac{\partial Y}{\partial \zeta}\right)^2} \quad (3.7)$$

The value of M in Eqs. (3.4) and (3.6) was taken to be 3. The normal to the boundaries is also required for the evaluation of coefficient matrices. The scalar components of a normal on a surface with constant η can be written as,

$$n_{11} = \frac{1}{J_s} \frac{\partial X}{\partial \zeta} \quad (3.8a)$$

$$n_{12} = \frac{-1}{J_s} \frac{\partial Y}{\partial \zeta} \quad (3.8b)$$

where

n_{11} = X -component of a normal to the surface

n_{12} = Y -component of a normal to the surface

3.4 Evaluation of The Direction of Ice-velocity

The direction of ice-velocity, $\mathbf{n}_v$, for any point $A(x_1, y_1)$ is defined as a unit normal to the the warmest ice-lens, surface S_1 , and passing through point A. We could try several points $C(x, y)$ on the surface S_1 till the distance AB becomes negligible (Fig. 3.2). The distance AB for any point $C(x, y)$ on the surface S_1 can be expressed as

$$AB = \frac{y_1 - \frac{n_{v2}}{n_{v1}}(x_1 - x) - y}{\sqrt{1 + \left(\frac{n_{v2}}{n_{v1}}\right)^2}} \quad (3.9)$$

where n_{v1} and n_{v2} are the scalar components of the unit normal vector $\mathbf{n}_v$. The divergence of $\mathbf{n}_v$ can be expressed as,

$$\nabla \cdot \mathbf{n}_v = \frac{\partial n_{v1}}{\partial x} + \frac{\partial n_{v2}}{\partial y} \quad (3.10)$$

If we assume the surface S_1 to be composed of small linear pieces, then $\nabla \cdot \mathbf{n}_v$ is zero for all the points except at the corners. The magnitude of the term corresponding to $\nabla \cdot \mathbf{n}_v$ is assumed to be negligible compared to other terms in the mass-transport equation and hence we shall take $\nabla \cdot \mathbf{n}_v$ to be zero.

3.5 Stability and Oscillation

The stability and oscillation of results depend upon two parameters. The first parameter, α , defines when the coefficient matrices are to be evaluated in any time step, whereas the second parameter, μ , defines when the equations are to be solved in any time step. The stability can be ensured by taking both α and μ larger than 0.5 (Lewis and Schrefler, 1978). This allows us to use any size of time-step without causing instability. The prevention of oscillation, however, puts more severe restrictions on these parameters. The only simple guarantee is to set both of them equal to 1. The accuracy of solution is decreased in this case and hence

some intermediate values may need to be used. O'Neill and Miller(1985) in their simulation of 1-D RIM found the optimum values of α and μ to be 0.5 and 0.75, respectively. The same values will be used in the present investigation.

3.6 Thermal Properties of Frozen Region

The thermal conductivity and the heat capacity for frozen region, Eqs. (2.30) and (2.17), depend upon the unfrozen water content only. The unfrozen water content does not change significantly in the frozen region. We could therefore assume the properties of the frozen region to be constant. This would make the analysis of frozen region relatively simple and would allow us to use a coarse mesh in the finite element discretization.

3.7 Convergence and Time-step Adjustments

The system of equations is highly nonlinear and hence we must iterate at each time-step. The solution is assumed to have converged when the change between two consecutive iterations become negligible. A change of less than or equal to 1% was considered negligible. We could check any combination of three basic unknowns, water pressures, temperatures and ice velocity, to determine the convergence. The convergence of one quantity does not ensure that the others have converged by the same degree. In the present analysis it was decided to check only ice velocity or heave rate for convergence because it is the most important quantity for the prediction of heave magnitude.

It was found that if the size of time-step were larger than that which the system can absorb, convergence was not possible even with 25 iterations. When this happened, the size of time-step was halved and the analysis for the same time-step was restarted. If the system converged in less than 5 iterations, than the size of time-step for the next increment is doubled. The required size of time step was very small in the beginning, but it kept on increasing as freezing progressed. This is expected because the temperature gradients are steep and the freezing is rapid in

the beginning. Note, however, that the size of time-step was not allowed to exceed some maximum value. This maximum value of time-step was very small in the beginning and kept on increasing.

3.8 Solution Procedure

First, the frozen region is analyzed to determine the boundary condition at the location of warmest ice-lens, Eq. (2.26). We begin the solution procedure in lens-free region by guessing or estimating the values of water pressure and temperature in the lens-free region at the end of a given time step. For convenience of this analysis, we assume them to be same as their values at the beginning of the time-step. Next, the estimated values are used to determine dependent properties, e.g. ice velocity. We then solve the finite element equations, Eq. (2.46) to update the assumed values of water pressure and temperature. This process is repeated until the required degree of accuracy is achieved.

After the completion of each time-step, the system is checked for the initiation of a new ice-lens. Points in a number of directions along the finite element edges surrounding the pipeline are checked for lens-formation. A new ice-lens is assumed to form in such a way that the warmest ice-lens always remains continuous, Fig. 3.3. Though this assumption has not been verified by any experiment, it can be argued that a discontinuous ice-lens segment cannot form if the soil was homogeneous in its unfrozen state. The formation of an ice-lens depends upon the variation of water pressure, temperature and stresses which are smooth since there are no abrupt changes in the properties of soil. Therefore, a discontinuous ice-lens segment cannot form. The above assumption greatly simplifies the problem, for otherwise we would have to consider the case-dependent flow conditions around the small curved ice-lens segments.

In addition to water pressure and temperature, the overburden stress and neutral pressure are evaluated in the freezing fringe and are compared to determine if the latter surpasses the former. If the absolute maximum difference between

overburden stress and neutral pressure is less than 1%, then ice-lens is assumed to have formed, Fig. 3.4. If the new ice-lens is about to form, then the finite element mesh of the lens-free region is reduced in size in order that it coincides with the location of the new warmest ice-lens. The finite element mesh for both lens-free and frozen region were generated automatically. When a new ice-lens forms, the new location of the warmest ice-lens is provided to the auto-mesh generation subroutines to update the finite element mesh of both the regions. The initial conditions (water pressure and temperature) at the new location of nodes are determined by interpolating between the values at existing nodes. If the maximum difference between neutral pressure and overburden stress is more than 1%, then ice-lens formation is assumed to have been missed. In this case, the size of time-step is adjusted till it coincides with the formation of a new ice-lens.

In the beginning of the frost heave process, heat extraction at the warmest ice-lens is high and freezing is rapid, leading to several closely spaced and extremely thin ice-lenses. In the numerical simulation, this phenomenon forces the size of time-step to be very small. In view of the negligible contribution of these early thin ice-lenses to the total heave, it would be reasonable to somehow avoid their formation or reduce the computation time for them. The latter can be achieved by assuming ice-velocity, i.e., regelation, to be zero and by assuming constant properties for freezing fringe and unfrozen region, resulting in a linearized form of Eqs. (1.5) and (1.7). The variation of I' and permeability are very high in the freezing fringe and hence we would use step functions to represent them in the freezing fringe (Fig. 3.5).

This linearization eliminates the need for many iterations during each time-step and also allows one to use larger size of time-steps. It was found that the nonlinear equations on the average required five iterations for each time-step. The linearized equations would reduce computing time by at least 80% for the initial period. The heave rate, while using linearized equations can be computed by considering mass balance over the full lens-free region, similar to the calculation of V_I . We could continue to use these linear equations as long as the amount of heave is negligible

compared to the expected total heave. If the expected total heave is not known, then it may be approximated using some empirical relationship. Here the concept of segregation potential (Konrad and Morgenstern, 1981, 1982a, 1982b) was used to calculate the expected water intake from the warm end. The heave due to freezing of in-situ pore water can be added to water intake to obtain the total heave. The depth D of frost penetration required to estimate heave due to in-situ freezing is given by Stefan relationship

$$D = \sqrt{\frac{12k_{hd}}{C_f}} \quad (3.11)$$

where C_f is the apparent heat capacity of frozen soil and it includes a term due to latent heat release. For the two-dimensional case several radial sections around a pipeline can be considered to calculate the expected heave.

Fig. 3.1. 8-noded isoparametric element

Fig. 3.2. Direction of ice-velocity in two-dimensional space

Fig. 3.3. Formation of a new ice-lens segment in two-dimensional case

Fig. 3.4. Variation of water pressure, ice pressure and neutral pressure in freezing fringe at the formation of new ice-lens

Fig. 3.5 Unfrozen water content and permeability variation and their linearized estimate

CHAPTER 4

Stress Analysis

4.1 General

The thermal and hydraulic analysis of ground freezing enables us to determine the change in neutral pressure and temperature and volumetric strains. An uncoupled analysis can be carried out using the above results to determine the stresses in soil. The magnitudes of heave obtained from the stress analysis will include the effect of the compressibility of soil grains. The stress field affects the criterion of formation of ice-lens and the boundary condition at the warmest ice-lens (Eq. 2.23) in the thermal and hydraulic analysis. Since the total stresses in soil are in equilibrium with external forces, they do not change considerably with neutral pressure, temperature and volumetric strains. The thermal and hydraulic analysis requires total stresses and hence we do not need to couple the detailed stress analysis with the thermal and hydraulic analysis. Although the total stresses do not change during freezing, the effective stresses and porosity do. By uncoupling the stress analysis, we are neglecting the effect of changing porosity.

In the present investigation, the neutral pressure and the temperature obtained from the thermal and hydraulic analysis would be used in the stress analysis. In the frozen region, only the temperature is determined while the ice pressure is assumed

to be the same as the overburden pressure at all the existing ice-lenses in this region. The ice pressure at the intermediate points can be determined by interpolation. The water pressure can be found using the Clausius-Clapeyron equation, Eq. (1.5). The neutral pressure can now be evaluated by using Eq. (1.6b). In addition to the above, the following assumptions are made for the stress analysis:

1. The ice-lenses are an impermeable discontinuity in the thermal and hydraulic analysis while the soil is a continuous medium for stress analysis.
2. The soil and structure are isotropic.
3. The soil and structure are elastoplastic without hardening or softening.
4. The creep in the soil and in the structure are negligible.
5. The deformations are small and hence the strains are linear.
6. The variation of the mechanical properties of frozen soils with temperature is governed by some empirical relationships.
7. The interface of soil and structure can be modelled using two springs between a node on soil and a node on a structure. The directions of these springs are normal and tangential to the interface.

The equations required for the stress analysis based on the above assumptions will be presented in this chapter. In practice, the differential heave causes the maximum stress in an underground structure, but the present case is restricted to the uniform conditions along the length of the structure, i.e plane strain conditions. Although the equations for the plane strain problem are presented they can be easily modified for the more general cases.

4.2 The Constitutive Equations

We will utilize Terzaghi's concept of effective stress for both frozen and unfrozen soils. The neutral pressure causes only volumetric strains in the soil; the major strains are caused by the effective stresses, i.e grain-to-grain contact stresses. The effective stress vector with the sign convention that tensile stress is positive can be

written as

$$\{\sigma'\} = \{\sigma_t\} + \mathbf{m}'\sigma_n \quad (4.1)$$

where

- $\{\sigma'\}$ = effective stress vector
- $\{\sigma_t\}$ = total stress vector
- σ_n = neutral pressure
- $\mathbf{m}'$ = equal to unity for the normal stress components and
zero for shear stress components

The $\{\sigma'\}$, $\{\sigma_t\}$ and $\mathbf{m}'$ for a plane strain problem are given by

$$\{\sigma'\} = \{\sigma'_{xx}, \sigma'_{yy}, \tau_{xy}, \sigma'_{zz}\}^T \quad (4.2a)$$

$$\{\sigma_t\} = \{\sigma_{xx}, \sigma_{yy}, \tau_{xy}, \sigma_{zz}\}^T \quad (4.2b)$$

$$\mathbf{m}' = \{1, 1, 0, 1\}^T \quad (4.2c)$$

where σ'_{ii} and σ_{ii} , $i = x, y, z$ are the effective and the total normal stresses, respectively, and τ_{xy} is the shear stress. The soil is assumed to be elastoplastic and hence the constitutive relation between the incremental effective stress and the incremental total strains in the soil can be written in tangential form as

$$d\{\sigma'\} = \mathbf{D}_{ep} (d\{\epsilon\} - d\{\epsilon_p\} - d\{\epsilon_T\} - d\{\epsilon_v\}) \quad (4.3)$$

where d denotes an incremental quantity and

- $\{\epsilon\}$ = total strain vector
- $\{\epsilon_T\}$ = thermal strain vector
- $\{\epsilon_p\}$ = volumetric strains due to neutral pressure
- $\{\epsilon_v\}$ = volumetric strains due to freezing
- $\mathbf{D}_{ep}$ = tangential elastoplastic constitutive matrix

It is to be noted that the contribution of the term due to change in the constitutive matrix D_{ep} caused by negative temperatures is assumed to be negligible. The total strain vector in the soil for the plane strain case may be written as

$$\{\epsilon\} = \{\epsilon_{xx}, \epsilon_{yy}, \gamma_{xy}, \epsilon_{zz}\}^T \quad (4.4)$$

where ϵ_{ii} , $i = x, y, z$ are the total normal strains and γ_{xy} is the total shear strain. It is to be noted that ϵ_{zz} is zero for plane strain conditions. The volumetric strains due to uniform compression of soil matrix by the neutral pressure are given by

$$d\{\epsilon_p\} = -m' \frac{d\sigma_n}{3K_s} \quad (4.5)$$

where

K_s = bulk modulus of soil grains

The volumetric strains due to neutral pressure are known to be relatively insignificant in the unfrozen soils (Lewis and Schrefler, 1978), but their contribution is not known in the frozen soils. We shall take into account the latter by assuming K_s to be constant.

The thermal strain vector due to the changing temperature is given by

$$d\{\epsilon_T\} = m' \frac{\beta dT}{3} \quad (4.6)$$

where

β = thermal coefficient of expansion of soil grains

The volumetric strains due to the freezing of soil are evaluated from the thickness and location of the ice-lenses calculated by the thermal and hydraulic analysis. These volumetric strains can be distributed uniformly over a finite element and may therefore be written as

$$d\{\epsilon_v\} = \frac{dA_i}{A_{cl}} \frac{m'}{3} \quad (4.7)$$

where

A_i = area of an ice-lens over an element, Fig. 4.1

A_{el} = area of an element

The tangential elastoplastic constitutive matrix, $\mathbf{D}_{ep}$, depends upon the level of effective stresses. The constitutive model that can be used to determine $\mathbf{D}_{ep}$ will be discussed in the next section. The constitutive equation for the structure can be written as

$$d\{\sigma_i\} = \mathbf{D}_{ep}(d\{\epsilon\} - d\{\epsilon_T\}) \quad (4.8)$$

where all the symbols were defined earlier but they now refer to the structure in this equation. The thermal strain vector for the structure, can be written as

$$d\{\epsilon_T\} = \mathbf{m}' \frac{\beta_s dT}{3} \quad (4.9)$$

where

β_s = thermal coefficient of expansion of the structure

4.3 Constitutive Models

A yield criterion defines the limits of elasticity for various combination of stress. It represents a closed surface in a stress space defined as a yield surface. If a point representing the current state of stress is inside this surface, then it is elastic, else it is plastic. The position and size of the yield surface are different for different materials and they depend upon whether the material strain hardens, softens or does neither. If we neglect strain hardening and/or softening, then the yield function can be written as

$$F(\{\sigma'\}) = 0 \quad (4.10)$$

where F is referred to as the yield function. The selection of yield criterion depends upon the type of material. The friction-failure criterion of Mohr-Coulomb has been

extensively used for soils to solve practical geotechnical problems. Though this criterion fails to consider certain characteristics of soils, its major advantage is its simplicity. Recently, many sophisticated yield criteria have been proposed, but the Mohr-Coulomb criterion is still extensively used. We shall use this criterion to model both frozen and unfrozen soils. The embedded structure is assumed to be made of metal for which the yield function is defined by the Von-Mises's criterion.

The direction of plastic strains is defined by the plastic potential function which can be determined experimentally. However, it is normally assumed that the plastic potential function is the same as the yield function, i.e. the flow rule is associated. The elastoplastic matrix for an associated flow rule (Owen and Hinton, 1980) is given by

$$\mathbf{D}_{ep} = \mathbf{D}_e - \frac{\mathbf{d}_D \mathbf{d}_D^T}{\mathbf{d}_D^T \mathbf{a}} \quad (4.11)$$

where

$$\begin{aligned} \mathbf{D}_e &= \text{elasticity matrix} \\ \mathbf{a} &= \frac{\partial F}{\partial \{\sigma'\}} \\ \mathbf{d}_D &= \mathbf{D}_e \mathbf{a} \end{aligned}$$

The elasticity matrix, $\mathbf{D}_e$, for the plane strain case is given by

$$\mathbf{D}_e = \frac{E(1-\nu)}{(1+\nu)(1-2\nu)} \begin{bmatrix} 1 & \frac{\nu}{(1-\nu)} & 0 & \frac{\nu}{(1-\nu)} \\ \frac{\nu}{(1-\nu)} & 1 & 0 & \frac{\nu}{(1-\nu)} \\ 0 & 0 & \frac{(1-2\nu)}{2(1-\nu)} & 0 \\ \frac{\nu}{(1-\nu)} & \frac{\nu}{(1-\nu)} & 0 & 1 \end{bmatrix} \quad (4.12)$$

where

$$\begin{aligned} E &= \text{tangent modulus of elasticity} \\ \nu &= \text{Poisson's ratio} \end{aligned}$$

The Mohr-Coulomb yield criterion in terms of the principal stresses is given by

$$\sigma'_1 - \sigma'_3 - 2C \cos \phi - (\sigma'_1 + \sigma'_3) \sin \phi = 0 \quad (4.13)$$

where

- σ'_1 = maximum principal effective stress
- σ'_3 = minimum principal effective stress
- C = cohesion in soil
- ϕ = friction angle of soil

The Von-Mises yield criterion can be written as

$$(J'_2)^{\frac{1}{2}} = \frac{1}{\sqrt{3}} \sigma_Y \quad (4.14)$$

where

- σ_Y = uniaxial yield stress
- J'_2 = second invariant of the deviatoric stresses

J'_2 can be expressed in terms of the principal stresses, i.e.

$$J'_2 = \frac{1}{6} [(\sigma'_1 - \sigma'_2)^2 + (\sigma'_1 - \sigma'_3)^2 + (\sigma'_3 - \sigma'_2)^2] \quad (4.15)$$

where σ'_2 is the intermediate principal effective stress. If Eq. (4.15) is to be used for the structures, then substitute the effective stresses by the stresses in structure.

The vector $\mathbf{a}$ can be evaluated from the yield functions. It can be written as (Owen and Hinton, 1980)

$$\mathbf{a} = C_1 \mathbf{a}_1 + C_2 \mathbf{a}_2 + C_3 \mathbf{a}_3 \quad (4.16)$$

where $\mathbf{a}_1$, $\mathbf{a}_2$ and $\mathbf{a}_3$ are given by,

$$\mathbf{a}_1^T = \{1, 1, 0, 1\} \quad (4.17a)$$

$$\mathbf{a}_2^T = \frac{1}{(J'_2)^{\frac{1}{2}}} \{\sigma_{xx}^o, \sigma_{yy}^o, 2\tau_{xy}, \sigma_{zz}^o\} \quad (4.17b)$$

$$\mathbf{a}_3^T = \{\sigma_{yy}^o \sigma_{zz}^o + \frac{J'_2}{3}, \sigma_{xx}^o \sigma_{zz}^o + \frac{J'_2}{3}, -2\sigma_{zz}^o \tau_{xy}, \sigma_{yy}^o \sigma_{xx}^o + \frac{J'_2}{3} - \tau_{xy}^2\} \quad (4.17c)$$

where σ_{ii}^o , $i = x, y, z$ are the deviatoric effective stresses. They are given by

$$\sigma_{ii}^o = \sigma_{ii}' - \frac{\sigma_{xx}' + \sigma_{yy}' + \sigma_{zz}'}{3} \quad (4.18)$$

The constants C_1 , C_2 and C_3 have different expressions for different yield surfaces. For the Mohr-Coulomb yield criterion they are as follows:

$$C_1 = \frac{1}{3} \sin \phi \quad (4.19a)$$

$$C_2 = \cos \theta \left[(1 + \tan \theta \tan 3\theta) + \sin \phi \frac{(\tan 3\theta - \tan \theta)}{\sqrt{3}} \right] \quad (4.19b)$$

$$C_3 = \frac{\sqrt{3} \sin \theta + \cos \theta \sin \phi}{2(J_2') \cos 3\theta} \quad (4.19c)$$

where θ is given by

$$\theta = \frac{1}{3} \sin^{-1} \left[\frac{-3\sqrt{3} \sigma_{zz}^o \{(\sigma_{zz}^o)^2 - J_2'\}}{2(J_2')^{\frac{3}{2}}} \right] \quad (4.20)$$

C_1 , C_2 and C_3 for the Von-Mises yield criterion are given by

$$C_1 = 0 \quad (4.21a)$$

$$C_2 = \sqrt{3} \quad (4.21b)$$

$$C_3 = 0 \quad (4.21c)$$

It can be seen that C_2 and C_3 are not defined when $\theta = \pm 30^\circ$ for Mohr-Coulomb yield criterion. In the latter case, they can be obtained by starting from the definition of a , which will lead to

$$C_2 = \frac{1}{2} \left(\sqrt{3} - \frac{\sin \phi}{\sqrt{3}} \right), C_3 = 0 \text{ for } \theta = 30^\circ \quad (4.22a)$$

$$C_2 = \frac{1}{2} \left(\sqrt{3} + \frac{\sin \phi}{\sqrt{3}} \right), C_3 = 0 \text{ for } \theta = -30^\circ \quad (4.22b)$$

Eqs. (4.13) to (4.22) enable us to evaluate the elastoplastic matrix for both the soil and the structure. The structure behaves linearly in the elastic range,

but the soil is observed to be nonlinear even in the elastic range. A widely used stress-strain relationship in the elastic range for the soil is a hyperbole. Duncan and Chang(1970) used the hyperbolic relationship and utilized the Mohr-Coulomb yield criterion to give the tangent modulus as

$$E_T = \left[1 - \frac{R_f(1 - \sin\phi)(\sigma'_3 - \sigma'_1)}{2C\cos\phi - 2\sigma'_1\sin\phi} \right]^2 E_i \quad (4.23)$$

where

- E_T = tangential elastic modulus
- E_i = initial elastic modulus
- R_f = a constant (less than 1)

A constant R_f was introduced to take into account the effect of an intermediate principal stress value which is not considered in the Mohr-Coulomb yield criterion.

4.4 Interface Element

The interface of soil and structure is modelled using two springs normal and tangent to the soil and structure, Fig.4.2. The stiffness of each of the springs are varied to simulate the loss of strength due to debonding, i.e loss of contact, and due to the slip-failure. Three distinct ranges for the values of the stiffness of the normal and tangential springs, k_n and k_t , can be defined (Desai, 1977)

$$k_n = 0 \quad \text{and} \quad k_t = 0 \quad \text{if} \quad \Delta u_n > 0$$

$$k_n = 10^{15} \quad \text{and} \quad k_t = k_t^c \quad \text{if} \quad \Delta u_n < 0 \quad \text{and} \quad F_t < \mu' F_n'$$

$$k_n = 0 \quad \text{and} \quad k_t = 0 \quad \text{if} \quad \Delta u_n < 0 \quad \text{and} \quad F_t > \mu' F_n'$$

where Δu_n and Δu_t are the relative displacements in a normal and tangential directions at the interface, Fig. 4.2, F_n' and F_t are the corresponding forces in the springs and μ' is the friction coefficient between the soil and the structure which should be determined experimentally. k_t^c is the magnitude of the tangential stiffness before slip begins, Fig. 4.3. The stiffness variation in the normal and tangential

directions is shown in Fig. 4.3. Note that we are neglecting the adhesion between the soil and the structure.

The stiffness matrix of the contact springs in the local coordinates of the interface (n and t in Fig. 4.2), may be written as

$$\mathbf{K}' = \begin{bmatrix} k_n & 0 \\ 0 & k_t \end{bmatrix} \quad (4.24)$$

where

$\mathbf{K}'$ = stiffness of contact springs in the local coordinates

The stiffness matrix in the global directions can be obtained by transforming $\mathbf{K}'$

$$\mathbf{K}_1' = \mathbf{T}_t^T \mathbf{K}' \mathbf{T}_t \quad (4.25)$$

where $\mathbf{T}_t$ is given by,

$$\mathbf{T}_t = \begin{bmatrix} \cos\theta_1 & -\sin\theta_1 \\ \sin\theta_1 & \cos\theta_1 \end{bmatrix} \quad (4.26)$$

θ_1 = an angle between a normal to the interface and X-axis

$\mathbf{K}_1'$ = stiffness matrix of the interface in global directions

The above stiffness matrix relates the relative displacements in the global directions. It can be transformed to relate absolute displacements in the global directions, i.e.

$$\mathbf{K}_2' = \mathbf{T}_{t1}^T \mathbf{K}_1' \mathbf{T}_{t1} \quad (4.27)$$

where $\mathbf{T}_{t1}$ is given by

$$\mathbf{T}_{t1} = \begin{bmatrix} -1 & 0 & 1 & 0 \\ 0 & -1 & 0 & 1 \end{bmatrix} \quad (4.28)$$

$\mathbf{K}_2'$ is a 4 by 4 stiffness matrix corresponding to the 4 degrees of freedom at the two nodes, Fig. 4.2.

2

of/de

2

MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS
STANDARD REFERENCE MATERIAL 1010a
(ANSI and ISO TEST CHART No. 2)

4.5 Mechanical Properties of Frozen Soil

The strength and deformation properties of frozen soil vary considerably with temperature. As the temperature drops, ice in the frozen soil forms a stronger bond with soil grains, which increases its strength and its modulus of elasticity. The experimentally measured magnitude of the cohesion, friction modulus, elastic modulus and Poisson's ratio at several temperatures are given by Tsytovich (1975). He also gave some empirical expressions which fit the available data points. The cohesion C is given by

$$C = b_1 + b_2\sqrt{-T} \quad (4.29)$$

where b_1 and b_2 are constants. He also provided some values of the friction angle for different freezing temperatures. The contribution of friction to the total shear strength is, however, of the order of 10 to 20 percent. Since, the variation of the friction angle is not significant and in view of its small contribution to the total shear resistance of frozen soil, it would be assumed to be constant.

The modulus of elasticity increases rapidly as the temperature is lowered below 0°C . The empirical expression for the modulus of elasticity, E , is given by

$$E = b_3 + b_4(-T)^l \quad (4.30)$$

where b_3 , b_4 and l are constants. The modulus of elasticity for silty soils increases by as much as 40 times as the temperature is lowered from 0°C to -1°C . The Poisson's ratio ν varies rapidly near the normal freezing point of water. Its value approaches 0.5 as the temperature is increased to 0°C from the freezing temperatures. An exponential curve can be fitted to the experimental data points.

$$\nu = b_5(-T)^{b_6} \quad (4.31)$$

where b_5 and b_6 are constants.

4.6 Finite Element Implementation

The equilibrium equations relating the total stress $\{\sigma_t\}$ to the body forces $\mathbf{b}$ and the boundary tractions $\mathbf{P}$ specified at the boundary S_a of the domain R_a are formulated in terms of the unknown displacements $\mathbf{u}$. Using the principle of virtual work, general equilibrium equations in incremental form can be written as

$$\int_{R_a} \delta\{\epsilon\}^T d\{\sigma_t\} dR - \int_{R_a} \delta\mathbf{u}^T d\mathbf{b} dR - \int_{S_a} \delta\mathbf{u}^T d\mathbf{P} dS = 0 \quad (4.32)$$

where

- R_a = domain of a problem
- S_a = boundary of a problem
- $\mathbf{u}$ = vector of displacements
- $\mathbf{b}$ = body forces
- $\mathbf{P}$ = boundary tractions

Substituting Eqs. (4.1) and (4.3) into the Eq. (4.32) gives

$$\begin{aligned} & \int_{R_a} \delta\{\epsilon\}^T \mathbf{D}_{ep} d\{\epsilon\} dR - \int_{R_a} \delta\{\epsilon\}^T \mathbf{D}_{ep} d\{\epsilon_p\} dR - \int_{R_a} \delta\{\epsilon\}^T \mathbf{D}_{ep} d\{\epsilon_T\} dR - \\ & \int_{R_a} \delta\{\epsilon\}^T \mathbf{D}_{ep} d\{\epsilon_v\} dR - \int_{R_a} \delta\{\epsilon\}^T \mathbf{m}' d\sigma_n dR - \int_{R_a} \delta\mathbf{u}^T d\mathbf{b} dR - \int_{S_a} \delta\mathbf{u}^T d\mathbf{P} dS = 0 \end{aligned} \quad (4.33)$$

We can apply the finite element method to the above integral equation. Accordingly, the displacements and strains can be expressed as

$$\mathbf{u} = \mathbf{N}' \mathbf{u}^s \quad (4.34a)$$

$$\{\epsilon\} = \mathbf{B}' \mathbf{u}^s \quad (4.34b)$$

where

- $\mathbf{N}'$ = a matrix of shape functions

$\mathbf{B}'$ = strain-displacement relationship matrix

$\mathbf{u}^s$ = a vector of nodal displacements

The 8-noded isoparametric element used for the thermal and hydraulic analysis will also be used for the stress analysis. There are two nodal degrees of freedom, displacement in X and Y directions, for a two-dimensional problem. The shape function matrix, $\mathbf{N}'$, for this case is given by

$$\mathbf{N}' = \{N_1, N_1, N_2, N_2, \dots, N_8, N_8\} \quad (4.35)$$

The shape functions N_1 to N_8 are given by Eq.(3.2). The displacements are assumed to be small and hence strains are functions of the first derivative of the displacements. The strain-displacement relationship matrix, $\mathbf{B}'$, for the case of plane strain is given by

$$\mathbf{B}' = \begin{bmatrix} \frac{\partial N_1}{\partial X} & 0 & \dots & \frac{\partial N_8}{\partial X} & 0 \\ 0 & \frac{\partial N_1}{\partial Y} & \dots & 0 & \frac{\partial N_8}{\partial Y} \\ \frac{\partial N_1}{\partial Y} & \frac{\partial N_1}{\partial X} & \dots & \frac{\partial N_8}{\partial Y} & \frac{\partial N_8}{\partial X} \\ 0 & 0 & \dots & 0 & 0 \end{bmatrix} \quad (4.36)$$

Substituting the finite element expression, Eq. (4.35), into the integral equation Eq. (4.34) and taking out the virtual displacements which are not zero, gives

$$\begin{aligned} & \int_{R_a} (\mathbf{B}')^T \mathbf{D}_{ep} \mathbf{B}' dR d\mathbf{u}^s - \int_{R_a} (\mathbf{B}')^T \mathbf{D}_{ep} d\{\epsilon_p\} dR - \int_{R_a} (\mathbf{B}')^T \mathbf{D}_{ep} d\{\epsilon_T\} dR - \\ & \int_{R_a} (\mathbf{B}')^T \mathbf{D}_{ep} d\{\epsilon_v\} dR - \int_{R_a} (\mathbf{B}')^T \mathbf{m}' d\sigma_n dR - \int_{R_a} (\mathbf{N}')^T d\mathbf{b} dR - \int_{S_a} (\mathbf{N}')^T d\mathbf{P} dS = 0 \end{aligned} \quad (4.37)$$

This equation can be written in a simpler form as

$$\mathbf{K}_{ep} d\mathbf{u}^s = d\mathbf{F}_p + d\mathbf{F}_T + d\mathbf{F}_v + d\mathbf{F}_n + d\mathbf{F}_l \quad (4.38)$$

where

$$\mathbf{K}_{ep} = \int_{R_a} (\mathbf{B}')^T \mathbf{D}_{ep} \mathbf{B}' dR$$

$$\begin{aligned}
\mathbf{F}_p &= \int_{R_a} (\mathbf{B}')^T \mathbf{D}_{ep} \{\epsilon_p\} dR \\
\mathbf{F}_T &= \int_{R_a} (\mathbf{B}')^T \mathbf{D}_{ep} \{\epsilon_T\} dR \\
\mathbf{F}_v &= \int_{R_a} (\mathbf{B}')^T \mathbf{D}_{ep} \{\epsilon_v\} dR \\
\mathbf{F}_n &= \int_{R_a} (\mathbf{B}')^T \mathbf{m}' \sigma_n dR \\
\mathbf{F}_1 &= \int_{R_a} (\mathbf{N}')^T \mathbf{b} dR - \int_{S_a} (\mathbf{N}')^T \mathbf{P} dS
\end{aligned}$$

The finite element equations for the structure are the special case of the above equation. The force terms $\mathbf{F}_p$, $\mathbf{F}_v$ and $\mathbf{F}_n$ are zero for the structure.

4.7 Tangential Stiffness Method

Eq. (4.38) is nonlinear because the elastoplastic stiffness matrix and the load terms depend upon the level of stresses. The equation would be solved using the Modified Newton-Raphson Method, i.e tangential stiffness method. This equation for a finite load increment of $\Delta \mathbf{f}$ can be written as

$$\mathbf{K}_{ep} \Delta \mathbf{u}^s = \Delta \mathbf{f} \quad (4.39)$$

The incremental displacements for the r th iteration, $\Delta \mathbf{u}_r^s$, in the tangential stiffness method are given by

$$\Delta \mathbf{u}_r^s = [\mathbf{K}_{ep}(\mathbf{u}_r^s)]^{-1} \Delta \{\psi_r\} \quad (4.40)$$

where $\mathbf{u}_r^s$ are the nodal displacements at the beginning of r th iteration and the residual forces $\Delta \{\psi_r\}$ for the r th iteration are given by

$$\Delta \{\psi_r\} = - \int_{\mathbf{u}_{r-1}^s}^{\mathbf{u}_r^s} \mathbf{K}_{ep}(\mathbf{u}^s) d\mathbf{u}^s + \Delta \{\psi_{r-1}\} \quad (4.41)$$

where $\Delta \{\psi_{r-1}\}$ are the residual forces for the $(r-1)$ th iteration and $\mathbf{u}_{r-1}^s$ are nodal displacement at the beginning of $(r-1)$ th iteration. Residual forces at the beginning of any load-step, $\Delta \{\psi_1\}$, are the same as $\Delta \bar{\mathbf{f}}$. The above process can be continued till we find that the incremental displacements are sufficiently small. If during any

iteration some points go beyond the yield surface, then they are brought back on the yield surface by adjusting the stresses using the radial return method(Owen and Hinton, 1980). The load terms F_n and F_1 are independent of stresses and hence they can be evaluated before starting to analyze for displacements. Note that in general the load terms due to the changing temperatures, neutral pressures and volumetric strains depend upon the level of stress, but these quantities will be updated only at the beginning of each load step.

Fig. 4.1. A segment of ice-lens over a finite element

Fig. 4.2. Interface displacements between soil and structure

Fig. 4.3 Load-displacement relationship for interface element
in (a) normal direction and (b) tangential direction

CHAPTER 5

Results and Discussion

5.1 General

Computer programs for the two-dimensional RIM and for the two-dimensional elastoplastic stress analysis of frozen soil were developed based on the theory discussed in the previous chapters. These programs are called 2D-RIGICE and FROSTRA, respectively. They are written in FORTRAN 77 and contain around 2700 lines each. It is to be noted that program 2D-RIGICE is not general because the subroutines for checking ice-lens formations and for adjusting mesh and initial conditions when a new ice-lens forms depend on the type of problem. The cases of one-dimensional freezing of a soil-column and the two-dimensional freezing around a pipeline carrying chilled gas were implemented. When a new ice-lens forms, the finite element mesh is moved which makes it essential to use auto-mesh generation. Auto-mesh generation subroutines for both one and two dimensional cases were included. Details of the programs with flow charts and the user's manual for preparing the input files are given in Appendix A.

Program 2D-RIGICE was verified by solving a one-dimensional example and checking the boundary conditions. A problem of internally pressurized thick cylinder under plane strain condition was solved using FROSTRA and the results were

found to be in good agreement with Owen and Hinton(1980).

Whenever the iterative procedure in program 2D-RIGICE did not converge in 25 iterations, the size of time-step was halved and the procedure was restarted. Sometimes this lack of convergence continued till the size of time-step became unreasonably small and hence a restriction was imposed on the minimum size of a time-step. This minimum value was small in the beginning of the freezing process but it increased as freezing progressed. When the size of time-step was less than or equal to the minimum value and the convergence did not occur, instead of halving the time-step, analysis for the next time-step was performed. The size of time-step was also not allowed to exceed certain maximum value. Program 2D-RIGICE can be run at any time desired, provided the value of the water pressures and temperatures are known at that time. The program was run in several stages and the results were checked and the maximum and minimum size of time-step were adjusted after the end of each stage. This manual adjustment of time-step was necessary since the maximum and minimum values referred to were not determined by any rational criterion. The program automatically resets the value of time-step to $\frac{1}{15}$ th of the time interval between the formation of the last two consecutive ice-lenses. When an iterative scheme for each load step used in program FROSTRA did not converge in 20 iterations, the program was stopped from running and was run again with increased number of load steps.

Two one-dimensional examples were solved to verify the above programs and the results were compared with available experimental and numerical results. The programs were used to simulate the Caen experiment (Dallimore et al, 1984) which uses a large scale testing facility to study various phenomena occurring during freezing around underground pipeline.

5.2 One-Dimensional Examples

5.2.1 Example I

To verify the numerical implementation described, an example from O'Neill and Miller (1985) was analyzed. A 35 m long soil column with 3°C temperature at the warm end and -5°C at the cold end was considered for the complete analysis, Fig. 5.1. At $t = 0$ the soil-column was assumed to have a 100 mm frozen region at the cold end while the temperature in the unfrozen region was assumed to be 3°C . The water table level was assumed to be at ground surface. This was simulated by specifying water pressure at the warm end to be $\rho_w g h_w$, where h_w is the depth of the warm end from the water table. The unfrozen water content and permeability variation with pressure difference, $(P_i - P_w)$, was assumed to be as illustrated in Fig. 3.5. In the beginning, the unfrozen water content curve was taken to be bilinear and the permeability to be a step function in the freezing fringe, Fig. 3.5. The overburden pressure on the ground surface was assumed to be 50 kPa. Since the magnitude of the permeability of unfrozen soil used by O'Neill and Miller (1985) was not available, a value of $5.0 \times 10^{-9} \text{ m/s}$ was assumed. There were a total 15 finite elements in the lens-free region out of which 6 were in the freezing fringe.

The variation of heave and water intake are shown in Fig. 5.2. The magnitude of the latter quantities at $t = 10^7$, where t is in seconds, was 20 – 25% less than the corresponding values obtained by O'Neill and Miller (1985). This difference is believed to be due to our assumed value of permeability. The expected total heave was calculated to be 51 mm, assuming the segregation potential to be constant ($15 \times 10^{-5} \text{ mm}^2/^{\circ}\text{C}$). The linearized equations were used as long as the heave was less than 1% of the total expected heave, i.e. till $t = 50000$. The magnitude of heave at this time was less than 1.5% of the final magnitude of heave and hence the effect of using linearized equations in the beginning was found to be negligible.

The variation of heave rate with time is shown in Fig. 5.3. Its magnitude diminishes with time but shows local oscillations. These oscillations are more prominent

in the next example and hence will be explained there. As the freezing progresses, the heat extraction at the warmest ice-lens drops rapidly, Fig. 5.4. This explains the rapid freezing and high heave rates in the beginning. The temperature of the warmest ice-lens was found not to change significantly with time and it varied in the range of -0.14°C to -0.21°C in each lensing cycle. Since the overburden stress at the warmest ice-lens keeps on increasing due to the self-weight of soil above it, suction at the warmest ice-lens diminishes based on Eq. 2.23. This causes a reduction in the rate of water intake and heave. As the heat extraction diminishes, the temperature gradient in the fringe also reduces (Fig. 5.6) which means that the thickness of freezing fringe increases with time (Fig. 5.5). The thickness of freezing fringe is just 0.09 m after 4 months in a 35 m long soil-column. O'Neill and Miller(1985) defined the global ice segregation ratio as the ratio of total thickness of ice-lenses to the length of frozen region. Its value is zero in the beginning and increases rapidly to reach a steady value of 3%, Fig. 5.7, in agreement with O'Neill and Miller (1985). The thickness of the individual ice-lenses and the time interval between the formation of two consecutive ice-lenses are shown in Fig. 5.8 and 5.9, respectively. Their magnitude increases with time and shows a linear relationship in a log-log graph. The transition zone from linear to nonlinear equations can also be seen in Fig. 5.8 and 5.9 by noticing the sudden jumps.

The boundary conditions and loading for the stress analysis of the same column are shown in Fig. 5.10. The following empirical expressions for the variation of C , E_i and ν with negative temperatures were obtained by fitting curves to the experimental data of Tsytovich (1975):

$$C = 50.0 + 141.02\sqrt{(-T)} \text{ kPa} \quad (5.1a)$$

$$E_i = 60.0 + 1520.2(-T)^{0.8679} \text{ MPa} \quad (5.1b)$$

$$\nu = 0.1933(-T)^{-0.3633} \quad (5.1c)$$

The magnitude of the initial elastic modulus and cohesion for the unfrozen region are given by Eqs. (5.1b) and (5.1a), respectively, using $T = 0^{\circ}\text{C}$. The value of

Poisson's ratio for unfrozen region was assumed to be 0.2. The value of cohesion was assumed to vary with depth, as shown in Fig. 5.10. The loads were applied in such a manner as to simulate actual physical conditions. The soil was first analyzed for external loads and self-weight. The large variation of strength and deformation properties of frozen soil with negative temperature makes it necessary to apply changes in neutral pressure and volumetric strain that are consistent with temperature changes. For example, consider a point at which temperature changed from 3°C to -2°C , and the neutral pressure dropped from 10 kPa to -100 kPa. Some of this pressure change has taken place at above 0°C and hence must be applied at above zero temperatures. All the ice-lenses form between -0.1°C and -0.2°C and hence all volumetric strains were applied in this temperature range.

The upward movement of ground surface obtained from stress analysis was 60% less than the magnitude of heave. This reduction in heave is due to the consolidation of unfrozen region. Water pressure in the unfrozen region decreases as the freezing front progresses, which increases the effective stress and causes downward settlement. This process is defined as quasi-consolidation. The quasi-consolidation effect in frozen soil is very small because of its high elastic modulus. In this example, the extent of unfrozen region (32 – 33 m) was much larger than the frozen region (2 – 3m) and hence the reduction in heave was considerable. This reduction in heave was found to increase as the bulk modulus of soil grains was increased. The consolidation of the unfrozen region is partly compensated for by the expansion of soil grains as they are released from pressure. As the bulk modulus is increased, the contribution of the expansion of soil grains reduces. The variation of effective stress (in the direction of soil-column) and neutral pressure along the soil-column is shown in Fig. 5.11. The magnitude of effective stress is very high in the frozen region, -30 kPa at the warmest ice-lens to -400 kPa at the cold end. The variation of neutral pressure shows a peak in the freezing fringe and whenever this peak offsets the overburden stress, a new ice-lens forms.

5.2.2 Example II

This example is intended to demonstrate the capabilities of the RIM in predicting many observed phenomena during the frost heave process. Penner (1986) studied the growth of ice-lenses in the laboratory under ramped temperature control. The ramped freezing test produces a thick freezing fringe together with a few widely spaced ice-lenses; hence, it allows one to study the importance of freezing fringe and the growth of ice-lenses in more detail.

The length of the soil sample was 190 mm and the temperature at the cold end was ramped from -0.35°C and that at the warm end from 0.55°C at the rate of $0.02^{\circ}\text{C}/\text{day}$. The assumed unfrozen water content curve is given in Fig. 5.12. The external overburden pressure was 50 kPa. The thermal properties of soil were assumed to be the same as used by Shen and Ladanyi (1988). It was not possible to use the linearized equations in this case because the freezing front was 40 mm below the cold end at the beginning of simulation. This condition reduces the heat and moisture transfer part of the present model to the RIM.

The permeability of the unfrozen soil was adjusted in such a way that the magnitude of heave matched the experimental results. The variation of heave and water intake for $K(n) = 2.25 \times 10^{-10} \text{ m/s}$ are shown in Fig. 5.13 and Fig. 5.14, respectively. It can be seen that more than 95% of heave is due to the water intake at the warm end, which is in agreement with the experiment. Penner (1986) observed a rapid rise in heave rate after the formation of a new ice-lens, followed by a large period of diminishing heave rate. The results here show a similar behaviour of heave rate, Fig. 5.15. The rise in heave rate when a new ice-lens forms is much sharper than that observed in the experiment. This is due to the assumption that as soon as a new ice-lens forms, it becomes an impermeable barrier to water flow while in reality this process happens more smoothly. The results also show a rise in the temperature of an ice-lens immediately after its formation (Fig. 5.16), as observed by Penner (1986) in his experiment. When a new ice-lens forms somewhere

below the existing warmest ice-lens, water flow towards the new ice-lens increases. This causes the release of a large amount of latent heat and a rise in temperature. However, our results of the time of formation of ice-lenses and the temperatures at which they form do not match with the experimental values. It is believed that these could be predicted if more accurate values of the properties of soil, especially of permeability, were available.

The effect of using different ice-lens formation criteria on the magnitude of heave was studied in this example. When the fixed segregation temperature was used for the ice-lens formation, the magnitude of heave was found to be 15% less. A lensing cycle, i.e. the period between the formation of two consecutive ice-lenses is marked by two consecutive minimums on the heave rate versus time curve, Fig. (5.15). If any heave criterion delays the process of ice-lens formation, then the minimums on the heave rate curve (Fig. 5.15) would go further down in each lensing cycle and hence the average heave rate and the magnitude of heave would become smaller.

The stress analysis of the soil specimen was carried out similar to Example I, using the same soil properties. The upward displacement of soil after stress analysis was 15% more than the magnitude of heave. This is because the extent of frozen and unfrozen region are similar in this case and the change in neutral pressure in the large freezing fringe is positive.

5.3 Two-dimensional Example

The present model is used to simulate the Caen experiment. The experimental facility consists of an 18 m long, 8 m wide and 5 m high refrigerated hall. The base or trough of the hall is 1.7 m deep. It is thermally and hydraulically controlled and is filled with soil. One half of the trough is filled with Caen silt, whereas the other half contains SNEC sand. An 18 m long, 0.273 m diameter pipeline is buried in the trough with 0.3 m of soil above it. The water table level was kept at the top of the pipeline, Fig. 5.17.

In the experiment, the pipeline and the ambient temperatures were maintained

at -2°C and -0.75°C , respectively. The computer program 2D-RIGICE cannot simultaneously simulate freezing from both ground surface and pipeline in its present form. Hence, the ambient temperature was assumed to be 0.1°C . This assumption would not affect the pipeline movement considerably because the ambient temperature is lower than the pipeline temperature and it would take time for the effect of ambient temperature to reach the pipeline. The soil along the length of the pipeline was assumed to be of the same type. In the first case, the soil around the pipeline was assumed to be Caen silt while in the second case it was assumed to be SNEC sand. The unfrozen water content for these soils assuming saturated are given in Fig. 5.18. The above curves give unfrozen water content by mass which were converted to obtain volumetric water contents. The average of the given two water content curves for Caen silt was used. The specified thermal and hydraulic boundary conditions for the problem are shown in the Fig. 5.19.

Temperatures in the freezing fringe showed a lot of oscillation in the beginning of simulation and hence they were forced to be linear after the end of each time-step. The concept of effective stress for determining the formation of ice-lens did not work well in this case and sometimes an ice-lens did not form till the existing ice-lens reached -0.3°C . This is unreasonable and hence a simple criterion of segregation temperature was utilized. Despite these adjustments, the results for SNEC sand contained numerous oscillations and they did not converge even for very small time-steps. The thickness of the freezing fringe is very small for sands and the magnitude of several parameters, e.g permeability, change by one or two orders over the thickness. This is believed to be one of the major reason for the failure of the model to simulate the case of SNEC sand. As a result, a simple one-dimensional analysis was performed for SNEC sand to calculate the magnitude of frost heave.

The thermal and hydraulic properties of both Caen silt and SNEC sand are summarized in Table 5.1. A one-dimensional analysis of SNEC sand was carried out in such a way as to simulate the conditions below the pipeline. A 1.15 m long soil-

column of SNEC sand with -2°C temperature and 18.0 kPa external overburden pressure at the top, and 0.1°C temperature and 13.1 kPa water pressure at the bottom, was analyzed. The variation of heave and water intake with time is shown in Fig. 5.20. The magnitude of heave after 35 days was just 8 mm, which is negligible.

For the two-dimensional analysis of Caen silt, it was assumed that when the existing warmest ice-lens reached -0.19°C , an ice-lens was assumed to form at the point where temperature was -0.15°C . These values of temperature were selected based on the experimental (Penner, 1986) and numerical (one-dimensional examples discussed earlier) values of temperature at the time of formation of ice-lens in silts. In Example II, we found that the magnitude of heave changes significantly with the ice-lens formation criterion. As explained earlier, this behaviour is due to the oscillating variation of heave rate in each lensing cycle. In Example I, the heave rate does show the oscillating variation in each lensing cycle, but this variation is insignificant compared to the overall variation of heave rate, Fig. 5.3. Thus, it can be concluded that the magnitude of heave does not depend considerably on the ice-lens formation criterion for step-freezing test. Since the Caen experiment involves step-freezing, we may assume that ground and pipeline movements are not affected by the ice-lens formation criterion.

**Table 5.1 Thermal and hydraulic properties of
Caen silt and SNEC sand**

Property	Caen Silt	SNEC sand
ρ_s	1850.0 kg/m^3	1850.0 kg/m^3
k_{hs}	1.95 $\text{J}/\text{m}^{\circ}\text{C}$	2.59 $\text{J}/\text{m}^{\circ}\text{C}$
C_s	2660.0 $\text{J}/\text{kg}^{\circ}\text{C}$	3000.0 $\text{J}/\text{kg}^{\circ}\text{C}$
n	0.36	0.18
$k_d(n)$	5.0E-09 m/s	1.0E-08 m/s

The finite element mesh for the lens-free region is shown in Fig. 5.21. Each 8-noded isoparametric element was drawn by connecting the corner nodes only,

which explains the kinks in the figure. There were 12 radial divisions around the pipeline with 8 elements in each division. Out of the total 96 elements, 48 were in the freezing fringe. The number of elements in the frozen region were just 24. The formation of ice-lens was checked in 24 directions around the pipeline. The aspect ratio of the elements in the freezing fringe is very high but it is believed that this would not affect the results significantly (Pande and Sharma, 1978).

A stress analysis of the combined soil and pipeline system was performed for self-weight. The total stresses obtained were used to evaluate the boundary condition at the warmest ice-lens. At $t = 0$, a 20 mm thin frozen region was assumed to exist around the pipeline. The linearized form of the equations was used till $t = 50000$ seconds. A stress analysis was carried out then and the pipeline was found to have moved upward by 0.2 mm which was less than 1% of the experimental value. The temperature variation in the freezing fringe was forced to be linear till $t = 100000$ seconds and afterwards it did not show significant oscillations.

The variation of heave rate with time for Caen silt is shown in Fig. 5.22. The magnitude of heave rate decreases with time but shows local oscillations. The reason for the local oscillations is given in Example II. These oscillations get smaller with time which indicates the increasing stability of system with time. The magnitude of heave rate or ice velocity was assumed to be the same everywhere in space, hence integration of heave rate over time gives the total thickness of ice lenses, I_t , in any direction around the pipeline. I_t increases with time at a decreasing rate as shown in Fig. 5.23. The total volume of ice-lenses and of water intake, as shown in Fig. 5.24, increases linearly with time. It can be seen that more than 80% of heave is caused by the water intake. If we assume a 9 m length of pipeline, then the total water intake can be calculated to be 2520 l in 35 days. As freezing progresses, the warmest ice-lens moves away from the cold pipeline. As the warmest ice-lens moves away from the pipeline, the heat extraction rate under the pipeline reduces rapidly with time, Fig. 5.25. The latter explains the reducing rate of freezing with time.

From the above heat and moisture transfer analysis the changes in the temper-

ature and the neutral pressure and the volumetric strains were obtained. These results were provided the input for the stress analysis program. The mechanical properties of Caen silt were assumed to be same as in Example I. From the stress analysis, the pipeline was found to move upward by 32.8 mm. The upward movement of pipeline was the same at its upper and lower points, but varied considerably at other points on it. The maximum upward movement was 37 mm while the minimum was 29 mm causing large relative displacements and stresses in the pipeline.

The upward movement of the pipeline was compared with the corresponding experimental value in Caen silt, at the end of the 18 m long pipeline. The value of upward movement at the end in Caen silt was not affected considerably by the presence of SNEC sand, hence it is the most suitable value for comparative purposes. The numerical value was found to be 50% more than the experimental value. The major reason behind this disparity is believed to be the lack of permeability data. In the one-dimensional examples it was shown that the magnitude of heave varied considerably with permeability. Initial conditions chosen in the simulation were also different from the experimental one. We assumed the initial temperature to be 2°C throughout the domain of problem, but the initial temperature in the experiment varied from 2°C to 10°C . This would change the location of the freezing front and the in-situ heave magnitudes, but the change in water intake would be small. The upward movement of ground surface directly above the pipeline was 62.5 mm, which is approximately twice the magnitude of upward movement of the pipeline.

The variation of neutral pressure and minimum principal effective stress (maximum compressive stress) under the pipeline are shown in Figs. (5.26) and (5.27), respectively. Their magnitude decreases towards the pipeline. The magnitude of effective stress near the pipeline was -1.8 MPa . The total stress under the pipeline can be calculated from these figures. It also reduces as we approach the pipeline. Its magnitude drops to as low as -1.2 MPa near the pipeline. The total stress changes considerably near the pipeline, but in the unfrozen region and freezing

fringe it remains almost constant. In the heat and moisture transfer analysis, only the total stress at the location of the warmest ice-lens was required and hence the uncoupling of stress analysis was justified.

The maximum tensile and compressive stresses in the pipeline were found to be 13.0 MPa and 16.0 MPa, respectively. The locations of the points where these stresses occurred are shown in Fig. 5.28. The maximum longitudinal stress in the pipeline due to differential heave was of the order of 40 MPa. This shows that stresses in the plane of the pipeline cross-section during freezing may be comparable to the longitudinal stresses. In the beginning of the simulation, all the points on the interface between the soil and pipeline were in contact, but at the end of freezing process several points lost contact, Fig. 5.28. This change of configuration of the interface was assumed to have caused large stresses in the pipeline and the soil near it.

Fig. 5.1. Soil column subjected to freezing for Example I

Fig. 5.2. Heave and water intake for Example I

Fig. 5.3. Variation of heave rate for Example I

Fig. 5.4. Heat extraction at the warmest ice-lens for Example I

Fig. 5.5. Variation of the thickness of freezing fringe with time for Example I

Fig. 5.6. Variation of temperature gradient in freezing fringe with time for Example I

Fig. 5.7. Global ice segregation ratio versus time for Example I

Fig. 5.9. Time interval between the formation of two consecutive ice-lenses for Example I

Fig. 5.10. Loading and boundary conditions for Example I

Fig. 5.11. Variation of effective stress and neutral pressure for Example I

Fig. 5.12. Unfrozen water content for Example II

Fig. 5.13. Heave variation for Example II

Fig. 5.14. Water intake for Example II

Fig. 5.15. Heave rate variation with time for Example II

Fig. 5.16. Warmest ice-lens temperature variation with time for Example II

(a)

(b)

Fig. 5.17. Schematic diagram of Caen-experiment:
(a) longitudinal section of trough and (b) cross section of trough.

After Dallimore et al.(1984)

Fig. 5.18. Unfrozen water content curves for Caen silt and SNEC sand. After Dallimore et al.(1984)

Fig. 5.19. Boundary conditions for the Caen-experiment

Fig. 5.20 Variation of heave and water intake
for SNEC sand

Fig. 5.21 Finite element mesh for lens-free region in the two-dimensional example

**Fig. 5.22 Heave rate variation with time for Caen silt
in the two-dimensional example**

**Fig. 5.23 Total thickness of ice-lense for Caen silt
in the two-dimensional example**

Fig. 5.24 Volume of ice-lenses and water intake for Caen silt in the two-dimensional example

Fig. 5.25 Heat extraction rate under the pipeline for Caen silt

Fig. 5.26 Variation of neutral pressure under the pipeline for Caen silt

Fig. 5.27 Principal effective stress under the pipeline for Caen silt

- Points of Maximum Tension
- Points of Maximum Compression

Fig. 5.28 Configuration of the interface between the soil and pipeline at the end of simulation

CHAPTER 6

Summary, Conclusions and Recommendations

6.1 Summary and Conclusions

The present two-dimensional frost heave models do not include the ice-segregation process, and the phenomena implicit in the Capillary and Clausius-Clapeyron equations. The RIM is considered to be one of the most comprehensive frost heave models and it includes the latent heat release during freezing, rhythmic ice-lens formation, the effect of overburden pressure and regelation. To date this model had been implemented for one dimensional problems. In this thesis, an attempt was made to extend the model to two-dimensional cases. A new ice-lens segment was assumed to form in such a way that the warmest ice-lens remained continuous. Since there is no experimental evidence to support this assumption directly, it remains an assumption. The model predicts rhythmic ice-lens formation around the pipeline and a reducing heave rate with time. The stress analysis predicts the movement of pipeline and the stresses in the soil and the pipeline. The pipeline may lose contact with the surrounding frozen soil, causing stresses of the order of 15.0 MPa in the pipeline. The magnitude of upward movement of the pipeline in the simulation of Caen experiment was found to be 50% more than the corresponding

experimental value.

It was also shown that the stress analysis can be uncoupled from thermal and hydraulic analysis of freezing soils to predict stresses in the soil and the pipeline and the magnitude of heave, including the effect of compressibility of soil grains. The amount of heave after the stress analysis could be considerably different from that obtained by hydraulic and thermal analysis only. The reduction in heave, due to a quasi-consolidation process, is partly compensated for by the expansion of soil grains as they are relieved from pressure. When the unfrozen region is much larger than the frozen region, the amount of consolidation exceeds the expansion of grains and hence the heave is reduced.

It was also shown that the highly nonlinear equations of the RIM can be linearized for the initial period. This reduces the amount of computation for the initial period by more than 80%, without adversely affecting the final magnitude of heave. However, despite this simplification, a large number of time-steps were required for using the nonlinear equations. The average CPU time required for each time-step on SUN 4.0 system was 50 seconds for one-dimensional cases and 360 seconds for two-dimensional cases. The number of time-steps required for the first one-dimensional example was 4100 and for the two-dimensional case was 4900. This means that the total amount of computation time for the one-dimensional example was approximately 3 days and for the two-dimensional case was 21 days. Such large computer time requirements make it difficult to further verify the model by solving a larger number of examples. Ideally the program should be run on a supercomputer or a workstation completely dedicated to the solution of this problem. The RIM is capable of predicting the experimentally observed rise of heave rate and the rise of the temperature in the warmest ice-lens immediately after an ice-lens formation under ramped freezing test conditions. Other existing freezing soil models fail to predict these phenomena.

In conclusion, the Rigid-Ice model, coupled with stress analysis, is a powerful analytical tool for predicting frost heave and stresses in soil and buried pipelines.

The enormous costs and environmental risks associated with the construction and operation of buried pipelines in the environment of Canadian North merits the application of the present sophisticated analytical tools.

6.2 Recommendations For Future Work

1. The RIM shows the importance of the freezing fringe for any frost heave model. All the freezing takes place and the large amount of latent heat is released within this fringe. The suction in the freezing fringe causes the migration of water from unfrozen region. The presence of the freezing fringe is accounted for by some assumed functions for unfrozen water content and permeability. The magnitude of frost heave very much depends upon these functions. Unfrozen water content is measured as a function either of subzero temperature or of water pressure in laboratory, but in the freezing fringe both water pressure and temperature vary. Attempts should be made to represent unfrozen water content as a function of both water pressure and temperature. Some measurements have been taken of the permeability of soils at freezing temperatures, but no reliable and accurate formula exists to predict its variation in the freezing fringe. Procedures for determining such variations will greatly enhance the modelling aspect of the problem.
2. It has been shown in Example II that the magnitude of heave depends upon the ice-lens formation criterion used. The heave rate was found to increase immediately after the formation of ice-lens even in the step freezing test, followed by a protracted period of reducing heave rate. If the heave criterion delays the ice-lens formation, then the heave would be less. Several heave criteria have been used in the past, but most do not predict the formation of ice-lens within the freezing fringe. When the concept of the stress partition factor is used to determine the formation of an ice-lens, an ice-lens is found to form within the freezing fringe. Another important factor that needs to be considered relates to the use of effective stress. All the soil grains are surrounded by a thin water

layer and hence the effective stress does not make much sense for freezing soils and the validity of the criterion is doubtful. Also, there is no experimental evidence to support this criterion. For instance, in Example II, we were not able to predict the time of formation of ice-lenses which is believed to be partly due to the ice-lens formation criterion used. It is therefore necessary to determine an experimentally verified, general heave criterion.

3. The most important assumption of our two-dimensional RIM is the continuous warmest ice-lens assumption. Some experimental evidence should be obtained to show its validity or some numerical results should be provided to show the difference in the results with and without this assumption.
4. The RIM also assumes uniform heave rate in space. This assumption has not been verified for one-dimensional problems and is even less likely to be valid for two-dimensional cases. It is unlikely that the same amount of ice accumulates in all directions around the pipeline. It is therefore recommended that some pseudo-static variation of heave rate be utilized and its validity be checked.
5. The stress analysis was uncoupled from the thermal and hydraulic analysis by assuming that the latter requires total stresses, which do not change during freezing process. The total stresses may change if the configuration of interface element changes during freezing. The effective stresses and porosity do change during freezing. More experimental and numerical work would be needed to verify the above assumption. The interface element used here was quite simple. More advanced and reliable interface elements for soil-structure interaction problem may be needed to fully model this aspect of the problem. In particular, the interface force-slip properties will need data derived from carefully conducted experiments.
6. The mechanical properties of frozen soils vary considerably with temperature. Measurements have been obtained for many soils and many empirical formulae have been suggested. These formulae are sometimes different for different types of soils and the constants in them depend upon many factors. The bonding

between ice, water and the soil grains should be explored in more detail and some models should be developed to give the mechanical properties of frozen soils as a function of their basic characteristics.

7. The linearized form of the equations was used till such time as the amount of heave was less than 1% of the total expected heave. The calculated heave value obtained from the linearized equations are, however, approximate. Hence, it may be possible to use the linearized equations till the heave reaches 5 or more percentage of the expected heave, without significantly affecting the final magnitude of heave.
8. In the present model, convergence was assumed when the change in heave rate in two consecutive iterations was less than 1 percent. This does not ensure the same degree of convergence for pressure and temperature. The change in pressure and temperature should be monitored in order to ascertain the accuracy of the convergence criterion. Preferably, other convergence criteria should be tried to obtain comparative values.
9. Partly manual and partly auto time-step adjustments were performed in the present study. This made it necessary to run the program in several stages. If the size of time-step is too large, then the accuracy of results diminishes. If it is too small then the computing effort increases. The optimum size of time-steps may be determined from the change in such quantities as pressure and temperature in the previous time-steps. When an ice-lens formation was missed, the size of time-step was adjusted from the data of two previous time-steps. This method required 5 to 7 time-steps to locate a new ice-lens after it was found that an ice-lens had been missed. There is scope for improvement in this procedure. Preferably, most of the procedures for convergence and time-step incrementation should be automated. However, the choice of intervention by the analyst should be retained in the program.
10. In the stress analysis, the deformation were assumed to be small and the term due to change in the constitutive matrix of soil caused by negative temperatures

was neglected. The strains of the order of 10% were observed in the examples solved and hence the small deformation theory may not give accurate results. Since variations of the mechanical properties of soil with negative temperature is large, the contribution of the term due to the changing constitutive matrix may be significant. The results of the stress analysis can be improved by using the large deformation theory and by including the effects of the changing constitutive matrix.

References

1. Aitchison, G.D. (1961), Relationship of moisture stress and effective stress in unsaturated soils, in *Pore Pressure and Suction in Soils*, pp 47-52, Butterworths, London.
2. Anderson, D. M. and Tice, A. R. (1972), Predicting unfrozen water contents in frozen soils from surface area measurements, *Highway Research Record*, **393**, 12-18.
3. Berg, R.L., Guymon G., Johnson T.C. and Hromadka T.V.(1980), Mathematical model to correlate frost heave of pavements with laboratory predictions, *CRREL Monogr. 80-10*, Cold Reg. Res. and Eng. Lab., Hanover, NH.
4. Biermans, M.B.G.M., Dijkema K.M. and deVries D.A.(1978), Water movement in porous media towards an ice front, *Journal of Hydrology*, **37**, 137-143.
5. Bishop, A.W. and Blight, G.E. (1963), Some aspects of effective stress in saturated and unsaturated soils, *Geotechnique*, **13**, 177-197.
6. Black, P.B. and Miller, R.D.(1985), A continuum approach to modelling of frost heaving, in *Freezing and Thawing of Soil-water Systems*, pp 36-45, Eds.: D. M. Anderson and P. J. Williams, ASCE, Technical council on Cold Regions Monograph.
7. Blanchard, D. and Fremond, M. (1985), Soils frost heaving and thaw settlement, in *Proceedings, Fourth International Symposium on Ground Freezing*, pp 209-216, Sapporo, Japan.
8. Bresler, E., Russo D. and Miller R.D.(1978), Rapid Estimate Of Unsaturated Hydraulic Conductivity Function, *Soil Sci. Soc. Am. J.*, **42**, 170-172.
9. Burt, T.P. and Williams, P.J.(1976), Hydraulic conductivity in frozen soils, *Earth Surface Processes*, **1**, 349-360.

10. Cary, J.W. and Mayland, H.F.(1972), Salt and water movement in unsaturated frozen soils, *Proceedings, Soil Science Society of America*, **36**, 4, 549-555.
11. Chamberlain, E.J.(1980), Determining differential frost heave by the probabilistic method, *CRREL In-House Laboratory Independent Research Progress Report, 80-43*, Cold Reg. Res. and Eng. Lab., Hanover, NH.
12. Chamberlain, E.J.(1981), Frost susceptibility of soils and review of index tests, *CRREL Monogr. 81-82*, Cold Reg. Res. and Eng. Lab., Hanover, NH.
13. Chamberlain, E.J.(1982), Overconsolidation effects of ground freezing, in *Ground Freezing 1980*, pp 97-110, Eds. P.E. Frivik, N. Janbu, R. Saetersdal and L.I. Finborud, Elsevier Scientific Publishing Company, NY.
14. Crank, J. (1981), How to deal with moving boundaries in thermal problems, in *Numerical Methods in Heat Transfer*, pp 177-200, Eds.: Lewis, Morgan and Zienkiewicz, John Wiley and Sons, NY.
15. Dallimore et al (1984) Experimental observations of differential heave and thaw settlement around a chilled pipeline, in *Pipelines and Frost Heave*, pp 3-17, Eds. S. R. Dallimore and P. J. Williams, Carleton University, Ottawa, Canada.
16. Desai, C. S. (1977), Soil-structure Interaction and Simulation Problems, in *Finite Element In Geomechanics*, pp 209-250, Ed. Gudehus, John Wiley and Sons, NY.
17. Dirkson, C. and Miller, R.D. (1966), Closed system freezing of unsaturated soil, *Soil Sci. Soc. Am. J.*, **30**, 168-173.
18. Dudek, S.J.M. and Holden, J.T.(1979), A theoretical model for frost heave, in *Numerical Methods in Thermal Problems*, pp 216-229, Eds. Lewis and Morgan, Pineridge Press, Swansea, UK.
19. Duncan, J.M. and Chang, C.Y. (1970) Nonlinear Analysis of Stress and Strain in Soils, *J. Soil Mech. Found. Div.*, ASCE, **96**, 1629-53.
20. Evgin, E. and Svec, O. J. (1988), Heat and moisture transfer characteristics of compacted Mackenzie silt, *Geotechnical Testing Journal*, **11**, 92-99.

21. Gilpin, R.R. (1979), A model for the liquid-like layer between ice and a substrate with application to wire regelation and particle migration, *Journal of Colloid and Interface Science*, **68**, 235-251.
22. Gilpin, R.R. (1980), A model for the prediction of ice-lensing and frost heave in soils, *Water Resources Research*, **15**, 918-930.
23. Groonvelt, P.H. and Kay, B.D. (1977), Water and ice potentials in freezing soils, *Water Resources Research*, **13**, 445-449.
24. Harlan, R.L.(1973), Analysis of coupled heat-fluid transport in partially frozen soils, *Water Resources Research*, **9**, 1314-1323.
25. Hillel, D. (1971), *Soil and Water, Physical Principles and Processes*, Academic Press, NY.
26. Holden, J.T., Piper D. and Jones R.H.(1985), Some developments of a rigid-ice model of frost heave, in *Ground Freezing 1985*, pp. 93-101, Eds. S. Kinisita and M. Fukuda, A.A. Balkema, Boston.
27. Hopke, S.W.(1980), A model for frost heave including overburden, *Cold Regions Science and Technology*, **3**, 111-127.
28. Horiguchi, K. and Miller, R.D. (1980), Experimental studies with frozen soil in an ice-sandwich permeameter, *Cold Regions Science and Technology*, **3**, 177-183.
29. Horiguchi, k. (1987), An osmotic model for soil freezing, *Cold Regions Science and Technology*, **14**, 13-22.
30. International Symposia on Ground Freezing:
 - First: March 8-10, 1978, Bochum, West Germany.
 - Second: June 24-26, 1980, Trondheim, Norway.
 - Third: June 24-26, 1982, Hanover, NH,USA.
 - Forth: August 5-7, 1985, Sapporo, Japan.
 - Fifth: July 26-28, 1988, Nottingham, England.
31. Jackson, R. D. (1965), Water vapour diffusion in relatively dry soil: IV. Temper-

- ature and pressure effects on sorption diffusion coefficients, *Soil Science Society of America Proceedings*, **29**, 144-148.
32. Jame, Y.W. and Norum, D.I.(1980), Heat and mass transfer in a freezing unsaturated porous medium, *Water Resources Research*, **16**, 811-819.
 33. Johansen, A.(1977), Thermal Conductivity of Soils, *Draft Transl. 637*, U.S Army Cold Regions Research Engg. Lab, Hanover, NH.
 34. Kay, B.D., and Groenevelt, P.H.(1974), On the interaction of water and heat transfer in frozen soils: I Basic theory, the vapour phase, *Soil Sci. Soc. Am. J.*, **38**, 395-400.
 35. Konrad, J.M. and Morgenstern(1980), A mechanistic theory of ice-lens formation in fine-grained soils, *Canadian Geotechnical Journal*, **17**, 473-486.
 36. Konrad, J.M. and Morgenstern(1981), The segregation potential of a freezing soils, *Canadian Geotechnical Journal*, **18**, 482-491.
 37. Konrad, J.M. and Morgenstern, N.R. (1982a), Effects of applied pressure on freezing soils, *Can. Geotech. J.*, **19**, 494-505.
 38. Konrad, J.M. and Morgenstern, N.R. (1982b), Prediction of frost heave in the laboratory during transient freezing, *Can. Geotech. J.*, **19**, 250-259.
 39. Konrad, J.M. and Morgenstern, N.R. (1984), Frost heave prediction of chilled pipelines buried in unfrozen soils, *Can. Geotech. J.*, **21**, 100-115.
 40. Koopmans, R.W.R. and Miller, R.D. (1966), Soil freezing and soil water characteristic curves, *Soil Sci. Soc. Am. J.*, **30**, 680-685.
 41. Ladanyi, B.(1985), Stress transfer mechanism in frozen soils, *Proceeding 10th CANCAM*, pp 11-23, London, Ontario.
 42. Ladanyi, B. and Shen, M.(1989), Mechanics of freezing and thawing in soils, *Proceedings, International Symposium on Frost in Geotechnical Engineering*, pp 73-103, Saariselka, Finland.
 43. Lewis, R.W. and Schrefler, B.A.(1978), *The Finite Element Method In The Deformation And Consolidation Of Porous Medium*, John Wiley and Sons, NY.

44. Lewis, R.W. and Sze, W. K. (1988), A finite element simulation of frost heave in soils, in *Ground Freezing 1988*, pp 73-81, Eds. R.H. Jones and J.T. Holden, A.A. Balkema, Rotterdam.
45. Loch, J.P.G. (1980) Frost actions in soils, State of the art, in *Proceedings, Second International Symposium on Ground Freezing*, pp 581-96, Trondheim, Norway.
46. Lunardini, V.J.(1982), *Heat Transfer in Cold Climates*, Von Nostrand Reinhold Co., NY.
47. Mageau, D. W. and Morgenstern, N. R. (1980), Observation on moisture migration in freezing soils, *Can. Geotech. J.*, **17**, 54-60.
48. Miller, R. D. (1970). Ice sandwich: Functional semipermeable membrane. *Science*, **164**, 584-585.
49. Miller, R.D. (1977) Lens initiation in secondary heaving, in *Proceedings, International Symposium on Frost Actions in soils*, pp 68-74, Lulea, Sweden.
50. Miller, R.D. (1978) Frost heaving in non-colloidal soils, *Proceedings, 3rd International conference on Permafrost*, pp 707-713, Edmonton, Alberta.
51. Miller, R.D (1980), Freezing phenomena in soils, in *Applications of Soil Physics*, Ed. D.Hillel, Academic Press, NY.
52. Nakano et al (1983) Transport of water in frozen soil: II Effects of ice on the transport of water under isothermal conditions, *Advances in Water Resources*, **6**, 15-26.
53. Nakano et al (1984) Transport of water in frozen soil: III Experiments on the effects of ice content, *Advances in Water Resources*, **7**, 28-34.
54. Nixon, J. F. (1982), Frost heave predictions using segregation potential concept, *Can. Geotech. J.*, **19**, 526-529.
55. Ohrai, T. and Yamamoto, H.(1985), Growth and migration of ice-lenses in partially frozen soils, in *Ground Freezing 1985*, pp. 79-85, Eds. S. Kinisita and M. Fukuda, A.A. Balkema, Boston.
56. Outcalt, S. I. (1979), The effect of iteration frequency on numerical model near

- surface ice segregation, In *Ground Freezing 1978*, pp 111-124, Ed. Hans L. Jessberger, Elsevier Scientific Publishing Company, NY.
57. Outcalt, S.I. (1980), A step function model of ice segregation, *Proceedings, Second International Symposium on Ground Freezing*, pp 515-524, Trondheim, Norway.
 58. O'Neill, K. (1983), The physics of mathematical frost heave model: A Review, *Cold Regions Science and Technology*, **6**, 275-291.
 59. O'Neill, K. and Miller, R.D.(1982), Numerical solutions for a rigid-ice model of secondary frost heave, *CRREL Monogr. 82-13*, Cold Reg. Res. and Eng. Lab., Hanover, NH.
 60. O'Neill, K. and Miller, R.D.(1985), Exploration of rigid-ice model of frost heave, *Water Resources Research*, **21**, 281-296.
 61. Owen, D.R.J. and Hinton E. (1980), *Finite Elements in Plasticity: Theory and Practice*, Pineridge Press Ltd., Swansea, UK.
 62. Pande, G. N. and Sharma, K. G. (1978), On joint/interface elements and associated problems of numerical ill-conditioning, *International Journal of Numerical and Analytical Methods in Geomechanics*, 293-300.
 63. Penner, E. (1959), The mechanism of frost heaving in soils, in *Highway Research Board Bulletin*, **225**, 1-22.
 64. Penner, E. (1986), Aspects of Ice-lens Growth in Soils, *Cold Regions Science and Technology*, **13**, 91-100.
 65. Penner, E. and Ueda, T.(1977), The dependence of frost heaving on load applications- preliminary results, in *Proceedings, International Symposium on Frost Actions in Soils*, pp 92-101, Lulema, Sweden.
 66. Philip, J.R.(1980), Thermal fields during regelation, *Cold Regions Science and Technology*, **3**, 193-204.
 67. Radd, F.J. and Oertle, D.H. (1973), Experimental pressure studies of frost heave mechanisms and the growth-fusion behaviour of ice, *Proceedings, 2nd*

International Conference on Permafrost, pp 377-384, North Am. Contr.

68. Romkens, M.J.M. and Miller, R.D. (1973), Migration of mineral particles in ice with a temperature gradient, *Journal of Colloid and Interface Science*, **42**, 103-111.
69. Shen, M. and Ladanyi, B.(1988), Calculation of the stress field in the soils during freezing, in *Ground Freezing 1988*, pp 121-26, Eds. R.H. Jones and J.T. Holden, A.A. Balkema, Rotterdam.
70. Slusarchuk et al (1978), Field test results of a chilled gas pipeline buried in unfrozen ground, in *Proceedings, 3rd International Conference on Permafrost*, pp. 878-890, Edmonton, Alberta.
71. Snyder, V.A. and Miller, R.D. (1985), Tensile strength of unsaturated soils, *Soil Sci. Soc. Am. J.*, **49**, 58-65.
72. Svec, O. J. (1981) Frost heave control of a chilled gas pipeline, *Cold Regions Science and Technology*, **4**, 215-225.
73. Taylor, G.S. and Luthin, J.N. (1978), A model for coupled heat and moisture transfer during soil freezing, *Canadian Geotechnical Journal*, **15**, 548-555.
74. Tsytovich, N. A. (1975), *The Mechanics Of Frozen Ground*, Translated By Scripta Technica Inc., Washington D.C.
75. Vignes, M. and Dijkema, K.M.(1974), A model for the freezing of water in a dispersed medium, *Journal of Colloid and Interface Science*, **49**, 165-172.
76. Williams, P.J. (1964), Unfrozen water content of frozen soils and soil moisture suction, *Geotechnique*, **14**, 231-246.
77. Williams, P.J. (1986), *Pipelines and Permafrost*, The Carleton University Press, Ottawa, Canada.
78. Williams, Peter J. and Smith, Michael W. (1989), *The Frozen Earth, Fundamentals of Geocryology*, Cambridge University Press, New York.
79. Zienkiewicz, O. C. (1985), *The Finite Element Method*, McGraw-Hill Book Company Limited, London, Uk.

APPENDIX A

USER'S MANUAL

The program developed here is based on theory discussed in Chapters 2 and 4. This program is divided into two parts: (i) 2D-RIGICE and (ii) FROSTRA. The first part analyzes soil for heat and moisture. It is based on the two-dimensional Rigid-Ice model developed in Ch. 3. The second part analyzes the soil and the structure for stresses. It considers changes in water pressure, decreasing temperatures and volumetric strains due to freezing obtained from the first part.

The program 2D-RIGICE can solve the problem of freezing around the chilled gas pipeline. It is necessary to change several subroutines to consider other cases. These changes were implemented to solve the one-dimensional problem of soil-column freezing. Linearized equations were used in the initial stages of freezing. That required few changes in some subroutines. In the following sections, we will discuss the purpose of major subroutines, the definition of important variables and the preparations of input files.

1. 2D-RIGICE

The program can be initiated by typing RIGICE. The input data should be provided in the file 'INPUT' and the output will be written in the file 'OUTP'. The output file gives water pressure and temperature at all the nodes in lens-free region and temperature at all nodes in frozen region for all the time-steps. If new ice-lens has formed, then the output file gives the new coordinates of all the nodes.

1.1 Purpose of Major Subroutines

SUBROUTINE	PURPOSE
MAIN	(i) calls subroutines to read input, analyze frozen and lens-free regions and to check for formation of an ice-lens (ii) if a new ice-lens forms calls subroutine to move mesh (iii) adjust the size of time-step
INPUT	reads mesh data, physical properties of soil and boundary conditions
BOUND	determines boundary conditions at the location of the warmest ice-lens in frozen region from the temperature distribution in lens-free region
THERMANAL	carries out thermal analysis of frozen region and determines heat extraction rate at the location of the warmest ice-lens

CON	calls subroutines to iterate for any time-step and checks for convergence
SOLVE	(i) calls subroutines to evaluate ice-velocity and all integration terms, (ii) assembles all matrices, (iii) applies boundary conditions and (iv) solves for pressures and temperatures
VI	evaluates ice-velocity
VINTEG	evaluates all the volume integrals
SINTEG	evaluates surface integrals on the warmest ice-lens
SINTEG1	evaluates the remaining surface integrals
BOUNDC	applies boundary conditions for lens-free region
LENSFORM	checks for the formation of ice-lens at several points in each element in the freezing fringe
MOVEMESH	if new ice-lens has formed, moves mesh for both lens-free and frozen region such that it coincides with the new warmest ice-lens and re-establishes initial conditions at the new location of nodes
INVERSE	solves equations to find the water pressures and the temperatures (the coefficient matrix is banded but not symmetric)

The flow of above subroutines and the overall flow chart are shown in Figs. (A.1) and (A.2), respectively.

1.2 Definition of Important Variables

It is to be noted that all variables refer to lens-free region, unless mentioned otherwise.

1. COMMON/A/ RHOI, RHOW, A, B, AL, DRHO, G, OMEGA, CS, CW, CI, POROS

RHOI	density of ice (ρ_i)
RHOW	density of water (ρ_w)
RHOS	density of soil grains (ρ_s)
A	$\frac{\rho_i}{\rho_w} - 1$
AL	latent heat of water (L)
B	$\frac{-\rho_i L}{273}$
G	gravitational acceleration (g)
OMEGA	surface tension of water at ice-water interface (ω_{iw})
CS	heat capacity of soil grains (C_s)

CW heat capacity of water (C_w)

CI heat capacity of ice (C_i)

POROS porosity of soil (n)

2. COMMON/B/ PERMC, CONDS, GAMMA, AA(6), EPSILON, THETA, HG, NPOINT

PERMC permeability of unfrozen soil ($K(n)$)

CONDS conductivity of soil grains (λ_s)

GAMMA a parameter defining variation of permeability, Eq. (2.29) (γ)

AA a vector of coefficients defining unfrozen water content, Eq. (2.27) (A_k)

EPSILON a constant between 0 and 1, used in time-marching scheme (ϵ)

THETA an angle between the Y-axis and the vertical axis

HG height of ground surface measured from origin

NPOINT number of points to be checked on each element surface for the determination of direction of ice velocity

3. COMMON/NODEL/ XALL(300), YALL(300), NOEL(150,8), NELT, NODES, NGAUSS

XALL X-co-ordinates of all nodes

YALL Y-co-ordinates of all nodes

NOEL contains the node numbers for all the elements

NELT number of elements

NODES number of nodes

NGAUSS number of Gauss points in each direction (maximum 4)

4. COMMON/SURFACE/ NS1, IS1(70), ISNO(70,3), NS3, IS3(70), IS3NO(70,3)

NS1 number of element surfaces on the warmest ice-lens

IS1 contains corresponding element numbers

ISNO contains corresponding three nodes

NS3 remaning number of element surfaces

IS3 contains corresponding element numbers

IS3NO contains corresponding three nodes

5. COMMON/D/ CONDF(2,2), PERMY(2,2), CST, PHI, GAMMAZ, ALPHA

CONDF conductivity matrix of soil

PERMY permeability matrix of soil

CST	cohesion in unfrozen soil
PHI	friction angle of unfrozen soil
GAMMAZ	unit weight of soil
ALPHA	a constant between 0 and 1 defining at what intermediate value of water pressure and temperature dependent properties are to be evaluated

6. COMMON/I/ NNCT, INNCT(30), NNCP, INNCP(30), ANNCT(30), ANNCP(30)

NNCT	number of nodes with specified temperatures
INNCT	corresponding node numbers
ANNCT	corresponding specified temperatures
NNCP	number of nodes with specified water pressures
INNCP	corresponding node numbers
ANNCP	corresponding specified water pressures

7. COMMON/J/ NECP, INECP(30), NECT, INECT(30), ANECT(30,2), ANECP(30,2)

NECT	number of element surfaces with specified heat flow
INECT	corresponding two end node numbers
ANECT	corresponding specified amount of heat flow
NECP	number of element surface with specified water flow
INECP	corresponding two end node numbers
ANECP	corresponding specified water flow

8. COMMON/NODELT/ XALT(300), YALT(300), NOET(150,8), NELTT, NODET, NGAUST

These variables refer to frozen region.

XALT	X-co-ordinates of all nodes
YALT	Y-co-ordinates of all nodes
NOET	element-nodal relationship
NELTT	number of elements
NODET	number of nodes
NGAUST	number of Gauss points in each direction (maximum 4)

9. COMMON/SURFACE/ NST1, IST1(70), ISNTO(70,3), NST3, IST3(70), ISO(70,3)

These variables refer to frozen region.

NST3	number of element surfaces on the warmest ice-lens
------	--

IST3 contains corresponding element numbers

ISO contains corresponding three nodes

NST1 remaining number of element surfaces

IST1 contains corresponding element numbers

ISNT0 contains corresponding three nodes

10. COMMON/C/ UW2(300), UW1(300), T2(300), T1(300), UW(300), T(300)

UW2 water pressure at all the nodes at the end of any time-step

UW1 water pressure at all the nodes at the beginning of any time-step

T2 temperature at all the nodes at the end of any time-step

T1 temperature at all the nodes at the beginning of any time-step

UW intermediate water pressure at all the nodes at which dependent properties are evaluated

T intermediate temperature at all the nodes at which dependent properties are evaluated

11. COMMON/Y/ TT2(150), TT1(150), QH(70)

These variables refer to frozen region.

TT2 temperature at all the nodes at the end of any time-step

TT1 temperature at all the nodes at the beginning of any time-step

QH heat extraction at the location of the warmest ice-lens

12. COMMON/X/ NECTT, INTT(20,2), NNCT1, INCT1(20), ANCT1(20), ANTT(20)

These variables refer to frozen region.

NECTT number of element surfaces with constant heat flow

INTT corresponding two end node numbers

ANTT corresponding constant heat flow

NNCT1 number of nodes with constant temperatures

INCT1 corresponding node numbers

ANCT1 corresponding specified temperatures

13. COMMON/W/ NNCTT, INCTT(20), IJUNK, ANCT1(20)

These are the boundary conditions for frozen region at the location of the warmest ice-lens determined from the temperature distribution in lens-free region.

NNCTT number of nodes on the warmest ice-lens
 INCTT their node numbers
 IJUNK integer (introduced to improve performance)
 ANCT1 temperatures of all the nodes on the warmest ice-lens

14. COMMON/R/ XI(30), YI(30), ERRMAX, IOPTION, IOPT, NSNODE

XI X-co-ordinates of points where conditions are favorable for the formation of new ice-lens
 YI Y-co-ordinates of points where conditions are favorable for the formation of new ice-lens
 ERRMAX maximum positive difference between neutral pressure and overburden pressure
 IOPTION option parameter determined by checking for ice-lens formation, =1 means ice-lens has formed, =2 means ice-lens has missed
 IOPT option defining type of problem
 NSNODE number of nodes on the warmest ice-lens

15. COMMON/S/ NELO, NELI, X1(30), Y1(30), XX(30), YY(30), NRAD, NDIV, GINC(30)

NELO number of points in the outside surfaces
 NELI number of points in the inside surfaces
 X1 X-co-ordinates of points in inside surface or of points in horizontal direction for soil-column
 Y1 Y-co-ordinates of points in inside surface or of points in vertical direction for soil-column
 XX X-co-ordinates of points in inside surface
 YY Y-co-ordinates of points in inside surface
 NRAD number of circumferential divisions
 NDIV number of radial divisions
 GINC relative size of elements in radial direction

16. COMMON/ST/ NELOT, NELIT, XXT(30), YYT(30), GINCT(30), NDIVT,

These variables refer to frozen region.

NELOT number of points in the outside surfaces
 NELIT number of points in the inside surfaces
 XXT X-co-ordinates of points in inside surface or of points in horizontal direction for

	soil-column
YYT	Y-co-ordinates of points in inside surface or of points in vertical direction for soil-column
NDIVT	number of radial divisions
GINCT	relative size of elements in radial direction
17. COMMON/VV/ VI1	
VI1	ice-velocity

1.3 Preparation of Input File

The following input data are required for any problem. They can be provided free of any fixed format. These input data are divided into several sets and each set in an input file must begin with a new line. The brief description of each required variable is given below. It is assumed that all the variables are for lens-free region, unless mentioned otherwise.

1. Title

SET 1.1

TITLE title of a problem up to 80 characters

2. Mesh Data

The data required for the auto-generation of mesh are different for 1-D and 2-D problem. The following data are necessary for 1-D case.

SET 2.1

NX number of points in X-direction for a rectangular grid

NY number of points in Y-direction for a rectangular grid

SET 2.2

X1 X coordinates of points in X-direction

SET 2.3

Y1 Y coordinates of points in Y-direction

SET 2.4

NYT number of points in Y-direction for a rectangular grid for frozen region

SET 2.5

Y1T Y coordinates of points in Y-direction for frozen region

SET 2.6

NS1 number of element surfaces on the warmest ice-lens

SET 2.7

IARB Auto mesh-generation program also lists all element surfaces, their element numbers and the node number of nodes on them. This array contains the number of element surfaces which correspond to the warmest ice-lens.

SET 2.8

NST1 number of element surfaces on the warmest ice-lens for frozen region

SET 2.7

IARB Auto mesh-generation program also lists all element surfaces, their element numbers and the node number of nodes on them. This array contains the number of element surfaces which correspond to the warmest ice-lens for frozen region.

The following data are necessary for 2-D case.

SET 2.1

NELO number of points on outside surface

NELI number of points in inside surface

SET 2.2

X1 X-coordinates of points on outside surface

Y1 Y-coordinates of points on outside surface

SET 2.3

XX X-coordinates of points on inside surface

YY Y-coordinates of points on inside surface

SET 2.4

NRAD number of circumferential divisions

NDIV number of radial divisions

SET 2.5

GINC relative size of elements in radial direction

SET 2.6

XCENT X-coordinate of the approximate center of points on inside surface

YCENT Y-coordinate of the approximate center of points on inside surface

SET 2.7

NELIT	number of points in inside surface for frozen region
SET 2.8	
XXT	X-coordinates of points on inside surface for frozen region
YYT	Y-coordinates of points on inside surface for frozen region
SET 2.9	
NDIVT	number of radial divisions for frozen region
SET 2.10	
GINCT	relative size of elements in radial direction for frozen region
SET 2.11	
NS1	number of element surfaces on the warmest ice-lens
SET 2.12	
IARB	Auto mesh-generation program also lists all element surfaces, their element numbers and the node number of nodes on them. This array contains numbers of element surfaces which correspond to the warmest ice-lens.
SET 2.13	
NST3	number of element surfaces on the warmest ice-lens for frozen region
SET 2.14	
IARBT	Auto mesh-generation program also lists all element surfaces, their element numbers and the node number of nodes on them. This array contains the number of element surfaces which correspond to the warmest ice-lens for frozen region.

3. Physical Properties

All the properties must be specified in SI system.

SET 3.1	
DT	size of first time-step
SET 3.2	
IPROP	an option for reading properties (if equal to 1, then properties are read from input file, else default properties for silt are being used)
SET 3.3	
RHOS	dry density of soil grains
CS	heat capacity soil grains
CONDS	thermal conductivity of soil grains

SET 3.4

CST cohesion in unfrozen soil
 PHI friction angle of unfrozen soil
 GAMMAZ wet unit weight of unfrozen soil

SET 3.5

POROS porosity of soil

SET 3.6

AA contains 6 coefficients defining the variation of unfrozen water

SET 3.7

PERMC permeability of unfrozen soil
 GAMMA a coefficient defining variation of permeability in freezing fringe

SET 3.8

EPSILON a constant between 0 and 1, used in time-marching scheme (ϵ)
 ALPHA a constant between 0 and 1 defining at what intermediate value of the water pressure and the temperature dependent properties are to be evaluated

SET 3.9

HG height of ground surface from origin
 THETA an angle between the Y-axis and vertical axis

SET 3.10

Q external overburden pressure on the ground surface

4. Boundary Conditions**SET 4.1**

NNCP number of nodes with specified water pressure
 NNCT number of nodes with specified temperature

SET 4.2

INNCP node numbers of nodes with specified water pressure
 ANNCP water pressure at these nodes

SET 4.3

INNCT node numbers of nodes with specified temperature
 ANNCT temperature at these nodes

SET 4.4

NECP number of element surfaces with specified water flow (surfaces with zero flow need not be specified)

NECT number of element surfaces with specified heat flow (surfaces with zero flow need not be specified)

SET 4.5

INECP two end node numbers for element surfaces with specified water flow

ANECP corresponding specified water flow

SET 4.6

INECT two end node numbers for element surfaces with specified heat flow

ANECT corresponding specified amount of heat flow

SET 4.7

NNCT1 number of nodes with constant temperatures for frozen region

SET 4.8

INCT1 node numbers of nodes with constant temperature for frozen region

ANCT1 corresponding specified temperatures (for frozen region)

SET 4.9

NECTT number of element surfaces with constant heat flow for frozen region (surfaces with zero flow need not be specified)

SET 4.10

INTT two end node numbers for element surfaces with specified heat flow

ANTT corresponding constant heat flow

SET 4.11

IRAMP an option to specify if ramped temperature profile is applied to the soil-column (for 1-D only)

SET 4.12

TGW ramped temperature rate at warm end

TGW ramped temperature rate at cold end

5. Initial Conditions

The following four sets are required only for 2-D case. They are used to determine the total stresses.

SET 5.1

NELST number of elements used for stress analysis

NNODST number of nodes used for stress analysis

SET 5.2

XST X-coordinates of all nodes used for stress analysis

YST Y-coordinates of all nodes used for stress analysis

SET 5.3

NOMST element nodal relationship used for stress analysis

SET 5.4

SIGMA total stresses (Sxx, Syy, Sxy) at all the nodes of each element

SET 5.5

TIME time at the start of the freezing process

SET 5.6

TT1 initial temperature at all the nodes of frozen region

SET 5.7

UW1 initial water pressure at all the nodes of lens-free region

SET 5.8

T1 initial temperatures at all the nodes of lens-free region

6. Other Data

As freezing progresses, length of freezing fringe and extent of frozen region increase and it may be necessary to change the size of elements or increase their number.

SET 6.1

IEXPA an option for increasing number of elements in frozen region (if it is equal to 1, then the number of elements in frozen region are to be increased)

SET 6.2

NDIVT number of radial divisions for frozen region

OR

NYT number of points in Y-direction for a rectangular grid for frozen region

SET 6.3

GINCT relative size of elements in radial direction for frozen region

OR

Y1T Y coordinates of points in Y-direction for frozen region
SET 6.4
NST3 number of element surfaces on the warmest ice-lens for frozen region
SET 6.5
IARBT Auto mesh-generation program also lists all element surfaces, their element numbers and the node number of nodes on them. This array contains the number of element surfaces which correspond to the warmest ice-lens for frozen region.
SET 6.6
MESHOP an option for changing the size of elements in lens-free region (if it is equal to 1, then the size of elements should be changed)
SET 6.7
GINC relative size of elements in radial direction
OR
Y1 Y coordinates of points in Y-direction
SET 6.8
NNCT1 number of nodes with constant temperatures for frozen region
SET 6.9
INCT1 node numbers of nodes with constant temperature for frozen region
ANCT1 corresponding specified temperatures (for frozen region)
SET 6.10
NECIT number of element surfaces with constant heat flow for frozen region (surfaces with zero flow need not be specified)
SET 6.11
INTT two end node numbers for element surfaces with specified heat flow
ANTT corresponding constant heat flow

2. FROSTRA

The program can be executed by typing FROSTRA. The input data should be provided in the file 'INPUT' and the output will be written in the file 'OUTPUT'. The output file contains displacements at all the nodes and stresses at gauss points for all the load steps.

2.1 Purpose of Major Subroutines

SUBROUTINE	PURPOSE
MASTER	(i) calls subroutines to read input data, to evaluate load vector, to evaluate stiffness matrix and to determine residual loads for each iteration (ii) checks for convergence for any load step (iii) divides all loads into proper load steps
INPUT	reads mesh data, physical properties, boundary conditions and load data
LOADS	determines load vector due to external loads and self weight
INTEGRATION	determines load vector due to change in neutral pressure, temperature and volumetric strain
STIFFNESS	evaluates stiffness matrix using elastoplastic constitutive laws for both soil and structure
DEP	evaluates elastoplastic constitutive matrix
CONTACT	evaluates stiffnesses of contact springs between soil and structure and assembles in global stiffness matrix
INVERSE	solves for displacements, global stiffness matrix is banded and symmetric and hence only upper banded half is stored.
RESIDUE	evaluates residual loads for any iteration of any load step

The flow of the above subroutines and the overall flow chart are shown in Figs. (A.3) and (A.4), respectively.

2.2 Definition of Important Variables

1. COMMON/LOAD/ GAMMA, GAMMAS, NELLO, INUMB(30), INODE(30,3), ALODE(30,2)

GAMMA	unit weight of soil
GAMMAS	unit weight of pipeline material
NELLO	number of element surfaces with uniformly distributed loads
INUMB	their element numbers
INODE	three nodes on element surfaces with loads
ALODE	uniformly distributed loads in X and Y directions

2. COMMON/CONC/ NCONC, NOCNC(50), ACONC(50,2)

NCONC	number of nodes with concentrated loads
NOCNC	their node numbers

ACONC concentrated loads in X and Y direction

3. COMMON/DISP/ U(600), NOMR(100,8), XG(300), YG(300), DU(600)

U total displacements at all nodes

NOMR element nodal relationship

XG X-coordinates of all nodes

YG Y-coordinates of all nodes

DU incremental displacements in any iteration

4. COMMON/GLOBAL/ AKT(600,120), F(600), FT(600), TEPSV(100)

AKT global stiffness matrix (upper banded half)

F load vector for any iteration

FT load vector due to all external loads and self-weight

TEPSV total volumetric strains for all elements

5. COMMON/NODAL/ NNODE, NELEM, NGAUSS, LOADST, LOPTION, ALOADF(20)

NNODE number of nodes

NELEM number of elements

NGAUSS number of Gauss points in each direction (maximum 3)

LOADST number of load steps

LOPTION number of load steps for the analysis of external loads and weights

ALOADF a vector containing load factors (dividing total load vector by this factor gives load vector for that step)

6. COMMON/STRESS/ SIGMA(100,9,4), DSIGC(100,9,4)

STRESS stresses (S_{xx} , S_{yy} , S_{zz} , S_{xy}) at all the Gauss points

DSIGC stresses due to change in neutral pressure, temperature and volumetric strains (to be subtracted from effective stress after the first iteration)

7. COMMON/PRT/ UW(300), T(300), EPSV(100), TNP(300), TTEMP(300)

UW change in neutral pressure at all nodes for any load step

T change in temperature at all nodes for any load step

EPSV change in volumetric strain in all elements for any load step

TNP total change in neutral pressure

TTEMP total change in temperature

8. COMMON/BOUND/ NNOD, NODNO(100), NBC(100), SU(100), SV(100)

NNOD	number of nodes having specified displacements
NODNO	their node numbers
NBC	boundary codes at these nodes (11 $\Rightarrow$ both the displacements are specified, 10 $\Rightarrow$ u (X direction) is specified, 01 $\Rightarrow$ v (Y direction) is specified)
SU	specified displacements in X direction
SV	specified displacements in Y direction

9. COMMON/SOIL/ ELASM, AMU, COH, PHI, HARD, EINIT, AMU1

ELASM	elastic modulus of soil
AMU	Poisson's ratio of soil
COH	cohesion in soil
PHI	friction angle of soil
HARD	hardness parameter of soil
EINIT	initial elastic modulus of unfrozen soil
AMU1	Poisson's ratio of unfrozen soil

10. COMMON/SOP/ RF, COEFF(4), COE(2), COMU(3)

RF	a constant in hyperbole elastic modulus formula
COEFF	a vector defining the variation of cohesion and friction angle of soil with negative temperatures (first two members define the variation of cohesion and the rest of friction angle)
COE	defining the variation of initial elastic modulus with negative temperature
COMU	defines the variation of Poisson's ratio of frozen soils

11. COMMON/PIPE/ EPIPE, AMUPIPE, NTYPE(100), AKS, BS, YIELDS

EPIPE	elastic modulus of pipeline
AMUPIPE	Poisson's ratio of pipe
NTYPE	defines the type of element, 0 means soil and 1 means pipeline
AKS	bulk modulus of soil grains
BS	coefficient of expansion of soil grains
YIELDS	yield stress of pipeline

12. COMMON/A/ A, B, OMEGA, AA(6)

A	$\frac{\rho_i}{\rho_w} - 1$
B	$\frac{-\rho_i L}{273}$
OMEGA	surface tension of water at ice-water interface (ω_{iw})
AA	a vector of coefficients defining unfrozen water content, Eq. (a ₁)
13. COMMON/INIT/ TNPI(300), TTEMP1(300), FT1(600)	
TNPI	vector of initial neutral pressure at all nodes
TTEMP1	vector of initial temperature at all nodes
FT1	intermediate load vector
14. COMMON/CON/ NCO, ICO(50,3), NNORM(50), PREST(50,3), DMU, CFORCE(50,4)	
NCO	number of pairs of contact springs between pipeline and soil
ICO	contains node number on pipeline, node number on soil and element number on pipeline for each pair of springs
NNORM	contains information about the direction of springs for corner nodes (= 1 means springs are normal and tangent to the element surface located to the right of a node)
PREST	stores previous stiffnesses of springs and previous normal relative displacement
DMU	a friction coefficient between soil and pipeline
CFORCE	contains forces in normal and tangential springs

2.3 Preparation of Input File

1. Mesh Data

SET 1.1

NELEM	number of elements
NNODE	number of nodes

SET 1.2

XG	X-coordinates of all nodes
YG	Y-coordinates of all nodes

SET 1.3

NOMR	contains the node number of all the elements
------	--

2. Physical Properties

SET 2.1

NTYPE	defines the type of element, 0 means soil and 1 means pipeline
SET 2.2	
RF	a constant in hyperbole elastic modulus formula
EINIT	initial elastic modulus of unfrozen soil
SET 2.3	
COEFF	a vector defining the variation of cohesion and friction angle of soil with negative temperatures (first two members define the variation of cohesion and the rest of the friction angle)
SET 2.4	
COE	defining the variation of initial elastic modulus with negative temperature
SET 2.5	
COMU	defines the variation of Poisson's ratio of frozen soils
SET 2.6	
AMU1	Poisson's ratio of unfrozen soil
SET 2.7	
EPIPE	elastic modulus of pipeline
AMUPIPE	Poisson's ratio of pipe
YIELDS	yield stress of pipeline
SET 2.8	
AKS	bulk modulus of soil grains
BS	coefficient of expansion of soil grains
SET 2.9	
A	$\frac{\rho_i}{\rho_w} - 1$
B	$\frac{-\rho_i L}{273}$
SET 2.10	
OMEGA	surface tension of water at ice-water interface (ω_{iw})
SET 2.11	
AA	a vector of coefficients defining unfrozen water content, Eq. (a ₁)

2. Load Data

SET 3.1

TNPI	initial neutral pressures at all nodes
SET 3.2	
TTEMPI	initial temperatures at all nodes
SET 3.3	
TNP	total change in neutral pressure
SET 3.4	
TTEMP	total change in temperature
SET 3.5	
TEPSV	total volumetric strains for all elements
SET 3.6	
GAMMA	unit weight of soil
GAMMAS	unit weight of pipeline
SET 3.7	
NELLO	number of element surfaces with uniformly distributed loads
SET 3.8	
INUMB	their element numbers
SET 3.9	
INODE	three nodes on element surfaces with loads
SET 3.10	
ALODE	uniformly distributed loads in X and Y directions
SET 3.11	
NCONC	number of nodes with concentrated loads
SET 3.12	
NOCNC	their node numbers
SET 3.13	
ACONC	concentrated loads in X and Y direction

4. Contact Springs Data

SET 4.1	
NCO	number of the pairs of contact springs between pipeline and soil
SET 4.2	

ICO contains node number on pipeline, node number on soil and element number on pipeline for each pair of springs

SET 4.3

NNORM contains information about the direction of springs for corner nodes (= 1 means springs are normal and tangent to the element surface located to the right of a node)

5. Boundary Conditions

SET 5.1

NNOD number of nodes having specified displacements

SET 5.2

NODNO their node numbers

SET 5.3

NBC boundary codes at these nodes (11 $\Rightarrow$ both the displacements are specified, 10 $\Rightarrow$ u (X direction) is specified, 01 $\Rightarrow$ v (Y direction) is specified)

SU specified displacements in X direction

SV specified displacements in Y direction

6. Other Data

SET 6.1

NGAUSS number of Gauss points in each direction (maximum 3)

LOADST number of load steps

LOPTION number of load steps for the analysis of external loads and weights

SET 6.2

ALOADF a vector containing load factors (dividing total load vector by this factor gives load vector for that step)

Fig. A.1. Flow of major subroutines for the program 2D-RIGICE

Fig. A.2. Flow chart for the program 2D-RIGICE

Fig. A.3. Flow of major subroutines for the program FROSTRA

Fig. A.4. Flow chart for the program FROSTRA

END

1 2 0 4 9 1

FIN