**PM-1 3 1/2"x4" PHOTOGRAPHIC MICROCOPY TARGET
NBS 1010a ANSI/ISO #2 EQUIVALENT**

PRECISIONSM RESOLUTION TARGETS

National Library
of Canada

Acquisitions and
Bibliographic Services Branch

395 Wellington Street
Ottawa, Ontario
K1A 0N4

Bibliothèque nationale
du Canada

Direction des acquisitions et
des services bibliographiques

395, rue Wellington
Ottawa (Ontario)
K1A 0N4

Your file Votre référence

Our file Notre référence

NOTICE

The quality of this microform is heavily dependent upon the quality of the original thesis submitted for microfilming. Every effort has been made to ensure the highest quality of reproduction possible.

If pages are missing, contact the university which granted the degree.

Some pages may have indistinct print especially if the original pages were typed with a poor typewriter ribbon or if the university sent us an inferior photocopy.

Reproduction in full or in part of this microform is governed by the Canadian Copyright Act, R.S.C. 1970, c. C-30, and subsequent amendments.

AVIS

La qualité de cette microforme dépend grandement de la qualité de la thèse soumise au microfilmage. Nous avons tout fait pour assurer une qualité supérieure de reproduction.

S'il manque des pages, veuillez communiquer avec l'université qui a conféré le grade.

La qualité d'impression de certaines pages peut laisser à désirer, surtout si les pages originales ont été dactylographiées à l'aide d'un ruban usé ou si l'université nous a fait parvenir une photocopie de qualité inférieure.

La reproduction, même partielle, de cette microforme est soumise à la Loi canadienne sur le droit d'auteur, SRC 1970, c. C-30, et ses amendements subséquents.

**CONTRIBUTIONS TO THE STUDY OF THE AERODYNAMICS OF
DAMAGED TURBINE BLADES**

by

WENDY A. KLEIN

B.Sc. (Mechanical Engineering)

A thesis submitted to
the Faculty of Graduate Studies and Research
in partial fulfilment of
the requirements for the degree of

**Master of Engineering
in Aerospace Engineering**

Ottawa-Carleton Institute for Mechanical and Aerospace Engineering

Department of Mechanical and Aerospace Engineering

Carleton University

Ottawa, Ontario

May, 1993

© copyright

1993, Wendy A. Klein

National Library
of Canada

Acquisitions and
Bibliographic Services Branch

395 Wellington Street
Ottawa, Ontario
K1A 0N4

Bibliothèque nationale
du Canada

Direction des acquisitions et
des services bibliographiques

395, rue Wellington
Ottawa (Ontario)
K1A 0N4

Votre titre / Notre référence :

Votre titre / Notre référence :

**THE AUTHOR HAS GRANTED AN
IRREVOCABLE NON-EXCLUSIVE
LICENCE ALLOWING THE NATIONAL
LIBRARY OF CANADA TO
REPRODUCE, LOAN, DISTRIBUTE OR
SELL COPIES OF HIS/HER THESIS BY
ANY MEANS AND IN ANY FORM OR
FORMAT, MAKING THIS THESIS
AVAILABLE TO INTERESTED
PERSONS.**

**L'AUTEUR A ACCORDE UNE LICENCE
IRREVOCABLE ET NON EXCLUSIVE
PERMETTANT A LA BIBLIOTHEQUE
NATIONALE DU CANADA DE
REPRODUIRE, PRETER, DISTRIBUER
OU VENDRE DES COPIES DE SA
THESE DE QUELQUE MANIERE ET
SOUS QUELQUE FORME QUE CE SOIT
POUR METTRE DES EXEMPLAIRES DE
CETTE THESE A LA DISPOSITION DES
PERSONNE INTERESSEES.**

**THE AUTHOR RETAINS OWNERSHIP
OF THE COPYRIGHT IN HIS/HER
THESIS. NEITHER THE THESIS NOR
SUBSTANTIAL EXTRACTS FROM IT
MAY BE PRINTED OR OTHERWISE
REPRODUCED WITHOUT HIS/HER
PERMISSION.**

**L'AUTEUR CONSERVE LA PROPRIETE
DU DROIT D'AUTEUR QUI PROTEGE
SA THESE. NI LA THESE NI DES
EXTRAITS SUBSTANTIELS DE CELLE-
CI NE DOIVENT ETRE IMPRIMES OU
AUTREMENT REPRODUITS SANS SON
AUTORISATION.**

ISBN 0-612-03003-2

Canada

Name _____

Dissertation Abstracts International is arranged by broad, general subject categories. Please select the one subject which most nearly describes the content of your dissertation. Enter the corresponding four-digit code in the spaces provided.

U·M·I

SUBJECT TERM

SUBJECT CODE

Subject Categories

THE HUMANITIES AND SOCIAL SCIENCES

COMMUNICATIONS AND THE ARTS

Architecture 0729
Art History 0377
Cinema 0900
Dance 0378
Fine Arts 0357
Information Science 0723
Journalism 0391
Library Science 0399
Mass Communications 0708
Music 0413
Speech Communication 0459
Theater 0465

EDUCATION

General 0515
Administration 0514
Adult and Continuing 0516
Agricultural 0517
Art 0273
Bilingual and Multicultural 0282
Business 0688
Community College 0275
Curriculum and Instruction 0277
Early Childhood 0518
Elementary 0524
Finance 0277
Guidance and Counseling 0519
Health 0680
Higher 0745
History of 0520
Home Economics 0278
Industrial 0521
Language and Literature 0279
Mathematics 0280
Music 0522
Philosophy of 0998
Physical 0523

Psychology 0525
Reading 0535
Religious 0527
Sciences 0714
Secondary 0533
Social Sciences 0534
Sociology of 0340
Special 0529
Teacher Training 0530
Technology 0710
Tests and Measurements 0288
Vocational 0747

LANGUAGE, LITERATURE AND LINGUISTICS

Language 0679
General 0289
Ancient 0290
Linguistics 0291
Modern
Literature 0401
General 0294
Classical 0295
Comparative 0297
Medieval 0298
Modern 0316
African 0591
American 0305
Asian 0352
Canadian (English) 0355
Canadian (French) 0593
English 0311
Germanic 0312
Latin American 0315
Middle Eastern 0313
Romance 0314
Slavic and East European

PHILOSOPHY, RELIGION AND THEOLOGY

Philosophy 0422
Religion 0318
General 0321
Biblical Studies 0319
Clergy 0320
History of 0322
Philosophy of 0469
Theology

SOCIAL SCIENCES

American Studies 0323
Anthropology 0324
Archaeology 0326
Cultural 0327
Physical
Business Administration 0310
General 0272
Accounting 0770
Banking 0454
Management 0338
Marketing 0385
Canadian Studies
Economics 0501
General 0503
Agricultural 0505
Commerce-Business 0508
Finance 0509
History 0510
Labor 0511
Theory 0358
Folklore 0366
Geography 0351
Gerontology
History 0578
General

Ancient 0579
Medieval 0581
Modern 0582
Black 0328
African 0331
Asia, Australia and Oceania 0332
Canadian 0334
European 0335
Latin American 0336
Middle Eastern 0333
United States 0337
History of Science 0585
Law 0398
Political Science 0615
General 0616
International Law and Relations 0617
Public Administration 0814
Recreation 0452
Social Work 0626
Sociology 0627
General 0938
Criminology and Penology 0631
Demography
Ethnic and Racial Studies
Individual and Family Studies 0628
Industrial and Labor Relations 0629
Public and Social Welfare 0630
Social Structure and Development 0700
Theory and Methods 0344
Transportation 0709
Urban and Regional Planning 0999
Women's Studies 0453

THE SCIENCES AND ENGINEERING

BIOLOGICAL SCIENCES

Agriculture 0473
General 0285
Agronomy
Animal Culture and Nutrition 0475
Animal Pathology 0476
Food Science and Technology 0359
Forestry and Wildlife 0478
Plant Culture 0479
Plant Pathology 0480
Plant Physiology 0817
Range Management 0777
Wood Technology 0746
Biology 0306
General 0287
Anatomy 0308
Biostatistics 0309
Botany 0379
Cell 0329
Ecology 0353
Entomology 0369
Genetics 0793
Limnology 0410
Microbiology 0307
Molecular 0317
Neuroscience 0416
Oceanography 0433
Physiology 0821
Radiation 0778
Veterinary Science 0472
Zoology
Biophysics 0786
General 0760
Medical
EARTH SCIENCES 0425
Biogeochemistry 0996
Geochemistry

Geodesy 0370
Geology 0372
Geophysics 0373
Hydrology 0388
Mineralogy 0411
Paleobotany 0345
Paleoecology 0426
Paleontology 0418
Paleozoology 0985
Palynology 0427
Physical Geography 0368
Physical Oceanography 0415

HEALTH AND ENVIRONMENTAL SCIENCES

Environmental Sciences 0768
Health Sciences
General 0566
Dentistry 0300
Chemotherapy 0992
Dentistry 0567
Education 0350
Hospital Management 0769
Human Development 0758
Immunology 0982
Medicine and Surgery 0564
Mental Health 0347
Nursing 0569
Nutrition 0570
Obstetrics and Gynecology 0380
Occupational Health and Therapy 0354
Ophthalmology 0381
Pathology 0571
Pharmacology 0419
Pharmacy 0572
Physical Therapy 0382
Public Health 0573
Radiology 0574
Recreation 0575

Speech Pathology 0460
Toxicology 0383
Home Economics 0386

PHYSICAL SCIENCES

Pure Sciences
Chemistry 0485
General 0749
Agricultural 0486
Analytical 0487
Biochemistry 0488
Inorganic 0738
Nuclear 0490
Organic 0491
Pharmaceutical 0494
Physical 0495
Polymer 0754
Radiation 0405
Mathematics 0605
Physics 0986
General 0606
Acoustics 0608
Astronomy and Astrophysics 0748
Atmospheric Science 0607
Atomic 0798
Electronics and Electricity 0759
Elementary Particles and High Energy 0609
Fluid and Plasma 0610
Molecular 0752
Nuclear 0756
Optics 0611
Radiation 0463
Solid State
Statistics
Applied Sciences
Applied Mechanics 0346
Computer Science 0984

Engineering 0537
General 0538
Aerospace 0539
Agricultural 0540
Automotive 0541
Biomedical 0542
Chemical 0543
Civil 0544
Electronics and Electrical 0348
Heat and Thermodynamics 0545
Hydraulic 0546
Industrial 0547
Marine 0794
Materials Science 0548
Mechanical 0743
Metallurgy 0551
Mining 0552
Nuclear 0549
Packaging 0765
Petroleum 0554
Sanitary and Municipal 0790
System Science 0428
Geotechnology 0796
Operations Research 0795
Plastics Technology 0994
Textile Technology

PSYCHOLOGY

General 0621
Behavioral 0384
Clinical 0622
Developmental 0620
Experimental 0623
Industrial 0624
Personality 0625
Physiological 0989
Psychobiology 0349
Psychometrics 0632
Social 0451

Carleton University
Ottawa, Canada K1S 5J7

30

Thesis contains black and white and/or coloured graphs/tables/photographs which when microfilmed may lose their significance. The hardcopy of the thesis is available upon request from Carleton University Library.

The undersigned recommend to the Faculty of Graduate Studies
and Research acceptance of the thesis

**CONTRIBUTIONS TO THE STUDY OF THE AERODYNAMICS OF
DAMAGED TURBINE BLADES**

submitted by Wendy A. Klein, B.Sc. (Mechanical Engineering)
in partial fulfilment of the requirements for
the degree of Master of Engineering
in Aerospace Engineering

Thesis Supervisor

Chair, Department of Mechanical and Aerospace Engineering

Carleton University

Abstract

Gas path analysis is frequently used in engine health monitoring systems to predict engine performance under damaged conditions. Users of this method have indicated a need for research on the aerodynamic effects of damage on individual engine components.

A streamline curvature program for analyzing flow in axial flow turbines is investigated for its ability to predict the performance of turbines with damaged blades. The program is altered to allow the tip losses to be concentrated in the tip region. Use of the program to analyze a turbine with simulated tip damage shows that overall engine performance parameters, such as efficiency and power output, are only slightly affected by increased tip clearance and that analysis with concentrated tip losses causes less of a change than with distributed tip losses. A greater effect is observed on the change in temperatures and pressures, across the annulus, at the rotor exit. The development of a new streamline curvature program is recommended for analyzing modern turbine geometries.

A method for manufacturing cascade blades with damage is developed. Preliminary aerodynamic tests of the blades is performed using trailing edge damage simulated by a semicircular cutout having a diameter 25% of chord. Qualitative results are presented which suggest that vortices are generated at the edge of the cutout.

Acknowledgements

This thesis is the culmination of a large amount of work and could not have been completed without the assistance of many people.

I am very grateful to my supervisor, Professor S.A. Sjolander, for guiding and assisting me in conducting and writing up my research and generously providing me with financial support.

I gratefully acknowledge the financial support of GasTOPS Ltd. and the Government of Ontario, under the University Research Incentive Fund.

I would like to thank the staff of the Engineering Mechanical Technical Centre all of whom provided me with cheerful assistance and in particular Robert Hill, who provided invaluable assistance in the production of the mould boxes. I would also like to thank Bruce Johnston and the Department of Mechanical Engineering technicians for their help.

I am grateful to fellow students Dave Whitehouse and Dave Isaacs for their assistance. I am especially grateful to Mike Abbott for assisting in moulding the blades and instruction on operating the wind-tunnel.

I am indebted to my parents for their help and encouragement. Individually, I wish to thank Arthur Klein for his editorial assistance and give photograph credit to Sylvia Klein.

There are no words to express my gratitude to my husband, Gabriel Warshaw, who lent a hand whenever needed, faithfully accompanied me on late night laboratory visits, provided editorial help, provided a great deal of moral support and most of all, patience.

Table of Contents

	Page
Abstract	iii
Acknowledgements	iv
Table of Contents	v
List of Tables	viii
List of Figures	ix
List of Symbols	xii
1.0 Introduction	1
2.0 Review of Previous Work	4
2.1 Streamline curvature method	4
2.1.1 Grid and coordinate system	5
2.1.2 Governing equations	8
2.1.3 Solution procedure	13
2.2 Loss correlations	16
2.2.1 Recent correlations	21
2.3 Engine health monitoring	36
2.4 In service damage to turbines	40
2.5 Studies of blades with altered profiles	42
3.0 Streamline Curvature Program	44
3.1 Program restoration	44

3.2	Tip loss calculation	46
3.3	Turbine blade data	48
3.4	Turbine simulations	51
3.5	Recommendations for improvement	63
4.0	Experimental Apparatus and Procedure	65
4.1	Definitions of flow quantities	65
4.2	Wind-tunnel and cascade test section	68
4.3	Model blade production	74
4.3.1	The mould boxes	76
4.3.2	Making the mould	79
4.3.3	Casting the blade	80
4.3.4	Finishing the blades	80
4.3.5	Modifying blades to simulate damage	80
4.3.6	Cascade installation in test section	81
4.4	Procedure and instrumentation	82
4.4.1	Three hole probe	83
4.4.2	Data acquisition	85
5.0	Experimental Results	88
5.1	Span-wise losses of undamaged blades	88
5.2	Span-wise losses with damaged blades	90
5.3	Recommendations for future experiments	95
6.0	Conclusions	97
6.1	Discussion and Conclusions	97
6.2	Recommendations	99
	References	101

Appendices:

106

- A Documentation for streamline curvature program**
- B Streamline curvature program, 1992 version**
- C Sample simulations using the streamline curvature program**
- D Turbine blade data**
- E Drawings for mould box**
- F Moulding and casting materials**
- G Equipment required to cast blades**
- H Detailed moulding and casting procedures**
- I Control surface settings**

List of Tables

2.1	IECMS Event recording parameters	37
3.1	Turbine data	52
3.2	Turbine performance (Comparison of Turbine Performance With and Without Concentrated Tip Loss For a Low Temperature, Pressure Turbine)	54
3.3	Turbine performance (Comparison of Turbine Performance With and Without Concentrated Tip Loss For a High Temperature, Pressure Turbine)	54

List of Figures

	Page
2.1 Streamline grid terminology	6
2.2 Streamline coordinate system	7
2.3 Fluid element in radial equilibrium	9
2.4 Turbine blade nomenclature	30
2.5 Profile-loss coefficients for conventional section blades at zero incidence	31
2.6 Variation of profile loss with incidence for typical turbine blades	32
2.7 Positive stalling incidences of cascade of turbine blades	33
2.8 Secondary losses in turbine blade rows	34
2.9 Effect of trailing-edge thickness of blade loss coefficients	34
2.10 Trailing edge loss coefficient correlated against the ratio of trailing edge thickness to throat opening	35
2.11 Trailing edge damage on a first-stage guide vane	41
2.12 Cutout dimensions	43
 3.1 Parabola	 46
3.2 Distributed and concentrated tip loss	47
3.3 Tip loss, by Yaras (1991)	49
3.4 Tip loss coefficient in rotor for LP turbine	56
3.5 Tip loss coefficient in rotor for HP turbine	56
3.6 (a) Comparison of total velocity at rotor exit, distributed versus concentrated tip loss, for LP turbine	57

(b)	Comparison of velocity components at rotor exit, distributed versus concentrated tip loss, for LP turbine	57
3.7	(a) Comparison of total velocity at rotor exit, distributed versus concentrated tip loss, for HP turbine	58
	(b) Comparison of velocity components at rotor exit, distributed versus concentrated tip loss, for HP turbine	58
3.8	Loss coefficients in rotor, for LP turbine	59
3.9	Loss coefficients in rotor, for HP turbine	59
3.10	Flow angle at rotor exit, for LP turbine	60
3.11	Flow angle at rotor exit, for HP turbine	60
3.12	Total temperature distribution at rotor exit, for LP turbine	61
3.13	Total temperature distribution at rotor exit, for HP turbine	61
3.14	(a) Comparison of temperatures at rotor exit, for two tip clearance (TCL) widths, with concentrated tip loss, for HP turbine	62
	(b) Comparison of temperatures at rotor exit, for two tip clearance (TCL) widths, with tip loss distributed, for HP turbine	62
4.1	Schematic of variable incidence cascade test section	69
4.2	Cascade geometry and measurement plane nomenclature	71
4.3	Probe span-wise position control	72
4.4	Schematic of wind-tunnel #2	73
4.5	Blade CC3 with simulated damage	75
4.6	Mould box, external	77
4.7	Mould box, internal	78
4.8	Three-hole pressure probe configuration and nomenclature	84
4.9	Schematic of data acquisition system	86
5.1	Comparison of span-wise variation of mass-averaged loss coefficient, $\bar{Y}$, to that found by Whitehouse	89
5.2	Span-wise variation of mass-averaged loss coefficient, $\bar{Y}$	91

5.3	Span-wise variation of flow angle measured downstream of centre blade	91
5.4	Vortical structure produced by cutout	92
5.5	Comparison of pressure coefficient at various span-wise positions	93
5.6	Comparison of flow angle at various span-wise positions	94

List of Symbols

A	Annulus area
AVR	Axial velocity ratio (Equation 4.2, p.66)
b	Blade span (also h, H)
C	Chord
C_x	Axial chord
C_{p0}	Total pressure coefficient (Equation 4.3, p.67)
C_L	Lift coefficient (Equation 2.18, p.19)
h, H	Blade height or span (also b)
h	Enthalpy
I	Rothalpy:
	$I = h_{0,rel} - \frac{1}{2}U^2$
I.D.	Diameter at hub
k	Tip clearance height
m	Mass flow rate
P, p	Pressure
q, Q	Dynami pressure
r, R	Radius
Re	Reynolds number (Equation 4.1, p.66)
REFAC	$[Re / 2 \times 10^5]^{-0.2}$

s	Entropy
s	Pitch, (blade spacing)
t_{max}	Blade maximum thickness (inches)
T	Temperature
V	Fluid velocity
$\bar{V}$	Mass averaged velocity
V_{a1}	Axial velocity at the measurement plane: $V_{a1} = \bar{V}_1 \cos \bar{\alpha}_1$
W	Velocity relative to blade row
w_a	Component of relative velocity in <i>a</i> direction
y	Measurement in pitch-wise direction
Y_k	Tip loss coefficient
Y'_k	Tip loss coefficient, concentrated tip loss method
$\bar{Y}_k$	Mass-averaged tip loss coefficient
Y	Total pressure loss coefficient (Equation 4.4, p.67)
$\bar{Y}$	Mixed out, mass average total pressure loss coefficient (Equation 4.6, p.68)
$\bar{Y}'$	Mass average total pressure loss coefficient (not mixed out) (Equation 4.5, p.67)
z	Measurement in span-wise direction
Z	Blade loading, (Equation 2.17)
α	Relative gas angles
α_m	Mean relative flow angle:

$$\alpha_m = \tan^{-1} \left[\frac{\tan \alpha_1 + \tan \alpha_2}{2} \right]$$

β	Blade metal angle
η	Efficiency
v_a	Velocity component in <i>a</i> direction
ρ	Density
ϕ	Angle between v_t and v_m
ϕ^2	Kinetic energy loss coefficient: $\left(\frac{\text{actual gas exit velocity}}{\text{ideal gas exit velocity}} \right)^2$
ω	Rotational speed

Subscripts

e	Outlet of the cascade
h,H	Hub
i,in	Inlet of the cascade
K	Tip clearance
m	Meridional direction
P	Profile
q	Quasi-orthogonal direction
r	Radial direction
S	Secondary
st	streamline or streamtube
t,T	Tip
TET	Trailing edge thickness

x	Axial direction
θ	Tangential (whirl) direction
0	Total (stagnation) condition
1	Cascade inlet measurement plane, or inlet to turbine blade row
2	Cascade outlet measurement plane, or outlet from turbine blade row

1.0 Introduction

Engine health monitoring (EHM) systems are used by all civilian and military users of gas turbine engines to increase the life of their engines and decrease maintenance costs. The systems collect and analyze information about the engine in an organized manner in order to detect problems. The goal is to detect problems in such a way as to allow corrective action to be taken before problems become serious enough to cause unscheduled down-time, which is expensive, or more critically in-flight shutdown.

The advancement of computer technology is allowing much more complex EHM systems to be developed and the high cost of gas turbine engines encourages this development. Current EHM systems are able to identify the presence of a problem and in broad terms the area of the engine in which it is occurring, but not the specific nature of the problem.

One method of monitoring used is performance monitoring based on gas path analysis. This is a process of comparing actual engine performance to engine performance generated by computer simulations which use thermodynamic analysis. The thermodynamic analysis is based on engine component characteristics. These characteristics are maps of parameters, such as compressor pressure ratios versus mass flow and efficiency versus mass flow, for various shaft speeds. These characteristics can be generated by engine testing or aerodynamic/thermodynamic simulations of engine components. At present, engine deterioration is simulated in the gas path analysis by adjusting the characteristics, for example decreasing the efficiency characteristic. However there is very little knowledge of how to adjust these characteristics realistically. Thus Muir et al., (1988) identified a need for

"fundamental research in the area of gas turbine performance analysis and testing under degraded component conditions."

Most engine deterioration is due to in-service damage of blades, such as blade surface roughening, leading and trailing edge damage, and tip damage. Current EHM systems cannot distinguish between the different types of blade damage without disassembling the engine. Since the cause of these different types of deterioration is different (for example, over-temperatures, vibration problems, blade cooling problems) a considerable amount of time and money can be spent diagnosing the specific nature of a problem. It is therefore desirable to have an EHM system which can distinguish between different types of damage.

In order to develop EHM systems which can distinguish between different types of damage it is necessary to have a knowledge of the aerothermodynamic effects which are specific to each damage mode. One way of determining the effects of a type of damage on the overall performance and other measurable parameters of an engine is to insert the damage into an engine and run it in a test cell. This method is very expensive and therefore the number of different types of damage which can be tested is very limited.

An alternative approach would be to develop an understanding of the aerodynamic effects of damage at the blade level: that is, to determine the effect of specific types of damage on the blade's losses and flow-turning ability. This would be done experimentally using cascade wind-tunnel testing and supplemented with three-dimensional Navier-Stokes computations. From this, modified cascade correlations would be developed and used to simulate the performance of a stage with specified damage. Finally, the characteristics of the damaged stages would be used in the engine model to simulate the behaviour of the damaged engine. A joint program involving GasTOPS Ltd. and Carleton University has been initiated to investigate this approach to improved EHM systems. The Carleton University contribution focuses on the studies of damaged blades and the prediction of the performance of individual stages with damage. GasTOPS will concentrate on the prediction of the overall engine

performance, and the identification of engine parameters which will allow the faults to be detected. This is an area in which the company has extensive expertise. At this stage, the program is examining the effects of damage only on the turbine section of the engine. The present thesis is a contribution to this program.

The study described in this thesis was divided into two major parts. First, the use of the streamline curvature approach for analyzing the throughflow in turbomachinery was evaluated as a method of predicting the performance of damaged stages. Secondly, a method for simulating damage in cascade blade measurements was developed and some preliminary data obtained.

Chapter Three describes the investigation of the streamline curvature approach using the program developed originally by Ngo and Millar (1973). The program was restored from a printed listing. A new method of calculating the tip loss was added to investigate the possibility of altering loss calculations in a way that would simulate losses due to damage. The effect on engine performance of tip damage, in the form of increased tip clearance, was also simulated.

Chapters Four and Five of this thesis discuss a preliminary study of cascade blades with damage. The first step in the study was to develop a method of producing inexpensive cascade blades since machined cascade blades are very expensive to manufacture and thus not appropriate for cutting to simulate damage. Chapter Four discusses the production, by casting, of several cascade blades suitable for the purpose of simulating damage.

The second step in the study was a preliminary investigation of the flow over a cascade blade with simulated trailing edge damage, in the form of a semi-circular cutout. The purpose of this study was to establish procedures and recommendations for future in-depth studies. Chapter Five discusses the results of this study.

Finally, Chapter Six summarizes the conclusions drawn from the present study and makes a number of recommendations for future work.

2.0 Review of Previous Work

Since studying the effects of damage on turbines is an immature field very little directly related research has been performed. This chapter discusses some background to the methods used in the present study.

This thesis investigates the use of a streamline curvature program for analyzing flow through damaged gas turbines. Therefore the streamline curvature computing method is outlined in Section 2.1. The program makes use of cascade loss correlations in calculating the losses through a turbine. The tip loss correlation was replaced by the author, therefore cascade loss correlations are reviewed in Section 2.2.

Current engine health monitoring (EHM) practices are discussed in Section 2.3. Section 2.4 discusses the types of damage which occur in gas turbines. Finally, Section 2.5 reviews a study where cascade blades have had their profiles altered to improve the downstream flow field.

2.1 Streamline curvature method

The streamline curvature method is a relatively simple method of predicting the axis-symmetric approximation to the flow through turbomachines. Using inlet fluid properties and machine geometry the program uses an iterative approach to finding the density and velocity fields which satisfy the radial component of the Navier-Stokes equation and the continuity equation, (Davis and Millar, 1975). The method assumes inviscid, axisymmetric flow, and uses the radial equilibrium method (Dixon, 1984) in

that all radial acceleration is assumed to take place within a blade row so that flow is in radial equilibrium outside the blade row. The effects of the blade row are limited to a deflection of the air and a total pressure loss, calculated using cascade correlations.

The majority of literature on the streamline curvature method and programs which use it, discuss its use in reference to compressor analysis: for example Davis (1971), Davis and Millar (1975) and Novak (1967). A turbine analysis program which uses the streamline curvature method was developed by Ngo and Millar (1973). That program was used in this thesis as discussed in Chapter 3. For a more detailed discussion of the program or the streamline curvature method it uses, the reader is referred to Ngo and Millar.

2.1.1 Grid and Coordinate System

The streamline curvature program uses a grid made up of streamlines and quasi-orthogonal planes, as shown in Figure 2.1. The streamline direction is referred to as the meridional direction and is in the direction of the meridional velocity, v_m , which is the vector sum of the radial and axial velocities.

$$v_m^2 = (v_r^2 + v_x^2) \quad (2.1)$$

The quasi-orthogonal planes, which are used as calculation stations, are set by the user in advance of the calculation. They are placed roughly perpendicular to the streamlines usually in the radial direction or parallel to the leading and trailing edge of blade rows. The quasi-orthogonal direction is indicated by q and is not necessarily the same for different calculation stations.

Calculations are performed in the (q,m,θ) coordinate system as shown in Figure 2.2, where θ is the tangential or whirl direction and the magnitude of the fluid velocity, V is:

$$V = \sqrt{v_m^2 + v_\theta^2}$$

Figure 2.1 Streamline Grid Terminology (adapted from Davis (1971))

Figure 2.2 Streamline Coordinate System (adapted from Davis, (1971))

2.1.2 Governing Equations

The basis of all streamline curvature through-flow computation methods is the radial equilibrium equation applied to grid points along the quasi-orthogonal stations. The radial equilibrium equation is the radial component of the momentum equation. This equation expresses the balance between pressure forces and inertia forces on a fluid in the radial direction. Because the flow has a tangential (whirl) component the pressure must increase with increasing radius in order to provide the force required to counteract the centripetal acceleration. Cohen et al. (1987) derive the equation by considering the forces acting on a fluid element as shown in Figure 2.3. The inertia forces in the radial direction (neglecting gravitational forces) arise from:

- (i) the centripetal force associated with circumferential flow;
- (ii) the radial component of the centripetal force associated with the flow along the curved streamline; and
- (iii) the radial component of the force required to produce the linear acceleration along the streamline.

The radial equilibrium equation in terms of pressure and velocity is

$$\frac{1}{\rho} \frac{dp}{dr} = \frac{v_\theta^2}{r} + \frac{v_m^2}{r_m} \cos\phi + \frac{dv_m}{dt} \sin\phi \quad (2.2)$$

The pressure force is on the left side and the inertia forces are on the right. For compressor calculations the last two terms are usually ignored since r_m is very large and ρ is very small. Turbines have a greater annulus taper and thus these terms become more significant.

The equation is written in terms of enthalpy and entropy by substituting the following equalities:

Figure 2.3 Fluid Element in Radial Equilibrium (adapted from Cohen et al., (1987))

$$h = h_0 - \frac{V^2}{2} = h_0 - \frac{1}{2}(v_x^2 + v_\theta^2)$$

so that

$$\frac{dh}{dr} = \frac{dh_0}{dr} - \left(v_x \frac{dv_x}{dr} + v_\theta \frac{dv_\theta}{dr} \right) \quad (2.3)$$

and the second law of thermodynamics for an ideal gas gives:

$$T ds = dh - \frac{dp}{\rho}$$

so that after rearranging, the variation of enthalpy with radius is:

$$\frac{dh}{dr} = T \frac{ds}{dr} + ds \frac{dT}{dr} + \frac{1}{\rho} \frac{dp}{dr} - \frac{1}{\rho^2} \frac{d\rho}{dr} dp$$

and dropping the second order terms leaves:

$$\frac{dh}{dr} = T \frac{ds}{dr} + \frac{1}{\rho} \frac{dp}{dr} \quad (2.4)$$

Equating 2.3 and 2.4

$$\frac{dh_0}{dr} = T \frac{ds}{dr} + \frac{1}{\rho} \frac{dp}{dr} + \left(v_x \frac{dv_x}{dr} + v_\theta \frac{dv_\theta}{dr} \right) \quad (2.5)$$

Now substituting Equation 2.2 into Equation 2.5 gives

$$\frac{dh_0}{dr} = T \frac{ds}{dr} + \frac{v_\theta^2}{r} + \frac{v_m^2}{r_m} \cos \phi + \frac{dv_m}{dt} \sin \phi + \left(v_x \frac{dv_x}{dr} + v_\theta \frac{dv_\theta}{dr} \right)$$

For steady flow the partial derivative of the meridional velocity, with respect to time is zero thus

$$\frac{dv_m}{dt} = v_m \frac{\partial v_m}{\partial m}$$

and the radial equilibrium equation can now be written in the following form:

$$\frac{dh_0}{dr} = T \frac{ds}{dr} + \frac{v_\theta^2}{r} + \frac{v_m^2}{r_m} \cos \phi + v_m \frac{\partial v_m}{\partial m} \sin \phi + \left(v_x \frac{dv_x}{dr} + v_\theta \frac{dv_\theta}{dr} \right) \quad (2.6)$$

The streamline curvature program used in the present study uses the following forms of the radial equilibrium equation. They are written in a rotating, quasi-orthogonal coordinate system where the velocity, $\vec{W}$ relative to the blade speed, ωr , is

$$\begin{aligned} \vec{W} &= \vec{w}_m + \vec{w}_q + \vec{w}_\theta \\ &= \vec{v}_m + \vec{v}_q + (\vec{v}_\theta - \omega r) \end{aligned} \quad (2.7)$$

and the rothalpy, I is

$$\begin{aligned} I &= h + \frac{1}{2} W^2 - \frac{1}{2} (\omega r)^2 \\ &= h_0 - (\omega r) v_\theta \end{aligned} \quad (2.8)$$

and ϵ is the angle between the normal direction and the quasi-orthogonal direction, q . (The normal direction is the direction perpendicular to the meridional direction).

Thus the radial equilibrium equation in the (q,m,θ) coordinate system is

$$\frac{\partial w_m}{\partial q} = \left[\frac{\sin \epsilon}{w_m} \frac{\partial w_m}{\partial m} - r_m \cos \epsilon \right] w_m + \left[\frac{\partial I}{\partial q} - T \frac{\partial s}{\partial q} - \frac{w_\theta}{r} \frac{\partial (r w_\theta + \omega r^2)}{\partial q} \right] \frac{1}{w_m} \quad (2.9)$$

This equation can also be expressed as a function of flow angle β

$$\frac{\partial w_m}{\partial q} = \left[\frac{\sin \epsilon}{w_m} \frac{\partial w_m}{\partial m} - r_m \cos \epsilon \right] w_m + \cos^2 \beta \left[\frac{\partial I}{\partial q} - T \frac{\partial s}{\partial q} - w_m \tan \beta \left\{ \frac{\partial \tan \beta}{\partial q} + \left(\tan \beta + \frac{2\omega r}{w_m} \right) \frac{\cos \psi}{r} \right\} \right] \quad (2.10)$$

where

$$\beta = \tan^{-1} \left[\frac{w_\theta}{w_m} \right]$$

These last two forms of the radial equilibrium equation are suitable for both rotating and stationary co-ordinates; in stationary co-ordinates the relative velocity becomes absolute since the rotational speed, ω is 0.

The Continuity Equation

The continuity equation is:
$$\dot{m} = 2\pi \int_{r_{in}}^{r_{out}} \rho v_m r \cos \epsilon \quad (2.11)$$

2.1.3 Solution Procedure

The method of solution described in Ngo and Millar (1973) is repeated here, with some minor corrections, for reference.

- I. The annulus is divided into a suitable number of streamtubes. The streamline positions are estimated by assuming uniform mass flow per unit area and constant meridional velocity along each quasi-orthogonal. The stagnation temperature, pressure and either the tangential velocity or flow angle of the inlet flow are specified across the annulus at the first quasi-orthogonal. Their locations are not necessarily the same as the initial streamline positions.
- II. Analytical curves are fitted to each streamline and the slope and curvature at each grid point are computed. The velocity distribution along each streamline, which is obtained from the mass flow rate and annulus area, is used to compute the stream-wise derivative dw_{θ}/dm . The stagnation properties and swirl velocity or angle are computed at each inlet streamline from the given inlet distribution by means of linear interpolation.
- III. With given inlet properties, the derivatives of enthalpy, entropy and tangential velocity are calculated. Thus, the coefficients of Equations (2.9) or (2.10) are known along the current calculation station. The equation now can be integrated numerically in terms of velocity at any point, normally at the hub, to yield the meridional velocity distribution across the annulus.
- IV. The mass flow rate due to this velocity distribution can then be calculated by integrating the continuity equation (2.11), noting that the annulus wall boundary layer or the blockage factor is not taken into account in the first iteration. The calculated mass flow rate is then compared to the actual

specified mass flow rate. If the difference between these mass flow rates is above a specified tolerance, the initial guess of the hub velocity is changed according to some suitable algorithm. Steps (III) and (IV) are repeated until convergence.

- V. The fluid properties, P_0 , I , $r\omega$ or β must now be calculated at the next calculation station. In a duct region with no blade row to extract work and generate losses, P_0 , T_0 and rV_0 are constant along each streamline. However, if there is a blade row between adjacent quasi-orthogonal planes, the total pressure loss coefficient Y and relative air angle β must be computed using cascade correlations (analysis mode, as described in Section 2.2) or using specified loss coefficients, flow angle or velocities (design mode).
- VI. Steps (III) to (V) are then repeated for each quasi-orthogonal station.
- VII. The initial streamline positions, which were based on a constant meridional velocity distribution, are then repositioned. The repositioning of the streamlines is based on the newly computed velocities and starts at the hub where an estimate of the position of the adjacent streamline is made. Linear interpolation is used to find the mass flow parameter at the new position and the trapezoidal rule is used to find the mass flow through that streamtube. If the computed mass flow differs from the desired mass flow, the position of the streamtube is changed according to some suitable algorithm. The previous steps are repeated until convergence and the same process carried out for successive streamtubes at all quasi-orthogonal planes. To avoid instability during the iterative process, a "damping factor" is applied to the streamline position shift.
- VIII. Steps (II) to (VII) are repeated using new streamline positions and velocity distribution until the change in streamline position or meridional velocity has come within a specified tolerance.

Summing up, there are two major iterations in the procedure. The outer iteration changes streamline position based on the velocity distribution at each station, and the inner iteration computes a velocity distribution which satisfies the continuity condition at each specified quasi-orthogonal.

In step V the loss coefficients are calculated using loss correlations which were initially intended for mean-line analysis. The loss correlations are applied at each grid point along the annulus despite the fact that the different loss components would actually be concentrated in different regions. In Chapter 3 a method of concentrating the tip loss in the tip region, where the majority of loss would occur, is discussed.

2.2 Loss Correlations

The loss correlations used by the streamline curvature method were developed by Ainley and Mathieson (1951). These correlations were widely accepted. They are based on numerous tests of turbine stages therefore their accuracy only applies to 'conventional' blade profiles. However, 'conventional' blade profiles are constantly changing and thus Ainley and Mathieson's correlations are less accurate with modern turbine designs. Dunham and Came (1970) suggested several improvements to the Ainley and Mathieson correlations in order to modernize them. These became widely accepted but are now outdated. More recently the correlations have been brought up to date again by Kacker and Okapuu (1982) and Moustapha et al. (1990).

The following paragraphs outline the loss correlations which are used in the streamline curvature program discussed in this document. Although the program was written after Dunham and Came's revised loss correlations were published they were not yet widely accepted. Thus the program makes use of a combination of Ainley and Mathieson and Dunham and Came's methods. For reference, improvements suggested by Dunham and Came, but not used in the program, are also reviewed below. Finally the correlations due to Kacker and Okapuu and Moustapha et al. are summarized since it would be desirable to implement them in the program. Figure 2.4 shows the blade nomenclature which applies to the correlations. It can be found at the end of this section along with the other figures referred to in this section.

The total loss coefficient, Y , in a turbine is equal to the stagnation pressure drop across the blade row as a proportion of the dynamic pressure exiting the blade row.

$$Y = \frac{P_{01} - P_{02}}{P_{02} - P_2} \quad (2.12)$$

Where P_{02} is the mass averaged total pressure.

This loss can be broken down into three main components: Profile losses, Y_p , which are the losses due to viscous friction on the blade surface and trailing edge losses; secondary losses, Y_s , which are the losses arising from complex three-dimensional flows set up as a result of the end wall boundary layers passing through the blade row (Dixon (1984)); and tip clearance loss, Y_t , which is the loss resulting from flows created by the clearance between the end of the blade and the adjacent wall. The sum of these three losses, Y , is equal to the stagnation pressure drop across the blade row as a proportion of the dynamic pressure exiting the blade row.

Profile Loss, Y_p

The profile loss, Y_p , is obtained by finding Y_p for nozzle and impulse blades from Figure 2.5, and substituting them into the following equation for the profile loss at zero incidence:

$$Y_{p(i=0)} = \left\{ Y_{p(\beta_1=0)} + \left(\frac{\beta_1}{\alpha_2} \right)^2 \left[Y_{p(\beta_1=\alpha_2)} - Y_{p(\beta_1=0)} \right] \right\} \left(\frac{t/c}{0.2} \right)^{p/\alpha_2} \quad (2.13)$$

$Y_{p(i=0)}$ should be restricted to values resulting from t/c in the range; $0.15 < t/c < 0.25$, if t/c is outside this range the loss should be taken as the value resulting from $t/c = 0.25$ or 0.15.

Y_p can be found from Figure 2.6 using $Y_{p(i=0)}$ and i/i_s , the ratio of incidence to stalling incidence. The stalling incidence is found from Figure 2.7 as follows:

- From Figure 2.7 find $\alpha_2(s/c = 0.75)$ using α_2
- From Figure 2.7b find $i_s(s/c = 0.75)$ using $\beta_1/\alpha_2(s/c = 0.75)$
- From Figure 2.7a find Δi_s for the actual value of s/c and hence determine i_s from: $i_s = i_s(s/c = 0.75) + \Delta i_s$

Dunham and Came recommended a correction for choked rows; however, since the program discussed in this thesis is unable to handle choked rows, it was not implemented. It is,

$$Y_p = (Y_p \text{ from equation 2.2}) \times \left[1 + 60(M_n - 1)^2 \right] \quad (2.14)$$

for $M_n > 1$

where M_n is the relative Mach number at exit from the blade row.

Secondary Loss, Y_s

The expression for secondary loss by Ainley and Mathieson is

$$Y_s = \lambda Z \quad (2.15)$$

where λ is an empirical function, f, of the annulus areas normal to the flow and radii as follows

$$\lambda = f \left\{ \frac{\left(\frac{A_3 \cos \beta_2}{A_2 \cos \beta_1} \right)^2}{1 + \frac{r_h}{r_i}} \right\} \quad (2.16)$$

f is found from Figure 2.8 and Z is Ainley's loading parameter

$$Z = \left(\frac{C_L}{s/c} \right)^2 \frac{\cos^2 \alpha_2}{\cos^3 \alpha_m} \quad (2.17)$$

where C_L is the lift coefficient:

$$C_L = 2 (s/c) (\tan \alpha_1 - \tan \alpha_2) \cos \alpha_m \quad (2.18)$$

Dunham and Came's revision of Ainley and Mathieson's secondary losses is used in the program. Their expression is:

$$Y_s = 0.0334 \left(\frac{c}{h} \right) \left(\frac{\cos \alpha_2}{\cos \beta_1} \right) Z \quad (2.19)$$

For Reynolds numbers less than 2×10^5 a correction factor to overall efficiency was recommended by Ainley and Mathieson as follows:

$$(1 - \eta_{corrected}) = (1 - \eta) \left(\frac{R_{e_{ann}}}{2 \times 10^5} \right)^{-0.2} \quad (2.20)$$

Dunham and Came recommended the following revision - used in the program - which is applied to individual blade rows:

$$\begin{aligned} (Y_p + Y_s)_{corrected} &= (Y_p + Y_s) \left(\frac{R_e}{2 \times 10^5} \right)^{-0.2} \\ &= (Y_p + Y_s) REFAC \end{aligned} \quad (2.21)$$

Tip Leakage Loss, Y_t

The method used in the program to calculate tip leakage losses is that described in Ainley and Mathieson:

$$Y_t = B \left(\frac{k}{h} \right) Z \quad (2.22)$$

(where $B = 0.5$ for blades with plain tip clearance and 0.25 for blades with shrouded tips)

Dunham and Came's suggested improvement to this is often quoted (Dixon (1984), Cohen et al. (1987)), but it is now widely agreed that it is not good, as shown in Yaras and Sjolander (1989). It is as follows:

$$Y_t = B \frac{c}{h} \left(\frac{k}{c} \right)^{0.78} Z \quad (2.23)$$

where $B=0.47$ for plain tip clearance, 0.37 for shrouded

Correction for Trailing Edge Thickness, Y_{TET}

If the trailing edge thickness of the blades is not approximately equal to 2% of the blade pitch then Figure 2.9 should be used to correct Y . Note that Y_{TET} is a multiplier not a loss coefficient.

Final form of total loss, Y

The final form of the total loss is:

$$Y = [(Y_p + Y_t)REFAC + Y_t] Y_{TET} \quad (2.24)$$

2.2.1 Recent Correlations

Recent correlations have been proposed by Kacker and Okapuu (1982) and Moustapha et al. (1992) to replace Ainley and Mathieson and Dunham and Came's methods. These correlations have taken into account modern turbine designs and used the increased amount of available cascade and turbine data. To date, these correlations do not include a practical tip loss correlation method; however, the method proposed by Yaras and Sjolander (1990) could be adapted for use with these correlations.

Design Point Correlations

Kacker and Okapuu (1982) developed a mean line loss system using Ainley and Mathieson's system as a foundation. This loss system predicts design point efficiencies to within $\pm 1.5\%$. The loss system modified the structure used by the Ainley and Mathieson and Dunham and Came system, (AMDC). The structure used is

$$Y = Y_p f_{(Re)} + Y_s + Y'_{TET} + Y_k \quad (2.25)$$

where $f_{(Re)}$ is a new correction for Reynolds numbers other than 2×10^5 and Y'_{TET} is a trailing edge loss coefficient.

Kacker and Okapuu's system (K & O) also introduce the effects of compressibility and shock losses into the calculation of profile and secondary loss coefficients. Their system is presented below.

Profile Loss Coefficient, Y_p , (K & O)

In order to allow negative inlet angles Equation 2.13 was changed to

$$Y_{p,AMDc} = \left\{ Y_{p(\beta_1=0)} + \left| \frac{\beta_1}{\alpha_2} \right| \left(\frac{\beta_1}{\alpha_2} \right) [Y_{p(\beta_1=\alpha_2)} - Y_{p(\beta_1=0)}] \right\} \left(\frac{t_{max}/c}{0.2} \right)^{\frac{\beta_1}{\alpha_2}} \quad (2.26)$$

In order to obtain Y_p for zero trailing edge thickness, Y_p is multiplied by 0.914. This is done because the trailing edge correction factor is added separately.

The profile loss coefficient Y_p becomes

$$Y_p = 0.914 \left(\frac{2}{3} Y_{p,AMDc} K_p + Y_{SHOCK} \right) \quad (2.27)$$

where

$$K_p = 1 - K_2(1 - K_1) \quad (2.28)$$

is a correction for exit Mach number and channel acceleration, and K_1 and K_2 are given by

$$K_1 = 1 - 1.25(M_2 - 0.2), \text{ FOR } M_2 > 0.2$$

$$K_2 = (M_1/M_2)^2$$

and

$$Y_{SHOCK} = \left(\frac{\Delta P_0}{q_1} \right)_{SHOCK} \left(\frac{p_1}{p_2} \right) \frac{1 - \left(1 + \frac{\gamma-1}{2} M_1^2 \right)^{\frac{\gamma}{\gamma-1}}}{1 - \left(1 + \frac{\gamma-1}{2} M_2^2 \right)^{\frac{\gamma}{\gamma-1}}} \quad (2.29)$$

is the blade inlet shock loss contribution to the **mean line** loss, where

$$\left(\frac{\Delta P_0}{q_1} \right)_{SHOCK} = \left(\frac{R_H}{R_T} \right) (0.75 (M_{1,HUB} - 0.4)^{1.75})$$

Reynolds Number Correction

The correction for Reynolds number is

$$\begin{aligned} f_{(Re)} &= \left(\frac{Re_c}{2 \times 10^5} \right)^{-0.4} \quad \text{for } Re_c \leq 2 \times 10^5 \\ &= 1.0 \quad \text{for } 2 \times 10^5 < Re_c < 10^6 \\ &= \left(\frac{Re_c}{10^6} \right)^{-0.2} \quad \text{for } Re_c > 10^6 \end{aligned} \quad (2.30)$$

Secondary Loss Coefficient, Y_s , (K & O)

The secondary loss coefficient is

$$Y_s = 1.2 Y_{sAMDc} K_s \quad (2.31)$$

where:

$$Y_{sAMDc} = 0.0334 f_{(AR)} \left(\frac{\cos \alpha_2}{\cos \beta_1} \right) Z \quad (2.32)$$

(Note: Z is given by Equation 2.17 and C_L by Equation 2.18)

and $f_{(AR)}$ is the new aspect ratio correction

$$\begin{aligned} f_{(AR)} &= \frac{1 - 0.25\sqrt{2 - h/c}}{h/c} \quad \text{for } h/c \leq 2 \\ &= \frac{1}{h/c} \quad \text{for } h/c > 2 \end{aligned} \quad (2.33)$$

also

$$K_s = 1 - K_3(1 - K_p) \quad (2.34)$$

where

$$K_3 = \left(\frac{1}{h/c_x} \right)^2$$

and K_p is given by Equation 2.28. (Note: c_x is axial chord)

Trailing Edge Loss Coefficient, Y'_{TET} , (K & O)

The trailing edge loss coefficient is found by interpolating the trailing edge energy coefficient using Figure 2.10 and the following formula.

$$\Delta\phi_{TET}^2 = \Delta\phi_{TET(\beta_1=0)}^2 + \left| \frac{\beta_1}{\alpha_2} \right| \left(\frac{\beta_1}{\alpha_2} \right) \left[\Delta\phi_{TET(\beta_1=\alpha_2)}^2 - \Delta\phi_{TET(\beta_1=0)}^2 \right] \quad (2.35)$$

This is then converted to a pressure loss coefficient by the following formula.

$$Y_{TET} = \frac{\left[1 - \frac{\gamma-1}{2} M_2^2 \left(\frac{1}{1 - \Delta\phi_{TET}^2} - 1 \right) \right]^{-\frac{\gamma}{\gamma-1}} - 1}{1 - \left(1 + \frac{\gamma-1}{2} M_2^2 \right)^{-\frac{\gamma}{\gamma-1}}} \quad (2.36)$$

Tip Clearance Loss Coefficient, Y_k , (K & O)

The tip clearance coefficient for shrouded turbine blades is:

$$Y_k = 0.37 \frac{c}{h} \left(\frac{k'}{c} \right)^{0.78} Z \quad (2.37)$$

where

$$k' = \frac{k}{(\text{number of seals})^{0.42}}$$

To find Y_k for un-shrouded rotor blades it is necessary to use the following equation and either an iterative approach or simplifying assumptions.

$$\frac{\frac{\Delta\eta}{\eta_o}}{\frac{\Delta k}{h \cos \alpha_2} \times \frac{R_{TIP}}{R_{MEAN}}} = 0.93 \quad (2.38)$$

The iterative approach suggested in Kacker and Okapuu is to calculate the turbine efficiency with zero tip clearance, η_o ; assess the efficiency penalty, $\Delta\eta$, due to tip clearance and increase the loss coefficient until the process converges on efficiency. This requires recalculating the velocity triangles and other loss coefficients for each iteration.

Tip Clearance Loss Coefficient, (Yaras and Sjolander)

Yaras and Sjolander (1990) developed an improved tip-leakage loss model which could be used in place of the method suggested by Kacker and Okapuu. Their formulation is designed to fit in a loss system where the total loss through the blade row is calculated from the following equation.

$$Y = Y_p + (Y_{sec})_{HUB} + (Y_{end})_{TIP} \quad (2.39)$$

where

$$(Y_{end})_{TIP} = Y_{gap} + k_s Y_{s.o} + Y_{tip}$$

In this formulation the secondary and tip losses are separated into secondary losses near the hub, $(Y_{sec})_{HUB}$, and losses associated with the tip clearance near the tip, $(Y_{end})_{TIP}$. The following equations were proposed to calculate $(Y_{end})_{TIP}$.

$$Y_{tip} = C K_G \frac{\left(\frac{c}{s}\right) C_D C_L^{1/2}}{\cos \alpha_m} \left(\frac{\tau}{h}\right)$$

where

(2.40)

$$C \equiv 0.007$$

$$K_G = 0.943 \quad \text{for front- or aft-loaded blades}$$

$$K_G = 1.0 \quad \text{for mid-loaded blades}$$

$k_t Y_{t,0} =$ $Y_{t,0}$ is the secondary loss coefficient at the tip for zero tip clearance and k_t is the fraction of the secondary loss which remains identifiably associated with a secondary flow structure. k_t is expected to be a function of inlet boundary layer thickness, tip gap height and rotation.

$$Y_{tip} = 2 K_E \left(\frac{c}{s}\right) \frac{\tau}{h} C_D \frac{\cos^2 \alpha_2}{\cos^3 \alpha_m} C_L^{1.5} \quad (2.41)$$

Off-design Correlations

Moustapha et al. (1990), (MKT) developed profile and secondary loss correlations for axial turbines operating at non-zero incidence. Their method gives improved correlation of cascade data, over Ainley and Mathieson and Dunham and Came's methods. The ability of the method to predict off-design performance of turbines still needs to be demonstrated. The major change in the MKT loss correlation is the addition of leading edge diameter, d , into the correlation. Their method is summarized below.

Profile Loss Coefficient, Y_p , (MKT)

MKT's off-design, profile loss coefficient is found by first calculating the design loss coefficient using K & O, Equation 2.27. Then the loss coefficient, $Y_{p(des)}$, is converted to a kinetic energy loss coefficient using the following equation.

$$Y = \frac{\left[1 - \frac{\gamma-1}{2} M_2^2 \left(\frac{1}{\phi^2} - 1 \right) \right]^{-\frac{\gamma}{\gamma-1}} - 1}{1 - \left(1 + \frac{\gamma-1}{2} M_2^2 \right)^{-\frac{\gamma}{\gamma-1}}} \quad (2.42)$$

The change in this loss coefficient is then calculated using the following equation.

$$\begin{aligned} \Delta\phi_p^2 &= 0.778 \times 10^{-5} \chi' + 0.56 \times 10^{-7} \chi'^2 + 0.4 \times 10^{-10} \chi'^3 + 2.054 \times 10^{-19} \chi'^6 \\ &\quad \text{for } 0 < \chi' < 800 \\ \Delta\phi_p^2 &= -5.1734 \times 10^{-6} \chi' + 7.6902 \times 10^{-9} \chi'^2 \\ &\quad \text{for } -800 < \chi' < 0 \end{aligned} \quad (2.43)$$

where

$$\chi' = \left(\frac{d}{s} \right)^{-1.6} \left(\frac{\cos \beta_1}{\cos \beta_2} \right)^{-2} [\alpha_1 - \alpha_{1(des)}] \quad (2.44)$$

The change in kinetic energy loss coefficient can now be added to the design kinetic energy loss coefficient and converted back into a pressure loss coefficient using Equation 2.42.

Secondary Loss Coefficient, Y_s (MKT)

The secondary loss coefficient for off design incidence is found using the following equation.

$$\left(\frac{Y}{Y_{(des)}} \right)_s = \exp(0.9\chi'') + 13\chi''^2 + 400\chi''^4$$

for $0 < \chi'' < 0.3$

$$\left(\frac{Y}{Y_{(des)}} \right)_s = \exp(0.9\chi'')$$

for $-0.4 < \chi'' < 0$

(2.45)

where

$$\chi'' = \frac{\alpha_1 - \beta_1}{180 - (\beta_1 + \beta_2)} \left(\frac{\cos \beta_1}{\cos \beta_2} \right)^{-1.5} \left(\frac{d}{c} \right)^{-0.3}$$
(2.46)

As previously mentioned, Moustapha et al. does not provide an off-design correlation for the tip losses.

a = Distance of Point of
Maximum Camber from
Leading Edge
 b = Maximum Camber
 c = Chord
 o = Blade "opening" or "throat"
 s = Blade Pitch

t = Maximum Thickness
 t_e = Trailing Edge Thickness
 β_1 = Inlet Blade Angle
 β_2 = Outlet Blade Angle
 ζ = Stagger Angle

Figure 2.4 Turbine Blade Nomenclature

Figure 2.5 Profile-loss Coefficients for Conventional Section Blades at Zero Incidence. ($\nu/c = .02$; $R_\nu = 2 \times 10^5$; $M < 0.6$) (adapted from Ainley and Mathieson (1951))

Figure 2.6 Variation of Profile Loss with Incidence for Typical Turbine Blades.
(adapted from Ainley and Mathieson (1951))

Figure 2.7 Positive Stalling Incidences of Cascades of Turbine blades. ($R_e = 2 \times 10^5$; $M < 0.6$) (adapted from Ainley and Mathieson (1951))

Figure 2.8 Secondary Losses in Turbine Blade Rows (adapted from Ainley and Mathieson (1951))

Figure 2.9 Effect of Trailing-edge Thickness on Blade Loss Coefficients

Figure 2.10 Trailing Edge Loss Coefficient Correlated Against the Ratio of Trailing Edge Thickness to Throat Opening. (adapted from Kacker and Okapuu (1982))

2.3 Engine health monitoring

Engine health monitoring is an evolving technology. Its purpose is to eliminate unscheduled down time including dangerous failures and to reduce down time and maintenance costs. It achieves this by determining which engine components are in need of repair prior to their failure. Currently, repairs are often trial and error searches for the cause of an instrument reading out of its normal range. This procedure can be quite costly since it can involve replacing the wrong parts and long down times.

A variety of methods are currently used to monitor engine components. Schofield et al. (1988) discusses the use by the Canadian Forces of the following methods: oil monitoring techniques (spectrometric oil analysis); magnetic particle detectors; vibration monitoring and analysis; and performance trending.

GasTOPS Ltd. has been developing methods for monitoring the engines of the Canadian Forces CF-18 aircraft. These methods, although now in routine use, are still under evaluation. They are outlined in Cue and Muir, (1991) and Muir et al., (1988). The following paragraphs summarize the work described in these references.

An on-condition maintenance program is being used for the F404-GE-400 engines of the CF-18 aircraft where maintenance is performed when engine conditions dictate the need, as opposed to using a fixed schedule. This is made possible by the In-Flight Engine Condition Monitoring System, (IECMS), which continuously monitors engine and performance parameters. These parameters are listed in Table 2.1.

The IECMS records the parameters during take-off and when an engine operating limit is exceeded (referred to as an "in-flight event"). The in-flight event recordings are used for troubleshooting the cause of in-flight anomalies. The take-off recordings are used for performance monitoring.

Symbol	Description
T_1	Inlet temperature
N_1	Fan speed
N_2	Compressor speed
W_{fm}	Main fuel flow
T_{36}	Exhaust gas temperature
P_{36}	Exhaust gas pressure
P_{d3}	Compressor discharge pressure
EOP	Engine oil pressure
VF	Fan Vibration
VC	Compressor Vibration
VB	Broadband vibration
PLA	Power level angle
A_n	Nozzle position
BAD	Bleed air door flag
APC	Approach Power compensator flag
VCS	Velocity control system flag
N2L	N ₂ Lock-up flag
BP	Boost pressure flag
DER	Derich flag
REC	Pilot record flag
SEN	Sensor failure flag
AI	Anti-ice flag
F_c	Computed thrust
M	Mach number
AOA	Angle of attack
T_o	Total temperature
P_{alt}	Pressure altitude

Table 2.1 IECMS Event Recording Parameters (from Cue and Muir (1991))

The in-flight event recordings are very useful for confirming that an in-flight anomaly has actually occurred and determining its cause.

The performance monitoring procedures are based on health indices calculated from the IECMS data. These include: compressor delivery pressure rise time; fan rotor acceleration time; the ratio of the two rotor speeds; fuel ratio units (a measure of fuel flow); maximum computed thrust, vibration and oil pressure; and engine airflow. These engine health indices are plotted on trend plots with left and right engine indices combined or plotted individually. The difference between the left and right engine indices may also be plotted. Using statistical analysis of over 2000 take-offs and 200 different engines, alarm limits have been established for the health indices. The data analysis program which calculates the health indices compares them to the alarm limits and displays a maintenance flag if they are out of bounds.

Performance monitoring techniques have been successful at tracking the general performance level of engines and sometimes help to identify specific problems.

The objectives of research and development in the area of performance monitoring are: to reduce the number of health indices required; to be able to identify the specific cause of degradation in engine performance; and to be able to identify problems prior to the occurrence of in-flight anomalies.

In order to identify the specific cause of the decline in engine performance it is necessary to know the effects on the engine of the various types of damage. Gas path analysis is being used to develop a "fault library" to achieve this end. This requires knowledge of the effects of damage on the aerodynamics and thermodynamics of the individual components. The research described in this thesis is a contribution to this field of knowledge.

Fast Response Wall Pressure Measurement

Another method being investigated for its ability to identify damaged engine blades is the examination of the pressure field around rotating blades for distortions caused by damage.

Mathioudakis et al. 1991 studied the distortions of the pressure field around rotating blades of a compressor for this purpose. They demonstrated that by calculating power spectra (of pressure measured by pressure transducers) and subsequently producing spectral comparison indices, the kind of blade fault can be identified. The behaviour of the indices suggested that the signatures are different for different blade faults, and that the signatures do not depend on the operating point, as long as the rotational speed remains the same.

Signatures for one of the tested faults were also produced by a simple computational procedure and the authors claimed very good agreement with the measured ones.

The faults studied were rotor fouling of all blades (rough blades), individual rotor blade fouling and individual twisted blades.

Finally, it was demonstrated that single-valued discriminants can be produced from the spectral indices, thus giving the possibility of introducing simple criteria for fault identification. This feature of the described procedure makes it suitable for inclusion in an expert system for fault diagnosis.

A shortcoming of this method is that the pressure must be sampled at a very high rate. In the Mathioudakis et al. study it was sampled at a rate of 32,000 Hz. The IECMS in the F-18 records pressures at a frequency of 1/5 Hz regularly and 10 Hz after an unusual event. Thus, radical alterations to the IECMS would be required to use this method.

2.4 In Service Damage to turbines

Mattheij (1985) discusses the different types of damage occurring in gas turbines and techniques used in their restoration. He discusses only the physical nature of the damage, not its effect on the aerodynamic performance of the machine. A brief summary is presented here.

According to Mattheij, the usual types of damage occurring in components of the hot section of gas turbines and requiring repair are: degenerated base material, corrosion, foreign-object damage, erosion and low-cycle fatigue.

Degenerated base material is usually accompanied by corrosion. Severe trailing edge damage is typically caused by these factors. The main problem with a degenerated structure is its low ductility. Pieces can break off and cause foreign-object damage to downstream blades. Typically, leading edge damage is the result.

Corrosion by various modes can cause degeneration over a large area of the blade or in localized regions. Thus surface damage, leading and trailing edge damage can all be the result of corrosion. Low-cycle fatigue causes cracking in the blades.

As an example, Figure 2.11 shows trailing edge damage on a first-stage guide vane caused by degeneration of the structure of the base material. The experimental part of the present study has focused on the effects of such trailing-edge damage on the performance of the blade.

Figure 2.11 Trailing Edge Damage on a First-Stage Guide Vane (reproduced from Mattheij (1985))

2.5 Studies of blades with altered profiles

There have been only two previous published studies of the aerodynamics of turbomachinery blades with trailing edge "damage" in the form of semi-circular cutouts. However, these cutouts were introduced as a design feature to enhance mixing of the blade wakes, not as a simulation of damage.

The studies were performed at the Air Force Institute of Technology by DeCook et al. (1993) and Veasart et al. (1990). They were performed on the flow field around and downstream of compressor cascade blades using cutouts shown in Figure 2.12. The purpose of the study was to investigate crenellations as a method of reducing blade wakes or mixing them out more quickly. Both sizes of crenellations, which were studied, improved wake mixing and reduced total pressure loss. In general turning angles and the static pressure rise across the cascade were reduced.

Figure 2.12 Cutout Dimensions (reproduced from DeCook et al.)

3.0 Streamline Curvature Program

A program for the design and analysis of axial flow turbines was developed by Ngo and Millar (1973). The program used the streamline curvature method described in Section 2.1 and was written in FORTRAN IV.

This program was used in the present study to investigate if the streamline curvature method could be used to simulate the flow through, and corresponding performance changes for, a turbine with damaged blades. It was hoped that, by using suitably modified loss correlations, the effect of the blade damage on the stage performance could be predicted.

The streamline curvature program uses Ainley and Mathieson's loss correlation. One of the disadvantages of this and similar correlations is that all losses are assumed to be distributed over the whole of the stage mass flow rate. However, for the blades with localized damage, the corresponding loss will be concentrated in a small region of the flow. It was therefore decided to modify the program to accept concentrated loss distributions. The tip leakage loss was used as an example.

3.1 Program Restoration

The streamline curvature program was available only in the form of a printed listing and required restoration. This listing was given in Ngo and Millar, (1973) and included two sample input data files and their resulting output. These data files corresponded to the two program modes, design and analysis. The program had been

typed into an ASCII file format by a previous graduate student and this was available on diskette. Problems with the typed code included typographical errors, format incompatibility for printouts, and a couple of logic errors. The author believes the logic errors were corrected by Ngo after printing the listing for his thesis but prior to producing the output files. The code was not well structured and did not include a list of variables with their meanings.

During the extensive debugging process a list of all variables was developed. To simplify changing the program as well as debugging it, each common block statement with its declaration of variables was placed in a file of its own. These files are then included by the compiler, in each subroutine for which they are needed. Thus any error in the common block or its declaration only needs to be corrected in one place. The same applies for any change to a variable, such as its dimension size or magnitude.

During the course of debugging and enhancing, the program was often altered to take advantage of structures available in FORTRAN 77. Since the program was written before the IF()THEN statement was introduced, this statement was often used to replace IF()GOTO statements in the original program. Comments were added liberally to ease following the program's logic and finding calculations of interest.

The additional documentation for the program generated during the present work can be found in Appendix A. It is not intended to be complete documentation. The process of determining the meaning of variables was greatly aided by the documentation in a report on a closely related streamline curvature program for compressors (Davis (1971)).

3.2 Tip Loss Calculation

An addition to the streamline curvature program was written to replace the tip loss coefficient, Y_t , calculated using Ainley and Mathieson's method with a new tip loss coefficient, Y'_t , which concentrated the tip loss near the tip of the blade. The total mass-averaged tip loss coefficient, $\bar{Y}_t$, (equation 3.1), was kept the same as for Ainley and Mathieson's correlation.

$$\bar{Y}_t = \frac{1}{\dot{m}} \sum (Y_t \cdot \dot{m}_{st}) \quad (3.1)$$

where $\dot{m}_{st}$ is the mass flow through individual streamtubes, and Y_t is the tip loss coefficient for that streamtube.

The tip loss study of Yaras (1991) shows that the span-wise distribution of the mass-averaged total pressure loss coefficient can be approximated by a parabola, as shown in Figure 3.1.

Figure 3.1 Parabola

A parabola was therefore used to represent the tip loss coefficient, Y_t , in the streamline curvature program. The parabola follows the equation

$$f(x) = y = Y_2 - a(x - X_2)^2 \quad (3.2)$$

and points 1 and 3 are fixed according to the following constraints:

$$X_1 = 0, \quad Y_1 = 0.5 Y_2$$

$$X_3 = 0.4 \left(\frac{PITCH}{CHORD} \right) CHORD, \quad Y_3 = 0$$

The values of these parameters are based on the experimental distributions of tip loss, as shown later.

Figure 3.2 Distributed and Concentrated Tip loss

To obtain the tip loss coefficients, Y'_k , for the individual streamlines, the equation for the parabola is adjusted iteratively until $\sum f(x) \cdot \bar{m}_n$ is equal to $\sum Y_k \cdot \bar{m}_n$. This is illustrated schematically in Figure. 3.2, where areas A and B are equal. The process requires an initial guess for Y_2 and only two iterations are generally required. Once this process is complete the coefficients of the parabolic equation, equation 3.2, are known.

The coefficients of the parabolic equation are calculated using the x values at the centre of the streamtubes, but the tip loss coefficients are required at the edges, on the streamlines. To obtain the Y'_k values on the streamlines the parabolic equation is used with x values taken at the streamline positions. $Y'_k = f(x)$ is calculated for each streamline.

The concentrated tip loss coefficients for each streamline are calculated by the subroutine TIPLOS. TIPLOS calls TIPCRV which calculates the coefficients of the parabola, a , X_2 and Y_2 . TIPDAT is the input program for the parameters which are altered most frequently. TIPDAT does not use a data file as the parameters are altered directly within it. This could easily be changed if regular use of an executable version were required. TIPWRT writes information about the last calculated parabola. It was used for developmental purposes only. These subroutines are discussed in more detail in Appendix A and are listed in Appendix B.

Earlier in this section it was explained that the constraints on the shape of the parabola were based on experimental studies by Yaras. Figure 3.3 shows experimental distributions of tip loss measured by Yaras. These experiments were performed in a cascade with a span, h , of 203 mm and pitch, s , of 150 mm. They indicate a tip loss with a parabolic shape having a loss at the tip-wall equal to approximately half the maximum loss, therefore Y_1 was set to $0.5Y_2$. The loss drops to zero at approximately 0.3 times the span from the wall, which is a distance approximately equal to 0.4 times the pitch. The losses are associated with the tip leakage vortex whose diameter is constrained more by the blade spacing than the passage height. Therefore, for subsequent calculations the width of the region of concentrated loss, X_2 , was set equal to $0.4s$ for all cases.

3.3 Development of Turbine Blade Data

Two data sets, representing two turbines, were used for turbine simulations. The first set of data was taken directly from Ngo (1973) and is discussed in Section 3.4. The second set of data represents the high pressure stage of a two stage turbine.

The data for both stages of the two stage turbine were obtained by measuring used blades from a current turbine design, and measuring drawings of blades for the same

Figure 3.3 Tip Loss by Yaras (1991)

turbine. These drawings were not detailed drawings, but showed some blade profiles. The blade data generated can be found in Appendix D.

Before the drawings became available an attempt was made to measure the profiles from the actual turbine blades. This process was very involved and had many problems. Although it was eventually abandoned, it is described in the following paragraphs.

A blade was mounted by its root on a vertical milling machine. A dial gauge was attached to the base of the machine with its tip against the blade. The blade was moved in one direction horizontally, in small steps, by moving the bed of the machine. The dial gauge was read at each step. In this way a profile of the blade could be obtained. After obtaining the profile coordinates they were entered into a CAD program and an attempt was made to assemble them to make an outline of the complete blade.

Many problems were encountered with this method. It was not possible to have a constant reference point, as it was necessary to move either the blade or the dial indicator to obtain the complete blade profile. If the dial indicator was mounted on an indicator stand, and reached a rapid change in blade profile, the stand moved. If it was mounted rigidly in the chuck of the milling machine and reached a rapid change, it jammed and the tip was bent. The tip of the dial indicator also interfered with the annulus walls attached to the stator blades. This limited the regions where profiles could be measured on these blades. Three blade profiles were obtained for each side of each of the four blades. However, they could not be obtained at matching span-wise positions. Without a single common reference point for the profiles it was extremely difficult to obtain the accurate geometry of the complete blade.

A coordinate measuring machine could be used to obtain blade profiles without the above mentioned problems. It is indicated that similar measurements should not be attempted without one. Once blade profiles have been determined using the coordinate measuring machine, a powerful three dimensional CAD package would be required to

obtain the type of data needed for simulation programs, such as inlet and outlet metal angles.

3.4 Turbine Simulations

The simulations were performed to determine the effect of concentrating the tip loss and the effect of tip damage. Ultimately the direction of this research is to develop a method of determining what type of damage has occurred in a turbine by examining quantities which can be measured during turbine operation such as temperatures, pressures and overall performance. If different types of damage affect these quantities in different ways, then simulating various types of damage and comparing the results to those of a turbine could determine the type of damage that has occurred in the turbine.

The analysis routine of the streamline curvature program was run with and without the concentrated tip loss method for two test cases. The data for these test cases are listed in Appendix C.

The first data set was obtained from Ngo's thesis (1973). These data represent a single-stage lightly loaded turbine, designed and tested by the National Gas Turbine Establishment of Great Britain. This turbine has a low inlet temperature, 356 K and pressure, 25.5 psi. It has a work coefficient, ψ of .15, and a flow coefficient, ϕ of 0.65. The blade profile has a parabolic camber line with maximum camber at 40% chord from leading edge. The design rotor tip clearance was 0.01", or about 0.69% of blade height.

The second set of data represents the high pressure turbine of a two stage turbine currently used in the engine of a fighter class aircraft. It has much higher inlet temperature and pressure: 1628 K and 337 psi respectively. Some data obtained for this turbine are shown in Table 3.1. The streamline curvature program is not capable

Two Stage, High Pressure, High Temperature Turbine Data		
	High pressure turbine	Low pressure turbine
Rotor speed (rpm)	16,200	13,100
Gas flow (lbm/sec)	97	107
Inlet temperature (R)	2930	2290
Inlet pressure (psi)	337	112
Pressure Ratio	3.00	2.08
$\Delta T / T$	0.218	0.154
Coolant flow (lbm/sec)	10	4
Efficiency	0.866	0.9125

Table 3.1 Turbine Data

of handling choked flow or coolant flows. Since this turbine has choked flow at the design mass flow and over 10% coolant flow, it was not possible to run the program at the design mass flow. Also, since the increase in mass flow rate due to cooling flow was not accounted for, it was not possible to run both stages of the turbine together.

The effect on the overall performance of the turbines due to concentrating the tip loss is shown in Tables 3.2 and 3.3. The tables show that for normal tip clearances there is little difference between concentrated and distributed tip loss. This is not surprising since the mass averaged value of the tip loss is kept constant; only the distribution is changed. If the tip clearance is increased, as in the case of tip damage, the difference between the methods increases. Table 3.3 compares overall performance of the high pressure turbine for two tip clearances, illustrating the increased difference with larger tip clearance (tip damage).

The concentrated tip loss method provides a more realistic simulation of the flow in a turbine than the distributed tip loss method. If one assumes that it therefore provides a more accurate simulation of the overall performance of a turbine, then the following conclusion can be drawn: the distributed tip loss method over-estimates the change in performance of a turbine caused by damage. Therefore, given a measured change in performance of a turbine, using the distributed tip loss method as a diagnostic would lead one to underestimate the actual damage present in the turbine. Table 3.3 shows that an increase in tip clearance from .03" to .05" results in a 1991 HP increase predicted by the distributed case compared to a 985 HP increase predicted by the concentrated case.

The overall performance predicted in simulations may be a valuable tool in predicting the extent of the damage that has occurred in a turbine. However it is not likely to be as useful for determining the type of damage, since different types of damage may cause similar changes in overall performance. The changes in local parameters, such as wall temperature and pressure at rotor exit, hold more promise for diagnosing the type of damage which has occurred.

Comparison of Turbine Performance With and Without Concentrated Tip Loss For A Low Temperature, Pressure Turbine		
Inlet Temperature	356 K	
Inle: Pressure	25.51 psi	
Mass Flow	10.81 lbm/sec	
Speed	12924.6 rpm	
	Distributed Tip Loss	Concentrated Tip Loss
Total Pressure Ratio	1.454	1.453
Total Temperature Ratio	1.103	1.102
Total Temperature Drop	33.15 K	33.07 K
Total-Total Efficiency	92.03 %	91.96 %
Power Output	219.5 HP	219.0 HP

Table 3.2 Turbine Performance

Comparison of Turbine Performance With and Without Concentrated Tip Loss For A High Temperature, Pressure Turbine				
Inlet Temperature	1627.8 K			
Inlet Pressure	337 psi			
Mass Flow	92.3 lbm/sec			
Speed	16200 rpm			
	Distributed Tip Loss, TCL = .03"	Concentrated Tip Loss, TCL = .03"	Distributed Tip Loss, TCL=.05"	Concentrated Tip Loss, TCL = .05"
Total Pressure Ratio	2.399	2.372	2.728	2.537
Total Temperature Ratio	1.191	1.188	1.217	1.201
Total Temperature Drop	261 K	258 K	290 K	272 K
Total-Total Efficiency	86.39 %	86.44 %	84.93 %	85.29 %
Power Output	17929 HP	17725 HP	19919.8 HP	18710.4 HP

Table 3.3 Turbine Performance

The tip loss was concentrated in a parabolic shape as shown in Figure 3.4 and 3.5, and discussed in Section 3.2. This shape is reflected on the plots for most of the flow parameters. Figures 3.6 to 3.11 show how the velocities, loss components and flow angles are redistributed for the two turbines. The profile and secondary losses are only slightly affected by the new tip loss distribution. This effect is probably caused by the small change in position of the individual streamtubes.

The total and static temperature distributions at exit from the rotor are affected significantly by the concentrated distribution as shown in the plots of total temperature, Figures 3.12 and 3.13. Figure 3.14 compares the total temperature at rotor exit of the high pressure turbine for two tip clearances. This figure suggests that temperature probes placed on the tip and hub walls of the turbine at the exit from the rotor would see changes in temperature with increased tip clearance. In this case the probe at the tip would see a 10 degree decrease in total temperature and the probe at the hub would see a 16 degree decrease in total temperature. The distributed tip loss simulation suggests a much larger overall total temperature decrease, as well as a much smaller difference between the hub and tip temperatures. Again the distributed tip loss simulation would under-predict the degree of damage which has occurred in a turbine with similar temperature changes.

In order to use the results of a streamline curvature simulation to isolate different types of damage in turbines, it would be necessary to have additional instrumentation in the turbine. Simulations of other commonly occurring damage, such as trailing edge damage and increased blade roughness, would be necessary to get a clear indication of the usefulness of a streamline curvature simulation in resolving types of damage in turbines. If the temperature changes at the tip and hub are significantly different for the various types of damage, streamline curvature simulations may be very useful. If the distributions are different but the temperatures at hub and tip are not much different then streamline curvature simulations may not be useful. It would not be very difficult to instrument the turbine with a temperature probe or

Figure 3.4 Tip Loss Coefficient in Rotor for LP Turbine

Figure 3.5 Tip Loss Coefficient in Rotor for HP Turbine

Figure 3.6a Comparison of Total Velocity at Rotor Exit, Distributed versus Concentrated Tip Loss, for LP Turbine

Figure 3.6b Comparison of Velocity Components at Rotor Exit, Distributed versus Concentrated Tip Loss, for LP Turbine

Figure 3.7a Comparison of Total Velocity at Rotor Exit, Distributed versus Concentrated Tip Loss, For HP Turbine

Figure 3.7b Velocity Components at Rotor Exit, Distributed versus Concentrated Tip Loss, for HP Turbine

Figure 3.8 Loss Coefficients in Rotor, for LP Turbine

Figure 3.9 Loss Coefficients in Rotor, for HP Turbine

Figure 3.10 Flow Angle at Rotor Exit, for LP Turbine

Figure 3.11 Flow Angle at Rotor Exit, for HP Turbine

Figure 3.12 Total Temperature Distribution at Rotor Exit, for LP Turbine

Figure 3.13 Total Temperature Distribution at Rotor Exit for HP Turbine

Figure 3.14a Comparison of Temperatures at Rotor Exit, for Two Tip Clearance (TCL) Widths, with Concentrated Tip Loss, for HP Turbine

Figure 3.14b Comparison of Temperatures at Rotor Exit for Two Tip Clearance (TCL) Widths, with Distributed Tip Loss, for HP Turbine

thermocouple at the tip and maybe the hub, however instrumentation across the annulus might be too expensive to install and maintain.

The obvious place to put thermocouples across the annulus would be on a radial strut, downstream of the blade row of interest. However, there is the concern that viscous forces will mix the flow between the blade row and the thermocouples. This will distribute the effect of damage, possibly enough to prevent resolving the types of damage. Thus, measurements made close to the damage may be the most useful for use in discriminating different types of damage.

3.5 Recommendations for future improvement

To enable the present streamline curvature program to handle modern turbine geometries, certain features must be added. It must be able to handle choked flow and coolant flow, now standard in turbine designs. It should vary the specific heat as the temperature drops through the turbine. It should have a boundary layer calculation to calculate the blockage through the turbine. The last two items become much more important in a two stage turbine. The program should also provide a method of span-wise mixing between blade rows so that concentrated loss diffuses laterally with downstream distance, as will happen in reality.

The addition of choked flow, coolant flow, specific heat and boundary layer calculations to this program is discussed by Ngo (1973). A program to provide span-wise mixing is being written by Verhiel (1993).

A streamline curvature program being written for the purpose of simulating turbines with damage should have a special feature. It should have modularized loss calculations so that different loss methods could easily be used. The modularization should also allow each of the loss components to be calculated using different methods during the same simulation. Presently, wind tunnel studies are being conducted to

determine cascade losses for damaged blades with various types of damage. A program which would allow use of the new overall loss coefficients and the new loss distributions is desirable.

If continued use of the streamline curvature program listed in Appendix B is planned, as opposed to writing a new program, it is recommended that Appendix A be referred to for a discussion of program convergence as well as a list of some bugs in the program.

4.0 Experimental Apparatus and Procedure

This chapter describes the apparatus and procedures used to conduct the cascade experiments. Section 4.1 defines the flow quantities which are used to conduct the experiments and reduce the resulting data. Section 4.2 describes the wind-tunnel and cascade test section. Section 4.3 describes the production of cascade blades used in the wind-tunnel. Lastly Section 4.4 describes the procedure used to conduct the experiments and the instruments and data acquisition system used to collect the data.

4.1 Definitions of flow quantities

In the course of experiments and reduction of the resulting data several flow quantities are calculated by the data acquisition and reduction program. This section defines the quantities used and where necessary discusses them.

The Reynolds number in the tunnel is defined as follows:

$$R_e = \frac{\rho V_{in} C}{\mu} \quad (4.1)$$

where:

ρ	=	Density
V_{in}	=	Inlet centre-line velocity, calculated from dynamic pressure at the reference plane
C	=	Blade chord
μ	=	Viscosity

The axial velocity ratio is a measure of the axial flow acceleration or deceleration across the blade passage. An axial velocity ratio of 1.0 is taken to indicate that the flow at blade midspan is two-dimensional. While this is only approximately true, it appears to be the most satisfactory criterion available. The significance of axial velocity ratio is discussed in more detail by Rodger (1992).

$$AVR = \frac{V_{a,te}}{V_{a,le}} \quad (4.2)$$

The axial velocity ratio was calculated using the axial velocity at the trailing edge plane and the leading edge plane. These values of axial velocity are estimated using linear interpolation between the mass averaged axial velocity at the inlet and outlet measurement planes.

The total pressure coefficient, C_{p_0} , expresses the total pressure loss in non-dimensional form. It was calculated for each probe position.

$$C_{p_0} = \frac{(P_0 - P_{0,in})}{\frac{1}{2} \rho V_{in}^2} \quad (4.3)$$

The mixed out, mass-averaged total pressure loss was calculated for each traverse. The total pressure loss is expressed in the form of a total pressure loss coefficient, Y , where

$$Y = \frac{(P_0 - P_{0,in})}{\frac{1}{2} \rho V_c^2} \quad (4.4)$$

The mass-averaged loss coefficient, Y' is then obtained from

$$Y' = \frac{1}{\dot{m}} \int_0^s Y \, d\dot{m} \quad (4.5)$$

where the integration is carried out over the data obtained across one blade pitch.

Pressure loss calculations are done using the data obtained from traverses performed at 40% axial-chord downstream of the trailing edge plane. In order to have loss values which are independent of the location of the measurement plane the loss value is adjusted to include mixing losses which take place downstream of the measurement plane. The mixed out, mass averaged total pressure loss coefficient, Y , has been

shown to be constant regardless of measurement plane by Goobie (1989). $\bar{Y}$ is made up of the mass averaged loss and the mixing loss, as shown below:

$$\bar{Y} = \frac{1}{\dot{m}} \int_0^s Y \, d\dot{m} + 1 - \frac{2 \int_0^s V_x^2 \, d(y/s)}{\left(\int_0^s V_x \, d(y/s) \right)^2} + \frac{\int_0^s V_x^3 \, d(y/s)}{\left(\int_0^s V_x \, d(y/s) \right)^3} \quad (4.6)$$

where mixing out to uniform conditions is assumed to occur at constant area.

4.2 Wind-tunnel and cascade test section

The cascade test section, shown in Figure 4.1, was designed by Goobie (1989). It has been used extensively to study off-design losses in turbines by Goobie (1989), Tremblay (1989), Rodger (1992) and Whitehouse (1993).

Uniform inlet flow and periodic outlet flow is established by adjusting the side flaps and tailboards. The periodicity is verified by examining the mid-span velocity at 41% of axial chord downstream of the blade's trailing edges.

The endplates allow the developed boundary layers on the test section walls to pass outside the test area of the cascade, reducing secondary flows and increasing the region of two dimensional flow. The endplates were modified and are discussed by Rodger (1992). They extend one axial chord upstream and downstream of the blade. The position of the endplates can be adjusted to control convergence or divergence of flow through the blade passage and thus set the axial velocity ratio to 1.0.

Figure 4.1 Schematic of Variable Incidence Cascade Test Section (figure from Rodger, (1992))

The blade geometry corresponds to the mid-span section of a modern power turbine. It has a nominal flow turning of 83 degrees and fairly uniform blade loading at design incidence. Figure 4.2 shows the cascade and blade geometry. As explained in Section 4.3, the blade is referred to as CC3 (Carleton Cascade 3) to differentiate it from other cascade blades in use at Carleton University.

The present study required the pressure probe, at the exit plane, to be positioned at several span-wise locations. At the time of the study, an automatic traverse mechanism, for this direction of motion, was not available. In order to move the probe in known and repeatable amounts brass spacers were used. The spacers were made 5 mm and 1 mm ± 0.001 thick. These spacers were placed on the holding rod of the probe outside the test section as shown in Figure 4.3.

Wind-tunnel number 2, shown in Figure 4.4, provided the air supply. This tunnel was previously used by Whitehouse (1993) and Rodger (1992) and is described in detail in the latter reference. The tunnel provides a maximum velocity of about 30 m/s (Mach 0.09) at the cascade inlet. The turbulence intensity is about 0.3%. Measurements were made at a Reynolds number of 3.0×10^5 based on inlet velocity and full blade chord.

A turbulence grid was designed and installed by Abbott (1993). This grid fits between the tunnel exit and the test section. It raises the turbulence intensity to 2 to 3%. The grid was installed to raise the turbulence intensity in the tunnel to a level closer to that produced by wind-tunnel Number 1, used extensively by Yaras (1990), and others. The purpose of this was to be able to compare data from the two tunnels more easily. A higher turbulence level would also provide conditions closer to that of an actual turbine. However, after the measurements presented here were made, this grid was found to adversely affect flow uniformity. This is discussed in detail in Section 5.1.

Inlet metal angle, β_{in}	25.51°	Pitch length (spacing), S	110.71 mm
Exit metal angle, β_{ex}	57.51°	Full blade span, h	200 mm
Inlet flow angle, α_{in}	28.35°	Design incidence, i_{des}	3.00°
Exit flow angle, α_{ex}	57.65°	Design deviation, δ_{des}	-0.145°
Stagger angle, γ	21.6°	Pitch to cord ratio, S/C	0.68
Chord length, C	162.3 mm	Aspect ratio (AR), h/C	1.23
Axial Chord length, C_x	149.4 mm	Maximum thickness to chord t_{max}/C	0.196
Leading edge diameter	16.7 mm	Trailing edge thickness	31.8 mm
Throat opening, σ	63.6 mm	Camber angle, θ	82.86°
Effective blade span, H	145 mm	Effective aspect ratio, H/C	.89

Figure 4.2 Cascade Geometry and Measurement Plane Nomenclature (adapted from Rodger (1992))

- A ROD
- B SET SCREWS
- C COLLAR
- D 1 mm SPACERS
- E 5 mm SPACERS
- F SET SCREW
- G VERTICAL TRAVERSE MECHANISM
- H SIDE VIEW OF SPACERS
- I TUNNEL WALL
- J PRESSURE PROBE

Figure 4.3 Probe Span-Wise Position Control

Figure 4.4 Schematic of Wind-tunnel #2 (figure from Rodger, (1992))

4.3 Model blade production

In order to examine the effect of damage on turbine blades it was necessary to have cascade blades to damage. Since the aluminum blades being used in the cascade wind-tunnels were expensive to machine it was not desirable to damage them. It was decided that casting blades from a machinable material would provide relatively inexpensive blades. The method used produces blades at approximately one fifth of the cost of having them machined, but is more labour intensive.

Various materials and methods were considered for making the moulds and casting the blades. The moulding material, used for making the mould box, is a quick setting, room temperature curing urethane rubber. It is a two component compound which cures a few minutes after the components are mixed. The casting material, used for making the blades, is a two component epoxy mixed with steel filings. These materials which were previously used by Sjolander (1975) were selected because they do not shrink or expand while setting and the casting material is machinable. The moulding material can be machined slowly if desired. The materials are identified more specifically in Appendix B.

There are three cascades in use at Carleton University. Cascade 1 (CC1) corresponds to the tip section of a modern turbine blade and it has been used extensively for tip-loss studies by Yaras (1990) and others. Cascade 2 (CC2) corresponds to the midspan section of a modern turbine. Cascade 3 (CC3) is similar to CC2 but has a modified leading edge radius and it was used by Whitehouse (1993). Several blades were cast from the mould created using a CC3 blade as the master and one blade from the mould created using CC1.

Figure 4.5 is a photograph of blade CC3 with simulated damage. The threaded rods on the right side are used for mounting the blade to the back-plate and are referred to as mounting rods. The two location pins (only one can be seen) are used to correctly

Figure 4.5 Blade CC3 with Simulated Damage

align the blade. Foam at each end creates a tight seal between the blade and the tunnel walls.

4.3.1 The mould boxes

Two mould boxes were designed, one for blade CC3 and one for blade CC1. They were designed to have as many common dimensions as possible. This allowed a savings in manufacturing set up costs, by having them made at the same time. Figures 4.6 and 4.7 show the outside and inside of the box made for blade CC3. Appendix E contains the drawings from which the boxes were manufactured. A pour hole and air release hole were added to each box after the mould from the original blade was cast.

Modifications to the box were made, after a couple of blades were cast, in order to correct problems encountered. Extra air holes were added to allow release of trapped air pockets. Two holes were drilled and tapped into the bottom half of the mould, in order to use set screws to push the blade out. The original intent was to use the mounting rods (see Figure 4.5) to pull the blade out. Due to the tight fit and position of the mounting rods this method was slow and resulted in damage to the blade. The use of the set screws is quick, effective and can be performed by one person. The addition of threaded holes to the top of the box, so that screws could be used to force the two halves apart would further simplify the de-moulding procedure.

A C clamp is used to hold the box together at the centre, preventing casting material from leaking out the bottom and between the mould halves.

- A Box Top
- B Box Bottom
- C Air holes
- D Blade mounting rods
- E Pour hole
- F Nuts and Bolts (hold box closed)
- G Alignment Pins
- H Set screw holes (for releasing blade)

Figure 4.6 Mould Box, external view

Figure 4.7 Mould Box, Internal View

2

PM-1 3½"x4" PHOTOGRAPHIC MICROCOPY TARGET
NBS 1010a ANSI/ISO #2 EQUIVALENT

PRECISIONSM RESOLUTION TARGETS

4.3.2 Making the mould

The mould was made in two steps. The suction side of the blade was cast in the bottom half of the mould box first, then the top was placed on the box and the pressure side was cast.

The main problem encountered in this process occurred in pouring the first half (suction side) of the blade. Air bubbles rose in the moulding material and were trapped under the blade and at the mould surface around the blade. This resulted in depressions in the mould on the suction side of the blade. There was no problem with air bubbles in the top half, since bubbles rose away from the blade. The blades cast in this mould box require sanding to remove the bumps on their suction side, which result from the depressions in the mould. As a result, the surface finish of the cast blades may be slightly inferior to that of the aluminum master blade. Therefore the cast blades may also be expected to have slightly higher profile losses.

When making the mould box for blade CC1 an attempt was made to prevent the problem encountered in moulding blade CC3. A hot air blower was used to try to speed up the release of the bubbles so that they would be released before the rubber hardened. Although this helped reduce the amount and size of trapped air bubbles it created another problem. Blade CC1 is made of acrylic and the combined heat of the blower and heat of the exothermic hardening of the rubber was enough to expand the blade causing an imperfect mould of the original.

A detailed description of the moulding procedure is provided in Appendix H. Appendix G provides a list of equipment required for the procedure.

4.3.3 Casting the blades

The procedure for casting the blades is fairly straight forward and described in detail in Appendix H. Appendix G provides a list of equipment required for the procedure. The procedure takes six to eight hours and includes the following steps: cleaning and coating the mould with release agent, inserting mounting rods, preparing the air and pour holes with tubes, mixing and pouring the casting material, drilling out the air holes and removing the new blade from the box. The blade takes approximately 40 hours to harden and also requires finishing.

4.3.4 Finishing the blades

After removal from the mould the blade is sanded to remove bumps. A Dremel tool can be used to remove the sprue. Plastic metal filler (see Appendix G) is used to fill any scratches, damage and holes. Water can be used to facilitate sanding but the blade must be dried thoroughly afterward to prevent rusting of exposed steel filings.

4.3.5 Modifying blades to simulate damage

The first blade cast was used to test the procedure for damaging the blade in a controlled manner. This blade was chosen since it had been previously damaged during de-moulding. As the initial damage, a semicircular cutout - with a diameter of approximately 25 percent of blade chord, located at midspan on the trailing edge - was chosen.

The blade was held at the ends of its span by a clamp during machining. It was placed in the clamp with its suction side up and, near the trailing edge, horizontal. Using a 1.5" diameter end-mill, 0.200" cuts were taken to a depth of 0.750", forming a 1.5" diameter semicircle. Small chipping resulted on the underside of the cut, not

visible during cutting. Blades being cut in the future should have the last cut or two no greater than 0.025" to prevent chipping.

4.3.6 Cascade installation in test section

Blades are mounted in the test section attached to a back-plate which mounts flush in the turntable. Once attached to the back-plate the 5 blades can be removed from the test section as a single unit. The epoxy blades were fit to their own back-plate with each blade having a specific position which cannot be changed. The damaged blade (described in Section 4.3.5) and an undamaged blade were fitted for the centre blade position.

The endplates have blade profile cutouts so they can slide over the ends of the blades. Leakage through the small clearance gap between the endplate and each blade causes three-dimensionality in the blade surface flow. Therefore sealing material must be placed around the blades to seal them to the endplate cutouts. Previously silicone caulking had been used by Whitehouse (1993) for this purpose. It was desired to have reusable sealing that would not need to be reapplied each time the blades were removed from the tunnel. As well, the author and Abbott (1993) were alternating use of the tunnel and Abbott required sealing which does not attach to the blades. Thick foam insulating tape was placed around the cutouts on the outer side of the endplates. Control surface settings (Appendix I) were established to give uniform inlet flow and periodic outlet flow at mid-span, and measurements done at several span-wise positions. The region of uniform flow was found to be much narrower than that obtained by Whitehouse (1993) and Rodger (1993). This was initially attributed solely to inadequate sealing. Later Abbott found it was also due to the turbulence grid (see Sections 4.2 and 5.1). Foam sealing continued to be used to allow the same control surface settings to be used. However, additional silicone caulking was used to improve the seal. Plasticine was also tried, but the silicone was easier to use.

4.4 Procedure and instrumentation

The procedure used to obtain experimental data is the same as that of Whitehouse (1993). It is briefly explained below. For a more in-depth discussion the reader should refer to Whitehouse.

The procedure for performing a traverse is as follows: The probe was placed at the desired location along the span by placing the appropriate number of spacers on the holding rod and fixing the holding rod position. (For the inlet traverses only one location was possible). The pitch-wise probe position was set to the desired traverse starting point and the data motor controller informed of its position. The probe angle was set to 0° for the inlet and 80° for the outlet, since these were close to the flow angles. The angles were set using a levelling protractor. The atmospheric conditions and initial transducer readings were entered into the data acquisition software. The software was given probe positions for the traverse and instructed to begin the traverse procedure. The software displayed the pressure transducer value which corresponded to the correct Reynolds number for the present atmospheric conditions. The blower was started and accelerated until the reading on the transducer matched the required value. The software was instructed to begin the traverse.

For all tests the tunnel was run at a speed which provided a Reynolds number of 3.0×10^5 , using the definition in Section 4.1. The blower speed required to produce this Reynolds number was calculated by the data acquisition software (discussed in Section 4.4.2) after being provided with the current atmospheric pressure and temperature.

Using undamaged cascade blades the inlet flow uniformity was established by adjusting the top and bottom flaps and bypass Number 2. Inlet flow traverses were done at the midspan position only. Outlet flow periodicity was established by adjusting the top and bottom tailboards. An iterative procedure was required to produce flow with both uniform inlet conditions and periodic outlet conditions. The

positions of the endplates were chosen so that the axial velocity ratio, AVR, defined in Section 4.1, was kept at 1.00 ± 0.02 for the undamaged blade at mid-span. The final control surface settings are listed in Appendix I.

Pitch-wise traverses measuring downstream pressure were done at 13 span-wise positions, using the probe described in Section 4.4.1. The stations were chosen 5 mm apart with seven stations through the cutout, one near each edge of it and four outside of it. All tests were done at design incidence. A few repeat traverses were performed at the blade midspan in order to establish the repeatability of the testing. These tests were done after performing some traverses at other span-wise positions. The tests were repeatable which confirmed that the calibration of the three-hole probe was unchanged.

The initial traverses indicated a narrower region of two-dimensional flow than previously obtained. The blades were resealed at the endplates. A few more traverses were performed along the span to establish the change created by the extra sealant.

After completing the measurements of the baseline losses for the undamaged blades, the centre blade was replaced with the damaged blade. Traverses were performed at the same span-wise positions as were performed for the undamaged blade. Additional traverses were performed near the regions of high total pressure loss, $\bar{Y}$. The same control surface settings and endplate positions were used as for the tests with the undamaged blade.

4.4.1 Three-hole probe

The three-hole pressure probe shown in Figure 4.8 was used to obtain total pressure and flow angle at the cascade outlet. A shorter in length, but otherwise identical, probe was used for measurements at the cascade inlet. The probes were calibrated by Whitehouse (1993) prior to this study and the calibration was checked and confirmed

Figure 4.8 Three-hole Pressure Probe Configuration (from Rodger, (1992))

by Abbott (1993) after this study. Previous studies (Yaras (1987)) have shown that the probes provide flow angles which are accurate to better than ± 0.5 degrees and dynamic pressures within ± 1 percent of local dynamic pressure.

4.4.2 Data acquisition

Figure 4.9 shows a schematic of the data acquisition system. This system described below is described in detail by Rodger (1992).

All pressures were obtained using Rosemount capacitive type pressure transducers. The pressures from the three-hole probe (Section 4.4.1) were connected to transducer Number 633 via a scanivalve. The scanivalve, controlled by the data acquisition software, successively switched the port pressures to the single transducer. The pressure was referenced to the upstream static pressure tap.

The total pressure at the reference plane was measured with a pitot tube positioned outside the boundary layer connected to transducer Number 591, which was also referenced to the upstream static pressure tap.

The transducer pressures were converted to digital signals with a Sciometric Instruments A/D convertor model 81/902 Serial Number 9023J/I9006, which was connected to the computer through a serial port. The conversion was performed with 12-bit resolution or 0.024% (1.2 mV/gain). The data acquisition software adjusted the pressure signal for the zero reading (entered prior to starting the traverse) and converted the signal into a pressure value using the transducer calibration factors.

For each pressure reading a 15 second waiting period was performed to allow the pressure to stabilize. This was followed by a 10 second gain check and finally the pressure was sampled for 30 seconds. The waiting and sampling times were established previously by Rodger (1992). The long waiting time was necessary due to

Figure 4.9 Schematic of Data Acquisition System (from Rodger, (1992))

the long length of tubing connecting the probe to the scanivalve and the scanivalve to the pressure transducer. Measurement times were conservative and had been found in the earlier studies to give reliable mean values of the pressures.

The program used for data acquisition and control was written by Whitehouse (1993) and is documented in his thesis. This program controls the motor which moves the three hole probe, obtains the pressure data from the AD converter and reduces the data to usable form. The program also contains a routine to calculate the mixed out, mass-averaged total pressure loss coefficient, $\bar{Y}$ from a traverse.

5.0 Experimental Results

The purpose of the present experiments was to make a preliminary assessment of the effect of blade damage on the flow, in order to determine the requirements for more accurate, extensive testing. The results will be used to establish the span-wise and pitch-wise measurement spacing, type of probe to be used and size of trailing-edge cutout.

Since the epoxy blades had not been used previously, it was necessary to perform span-wise traverses of the downstream flow of undamaged blades in order to determine if the blades produced the same results as the aluminum blades CC3, from which they were cast. The aluminum blades were used by Whitehouse in his 1993 studies. This process would also provide a baseline against which to compare the damaged case.

5.1 Span-wise losses of undamaged blades

Three hole probe measurements were performed downstream of the blades at various span-wise positions. Fully mixed-out loss coefficients were calculated from these measurements. A comparison between these loss coefficients and those obtained by Whitehouse is shown in Figure 5.1. It is clear that the extent of two-dimensional flow, as indicated by the central region of constant loss, is much narrower for these tests than those of Whitehouse. The reduction of the two-dimensional region has been studied by Abbott (1993). He has found that it is caused by the turbulence grid which was mounted at the upstream end of the test section for his and the present

Figure 5.1 Comparison of Span-wise Variation of Mass-averaged Loss Coefficient, Y , To That Found by Whitehouse

measurements. It appears that the wakes from the grid rods are not fully mixed-out by the time the flow reaches the cascade. Thus, future measurements should be made with the grid removed or with a redesigned grid.

Although the flow quality is not good, the midspan loss is very similar to that measured by Whitehouse. This suggests that the epoxy blade does in fact have loss characteristics which are very similar to those of the aluminum master blade. Also, the present measurements do give a valid baseline against which to make a preliminary examination of the effects of damage, provided the latter measurements are made for the same inlet flow conditions.

5.2 Span-wise losses with damaged blades

The span-wise variation of mass-averaged loss coefficients and flow angles, for the damage described in section 4.2.5, are shown in Figures 5.2 and 5.3. The high loss peaks, occurring downstream of the inner edges of the cutout are believed to be caused by vortices generated at the edge of the cutout. These vortices are thought to have a structure as shown in Figure 5.4. The effect of the damage on span-wise loss is similar to that seen in numerical analysis by Isaacs (1993).

It is seen that the two peaks of high loss are not the same magnitude, as would be expected. The peak of greater loss is on the same side of the blade showing a greater loss in the undamaged case. Thus the unsymmetrical behaviour is thought to be partly due to the inlet flow non-uniformity.

More detailed results for a number of span-wise stations are presented in Figures 5.5 and 5.6, which show total pressure loss and flow angles respectively.

Figure 5.5 shows that the local wake changes considerably as one moves from the undamaged portion of the blade through to the centre of the cutout. At the centre of

Figure 5.2 Span-wise Variation of Mass-Averaged Loss Coefficient, Y .

Figure 5.3 Span-wise Variation of Flow Angle Measured Downstream of Centre Blade

Figure 5.4 Vortical Structure Produced by Cutout

Figure 5.5 Comparison of Pressure Coefficient at Various Span-wise Positions

Figure 5.6 Comparison of Flow Angle at Various Span-Wise Positions

the cutout the wake is actually smaller than for the undamaged case. This might be due to the fact that the cutout shortens the length over which the surface boundary layers develop, thus reducing the skin-friction contribution to the profile losses. However, the trailing edge is somewhat thicker in the cutout and this would be expected to increase the trailing edge losses. Evidently the net effect was a small decrease in the overall profile loss. Near the edge of the cutout the wake has a somewhat unexpected double minimum. This is presumably associated with the vortical structure mentioned earlier. The losses in this region are clearly larger than elsewhere and there will be further significant loss production as the vortices mix out with downstream distance.

Figure 5.6 shows the flow angle variations at the same span-wise stations as Figure 5.5. This figure shows that the flow angle distribution has been radically changed by the presence of the cutout. Rather than the fairly constant overall turning, with under and over turning in the pressure and suction side of the wake respectively for the undamaged case, it is seen that almost the entire pitch is under-turned with only the edge of the suction side overturned. This may be partially caused by mixing taking place in the added distance from the edge of the blade, since the measurements were taken at a constant distance downstream of the cascade.

5.3 Recommendations for future experiments

As mentioned, the present measurements were intended mainly to provide guidance for the future more detailed study of trailing edge damage. A number of recommendations are therefore given here.

Future experiments in this area should be done using an established region of two-dimensional flow which is larger than the cutout, ideally large enough to be beyond the region of reduced pressure loss which occurs outside the cutout. In order to clearly define the region of minimum and maximum loss near the edge of the

cutout, span-wise measurements should be taken quite close together in that region. Steps of 2 to 3% of the cutout diameter would be appropriate. The rest of the span is adequately defined by steps of approximately 10% cutout diameter.

Because the flow structures generated by the cutout are believed to be three dimensional, a three-dimensional pressure probe, such as a four-, five- or seven-hole probe should be used to establish the pitch (span-wise) angles present in the flow. If these are found to be reasonably small (say, less than 10 degrees) the measurements can be continued with the three-hole probe.

During the present experiments the probe angle was set using a levelling protractor placed manually on the probe when locating the probe. It was necessary to reset the probe angle after changing the span-wise position of the probe. The usual practice is of using a traverse gear for motion in the span-wise direction would greatly improve the quality of the data, since it would not be necessary to move the probe.

A study using three blades with cutouts might make it possible to establish periodic flow for the damaged case or investigate the interaction of adjacent blades with similar damage.

The blades developed a rough surface during the course of the undamaged study. This was caused by rusting of the steel component of the epoxy-steel composite blades. The blades rusted only in the areas where they had been sanded and this was accelerated by high humidity in the laboratory. Although it was easily removed with emery cloth, the profile of the blades will be affected by repeated abrasion. Some method of sealing the blade surface should be considered.

6.0 Conclusions and Recommendations

6.1 Conclusions

The first part of this thesis examined the ability of the streamline curvature method to simulate the performance of a turbine with damaged blades. The second part was the initiation of an experimental study of cascade blades with simulated damage.

A streamline curvature program was restored and a method of calculating the tip loss coefficients as a concentrated loss was added. Using data for a low pressure and a high pressure turbine, simulations with and without concentrated tip loss were compared for design tip clearances and increased tip clearance (which simulated tip damage). The conclusions made are summarized as follows:

- i. Overall turbine performance is very similar for both methods of calculating the tip loss given design tip clearances.
- ii. The difference in overall performance calculated by the two methods increases with increasing tip clearances.
- iii. The change in stage performance, for a given change in tip clearance (simulating tip damage), is less using the concentrated tip loss method than using the distributed tip loss method. Therefore if the program is to be used for the prediction of tip damage, then, based on a measured change in stage

performance, the concentrated tip loss method provides the more conservative choice.

- iv. Changes in local parameters such as rotor outlet temperature at hub and tip are more significantly affected by the tip clearance changes. Therefore, they may be more useful than the overall performance parameters in diagnosing the specific type of damage which is occurring in a stage.

Cascade blades were cast out of an epoxy steel compound and cascade tests were done for the undamaged blade to establish a baseline case. Subsequently, pitch-wise tests were performed at 15 span-wise positions using a centre blade with simulated damage. The damage was a semicircular cutout, with a diameter of 25% of the blade chord, at the mid-span of its trailing edge. The conclusions made are summarized as follows:

- i. Casting blades provides a less expensive and very satisfactory method of producing cascade blades.
- ii. The cast blades have loss characteristics similar to those of the aluminum master blade.
- iii. The span-wise variation of pressure loss, for the damaged blade, has peaks of very high loss downstream of the inner edges of the cutout. These are believed to be caused by vortices generated at the edges of the cutout.
- iv. The downstream losses at the centre of the cutout are less than those for the undamaged blade. This suggests that at this position the reduction in profile losses due to the shorter blade length is greater than the increased trailing edge losses due to the thicker trailing edge thickness.
- v. The flow angle downstream of the cutout is mostly under-turned at all span-wise stations. This is different from the undamaged case where the flow

angles are fairly constant with under- and over-turning in the pressure and suction side of the wake respectively.

6.2 Recommendations

In order to use the streamline curvature method to simulate performance of modern turbines it is recommended that a new streamline curvature program be written. Specifically, this program should incorporate the following features:

- i. Management of choked and coolant flows and incorporation of span-wise mixing (simulated viscosity) in the duct regions.
- ii. Use of recent loss correlation methods such as Kacker and Okapuu (1990) for the design point losses and a combination of Moustapha et al. (1990) and Yaras and Sjolander (1990) for the off design losses.

An improved streamline curvature program with the above-mentioned features is recommended for use in simulating a variety of types of blade damage, such as leading and trailing edge damage and surface roughness.

Some recommendations for the study of cascade blades with trailing edge damage are as follows:

- i. A two-dimensional region of flow which is wider than the cutout should be established. This will require further investigation into the problems attributed to the turbulence grid.
- ii. Approximately 12 span-wise measurements should be taken at intervals of 10 to 15% of the cutout diameter. In order to adequately define the maximum

and minimum pressure loss in the vortex area, additional measurements at approximately 3% of the cutout diameter should be performed in these regions. Therefore about 28 span-wise stations would be required to define the losses in the region affected by the cutout.

- iii. Testing with a three-dimensional pressure probe should be performed to determine if the pitch angles present in the flow are small enough to allow effective use of a two-dimensional probe.
- iv. A study using three blades with cutouts might make it possible to establish periodic flow for the damaged case or investigate the interaction of adjacent blades with similar damage.

References

Abbott, M.	1993	Master of Engineering Thesis, ("In Preparation"), Department of Mechanical and Aerospace Engineering, Carleton University, Ottawa, 1993.
Ainley, D.G.	1951	"A Method of Performance Estimation for Axial-Flow Turbines", Aeronautical Research Council of Great Britain, Reports and Memoranda No. 2974, December, 1951.
Mathieson, G.C.R.		
Cohen, H.	1987	<i>Gas Turbine Theory, 3rd edition</i>, Longman Scientific & Technical imprint, New York, 1987.
Rogers, G.F.C.		
Saravanamuttoo, H.I.H.		
Cue, R.W.	1991	"Engine Performance Monitoring and Troubleshooting Techniques for the CF-18 Aircraft," Transactions of the ASME, Journal of Engineering for Power, January 1991, Vol. 113, pp. 11-19.
Muir, D.E.		
Davis, W. R.	1971	"A Computer Program For The Analysis and Design of Turbomachinery - Revision", Division of Aerothermodynamics, Carleton University, Report No. ME/A 71-5, September 1971.

- Davis, W. R. 1975 "A Comparison of the Matrix and Streamline Curvature Methods of Axial Flow Turbomachinery Analysis, From a User's Point of View," Transactions of the ASME, Journal of Engineering for Power, October 1975. pp. 549-560.
- DeCook, S.J. 1993 "Wake Mixing and Performance of a Compressor Cascade with Crenulated Trailing Edges," AIAA, Journal of Propulsion and Power, Vol.9, No.2, March-April 1993, pp. 293-300.
- King, P.I.
Elrod, W.C.
- Dixon, S.L. 1984 *Fluid Mechanics, Thermodynamics of Turbomachinery, 3rd edition*, Pergamon Press, Oxford, 1984.
- Dunham, J. 1970 "Improvements to the Ainley-Mathieson Method of Turbine Performance Prediction", Transactions of the ASME, Journal of Engineering for Power, July 1970, pp. 252-256.
- Came. P.M.
- Goobie, S.M. 1989 "A Test Section for Investigating the Off-Design Performance of a Planar Cascade", Master of Engineering thesis, Carleton University, Ottawa, 1989.
- Isaacs, D. 1993 "Aerodynamics of Turbine Blades with Trailing-Edge Damage: Measurements and Computations", Master of Engineering thesis, ("In Preparation"), Department of Mechanical and Aerospace Engineering, Carleton University.

- Kacker, S.C. 1982 "A Mean Line Prediction Method for Axial Flow
Okapuu, U. Turbine Efficiency", ASME Journal of
Engineering for Power, January 1982, Vol. 104,
p.111.
- Mathioudakis, K. 1991 "Fast Response Wall Pressure Measurement as a
Papathanasiou, A. Means of Gas Turbine Blade Fault Identification",
Loukis, E. Transactions of the ASME, Journal of
Papailiou, K. Engineering for Gas Turbines and Power, April
1991, Vol. 113, No. 2, pp.269-275.
- Mattheij, J.H.G. 1985 "Role of Brazing in Repair of Superalloy
Components - Advantages and Limitations", The
Institute of Metals, Materials Science and
Technology, Vol.1, No.8, August 1985,
pp. 608-612.
- Muir, D.E. 1988 "CF-18 Engine Performance Monitoring",
Rudnitski, D.M. AGARD Conference Proceedings, "Engine
Cue, R.W. Condition Monitoring - Technology and
Experience", Paper No.7, AGARD-CP-448.
- Ngo, V.H. 1973 "The Design and Performance Prediction of Axial
Millar,D.A.J. Flow Turbines", Department of Mechanical and
Aeronautical Engineering, Carleton University,
Report No. ME 73-3, June 1973
- Novak, R.A. 1967 "Streamline Curvature Computing Procedures for
Fluid-Flow Problems", Transactions of the
ASME, Journal of Engineering for Power,
October 1967. Pages 478 to 490.

Rodger, P.	1992	"Establishing Two-Dimensional Flow in a Large-Scale Planar Turbine Cascade", Master of Engineering Thesis, Department of Mechanical and Aerospace Engineering, Carleton University, Ottawa, 1992.
Schofield, C.	1988	"Canadian Forces Aircraft Engine Condition/Health Monitoring - Policy, Plans and Experience", AGARD Conference Proceedings,
La Grandeur, R.		"Engine Condition Monitoring - Technology and Experience", Paper No.7, AGARD-CP-448.
Dubé, F.		
Harris, T.		
Cue, R.		
LeBlanc, A.		
Sjolander, S.A.	1975	"The Endwall Boundary Layer in an Annular Cascade of Turbine Nozzle Guide Vanes", Master of Engineering Thesis, Department of Mechanical and Aeronautical Engineering, Carleton University, Ottawa, 1975.
Tremblay, B.	1989	"Measurement and Correlation of Off-Design Performance of Axial-Flow Turbines", Master of Engineering Thesis, Carleton University, December 1989.
Veesart, J.L.	1990	"Wake Mixing Improvements in a Linear Compressor Cascade with Crenulated Trailing Edges," American Society for Mechanical Engineers Paper, 90-GT-218, Brussels, Belgium, June 1990.
King, P.I.		
Elrod, W.C.		
Wennerstrom, A.J.		
Verhiel, J.	1993	Master of Engineering Thesis, ("In Preparation"), Department of Mechanical and Aerospace Engineering, Carleton University, Ottawa, 1993.

Whitehouse, D.	1993	"The Effect of Axial Velocity Ratio, Turbulence Intensity, Incidence and Leading Edge Geometry on the Midspan Performance of a Turbine Cascade", Masters of Engineering Thesis, Department of Mechanical and Aerospace Engineering, Carleton University, Ottawa, 1993.
Yaras, M.I.	1991	Private communication, Data obtained during 1987 study but not presented in thesis.
Yaras, M.I.	1987	"Flow in the Tip Gap of a Rectilinear Turbine Cascade," Masters of Engineering Thesis, Department of Mechanical and Aerospace Engineering, Carleton University, Ottawa, 1987.
Yaras, M.I.
Sjolander, S.A.	1992	"Prediction of Tip-Leakage Losses in Axial Turbines", Transactions of the ASME, Journal of Turbomachinery, Vol. 114, January 1992, pp. 204-210.
Yaras, M.I.
Sjolander, S.A.	1989	"Losses in the Tip-Leakage Flow of a Planar Cascade of Turbine Blades", AGARD Specialists Meeting "Secondary flows in Turbomachines." Luxembourg, August 1989. AGARD-CP-469, Paper No.20.

Appendix A

Documentation for Streamline Curvature Program

This appendix contains the streamline curvature program documentation which was generated during the debugging and enhancing of the program, discussed in section 3.1. It is not intended to be complete documentation.

Contents	Page
Table A-1, Summary of principal program subroutine	A-2
Table A-2, Subroutines and the common blocks which they use	A-3
Units and fundamental equations	A-4
Figure A-1, Streamline grid terminology	A-6
Variable list	A-7
New subroutines	A-18
changes to original program	A-18
Discussion of program convergence	A-19
Errors in program	A-20

INNER LOOP	
RVELM	solves equation 9 or 10 (Ngo and Millar, (1973)) for the radial distribution of the meridonal velocity. meridional velocity distibution is checked and recalculated to satisfy mass flow rate or continuity at each station.
TLINK	relates P_o, T_o, V_o
PRLOSS	Calculates design loss coefficients (used for design mode)
CASCAD	Calculates off-design loss coefficients (used for analysis mode)
OUTER LOOP	
REPOS	Reposition the streamlines based on newly computed velocity distribution Check convergence of streamline position shift
BLCAL	Calculate the end-wall boundary layer
RCURV	Calculates the new streamline curvatures and slopes (Note: program only works for curvatures set to 0)

Table A-1 Summary of principal program subroutines

	Common Block Number													
Subroutine		1	2	3	4	5	6	7	8	9	10	11	12	21 new
MAIN		X	X	X	X	X	X							
INPUT		X	X	X	X		X							
CURFIT														
RCURV		X	X	X	X								X	
SPLINE														
RVELM		X	X	X	X						X		X	
TLINK		X	X	X	X	X	X	X	X					X
PROSS								X						
CASCAD						X								
WRITE		X	X	X	X		X		X		X			
REPOS		X	X	X	X						X		X	
BLCAL		X	X	X	X									
new subroutines														
TIPDAT					X									X
TIPLOS		X		X	X	X	X				X			X
TIPORV						X								X

Table A-2 Subroutines and the common blocks which they use

Units and fundamental equations**Units**

m	mass	lbm
a	acceleration	ft/s ²
F	force	lbf
V	volume	ft ³ /lbm
ρ	density	lbm/ft ³
P	pressure	lbf/ft ²
T	temperature	K
a	sonic velocity	
h	enthalpy	Btu/lbm
v	velocity	ft/s
M	Mach number	
C_p	specific heat, constant pressure	Btu/(lbm R)
g	gravitational acceleration	ft/s ²
g_c	conversion factor	32.174 $\frac{\text{lbm} \cdot \text{ft}}{\text{lbf} \cdot \text{s}^2}$
J	conversion factor	778.16 $\frac{\text{ft} \cdot \text{lbf}}{\text{Btu}}$
A	conversion factor	$\frac{9}{5} \frac{R}{K}$
R	gas constant	$\frac{\text{Btu}}{\text{lbm} \cdot R} \left(\frac{\text{ft} \cdot \text{lbf}}{\text{Btu}} \cdot \frac{R}{K} \right)$ $\frac{\text{ft} \cdot \text{lbf}}{\text{lbm} \cdot K}$

Some Fundamental Equations

$$F = \frac{m a}{g_c}$$

$$\Delta P = \rho L \frac{g}{g_c}$$

$$h_o = h + \frac{v^2}{2(g_c J)}$$

$$T_o = T + \frac{v^2}{2C_p (g_c A J)}$$

$$C_v = C_p - \frac{R}{AJ}$$

$$a = \sqrt{\gamma g_c R T}$$

$$M = \frac{v}{a}$$

$$\gamma = \frac{C_p}{C_v}$$

$$\frac{\gamma - 1}{\gamma} = \frac{R}{C_p AJ}$$

$$\rho = \frac{P}{R T}$$

Figure A-1 Streamline Grid Terminology (adapted from Davis (1971))

Variable List

Following is a list of variable names used in the program and an indication of which subroutine contains the variable. A short description of some of the variables is also given. In order to reduce the length of the document some abbreviations have been created and used. They are described below. If units are not specified they can be assumed to conform to the units listed earlier in this section.

CB1-indicates the variable is located in common block CB1

CB2- " CB2

CBx- " CBx

where x indicates the common block number

INP "prog"- indicates an input variable that is read in by the program in quotes

real-real number

int-integer value

inp-input

convt-converted to

1	A2	(BLCAL)(real)
2	A2	(RVELM)(real) sonic velocity squared
3	A2	(TLINK)outlet sonic velocity
4	ABL	(BLCAL)(real)
5	ABLH	(BLCAL)(real)
6	ABLT	(BLCAL)(real)
7	ABORT	(CB3)
8	ACIN	(CB5)
9	AD	(RINPUT)(real)
10	AINL (NSTAT+1,NGRID)	(CB8)
11	AJ	(CB4)(inp RINPUT) conversion factor,1400.79 ft-lbf-R/btu-K if temperature is input in Kelvin (or 778.2 ft-lbf/Btu if temperature is input in Rankine).(778.2 ft-lbf/Btu x 9/5 R/K)
12	AL	(BLCAL)(real)
13	ALN (NSTAT)	(CB1) Annulus width measured along the quasi-normal (R-r)
14	ALP (ngrid)	(CB2)Beta2*pv/180*((1. stator or duct) or (-1 rotor)); air angle (greek letter) beta
15	AM	(RINPUT)(real)
16	AM (ngrid)	(TLINK)inlet relative mach number (relative to blade speed)
17	AM2	(RVELM)(real) mass flow
18	AMA	AMA-mach number
19	AMA (nstat)	(BLCAL)(real)
20	AMA2	(BLCAL)(real)
21	AMAB	(BLCAL)(real)

22	AMAV	(BLCAL)(real)
23	AMCAL (nstat)	(CB10)=AM2 ,used to print mass flow (RVELM,WR calculated total mass flow through station
24	AMI (nstat)	(BLCAL)(real)
25	AMO (nstat)	(BLCAL)(real)
26	AMOLD	(RVELM)(real)
27	ANU (30)	(BLCAL)(real)
28	ANU (NGRID)	(TLINK) ?kinematic viscosity
29	AO2	(BLCAL)(real)
30	APL (NSTAT+1,NGRID)	(CB8)
31	AR	(CB7)(INP TLINK)(real),blade aspect ratio-blade span/chord length
32	ARA (NSTAT)	(CB1)
33	ARAD	(RINPUT)(real)
34	AREA (NSTAT)	(CB1)
35	ASL (NSTAT+1,NGRID)	(CB8)
36	AVH	(inp RINT)(btu/lbm)average work done=1.0 for analysis mode
37	AVH	(RINPUT)(real)
38	AWT	(TLINK)tangential velocity relative to blade speed
39	B1 (ngrid)	(TLINK)beta1, inlet relative gas angle (inlet to station in question)
40	BDHT	(CB5)(TLINK)(inches) blade height from average hub and tip across the station (assumes straight edged hub and tip)
41	BET1	(CB5)
42	BETA1	(CB7)(TLINK)=B1(ngrid) inlet relative gas angle
43	BETA2	(CB7)(TLI relative gas angle
44	BLCK (NSTAT)	(CB1)(inp RINPUT)blockage factor Kb
45	BTI (nstat)	(BLCAL)(real)
46	C1	(BLCAL)(real)
47	C2	(BLCAL)(real)
48	C3	(BLCAL)(real)
49	C4	(BLCAL)(real)
50	C5	(BLCAL)(real)
51	CARL (NSTAT+1,NGRID)	(CB8)
52	CFAL (ngrid+1)	(CB2) Curve fitted entry flow angle
53	CFPO (ngrid+1)	(CB2) Curve fitted inlet stagnation pressure
54	CFRE	(TLINK) (related to reynolds # see tlink)
55	CFTO (ngrid+1)	(CB2) Curve fitted inlet stagnation temperature
56	CFVT (ngrid+1)	(CB2) Curve fitted entry flow tangential velocity
57	CHB (NSTAT)	(inp RCURV)(1/ft)curvature at hub (read only for NRDIM=1,read in slopes and curvatures)
58	COFD (12)	(RINPUT)(real)

59	COFF (12)	(RINPUT)(real)
60	COFT (12)	(RINPUT)(real)
61	CON1	(BLCAL)(real)
62	CON1	(RVELM)(real) $1/(gamma-1)$
63	CON2	(RVELM)(real) $Gc * AJ * Cp$
64	CORD	(TLINK) chord in direction of meridional velocity
65	CP	(CB4)(inp RINPUT)0.2405 Btu/lbm-R, Specific heat constant pressure, must be input in Btu/lbm-R
66	CTP (NSTAT)	(inp RCURV)(1/R)curvature at tip (read only for NRDKM=1;read in slopes and curvatures)
67	CV	(RINPUT)(Btu/lbm-R) specific heat at constant volume
68	D2	(RVELM)(real)
69	D3	(BLCAL)(real)
70	D4	(BLCAL)(real)
71	DEF (NSTAT+1,NGRID)	(CB6)
72	DEG	PI/180.0
73	DELN (NSTAT,NGRID)	(CB1)(rcu Non-Dimensional distance from hub to grid point; distance along the quasi-normal, from the hub, normalized with respect to ALN
74	DELPO (NSTAT,NGRID)	(CB2)(inp TLINK)(real)pressure loss coefficient (Y)
75	DELR	(BLCAL)(real)
76	DELR	(RINPUT)(R) radius at shroud minus radius at hub,length of calculation plane perpendicular to axis.(DELTA R)
77	DELT (NSTAT,J)	DELT (NSTAT,J)-(CB1) ?boundary layer displacement thickness?
78	DELZ	(BLCAL)(real)
79	DELZ	(RINPUT)(length in axial direction of calculation plane.(DELTA Z)
80	DEQF (22,10)	(CB6)blade loading (=WV=Z)
81	DEQM (KB,ngnd)	(CB6)Profile loss at zero incidence (Yp (mu)
82	DER1	(RVELM)(real)
83	DER2	(RVELM)(real)
84	DESM	(CB4)(inp RINT)(lbm/s)desired mass flow rate
85	DEV	(CB5)
86	DEVM (KB,NGRID)	(CB6)Profile loss at zero incidence (YPIN)
87	DFAC (22,10)	(CB6)Tip clearance loss (=YK)
88	DH1	(BLCAL)(real)
89	DH2	(BLCAL)(real)
90	DHDS	(RVELM)(real)? rate of change of rothalpy with quasi-normal (s)
91	DHO	(inp TLINK)(Btu/lbm)delta ho, read for design case
92	DI (22,10)	(CB6)Stalling incidence angle (=SI)
93	DISP (nstat)	(BLCAL)(real)
94	DISP2	(BLCAL)(real)
95	DISP3	(BLCAL)(real)

96	DISPO (KS)	(BLCAL)(real) DISPO(1)=DM1/RH(1) , DISPO(2)=DM1/RT(1); ?Initial momentum thickness
97	DL (22,10)	(CB6)secondary loss (=YS) (Ys)
98	DM1	(BLCAL)(real)
99	DM1	(RINPUT)(real)
100	DM1	(TLINK)2*
101	DM2	(RINPUT)(real)
102	DM2	(TLINK)GAMA/(GAMA-1)
103	DM3	(RINPUT)(real)
104	DM3	(TLINK) 2*gamma*Go*Rgas*inlet stagnation temperature relative to blade row
105	DM4	(RINPUT)(real)
106	DM4	(TLINK) (gamma-1)* (blade speed (ft/s) at grid #) ^2
107	DM5	(TLINK)1/(gamma-1)
108	DN (NSTAT,NGRID+1)	(CB1) (real) streamtube width normalized with respect to ALEN, (ds), (change in quasi-normal direction)
109	DN1	(RVELM)(real)
110	DN2	(RVELM)(real)
111	DPV	(BLCAL)(real)
112	DQDS	(RVELM)(real)
113	DQDS	(RVELM)(real) rate of change of entropy change(Q(ngrid)) with quasi-normal(s)(DN)
114	DR	(RVELM)(real)
115	DR1	(RINPUT)(real)
116	DR2	(RINPUT)(real)
117	DRH	(BLCAL)(real)
118	DRT	(BLCAL)(real)
119	DSM (NSTAT,J)	(CB1)?distance measured along a streamline from the 1st station to the streamline considered
120	DSPA	(BLCAL)(real)
121	DSPT (NSTAT,J)	(CB1)?boundary layer momentum thickness (theta) at the hub and shroud
122	DUM1	(CB5)
123	DUMH (agrid)	(CB2)(link) enthalpy of something (see link for equation) ? rothalpy?(dummy variable containing either Hr or H depending on the type of station
124	DUMV	(RINPUT)(real)
125	DUMY	(BLCAL)(real)
126	DVDM	(BLCAL)(real)
127	DVDS	(RVELM)(real) rate of change of tangent beta with quasi-normal (di tan(beta)/ di s)
128	DVTN	(RVELM)(real)
129	DX	(RVELM)(real)
130	DX (NSTAT)	(BLCAL)(real)
131	DX1	(RVELM)(real)
132	DX2	(RVELM)(real)

133	DZH	(BLCAL)(real)
134	DZT	(BLCAL)(real)
135	E3	(RVELM)(real)
136	EFX	(CB7)fluid deflection angle ($\alpha_1 + \alpha_2 = \epsilon$)
137	ET1	(CB5) -R(NST,J)
138	ET2	(CB5) R(NST+1,J)
139	ETA	(BLCAL)(real)
140	EX	(TLINK) exponent for calculation of CFRE from REYN
141	F1	(RVELM)(real)
142	F2	(RVELM)(real)
143	F3	(RVELM)(real)
144	FACL (NSTAT+1,NGRID)	(CB8)
145	FLA (ngrid)	(degrees)flow angle
146	FLD (ngrid)	(degrees)flow angle relative to downstream row
147	FLU (ngrid)	(degrees)flow angle relative to upstream row
148	FMN (NSTAT,J)	(CB1)
149	GAMA	(CB4);=GM:ratio of specific heats (C_p/C_v)
150	GEOM (KB,1,K)	(inp TLINK)read for analysis case (inches or ratio)
151	GM	(CB5)(TLINK)=gamma: ratio of specific heats (C_p/C_v)
152	GMI	(CB7)(TLINK)=GM=GAMA
153	GO	(CB4)(set in main) 32.179 ft/s ² or lbf/(lbf s ²)gravitational acceleration of constant
154	H	(BLCAL)(real)
155	HO	(CB4)(RINPUT)
156	HT	(RVELM)(real)
157	I	(BLCAL)(int) for looping through stations (index for items dimensioned on nstat)
158	IRD	(CB4)
159	IT	(RVELM)(int) iteration counter (rvelm iterates to find meridional velocity dist. to satisfy mass flow rate or continuity)
160	ITR	(BLCAL)(int)
161	IWT	(CB4)
162	JS	(BLCAL)(int)
163	KAL	(CB3)
164	KAP1	(CB5)(TLINK)(real) α_1 , inlet metal angle
165	KAP2	(CB5)(TLINK)(real) $\arcsin(o/s)$; used for α_2 , outlet metal angle
166	KB	(CB6)(inp TLINK)(int)Blade row number =KBST(NST)
167	KBBL	(CB5) =KBL (0 for first iteration, 1 for all other iteration for stream line convergence)
168	KBL	(CB3) 0 for first iteration, 1 for all other iterations for streamline convergence.
169	KBLAD(KB)	(CB6)(inp at)(TLINK)(int) Blade type 1-65 series, 2-c series, 3-D.C.A

170	KBST(NST)	(CB6)(int) BLADE ROW # at nst station
171	KDB	(RVELM)(int)
172	KDB	(RVELM)(int)location of last station = NTYPE(nst-1)
173	KDE	(CB7)(TLINK)(int)=KODE
174	KLOSS	(CB7)(inp RINPUT)(int)design loss correlation, read only for design mode,0-input losses,1-Ainley and Mathieson,2-Soderberg's,3-A F.Carter's
175	KNEG	(RVELM)(int)
176	KOD	(CB5)(CASCAD)(int)=KODE
177	KODE	(CB3)(int)code to indicate location of calculation plane;=NTYPE(NST),1-entrance to rotor,2-entrance to stator,3-entrance to duct
178	KS	(BLCAL)(int)
179	KSER	(CB5)(TLINK)=KBLAD(KB) blade type (1 -65 series,2 -c series,3 -D C A)
180	KVT	(CB3)(inp RINPUT)(int) 1 for tangential velocity (VO) specified at inlet, 0 if angle is specified
181	MDF	(RVELM)(int)
182	MTHOD (NSTAT)	(CB1)
183	NCTR	(inp RINPUT)(int)code,1-rotational speed(rad/s) of each row is to be read in
184	NCTR	(RINPUT)(int)
185	NFBL	(CB3)(inp RINPUT)(int)boundary layer calculation flag,0-blockage factors used,1-Jansen method,2-Stratford method
186	NFDES	(CB3)(inp RINPUT)(int) 0-for design mode,1-for analysis mode
187	NG	(RVELM)(int) = NGRID
188	NGR	(CB5)
189	NGR	(TLINK) =j grid #
190	NGRID	(CB4)(inp RINPUT)(int) number of grid points per quasi-orthogonal (station)
191	NTT	(CB3) current iteration number
192	NNO	(TLINK)(int) = NTYPE(NST) code for location of calculation plane 1- rotor,2-stator,3-duct
193	NOIT	(RVELM)(int) after this value has been exceeded by IT, RVELM will finish although it has not reached the desired velocity tolerance
194	NORDI	(CB4)(inp RINPUT)(int)order of polynomial fit to inlet properties (I DON'T KNOW IF IT IS USED, (JUN '91,WAK))
195	NPRNT	(CB6)(inp RINPUT)(int)flag for intermediate printout;0-last iteration only;1-first, middle and last iteration
196	NPTS	(CB4)(inp RINPUT)(int)no. of points at which inlet properties are given(TSTAG,PSTAG,PDUM,PT)
197	NQN	(CB5)
198	NQN	(TLINK)number of next station (nst +1)
199	NRDKM	(CB3)(inp RINPUT)(int)flag for specifying slopes and curvatures,0-calculated by spline,1-read in,2-set to zero
200	NROT	(CB6)(int) counting variable to count number of rotors (incremented in TLINK)
201	NS	=NSTAT
202	NSCT (KB)	(CB6)(inp TLINK)(int)no. of sections(radial) at which blade properties are specified
203	NSEC	=NSCT (KB)=# of radial sections at which the blade properties (geometry) are specified.
204	NSGI	(RVELM)(int)

205	NSG2	(RVELM)(int)
206	NST	(CB3)(int) current calculation plane
207	NSTAT	(CB4)(inp RINPUT)(int) number of quasi-orthogonals (calculation planes, stations)
208	NSTOR	(CB6)(int) counting variable to count number of stators (incremented in TLINK)
209	NT	(CB3)(inp RINPUT)(int) maximum number of iterations allowed by program on streamline position.
210	NTUBE	(CB4)
211	NTYPE (net)	(CB1)(inp RINPUT)(int) code to indicate location of calculation plane; 1-entrance to rotor; 2-entrance to stator; 3-entrance to duct
212	ODD (22,10)	(CB6)Deviation angle (=DEV)
213	ODI (22,10)	(CB6) incidence angle (=ACIN)
214	ODL (22,10)	(CB6)(=CFRE)
215	OK	(CB3) 0 case converged, 1 case not converged (case converged when streamline shift is less than TOLS)
216	OMA	(CB3)(rad/s) set in tlink to ROTV(NST) the angular velocity of the station in rad/s
217	OMA	(CB3)(rpm)= ROTV(NST) = angular velocity of the coordinate system being used
218	OMEG	(CB3)(inp RINT)(real)(rpm)rotational speed
219	OMEGA	(TLINK)(rad/s) OMEG converted to radians/s
220	PA	(psi)total pressure
221	PBAN	(BLCAL)(real)
222	PBH	(BLCAL)(real)
223	PBT	(BLCAL)(real)
224	PCTN	(inp RINPUT)(fraction of OMEG desired (ie 0.9) (RINPUT)(real)
225	PDUM (nps)	(RINPUT)(deg or ft/s?)(inlet flow angle(KVT.NE.1) or inlet tangential velocity(KVT=1)
226	PH	(BLCAL)(real)
227	PHI	(CB1) streamline slope (rcurv)(greek phi)
228	PHSL	(TLINK) cosine of streamline angle; (axial component of the streamline vector)/streamline
229	PI	(CB4)3.141592654, set in MAIN.CASCAD
230	PMS	mass flow parameter lbm/s*(k)^.5
231	PMS	(RINPUT)(real)
232	PO	(CB4)(inp on nt)RINPUT);mass-averaged inlet stagnation pressure;input in psi converted to lbf/ft^2 in RINPUT
233	PO1	PO
234	PO1	total pressure at rotor outlet
235	PO1	(RINPUT)(real)
236	PO2IS	(TLINK) isentropic (no pressure loss) outlet relative stagnation pressure(POR2IS would have been a better name)
237	POR1	(TLINK)inlet relative stagnation pressure
238	POR2 (ngrid)	(CB2)(TLINK)outlet relative stagnation pressure
239	POUT	PO converted back to psi
240	POUT	(RINPUT)(real)

241	PPR	(BLCAL)(real)
242	PROL (KB,NGRID)	(CB6)Profile loss (YP)
243	PS	(BLCAL)(real)
244	PSI (NSTAT)	(CB12)(real) slope of calculation planes ($\arctan(DZ/DR)$) (measured from perpendicular to axial direction)(greek letter psi)
245	PST (NSTAT,J)	(CB1) stagnation pressure
246	PSTA (NPTS)	(RINPUT)(psi) PSTAG in psi, used for output of static pressure from RINPUT
247	PSTAG (aps)	(inp RINPUT)(real)(input psi, converted to lb/ft^2)inlet total pressure
248	PSTAG (NPTS)	(INP RINPUT):inlet stagnation pressure,input in psi converted to lb/ft^2 in RINPUT
249	PT (NPTS)	(INP RINPUT)(real)(inches)distance from hub at which inlet properties are given,Convert in Rinput to a ratio of the inlet length, AD.
250	Q (NGRID)_	(CB2)entropy change from turbine inlet to outlet relative ($S_{2\text{rel}} - S_{\text{inlet}}$)
251	R (NSTAT,NGRID)	(CB1)(feet)radius
252	RAD (NGRID)	(inches)radius
253	RARG	(RVELM)(real) T_o/T
254	RAT	(TLINK) ratio $1-P_2/P_{O2}$
255	RBAR	(TLINK) $\text{DELN}(\text{NST,J}) \times 100$
256	RD	(TLINK) radius to be used to calculate geometry at a grid point by linear interpolation from radii where geometry is specified
257	RD12	(TLINK)average of inlet and outlet radii
258	RDIN	(TLINK)=R(NST,NGRID) inlet radius
259	RDOUT	(TLINK)=Routlet radius
260	RDUM (KB,NSEC)	radius at which geom. of blades is specified read-in in inches, converted to feet
261	REYN	(TLINK) reynolds number multiplied by something?
262	REYS	(BLCAL)(real)
263	RGAS	(CB4) gas constant for air 96.02 ft-lb/lbm-K (53.35 ft-lb/lbm-R if temperature input in Rankine)
264	RGU	(TLINK)(btu/lbm R) Gas constant for air
265	RH (NSTAT)	(CB1)(inp RINPUT) radius at hub for each calculation plane (quasi-Orthogonal,in inches converted to feet)
266	RM2	(CB5)(TLINK)outlet relative Mach number
267	RM2	?exit Mach number in tangential direction
268	RMD2	(CB7)(TLINK)=RM2=outlet relative Mach number
269	RO	(RVELM)(lbm/ft^3) density (static)
270	RO (agrid)	(TLINK)(lbm/ft^3) outlet density (static)
271	RO1	(RINPUT)(real)
272	RO2	(RINPUT)(real) static density
273	RO3	(RINPUT)(real) total density
274	ROA	(BLCAL)(real)
275	RODM	(BLCAL)(real)
276	RODM	(RVELM)(lbm/ft^3)outlet stagnation density(density based on stagnation properties)(greek rho,sub o)

277	ROOM	(TLINK)(lbm/ft^3)outlet stagnation density(density based on stagnation properties)(greek rho.sub 0)
278	RORT	(RINPUT)(real)
279	ROS (axial)	(BLCAL)(real)
280	ROTV (NSTAT)	(CB1)(rad/s)rotational speed at each station,calculated from OMA (or read for NCTR=1 (inp RINT))
281	RT (NSTAT)	(CB1)(inp RINPUT);input in inches converted to feet;radius at tip (shroud) for each calculation plane (quasi-Orthogonal station)
282	RU	gas constant for air 0.06855 Btu/lbm-R
283	RU	(RINPUT)(real)
284	RVT	(BLCAL)(real)
285	RVT (agrid)	(RVELM)(real) tan ALP(agrid), tangent of the air angle. (same as TM6)
286	S (1,NGRID)	(TLINK)
287	S (1-8,NGRID)	(TLINK) GEOM(KB,1-8,NSEC) after linear interpolation to determine geometry at each grid point.
288	S (2,NGRID)	(TLINK)
289	S (3,NGRID)	(TLINK)
290	S (4,NGRID)	(TLINK)pitch/chord (pitch chord ratio) (the inverse of this being solidity)
291	S (5,NGRID)	(TLINK)
292	S (6,NGRID)	(TLINK)
293	S (7,NGRID)	(TLINK)=te/s, trailing edge thickness/pitch
294	S (8,NGRID)	(TLINK)=k, tip clearance
295	SI	(RVELM)(real)mass flow/2*pi*alen(nst) -removed June '91 by Wendy Klein
296	SGN	(TLINK)(real) sign (-1 if calculation plane is at entrance to rotor,1 otherwise)
297	SHB (NSTAT)	(inp RCURV)(real)(deg)slope at hub at each calculation plane
298	SHL (22,10)	(CB6)(=REYN)
299	SHP (NSTAT,J)	(CB1) ?boundary layer shape factor (H) at hub and shroud
300	SI	(CB5)
301	SKF	(BLCAL)(real)
302	SODL (NSTAT+1,NGRID)	(CB8)
303	SOL	(CB5)(TLINK) component of pitch cord ratio in axial direction? (solidity in axial direction)
304	SPD	(RINPUT)(real)
305	STP (NSTAT)	(inp-RCURV)(real)(deg)slope at shroud at each calculation plane
306	SUM1	(RVELM)(real)
307	SVM	(RVELM)(real) average of meridional velocities through station
308	SVM1	(RVELM)(real)
309	T	(BLCAL)(real)
310	T	(TLINK)(K or R) inlet static temperature
311	T (agrid)	(RVELM)(real)
312	T*	(TLINK)outlet static temperature
313	TA	(K)total temperature

314	TA1	static temperature in front of rotor
315	TA1	(RINPUT)(real)
316	TCL	(CB5) $S(8.1 - ngrid) = k$, tip clearance
317	TER	(CB5) $S(6.NGRID)=s/e$ (pitch/ blade back curvature)
318	TER1	(CB1)
319	TET	(CB5) = te/s , trailing edge thickness/pitch
320	TM1 (NGRID)	(CB2) = $TER1(nst, ngrid)$
321	TM2 (NGRID)	(CB2) $(DHDS-TS*DQDS)*GO*AJ$; part of equation 10 "Ngo"
322	TM3 (ngrid)	(RVELM)(real) most of last term equation 10 "Ngo"
323	TM4 (ngrid)	(RVELM)(real) $(\cosine\ beta)^2$ (note $ALP=beta$)
324	TM5 (ngrid)	(RVELM)(real) part of last term in equation 10 "Ngo"
325	TM6 (ngrid)	(RVELM)(real) $\tangent\ beta$ (note $ALP = beta$)
326	TO	(CB4)(inp RINPUT)(K or R), mass-averaged inlet stagnation temperature, input in Kelvin in the example, may be possible to input in degrees Rankine
327	TO1	TO
328	TO1	total temperature at rotor outlet
329	TO1	(RINPUT)(real)
330	TOLM	(CB4)(inp RINPUT)(lbm/s) mass flow tolerance (convergence factor for mass flow)
331	TOLS	(CB4)(inp RINPUT) streamtube width tolerance (based on an annulus width of 1.0)
332	TOR1	(TLINK) inlet stagnation (total) temperature relative to blade row (for the streamline)
333	TOR2 (ngrid)	(CB2)(TLINK) outlet relative stagnation temperature (of the streamline) (inlet stagnation temp + change in dynamic temp. due to difference in radius from 1 to 2)
334	TRAT	(CB5)(TLINK) = component of V_c in the axial direction
335	TS	(RVELM)(real) outlet static temperature
336	TST (nstat, ngrid)	(CB1)(K or R) stagnation temperature
337	TSTA	(K) static temperature
338	TSTAG (opts)	(inp RINPUT)(real)(R or K) inlet total temperature
339	TSTC (nstat)	(BLCAL)(real)
340	V1	(BLCAL)(real)
341	V2	(BLCAL)(real)
342	V2	(RVELM)(real)
343	V2	(TLINK, WRITE) (ft^2/s^2) square of absolute velocity
344	VFIC (30)	(BLCAL)(real)
345	VISA	(BLCAL)(real)
346	VM (NSTAT, NGRID)	(CB1)(ft/s) meridional velocity
347	VMA	(BLCAL)(real)
348	VNEW	(RVELM)(real)
349	VOLD	(RVELM)(real)
350	VRAT	(CB5)(TLINK) relative velocity ratio (inlet relative velocity)/(outlet relative velocity)

351	VRATD	(CB7)(TLINK)=VRAT=(inlet relative velocity)/(outlet relative velocity)
352	VRTIO (NSTAT+1,NGRID)	(CB8)
353	VS2	(TLINK)outlet absolute velocity squared
354	VT (NSTAT,NGRID)	(CB1) (ft/s) tangential velocity
355	VTAB (ngrid)	(CALC WRITE)(ft/s) total velocity
356	VTR (KB,NSCT(KB))	(inp TLINK)(ft/s)swirl velocity at rotor exit;read only for stator, design mode
357	VX	(RVELM)(real) =VM cos(Psi+Phi) ,see "Davis" report N. ME/A 71-5 Sept '71
358	W2	(RVELM)(real)
359	W2	(TLINK)(ft^2/s^2)square of the relative velocity
360	WGHT	(CB4)(inp RINPUT)(real)damping coefficient for streamline repositioning
361	WO (30)	(BLCAL)(real)
362	WSQ (ngrid)	(RVELM)(real) outlet relative velocity squared
363	WT	(RVELM)(real)
364	WT1	(TLINK)(ft/s) inlet relative velocity
365	WT2 (ngrid)	(TLINK)(ft/s) outlet relative velocity
366	WTBL	(BLCAL)(real)
367	WTI	(BLCAL)(real)
368	WTO	(BLCAL)(real)
369	WTW2	(TLINK) outlet relative tangential velocity
370	WU	(CB5)
371	WUD	(CB7)
372	Y (NGRID)	(RVELM)(real)
373	YK	(CB5)tip clearance loss coefficient
374	YPD	(CB7)
375	YPIN	(CB5)
376	YPO	(CB5)
377	YQ (ngrid)	(CB2)(RVELM)(WRITE)
378	YS	(CB5)
379	YSD	(CB7)
380	YTA	(CB7)
381	YTC	(CB7)
382	YTS	(CB7)
383	Z (NSTAT,ngrid)	(CB1)(ft)axial position of calculation point
384	ZETA	(CB7)
385	ZH (NSTAT)	(CB1)(inp RINPUT)inp in inches convt feet;axial dimension of the calculation plane (quasi-Orthogonal station) at the Hub.
386	ZT (NSTAT)	(CB1)(inp RINPUT)inp in inches convt ft;axial dimension of the calculation plane (quasi-Orthogonal station) at the tip.

New Subroutines

TIPLOS

This subroutine is called by TLINK when the tip losses are to be concentrated near the tip. Using the mass flow in each streamtube calculated by RVELM this subroutine calculates the mass averaged tip loss across the annulus given by the cascade correlations and redistributes it in a parabolic shape. The subroutine returns (to TLINK) tip loss coefficients for each grid point of the calculation station.

TIPCRV

This subroutine (called by TIPLOS) which calculates the coefficients of the parabola, given the required area of the parabola.

TIPDAT

This subroutine is called from XMAIN to set the variables related to concentrating the tip losses.

TIPWRT

This subroutine is called from XMAIN to write information calculated in TIPLOS. It is meant for use during development of the program.

Changes to Original Program

In order to add the new programs it was necessary to add some code to TLINK and RVELM. In TLINK it was necessary to add code to call the TIPLOS and incorporate the new tip losses calculated. In RVELM it was necessary to save the mass flow for each streamtube along with the total mass flow through the annulus.

Discussion of Program Convergence

The streamline curvature program has two variables which can be set to dictate convergence requirements. As well as these two variables the number of grid points chosen will affect the final result. TOLS is the convergence criteria dictating the maximum amount which the streamlines can have moved from the last iteration. TOLM is the convergence criteria for mass flow and dictates how close the mass flow through the annulus must be to the desired mass flow in order to allow convergence.

A study of the effect of these parameters on convergence indicates that they are inter-related and that there is no simple way to adjust them for improved convergence. Decreasing TOLS usually requires decreasing TOLM and vis versa. TOLS can be decreased in larger percentage steps of its total than TOLM can.

TOLS has the greatest affect on controlling convergence. The program can claim convergence and stop even if the mass flow tolerance is not met at all stations. This is because the mass flow tolerance is checked in subroutine RVELM which allows itself to be exited without mass flow convergence. This allows intermediate solutions near choked flow conditions and thus allows simulation of turbines with higher Mach numbers. However an extra check of mass flow tolerance should be made prior to the completion of the program. Decreasing TOLS may prevent this problem but usually it is necessary to reduce the total mass flow required (thereby reducing the maximum Mach number).

Since the program uses finite difference formulations between grid points the greater the number of grid points the smoother the final solution will be. Eight to 10 grid points are required in any area of change. Presently the program distributes the specified number of grid points evenly across the annulus. In future it may be desirable to allow the concentration of grid points in certain areas. This would greatly reduce the total number of grid points, and thus calculation time required. For instance the simulations discussed in Chapter 3 required 50 grid points in order to

obtain 10 grid points through the region of concentrated tip losses. However the rest of the annulus would have been adequately defined with less than 10 grid points.

Errors in Program

While writing up this thesis it was discovered that the cascade correlation for secondary loss uses inlet flow angle as opposed to inlet metal angle dictated by the correlation. Since inlet metal and flow angles were similar for the simulation discussed in Chapter 3 this error would not have a significant effect on their result. However it should be corrected by future users of the program.

The sign of inlet metal angle for second and subsequent turbine stages is reversed. Thus the program can only properly run multi stag turbines with the second stage having an inlet metal angle of zero. This was not corrected since it was not possible to run the two stage turbine for other reasons discussed in Chapter 3.

Appendix B

Streamline Curvature Program, 1992 version

This appendix contains a listing file for the streamline curvature program. It corresponds to the 10 grid-point data file and output file listed in Appendix C.

CONTENTS	PAGE
XMAIN.FOR (beginning of program)	B-2
RINPUT.FOR	B-2
CURFIT.FOR	B-6
RCURV.FOR	B-7
SPLINE.FOR	B-9
RVELM.FOR	B-10
TLINK.FOR	B-13
CASCAD.FOR	B-19
PRLOSS.FOR	B-21
SLINE.FOR	B-21
WRITE.FOR	B-22
REPOS.FOR	B-26
BLCAL.FOR	B-28
TIPDAT.FOR	B-30
TIPCRV.FOR	B-31
TIPLOS.FOR	B-33
TIPWRT.FOR	B-35
XMAIN.FOR (most of program)	B-36

Options: list,del,extensions, warnings,types,terminal,check,army,check

*TEST MAIN PROGRAM TO BE USED TO TEST SUBROUTINES

*****This file was last edited JUN 2, '91

*FILES TO BE INCLUDED FOR CALL STATEMENTS

* SUBROUTINE INPUT

* CURFIT FOR

* BCURV FOR

* SPLINE FOR

* RVELM FOR

* TLINK FOR

* CASCADE FOR

* PILOSS FOR

* SLINE FOR

* WRITE FOR

* REPOS FOR

* BUCAL FOR

* TIRDAT FOR

* TPCRV FOR

* TIFLOS FOR

* TFWRT FOR

CENCLUDE SUPRGS FOR

CENCLUDE INPUT FOR

1 SUBROUTINE INPUT

C PROGRAM TO READ THE STATION DATA

*****This file was last edited Jun 18, '91

```

*****start 11, ngrid 50, ngrid+1 51
5  COMMON /CB/OM(11,51),
1  VM(11,50),VT(11,50),PST(11,50),TST(11,50),DELN(11,50),
1  R(11,50),Z(11,50),TER(11,50),PMN(11,50),PHI(11,50),
1  ALEN(11),BLCK(11),AREA(11),NTY PR(11),ROTV(11),
1  DELFO(11,50),DSM(11,50),SHR(11,2),DSPT(11,2),DELT(11,2),
1  ARA(11),RH(11),ZRH(11),RT(11),ZT(11)
*****METHOD(11),
CENCLUDE TWO.BLK
*2 initialize variables from block two
6  REAL TM1,TM2,FOR2,TOR2,QALP,DUMHLCFPO,CFPO,FPVT,CFAL,YQ
* .....
*****ngrid = 50, ngrid+1 = 51
7  COMMON /CB2/TM1(50),TM2(50),FOR2(50),TOR2(50),Q(50),ALP(50),
1  DUMH(50),YQ(50),
2  CFPO(51),CFPO(51),CFVT(51),CFAL(51)
CENCLUDE THREE.BLK
*3 initialize variables from block three
8  INTEGER NT,KODE,NRDKM,NFDES,NFBLNST,KBLABORT,NIT,KAL,KVT
9  REAL OMEG,OMA,OK
* .....
10  COMMON /CB3/NT,KODE,NRDKM,NFDES,NFBLNST,KBLABORT,NIT,
1  KAL,KVT,OMEG,OMA,OK
CENCLUDE FOUR.BLK
*4 initialize variables from block four
11  INTEGER NSTAT,NGRID,NTUBE,NORDI,NPTS,IRD,IWT
12  REAL PO,TO,H0,DESM,GAMA,RGAS,CT,GO,PLAJ,TOLS,TOLM,WGHT
* .....
13  COMMON/BLK1/NSTAT,NGRID,NTUBE,NORDI,PO,TO,H0,DESM,GAMA,RGAS,CT,
CENCLUDE SIX.BLK
*11 initialize variables from block six (Nied)
14  INTEGER NPRINT,NROT,NSTOR,KB,KBLAD,NSCT,KBST
15  REAL ODL,DL,ODD,PROL,DEQ,DFAC,SHL,ODL,DEQM,DEVM
* .....start 11, ngrid 50
16  COMMON /BLAD/NPRINT,NROT,NSTOR,KB,KBLAD(11),NSCT(11),KBST(11),
1  ODM(11,50),DK(11,50),DL(11,50),ODD(11,50),PROL(11,50),
2  DEQM(11,50),DFAC(11,50),SHL(11,50),ODL(11,50),
3  DEVM(11,50),DEVM(11,50)
*****
* initialize all non-common variables
* dimension for ages
17  REAL PSTAG(12),TSTAG(12),PMN(12),PT(12)
* dimension for ngrid+1
18  REAL COFR(51),COFT(51),COFD(51)
19  REAL RU,CV,DELZ,AD,PCTN,AVH

```



```

73      CPVT(I)=COFDT(I)
74      ENDIF
75 26    CONTINUE
.....
76      IF(AJ.GT.779) THEN
77          WRITE(NWT,9)
78 9      FORMAT(/,10X,20HTEMPERATURE IN DEG.K/)
79      ELSE
80          WRITE(NWT,5)
81 5      FORMAT(/,10X,20HTEMPERATURE IN DEG.R/)
82      ENDIF
.....
..... 11  WRITE(NWT,7)
..... 7  FORMAT(IH1)
..... 7  FORMAT(/)
83  WRITE(NWT,51) PO,TO
84 51  FORMAT(10X,44HMASS AVERAGED INLET PRESSURE AND TEMPERATURE/,
1      31X,P6,25X,F7.2)
.....
*convert PO from psi to lbf/(ft^2)
85  PO=PO*144.0
86  IF(AJ.GT.779) THEN
87      WRITE(NWT,52)
88 52  FORMAT(31X,(P 5.1),6X,(DEG K)/)
89  ELSE
90      WRITE(NWT,54)
91 54  FORMAT(31X,(P 5.1),6X,(DEG R)/)
92  ENDIF
93 53  WRITE(NWT,56) CP,GAMA
94 56  FORMAT(10X,'SPECIFIC HEAT constant pressure (Cp) = ',P6.3/,
1      34X,'RATIO (Cp/Cv) = ',F5.2/)
.....
*write the duct geometry and convert the geometry from inches to feet
.....
95  WRITE(NWT,660)
96 660  FORMAT(29X,'DUCT GEOMETRY (inches)/125X,3HHUB,24X,6HSHROUD/16X,
1      8HDISTANCE,6X,6HRADIUS,9X,8HDISTANCE,6X,6HRADIUS/19X,
2      3H21.9X,3HR114X,3H21.9X,(R1)/)
.....
C
97  DO 65 I=1,NSTAT
98      WRITE(NWT,670) ZH(I),RH(I),ZT(I),RT(I)
99 670  FORMAT(16X,F7.3,6X,F7.3,10X,F7.3,6X,F7.3)
100  RH(I)=RH(I)/12.0
101  RT(I)=RT(I)/12.0
102  ZH(I)=ZH(I)/12.0
103  ZT(I)=ZT(I)/12.0
104 65  CONTINUE
.....
C
.....
*write the number of grid points and the tolerance factors
.....
105  WRITE(NWT,75) NGRID,TOLM,TOLS,WGHT
106 75  FORMAT(/,10X,'NO. OF GRID POINTS (NGRID) =',13/,
10X,TOLERANCE (MASS) (TOLM) = ',F5.5/,
2      10X,TOLERANCE (DIST) (TOLS) = ',F5.5/,
3      10X,'WEIGHTING FACTOR (WGHT) = ',F5.2/)
.....
*determine how curvatures and boundary layers are computed
*write the result
*curvatures:
107  IF(NRDKM.EQ.2) GO TO 95
108  IF(NRDKM.EQ.1) GO TO 90
109  WRITE(NWT,80) NRDKM
110 80  FORMAT(10X,'CURVATURES ARE COMPUTED BY A SPLINE FIT',,
1      'NRDKM = ',12/)
111  GO TO 97
112 90  WRITE(NWT,85) NRDKM
113 85  FORMAT(10X,'CURVATURES ARE READ IN, (NRDKM) = ',12/)
114  GO TO 97
115 95  WRITE(NWT,96) NRDKM
116 96  FORMAT(10X,'CURVATURES ARE SET TO ZERO, (NRDKM) = ',12/)
117 97  CONTINUE
*boundary layer:
118  IF(NFBL=1) 22,21,21
119 21  WRITE(NWT,23) NFBL
120 23  FORMAT(10X,'BOUNDARY LAYERS COMPUTED, (NFBL) = ',12/,
121  GO TO 24
122 22  WRITE(NWT,25) NFBL
123 25  FORMAT(10X,'BLOCKAGE FACTORS ARE READ IN, (NFBL) = ',12/)
124 24  CONTINUE
.....
.....
*second entry point
125  ENTRY RNT
.....
.....
126  NSTOK=0
127  NROT=0
128  NIT=0
129  DO 10 I=1,NSTAT
130      R(I)=RH(I)
131      R(LNGRID)=RT(I)
132      Z(I)=ZH(I)
133      Z(LNGRID)=ZT(I)
.....
C INITIALIZE THE ARRAY OF STREAMTUBE WIDTHS

```

```

134 DM(LNCGRID+1)=0.
135 DM(L)=0.
136 DELN(LNCGRID)=1.0
137 DELN(L)=0.
138 10 CONTINUE
.....
.....
139 HO=CP*TO
140 PO1=PO
141 TO1=TO
*read in the desired mass flow, rotational speed, fraction of
*nominal speed desired, average work done
142 READ(RD,1) DESM,OMEG,PCTN,AVH
*if end of file flag bit then stop
143 IF(DESM.GT.1000.)GO TO 630
*set angular velocity of coordinate system
144 OMA=OMEG*PCTN
145 IF(NCTR.EQ.1)THEN
146 READ (RD,2)(ROTV(I),I=1,NSTAT)
147 ELSE
148 DO 8 K=1,NSTAT
149 IF(NTYPE(K).EQ.1)THEN
150 ROTV(K)=OMA*PI/30.0
151 ELSE
152 ROTV(K)=0.0
153 ENDIF
154 8 CONTINUE
155 ENDF
.....
*write desired mass flow rate,speed,% of design speed.
*average work done
*
156 WRITE(TWT,202)
157 206 FORMAT(10X,'MASS FLOW RATE. DESM = 'F10.2,' lbm/sec'//
1 10X,'SPEED. OMA = 'F10.2,' rpm'//
2 10X,'% DESIGN SPEED. PCTN*100% = 'F99.1,' %'//
158 IF(AJ.GT.779)THEN
159 WRITE(TWT,207) AVH
160 207 FORMAT(10X,'WORK OUTPUT. AVH = 'F9.2,' chm/lbm'//
161 ELSE
162 WRITE(TWT,209) AVH
163 209 FORMAT(10X,'WORK OUTPUT. AVH = 'F9.2,' bwh/lbm'//
164 ENDF
.....
*calculate and write mass flow and speed parameters
165 POUT=PO/144.0
166 PMS=DESM*SQRT(TO)/POUT
167 SPD=OMASQRT(TO)
168 WRITE(TWT,618) PMS,SPD
169 618 FORMAT(/21X,'NON DIMENSIONAL FLOW AND SPEED'//
1 10X,'MASS FLOW PARAMETER. DESM*(TO)^.5*PO = 'F7.2//
1 10X,'SPEED PARAMETER. OMA*(TO)^.5 = 'F7.1//
.....
.....
C
C COMPUTE THE AREA AT EACH NORMAL AND THE LENGTH OF THE NORMAL
170 DM1=2.0*GOV*AJ*CP
171 DM2=GAMA/GAMA-1)
172 DM3=GAMA-1
173 DM4=1/DM3
174 DO 30 I=1,NSTAT
175 IF (NFDES EQ 1)THEN
176 DO 613 J=LNGRID
*set delpo to 1 instead of 0.05 as before , within july 2,92
177 DELPO(LJ)=0.10
178 613 CONTINUE
179 ENDF
180 DELR=RT(I)-RH(I)
181 DELZ=ZT(I)-ZH(I)
182 ALEN(I)=SQRT(DELR**2+DELZ**2)
183 AREA(I)=PI*(RT(I)+RH(I))*ALEN(I)
*
184 IF( I EQ 1 ) GO TO 70
* for all but first station
185 IF(NTYPE(I-1).NE.1) GO TO 70
* for exit from rotor
186 IF(NFDES EQ 1)THEN
*analysis mode (exit from rotor)
187 TA1=TO1-VME(I-1)**2/DM1
188 AM=VME(I-1)**2/(GAMA*GOV*RGAS*TA1)
189 RO2=DESM/VME(I-1)*AREA(I)
190 RO3=RO2*(1.0+DM3)*AM/2.0**DM4
191 RORT=RO/RO1
192 TO1=TO1*RORT**DM3
193 PO1=PO1*RORT**GAMA
194 WRITE(TWT,69) AM,RO3,TO1,PO1
195 69 FORMAT(10X,'AM = 'E12.4/10X,'RO3 = 'E12.4/
1 10X,'TO1 = 'G12.4/10X,'PO1 = 'G12.4//
196 ELSE
*design mode (exit from rotor)
197 RORT=1.-AVH/.89*CP*TO1)
198 PO1=PO1*RORT**DM2
199 TO1=TO1-AVH*CP

```

```

200      ENDP
201 70      CONTINUE
202      *      for all stations, design and analysis
203      ROI=POI/(RCAS*TOI)
204      DUMV=DESMA/AREA(P*ROI)
205      TAI=TOI-DUMV**2/DM1
206      AM=DUMV**2/(GAMA*GO*RGAS*TAI)
207      DUMV=DUMV*(1+DM1*AM/2)**DM4
208      VM(L1)=DUMV
209      IF(ABS(DBLR1)/GT(1.0E-03)) THEN
210          DRI=4*H1
211          ARAD=AREA(P*DELR/ALEN(P*NTUBE*PI))
212          DO 60 J=2,NCRID
213              DR2=SQRT(ARAD*DR1**2)
214              VM(LJ)=DUMV
215              DN(LJ)=(DR2-DR1)/DELR
216 60      CONTINUE
217      ELSE
218          DO 50 J=2,NCRID
219              VM(LJ)=DUMV
220              DN(LJ)=1/NTUBE
221 50      CONTINUE
222      ENDP
223      ***** at VT (tangential velocity) to 0.0 usually (added to
224      ***** program may 16, '91 by W. Klem to fit analysis mode)
225 300      DO 300 J=1,NCRID
226          VT(LJ)=0.0
227 300      CONTINUE
228      *      continue for next station
229      *      continue here for end of file flag
230      CONTINUE
231      RETURN
232      END

```

* N - (integer) array size of X and Y
 * LAST - order of polynomial fit
 * returned by curfit: COF - real array of size 'LAST+1'

```

231      INTEGER N,LAST
232      REAL X(N),Y(N),A(50,50),SUMX(50),SUMY(50),COF(LAST+1)
233      SUMX(1)=0.0
234      SUMY(1)=0.0
235      DO 90 I=1,N
236          SUMX(I)=SUMX(I)+1.
237          SUMY(I)=SUMY(I)+Y(I)
238 90      CONTINUE
239      DO 172 NORD=1,LAST
240          J=2*NORD
241          SUMX(J)=0.0
242          SUMY(J)=0.0
243          SUMY(NORD+1)=0.0
244          DO 172 I=1,N
245              SUMX(J)=SUMX(J)+X(I)**J-1
246              SUMX(I+1)=SUMX(I+1)+X(I)**J
247              SUMY(NORD+1)=SUMY(NORD+1)+Y(I)*X(I)**NORD
248 172      CONTINUE
249      C      SET UP MATRIX
250      L=LAST+1
251      KK=L+1
252      DO 101 I=1,L
253          DO 100 J=1,L
254              IK=I+J
255              A(IJ)=SUMX(IK)
256              A(IKK)=SUMY(IK)
257 101      CONTINUE
258      C      INVERT MATRIX
259      DO 140 I=1,L
260          A(IKK)=1.0
261          DO 110 J=KK,KK
262              A(IKK,J)=0.0
263 110      CONTINUE
264          C=1.0/A(IJ)
265          DO 120 B=2,KK
266              DO 120 J=KK,KK
267                  A(IJ)=A(IJ)+A(I)*A(BI)*C
268 120      CONTINUE
269          DO 140 B=1,L
270              DO 140 J=KK,KK

```



```

271      A(LJ)=A(B+1,J)
272 140 CONTINUE
273 173 DO 500 NC=1,L
274     CORDC=ANC(KK)
275 500 CONTINUE
276     RETURN
277     END

*****
*****
C
C CONCLUDE RCURV FOR
278 SUBROUTINE RCURV
C
C PROGRAM TO COMPUTE THE CURVATURE AT ALL GRID POINTS
C SPLINE CURVE FITTING TECHNIQUE IS USED
C DELN-- THE NON-DIM DISTANCE FROM THE HUB TO THE GRID POINT
C KBL-- FLAG TO INDICATE IF THE POSITION OF THE HUB AND TIP STREAMLINE
C HAS BEEN CHANGED BETWEEN ITERATIONS
*****
*****
*****This file was last edited Mar 7, '91
*****
C CONCLUDE ONE BLK
*1 Initialize variables from block one
279 INTEGER NTYPE
280 REAL DN,VM,VT,PST,TST,DELN,B,Z,TER1,FMN,PH,ALEN,BLCK,AREA,
1 ROTV,DELP,DSM,SHIP,DSPT,DELT,ABA,RU,ZH,RT,ZT
*****METHOD
*****
*****Mar 11, April 50, April+1 51
281 COMMON ACB/DXN(11,51),
1 VM(11,50),VT(11,50),PST(11,50),TST(11,50),DELN(11,50),
1 R(11,50),Z(11,50),TER1(11,50),FMN(11,50),PH(11,50),
1 ALEN(11),BLCK(11),AREA(11),NTYPE(11),ROTV(11),
1 DELP(11,50),DSM(11,50),SHIP(11,2),DSPT(11,2),DELT(11,2),
1 ABA(11),RU(11),ZH(11),RT(11),ZT(11)
*****METHODX(11),
C CONCLUDE TWO BLK
*2 Initialize variables from block two
282 REAL TM1,TM2,POR2,TOR2,Q,ALP,DUMH,CFFO,CFTO,CFTV,CFAL,YQ
.
*****
*****April - 50, April+1 - 51
283 COMMON ACB/TM(50),TM2(50),POR2(50),TOR2(50),Q(50),ALP(50),
1 DUMH(50),YQ(50),

```

```

2 CFFO(51),CFTO(51),CFTV(51),CFAL(51)
C CONCLUDE THREE BLK
*3 Initialize variables from block three
284 INTEGER NT,KODE,NRDIM,NFDES,NFIL,NST,KBL,ABORT,NT,KALK,KVT
285 REAL OMEG,OMAX,OK
.
*****
286 COMMON ACB/NT,KODE,NRDIM,NFDES,NFIL,NST,KBL,ABORT,NT,
1 KALK,KVT,OMEG,OMAX,OK
C CONCLUDE FOUR BLK
*4 Initialize variables from block four
287 INTEGER NSTAT,NGRID,NTUBE,NORDI,NPTS,BRD,IWT
288 REAL PO,TO,HODESM,GAMA,IGAS,CP,GO,PLA,TOLS,TOLM,WGHT
.
*****
289 COMMON/BLK1/NSTAT,NGRID,NTUBE,NORDI,PO,TO,HODESM,GAMA,IGAS,CP,
1 GO,PLA,TOLS,TOLM,WGHT,NPTS,BRD,IWT
C CONCLUDE TWELVE BLK
*12 Initialize variables from block 12 (c06)
290 REAL PSI
.
***** Mar 11
291 COMMON /CB6/PSI(11)
*****
*****
*dimension for stat
292 REAL CHN(11),CTR(11),SHN(11),STR(11),R(11),SLR(11),DL(11),
1 Y(11),T(11),X(11)
*dimension for ngrid
293 REAL SDV(11),CDW(11)
294 REAL SN(50),SN(50)
*****
295 EQUIVALENCE (SDV,CDV,F,Y)
.
296 REAL AALB,XA
297 INTEGER NS,NGJJ,K
*****
*see if position of the hub and tip streamline has been changed
*check flag KBL (0 for first iteration, 1 for the rest)
298 IF(KBLEQ1) GO TO 342
299 AA=0.0
300 BB=0.0
C
C CALC THE SLOPE OF THE CALC. PLANES
301 DO 500 I=1,NSTAT
302     DZ=Z(LNGRID)-Z(L1)
303     DR=R(LNGRID)-R(L1)
304     IF(ABS(DR).GT 1.0E-4) THEN
305         PSK(I)=ATAN(DZ/DR)
306     ELSE

```

```

307      PS(K)=PI/2.0
308      ENDF
309 500  CONTINUE
310 342  *continues here for all subsequent iterations for streamline conv
311 342  CONTINUE
312  NS=NSTAT
313  NG=NGRID
314  C TRANSFORM THE GRID POINTS TO R-Z PLANE
315  DO 40 J=1,NGRID
316  IF(J.EQ.1.OR.J.EQ.NGRID)GO TO 43
317  DO 10 I=1,NSTAT
318  IF(J.EQ.2) THEN
319  DELN(LJ)=DN(LJ)
320  ENDF
321  DELR=R(L,NGRID)+R(L,I)
322  R(LJ)=DELN(LJ)+DELR+R(L,I)
323  check sign of slope of normal
324  DELZ=Z(L,NGRID)+Z(L,I)
325  Z(LJ)=Z(LI)+DELN(LJ)+DELZ
326  *
327  *
328  *
329  *
330  *
331  *
332  *
333  *
334  *
335  *
336  *
337  *
338  *
339  *
340  *
341  *
342  *
343  *
344  *
345  *
346  *
347  *
348  *
349  *
350  *
351  *
352  *
353  *
354  *
355  *
356  *
357  *
358  *
359  *
360  *
361  *
362  *
363  *
364  *
365  *
366  *
367  *
368  *
369  *
370  *
371  *
372  *
373  *
374  *
375  *
376  *
377  *
378  *
379  *
380  *
381  *
382  *
383  *
384  *
385  *
386  *
387  *
388  *
389  *
390  *
391  *
392  *
393  *
394  *
395  *
396  *
397  *
398  *
399  *
400  *
401  *
402  *
403  *
404  *
405  *
406  *
407  *
408  *
409  *
410  *
411  *
412  *
413  *
414  *
415  *
416  *
417  *
418  *
419  *
420  *
421  *
422  *
423  *
424  *
425  *
426  *
427  *
428  *
429  *
430  *
431  *
432  *
433  *
434  *
435  *
436  *
437  *
438  *
439  *
440  *
441  *
442  *
443  *
444  *
445  *
446  *
447  *
448  *
449  *
450  *
451  *
452  *
453  *
454  *
455  *
456  *
457  *
458  *
459  *
460  *
461  *
462  *
463  *
464  *
465  *
466  *
467  *
468  *
469  *
470  *
471  *
472  *
473  *
474  *
475  *
476  *
477  *
478  *
479  *
480  *
481  *
482  *
483  *
484  *
485  *
486  *
487  *
488  *
489  *
490  *
491  *
492  *
493  *
494  *
495  *
496  *
497  *
498  *
499  *
500  *
501  *
502  *
503  *
504  *
505  *
506  *
507  *
508  *
509  *
510  *
511  *
512  *
513  *
514  *
515  *
516  *
517  *
518  *
519  *
520  *
521  *
522  *
523  *
524  *
525  *
526  *
527  *
528  *
529  *
530  *
531  *
532  *
533  *
534  *
535  *
536  *
537  *
538  *
539  *
540  *
541  *
542  *
543  *
544  *
545  *
546  *
547  *
548  *
549  *
550  *
551  *
552  *
553  *
554  *
555  *
556  *
557  *
558  *
559  *
560  *
561  *
562  *
563  *
564  *
565  *
566  *
567  *
568  *
569  *
570  *
571  *
572  *
573  *
574  *
575  *
576  *
577  *
578  *
579  *
580  *
581  *
582  *
583  *
584  *
585  *
586  *
587  *
588  *
589  *
590  *
591  *
592  *
593  *
594  *
595  *
596  *
597  *
598  *
599  *
600  *
601  *
602  *
603  *
604  *
605  *
606  *
607  *
608  *
609  *
610  *
611  *
612  *
613  *
614  *
615  *
616  *
617  *
618  *
619  *
620  *
621  *
622  *
623  *
624  *
625  *
626  *
627  *
628  *
629  *
630  *
631  *
632  *
633  *
634  *
635  *
636  *
637  *
638  *
639  *
640  *
641  *
642  *
643  *
644  *
645  *
646  *
647  *
648  *
649  *
650  *
651  *
652  *
653  *
654  *
655  *
656  *
657  *
658  *
659  *
660  *
661  *
662  *
663  *
664  *
665  *
666  *
667  *
668  *
669  *
670  *
671  *
672  *
673  *
674  *
675  *
676  *
677  *
678  *
679  *
680  *
681  *
682  *
683  *
684  *
685  *
686  *
687  *
688  *
689  *
690  *
691  *
692  *
693  *
694  *
695  *
696  *
697  *
698  *
699  *
700  *
701  *
702  *
703  *
704  *
705  *
706  *
707  *
708  *
709  *
710  *
711  *
712  *
713  *
714  *
715  *
716  *
717  *
718  *
719  *
720  *
721  *
722  *
723  *
724  *
725  *
726  *
727  *
728  *
729  *
730  *
731  *
732  *
733  *
734  *
735  *
736  *
737  *
738  *
739  *
740  *
741  *
742  *
743  *
744  *
745  *
746  *
747  *
748  *
749  *
750  *
751  *
752  *
753  *
754  *
755  *
756  *
757  *
758  *
759  *
760  *
761  *
762  *
763  *
764  *
765  *
766  *
767  *
768  *
769  *
770  *
771  *
772  *
773  *
774  *
775  *
776  *
777  *
778  *
779  *
780  *
781  *
782  *
783  *
784  *
785  *
786  *
787  *
788  *
789  *
790  *
791  *
792  *
793  *
794  *
795  *
796  *
797  *
798  *
799  *
800  *
801  *
802  *
803  *
804  *
805  *
806  *
807  *
808  *
809  *
810  *
811  *
812  *
813  *
814  *
815  *
816  *
817  *
818  *
819  *
820  *
821  *
822  *
823  *
824  *
825  *
826  *
827  *
828  *
829  *
830  *
831  *
832  *
833  *
834  *
835  *
836  *
837  *
838  *
839  *
840  *
841  *
842  *
843  *
844  *
845  *
846  *
847  *
848  *
849  *
850  *
851  *
852  *
853  *
854  *
855  *
856  *
857  *
858  *
859  *
860  *
861  *
862  *
863  *
864  *
865  *
866  *
867  *
868  *
869  *
870  *
871  *
872  *
873  *
874  *
875  *
876  *
877  *
878  *
879  *
880  *
881  *
882  *
883  *
884  *
885  *
886  *
887  *
888  *
889  *
890  *
891  *
892  *
893  *
894  *
895  *
896  *
897  *
898  *
899  *
900  *
901  *
902  *
903  *
904  *
905  *
906  *
907  *
908  *
909  *
910  *
911  *
912  *
913  *
914  *
915  *
916  *
917  *
918  *
919  *
920  *
921  *
922  *
923  *
924  *
925  *
926  *
927  *
928  *
929  *
930  *
931  *
932  *
933  *
934  *
935  *
936  *
937  *
938  *
939  *
940  *
941  *
942  *
943  *
944  *
945  *
946  *
947  *
948  *
949  *
950  *
951  *
952  *
953  *
954  *
955  *
956  *
957  *
958  *
959  *
960  *
961  *
962  *
963  *
964  *
965  *
966  *
967  *
968  *
969  *
970  *
971  *
972  *
973  *
974  *
975  *
976  *
977  *
978  *
979  *
980  *
981  *
982  *
983  *
984  *
985  *
986  *
987  *
988  *
989  *
990  *
991  *
992  *
993  *
994  *
995  *
996  *
997  *
998  *
999  *
1000  *

```

```

382 DO 210 I=2,NSTAT
383   DZ=Z(I)-Z(I-1,I)
384   DR=R(I)-R(I-1,I)
385   DL(I)=SQRT(DZ**2+DR**2)
386   DSM(I)=DSM(I-1,I)+DL(I)
387 210 CONTINUE
388 ENDIF
C
C COMPUTE STREAMLINE SLOPE TERMS
389 DO 410 I=1,NSTAT
390   X(I)=DSM(I,J)
391   R(I)=VM(I,J)
392 410 CONTINUE
393 CALL SPLINE(X,F,N,AA,BB,1,0,1,0,2,2,SDV,CDV)
394 DO 51 KC=1,N
395   IF(NRDKM.NE.0)GO TO 320
396   CUR=TRICK(I,0)+SLR(KC)**2**1.5
397   DM1=ATAN(SLR(KC))
398   GO TO 321
*****Do for first iterations only
399 320 IF(1.GT.1 OR KC.GT.1)GO TO 322
400   IF(KBLEQ.1)GO TO 322
401   IF(NRDKM.EQ.2)GO TO 324
***** res. in the slopes and curvatures
402   READ(IRD,70) (CHB(I),CTP(I),I=1,NSTAT)
403   READ(IRD,70) (SHB(I),STP(I),I=1,NSTAT)
404 70 FORMAT(8F10.0)
***** change slopes to radians
405   DO 501 I=1,NSTAT
406     SHB(I)=SHB(I)*PI/180.0
407     STP(I)=STP(I)*PI/180.0
408 501 CONTINUE
409   GO TO 322
***** set curvatures (at hub & abroad) and
***** slopes (at hub & abroad) to 0.
410 324 DO 323 I=1,NSTAT
411   CHB(I)=0.0
412   CTP(I)=0.0
413   SHB(I)=0.0
414   STP(I)=0.0
415 323 CONTINUE
416 322 *****
*****
417   CUR=(CHB(KC)+DELN(KC,J)*(CTP(KC)-CHB(KC)))/(ALEN(KC))
418   DM1=SHB(KC)+DELN(KC,J)*STP(KC)-SHB(KC)
419   TETA=0.0
420 321 CONTINUE

```

```

421 PHB(KC,J)=DM1*TETA
422 DM1=SHB(KC)+PHB(KC,J)
423 DVM=SDV(KC)
424 TER(KC,J)=SIN(DM1)*DVM+VM(KC,J)+CCUR*COB(DM1)*ALEN(KC)
***** 53 CONTINUE
426 40 CONTINUE
427 RETURN
428 END

```

```

*****
C CONCLUDE SPLINE FOR
429 SUBROUTINE SPLINE(X,F,N,AA,BB,CC,DD,KA,NB,SLP,T)
* gives X,F,N,AA,BB,CC,DD,KA,NB,
* returns SLP,T
*****
430 INTEGER N,KA,NB,KD1,KDN
431 INTEGER I,J,K
432 REAL X(N),F(N),SLP(N),T(N)
433 REAL AA,BB,SLP1,SLP2
434 REAL DR(50),AL(50),SB(50),CL(50)
*****
435 REAL CC,DD,ALAM1,ALAM2
*****
436 SLP1=AA
437 SLP2=BB
438 ALAM1=CC
439 ALAM2=DD
440 KD1=KA
441 KDN=KB
*****
C***PROGRAM TO DETERMINE THE SLOPES AND CURVATURES BY THE SPLINE FIT
C***SLP1=SLOPE AT END 1
C***SLP2=SLOPE AT END 2
C***ALAM1--PARAMETER TO BE USED FOR RUNOUT AT END 1
C***ALAM2--AS ABOVE FOR END 2
C***KD1,KDN--FLAGS WHICH INDICATE THE END CONDITIONS
C   KD=1,SLOPES SPECIFIED
C   KD=2,RUNOUT SPECIFIED
C***KD=3,FLEX POINT SPECIFIED
C***SLOP--SLOPE AT EACH GRID POINT
C***C***SLP--slope at each grid point
*****
442 AL(1)=0
443 DR(1)=0
444 DO 10 I=2,N
445   AL(I)=X(I)-X(I-1)

```

```

446 DR(I)=R(I)-R(I-1)
447 10 CONTINUE
448 DO 520 J=1,N
449 IF(J.GT.1.AND.J.LT.N) GO TO 555
C KEND IS THE CODE WHICH DETERMINES THE END CONDITIONS
450 KD=KDN
451 IF(J.EQ.1) KD=KDI
452 IF(KD.EQ.1) GO TO 525
453 IF(KD.EQ.2) GO TO 530
C FOR FLEX POS.
454 W=0.
455 SINJ=0.
456 G(I)=0
457 GO TO 520
C COEFF'S FOR THE SLOPES SPECIFIED
458 525 IF(J.EQ.N) GO TO 535
459 A=0.
460 B=AL(2)/3
461 C=AL(2)/6
462 D=DR(2)/AL(2)*SLP1
463 GO TO 540
464 535 A=AL(N)/6
465 B=AL(N)/3
466 C=0.
467 D=SLP2*DR(N)/AL(N)
468 GO TO 545
C COEFF'S FOR RUNOUT
469 530 IF(J.EQ.1) GO TO 550
470 A=ALAM2
471 B=1
472 C=0.
473 D=0
474 GO TO 545
475 550 A=0
476 B=1
477 C=ALAM1
478 D=0
479 540 W=B
480 SINJ=C/W
481 G(I)=D/W
482 GO TO 521
483 555 A=AL(J)/6
484 B=(AL(J)+AL(J+1))/3
485 C=AL(J+1)/6
486 D=DR(J+1)/AL(J+1)*DR(J)/AL(J)
487 C=AL(J+1)/6
488 C=AL(J+1)/6

```

```

489 D=DR(J+1)/AL(J+1)*DR(J)/AL(J)
490 545 W=B-A*SIN(J-1)
491 SINJ=C/W
492 G(I)=(D-A*G(J-1))/W
493 521 CONTINUE
494 520 CONTINUE
495 T(N)=G(N)
496 DO 30 K=2,N
497 KK=N+1-K
498 30 T(KK)=G(KK)*SIN(KK)*T(KK+1)
499 SLP1=(T(1)-T(1))/AL(2)/3-T(2)/AL(2)*6+DR(2)/AL(2)
500 DO 45 KP=2,N
501 SLPK=P-T(KP)*AL(NP)/3+T(KP-1)*AL(KP)*6+DR(KP)/AL(KP)
502 45 CONTINUE
503 RETURN
504 END

```

```

C
C$INCLUDE RVELM FOR
505 SUBROUTINE RVELM
C
C PROGRAM TO COMPUTE THE MERIDIONAL VELOCITY DISTRIBUTION FOR ANY NORM
C CHECK FOR CHECKED FLOW
*****
506 IMPLICIT LOGICAL(A-Z)
*****add common statements and their initializations
C$INCLUDE ONE BLK
*1 initialize variables from block one
507 INTEGER NTYPE
508 REAL DN,VM,VT,PST,TST,DELN,R,Z,TER1,FNN,PHI,ALEN,BLCK,AREA,
1 ROTV,DELPO,DSM,SHIP,DSPT,DELTA,ARA,RHZ,RT,ZT
*****METHOD
*****
*****real 11, legend 50, legend+1 51
509 COMMON /CB1/DN(11,51),
1 VM(11,50),VT(11,50),PST(11,50),TST(11,50),DELN(11,50),
1 R(11,50),Z(11,50),TER1(11,50),FNN(11,50),PHI(11,50),
1 ALEN(11,BLCK(11),AREA(11),NTYPE(11),ROTV(11),
1 DELPO(11,50),DSM(11,50),SHIP(11,2),DSPT(11,2),DELTA(11,2),
1 ARA(11,ARA(11),ZIN(11),RT(11),ZT(11))
*****METHOD(11)
C$INCLUDE TWO BLK
*2 initialize variables from block two
510 REAL TM1,TM2,POR2,TOR2,Q,ALP,DU,MH,CFPO,CTO,CFVT,CFAL,YQ

```



```

553      TMX(J)=TMX(J)*ALEX(NST)
554      WSQ(J)=VM(NST,J)**2*(1.0+TM4(J)**2)
555 300 CONTINUE
556      GO TO 830
557      *
558      *do the following for design mode
559      *or the first station of analysis mode
560      C TANG. VELOCITY KNOWN
561      *compute functions of tangential velocity Vo which are required to
562      *solve radial equilibrium equation
563      C
564 820 OMA=0.0
565      DO 310 J=1,NG
566      TM4(J)=VT(NST,J)*VM(NST,J)**2)
567      TM4(J)=1.0
568      RVT(J)=R(NST,J)*VT(NST,J)
569      TM5(J)=0.0
570      WSQ(J)=VM(NST,J)**2*VT(NST,J)**2
571 310 CONTINUE
572      *
573      C
574      C COMPUTE THE PROPERTY DERIVATIVES
575      * of  $d(\rho/\delta S)/d(\ln r^2)/(\beta T A)/\rho a_c d(RV)/\delta S$ 
576      * using forward, central, backward finite difference technique
577      DO 520 J=1,NG
578      DN1=DN(NST,J)
579      IF(J.EQ.NG)THEN
580      DQDS=DER1(Q(J),Q(J+1),DN1)
581      DVDS=DER1(RVT(J),RVT(J+1),DN1)
582      DHDS=DER1(DUMH(J),DUMH(J+1),DN1)
583      ELSE IF(J.EQ.1)THEN
584      DN2=DN(NST,2)
585      DQDS=DER1(Q(J+1),Q(J),DN2)
586      DVDS=DER1(RVT(J+1),RVT(J),DN2)
587      DHDS=DER1(DUMH(J+1),DUMH(J),DN2)
588      ELSE
589      DN2=DN(NST,J+1)
590      DQDS=DER2(Q(J+1),Q(J),Q(J+1),DN2,DN1)
591      DVDS=DER2(RVT(J+1),RVT(J),RVT(J+1),DN2,DN1)
592      DHDS=DER2(DUMH(J+1),DUMH(J),DUMH(J+1),DN2,DN1)
593      ENDF
594      TS=FOR2(J),WSQ(J),2.0*CON2)
595      TM1(J)=TER1(NST,J)
596      TM2(J)=DHDS-TS*DQDS**0.50**A1

```

```

586      TMX(J)=TM4(J)*(DVDS+TM5(J))
587 520 CONTINUE
588 50 DO 10 J=1,NGRID
589      IF(J.EQ.1) GO TO 15
590      C
591      C PREDICT THE meridional VELOCITY.
592      DVTN=TM4(J-1)
593      DVTN=DVTN*(TM2(J-1)*VM(NST,J-1)*(TM1(J-1)+TMX(J-1))*VM(NST,J-1))
594      VM(NST,J)=VM(NST,J-1)*DN(NST,J)*DVTN
595      C
596      C CHECK THIS VELOCITY AND IF O.K., CORRECT THE VELOCITY
597      IF(VM(NST,J).GE.10.0)GO TO 16
598      DO 17 K=J,NGRID
599      VM(NST,K)=10.0
600      CONTINUE
601      KNEG=1
602      GO TO 15
603      C
604      D2=TM4(J)*(TM2(J)*VM(NST,J)*(TM1(J)+TMX(J))*VM(NST,J))
605      DVTN=(D2+DVTN)/2.0
606      IFNIT EQ 0)DVTN=0.0
607      VM(NST,J)=VM(NST,J-1)*DN(NST,J)*DVTN
608      IF(VM(NST,J).GE.10.0)GO TO 15
609      DO 14 K=J,NGRID
610      VM(NST,K)=10.0
611      CONTINUE
612      KNEG=1
613      GO TO 15
614      C
615      *if first station go to calculation of flow properties
616      IF(NST EQ 1) GO TO 510
617      * if design mode (NFDES=0) and if last calculation plane was at
618      * entrance to rotor (NTYPE=1)
619      IF(NFDES EQ 0 AND NTYPE(NST-1) EQ 1)THEN
620      * calculate flow properties V*2,Ts,Po
621      V2=VM(NST,J)**2*VT(NST,J)**2
622      T(J)=TST(NST,J)+V2/2.0*CON2)
623      PST(NST,J)=FOR2(J)*TST(NST,J)*FOR2(J)**GAMA*CON1)
624      GO TO 512
625      ENDF
626      * if location of last calculation plane is not at entrance to duct (NTYPE=3)
627      * compute tangential velocity Vo,Vow
628      IF(NFDES EQ 0 OR NTYPE(NST-1) EQ 3)GO TO 510
629      WT=VM(NST,J)*TAN(ALPH(J))
630      VT(NST,J)=WT+OMA*R(NST,J)
631      * calculate flow properties V*2,W*2,Ts,Ts,Po
632      CONTINUE
633 510

```


B-14


```

718 REAL XX(50),YY(50),ZZ(50)
      *Assumes for right
719 REAL AM(50),B(50),ANU(50),DLH(50),RO(50),WT(50),VT(50)
      *
      *RMAC(10) I can find no use for this W. Klein Aug 2, '91.
      *****
720 INTEGER NSEC,J
721 REAL RD,RDEN,RDOUT
722 REAL DM1,DM2,DEG,PHSL
      *****
723 GAM=GAMA
724 KOD=KCODE
725 KDE=KCODE
726 DEG=PI/180.0
727 BDHT=(RT(NST)*RT(NST+1)-(RM(NST)+RM(NST+1)))**12.0/2.0
728 DM1= 2.0*GO *AJ *CP
729 DM2= GAMA/(GAMA-1)
      *****
730 IF(KODE.EQ.3) GO TO 100
      C
      C for act obtained to duct
      C
731 IF(KBL.EQ.1) GO TO 110
      C
      C for first iteration of main program for stream line
      C convergence (KBL=0)
      C read initial pressure loss conf. (Y) distribution
      C
732 READ(IRD,4) (DELPQ(NST+1,J),J=1,NGRID)
733 IF(NPDES.EQ.1) GO TO 110
      C
      C for DESIGN MODE, read aspect ratio and design loss
      C correlation method (KLOSS: 0=import loss,1=A&M,2=
      C Sed-ridge,3=A.F.Carter)
734 READ(IRD,2)AB,KLOSS
735 WRITE(IRT,46) AB
736 46 FORMAT(1H1, //20X, 21HBLADE ASPECT RATIO OF ,F5.2)
      *
737 IF(KLOSS.EQ.0) GO TO 70
      *
      * design losses are to be calculated
      * GO TO (40,50,60),KLOSS
738 GO TO (40,50,60),KLOSS
739 40 WRITE(IRT,45)
740 45 FORMAT(//20X, 'ADNLEY&MATHIESON LOSS COEFFICIENT')
741 GO TO 110
742 50 WRITE(IRT,55)
743 55 FORMAT(//20X, 'SODERBERG LOSS COEFFICIENT')
      *
744 GO TO 110
745 60 WRITE(IRT,65)
746 65 FORMAT(//20X, 'A.F. CARTER LOSS COEFFICIENT')
747 GO TO 110
      *
748 70 CONTINUE
      * design losses are to be read as
749 WRITE(IRT,75)
750 75 FORMAT(//20X, ' INPUT LOSS COEFFICIENT')
751 GO TO 110
      *****
752 100 CONTINUE
      C for entrance to duct only,(all iterations) set pressure loss
      C conf (Y) distribution to 0.0
753 DO 101 K=1,NGRID
754 DELPQ(NST+1,K)=0.0
755 101 CONTINUE
      *****
756 110 CONTINUE
      C continue for design and analysis mode, all iterations
757 OMA=ROTV(NST)
      C
758 DO 111 J=1,NGRID
      *****
      * compute flow properties for inlet station
      *
759 AWT=VT(NST,J)*OMA*R(NST,J)
760 W2=AWT**2+VM(NST,J)**2
761 V2=VT(NST,J)**2+VM(NST,J)**2
762 T=TST(NST,J)-V2/DM1
763 AM(J)=SQRT(W2/GAMA*GO*RGAS*T)
764 B1(J)=ATAN2(AWT,VM(NST,J))
765 TOR1=T+W2/DM1
766 POR1=PT(NST,J)*(TOR1/TST(NST,J))**DM2
      *****
      * compute flow properties for outlet station
      *
767 DM3= 2 *GAMA*GO*RGAS*TOR1
768 DM4=(GAMA-1)*(OMA*R(NST+1,J))**2
769 TOR2=(TOR1**1+DM4/DM3)**(1-(R(NST,J)/R(NST+1,J))**2))
      * calculate the isentropic exit relative stagnation pressure
770 PO2IS=POR1*(TOR2)/(TOR1)**DM2
      C
771 IF(KODE.EQ.3) THEN
      C for duct assume no pressure loss (ie isentropic)
772 POR2=(PO2IS
773 GO TO 106

```



```

* read blade row  $\theta$ ,  $\theta$  of radial section blade prop. specified, and
* blade type
833 READ(RD,3) KB,NSEC(KB),KBLAD(KB)
*
834 NSEC=NSEC(KB)
835 KBST(NST)=KB
836 ENDIF
*
837 IF(NPDES.NE.1) GO TO 130
*
* for analysis mode
838 IF(KBL.EQ.1) GO TO 203
* for first iteration of MADM for nonlinear convergence
C
C READ THE INLET BLADE ANGLE
C READ THE CAMBER
C READ THE THICKNESS RATIO
C READ THE SOLIDITY
C AT EACH OF NSEC BLADE ELEMENTS OR SECTION AND THEN FIT POLYNOMIAL
C OF ORDER NORS TO EACH AS A FUNCTION OF RADIUS.
C
C READ THE LOSS AND DEVIATION METHODS FOR THIS BLADE ROW
839 READ(RD,4) (GEOM(KB,1),GEOM(KB,2),GEOM(KB,3),
1 GEOM(KB,4),GEOM(KB,5),GEOM(KB,6),GEOM(KB,7),
2 GEOM(KB,8),GEOM(KB,9),GEOM(KB,10),GEOM(KB,11),
840 READ(RD,5) (RDUM(KB,1),GEOM(KB,1),NSEC)
*
841 NNO=NTYPE(NST)
* convert the stations and rotors?
842 IF(NNO.EQ.1) THEN
* for rotor
843 NROTOR=NROTOR+1
844 ELSE
845 IF(NNO.EQ.2) THEN
* for stator
846 NSTOR=NSTOR+1
847 ENDIF
848 ENDIF
* write the rotor or stator number
849 GO TO (440,442,444),NNO
850 440 WRITE(TWT,441) NROTOR
851 441 FORMAT(/34X,10HROTOR NO.13/)
852 GO TO 444
853 442 WRITE(TWT,443) NSTOR
854 443 FORMAT(/33X,11HSTATOR NO.13/)
*
855 444 CONTINUE
*
* write the blade geometry
856 WRITE(TWT,446)
857 WRITE(TWT,447)
858 FORMAT(33X,14HBLADE GEOMETRY/)
859 447 FORMAT(1X,6HBLADE INLET 2X,13HBLADE OPENING 2X,
1 9HTHICKNESS 2X,5C'2X'CHORD'2X'SE'2X'TETS'2X,
1 'TCL',
1 /11X,'ANGLE'6X,'MATCH (deg)'5X,SHRATIO)
860 WRITE(TWT,449) (RDUM(KB,1),GEOM(KB,1),GEOM(KB,2),
1 GEOM(KB,3),GEOM(KB,4),GEOM(KB,5),GEOM(KB,6),
2 GEOM(KB,7),GEOM(KB,8),GEOM(KB,9),GEOM(KB,10),
* convert radii to feet
861 DO 200 J=1,NSEC
862 RDUM(KB,J)=RDUM(KB,J)/12.0
863 200 CONTINUE
*
864 203 CONTINUE
* continue here for all iterations: analysis mode
*
865 KB=KBST(NST)
866 NSEC=NSCT(KB)
*
867 DO 205 J=1,NGRID
868 RDN=R(NST,J)
869 RDOUT=R(NST+1,J)
870 RD121=(RDN+RDOUT)/2.
871 DO 205 K=1,8
872 RD=RD121
873 IF(K.EQ.2.OR.K.EQ.6.OR.K.EQ.7) XD=RDOUT
874 IF(K.EQ.1) RD=RDN
875 DO 205 L=1,NSEC
876 XX(L)=RDUM(KB,L)
877 YY(L)=GEOM(KB,K,L)
878 205 CONTINUE
* use linear interpolation to determine geometry at each
* grid point
879 S(K,J)=SLINE(RD,NSEC,XX,YY)
880 CONTINUE
881 205 CONTINUE
*
882 DO 204 J=1,NGRID
883 KAP1=S(1,J)
884 PHSL=ATAN(R(NST+1,J)-R(NST,J)/R(NST+1,J)-Z(NST,J)))
885 PHSL=CCOS(PHSL)
886 KAP2=ACOS(S(2,J))/DEG
* following 3 are components in axial direction?
887 TRAT=S(3,J)/PHSL

```

```

888 SOL=S(4,J)PHSL
889 CORD=S(5,J)PHSL
890
891 TER=S(6,J)
892 IF(KODE.EQ.1)THEN
893   SGN=1.0
894 ELSE
895   SGN=1.0
896 ENDIF
897 TET=S(7,J)
898
899 *tip clearance
900 TCL=S(8,J)
901 IF(KBLEQ.1) GO TO 605
902 REYN=2.0
903 CPRE=1.0
904 GO TO 602
905 CONTINUE
906 REYN=1.0E-05*WT2/J*CORD/(ANU(J)*12.)
907 EX=0.2
908 IF(REYN GT 2.0) EX=0.1
909 CPRE=(2.0*REYN)**EX
910 CONTINUE
911 INQ=NST+1
912 NCR=J
913 BET1=B(1,J)/DEG
914 VRAT=VM(NQNJ)/VM(NST,J)
915 RRAB=DEL(NST,J)*100
916 K99L=K9L
917 KSEB=KBLAD(KB)
918
919 *
920 *
921 *
922 ET1=S(NST,J)
923 ET2=S(NST+1,J)
924
925 C
926 CALL CASCAD
927
928 C
929 DQ9M(KB,J)=YPO
930 DEVN(KB,J)=YFN
931 ODK(KB,J)=ACN
932 DK(KB,J)=SI
933 DL(KB,J)=YS
934 ODD(KB,J)=DEV
935 PROL(KB,J)=YP
936 DQ9N(KB,J)=WU
937
938 ***** tip clearance loss coefficient
939 DFAC(KB,J)=YK
940
941 *****YTIP(KB,J)=YCURVE
942
943 SHL(KB,J)=REYN
944 ODL(KB,J)=CPRE
945 ALP(J)=BET2*DEG*SGN
946 DELPO(NQNJ)=YS+YF*CPRE+YK
947 IF(DELPO(NQNJ).GT 0.5)DELPO(NQNJ)=0.5
948
949 * next J (next grid point)
950
951 204 CONTINUE
952
953 C
954 C
955 C
956 C
957 C
958 C
959 C
960 C
961 C
962 C
963 C
964 C
965 C
966 C
967 C
968 C
969 C
970 C
971 C
972 C
973 C
974 C
975 C
976 C
977 C
978 C
979 C
980 C
981 C
982 C
983 C
984 C
985 C
986 C
987 C
988 C
989 C
990 C
991 C
992 C
993 C
994 C
995 C
996 C
997 C
998 C
999 C
1000 C

```

```

999      XX(L)=DUM(KB,L)
900      YY(L)=DHO(KB,L)
901      CONTINUE
902      DO 754 J=1,NGRID
903          RD=R(NST+J)
904          VTT(J)=SLINE(RD,NSBC,XX,ZZ)
905          DLH(J)=SLINE(RD,NSBC,XX,YY)
906          CONTINUE
907          OMEGA=OMEG*PI/70
908          DO 131 J=1,NGRID
909              VT(NST+J)=GOPAJ*DLH(J)*OMEGA+R(NST+J)*VTT(J)*R(NST+J)
910              TST(NST+J)=TST(NST,J)
911          CONTINUE
912          GO TO 520
913      *
914      *   for entrance to rotor
915      DO 655 J=1,NGRID
916          VT(NST+J)=VTT(J)
917          TST(NST+J)=TST(NST,J)+DLH(J)*CF
918          DUMH(J)=CF*TST(NST+J)
919      CONTINUE
920      *
921      *   continue from here for analysis mode
922      CONTINUE
923      CONTINUE
924      *****F O R M A T   S T A T E M E N T S*****
925      2   FORMAT(P10.0,12)
926      3   FORMAT (E2)
927      4   FORMAT(16F5.0,16F5.0,16F5.0,16F5.0)
928      5   FORMAT(BF10.0)
929      6   FORMAT(BF10.0)
930      333  FORMAT(IH1)
931      449  FORMAT(1X,F6.3,4X,F6.2,7X,F6.3,8X,F4.2,5X,F4.2,
932            1 2X,F5.2,2X,F5.2,2X,F5.2,2X,F5.2)
933      448  FORMAT (15X,'DESIGN BLADE LOADING' //5X,'ENTHALPY DROP' //10X,
934            1 1X,'SWIRL VELOCITY',6X,'RADIUS',
935            1 //25(7X,F6.3,12X,F6.3,12X,F5.2,/)
936      *****
937      RETURN
938      END
939
940      *****
941      SUBROUTINE CASCAD FOR
942      SUBROUTINE CASCAD
943      C
944      C

```

```

1015 30  CONTINUE
      *Deviation for outlet relative mach number greater than 1
      *using isentropic relation to find Area/(Area at sonic throat)
1016      AA=2.0/(GM+1.0)
1017      AS=1.0/(GM-1.0/2.0)*RM2**2
      *****
      **the following line includes a variable which does not exist (M2IN)
      **therefore I am replacing M2IN with RM2 which is what I believe it should
      **be Wendy Klein Dec. 18, '90.
      **      AA=1.0/M2IN
      *****
1018      AA=1.0/RM2
1019      EX=(GM+1.0/2.0*(GM-1.0))
1020      ARAT=AA*(AA**AS)**EX
1021      CSB2=ARAT**COS(KAT2*DEG)
1022      B2=ACOS(CSB2)
1023      BET2=B2/DEG
1024      DEV=KAP2*BET2
      *
1025 40  CONTINUE
      * for all outlet M #'s and iterations for MAIN
      C
      C *****PROFILE LOSS - ANLEY & MATHIESON CURVES*****
      C *****
      * beta1 = 0
1026      E1=1078E+00+.2541E-03*BET2
1027      E2=1948E+00+.60714E-03*BET2
1028      E3=5430E-01+.1530E-02*BET2
1029      YPN=E1+E2*SOL+E3*SOL**2
      * beta1 = beta2
1030      B4=3125E+00-12646E-02*BET2
1031      B5=7932E+00+.6746E-02*BET2
1032      B6=3901E+00-1692E-02*BET2
1033      YPI=B4+B5*SOL+B6*SOL**2
      C
      C PROFILE LOSS AT ZERO INCIDENCE
      C *****
1034      ANR=ABS(BET1/BET2)
1035      TTR=TRAT/0.2
1036      YPO=YPI*ANR**2*(YPI*YPN)**TTR**ANR
      C
      C COMPUTE STALLING INCIDENCES
      C *****
      * fig 14c Ngo
1037      BF(SOLLE 0.75) THEN
1038      DELLS=18.30E-23.62*SOL
1039      ELSE

```

```

      C1=1798E+03-.3027E+01*BET2
      C2=.4664E+03+.8377E+01*BET2
      C3=.2804E+03-.5785E+01*BET2
      DELLS=C1+C2*SOL+C3*SOL**2
1044      ENDP
      *****
      C STALLING INCIDENCE AT SOC=0.75
      C *****
      * fig 14 b Ngo
1045      D1=-.245E+02+.9033E+00*BET2
1046      D2=-.4554E+01-.720E-01*BET2
1047      D3=-.3920E+02-.9402E+00*BET2
1048      SB=D1+D2*ANR+D3*ANR**2
      C
      * fig 14b and 14a combined to get stalling incidence at sc
      C SI=SB*DELLS
1049      *****
      C PROFILE LOSS AT ANGLE OF INCIDENCE
      C *****
      C ACTN=BET1-KAP1
1050      SINR=ACTN/SI
1051      *****
      * curve fit of fig 15 Ngo
1052      YPN=YPO*(1.0-.0835*SINR+.89*SINR**2+.35*SINR**3+.055*SINR**4)
      C
      C SECONDARY LOSS -- DUNHAM'S IMPROVED METHOD
      C *****
1053 64  B1=BET1*DEG
1054      TBM=(TAN(B2)+TAN(B1))/2.0
1055      BETAM=ATAN(TBM)
1056      WU=.4*(TAN(B1)+TAN(B2))**2**COS(B2)**2**COS(BETAM)
1057      AR=BDMT/CORD
1058 65  YS=.0334*WU**COS(B2)/COS(B1/PAR)
      C
      C EFFECT OF TRAILING EDGE THICKNESS
      C *****
      * equation 43 Ngo (linear approximation to Fig 22 Ngo)
1059      THF=.1*(.07*(P/TET-.02))
1060      YP=YPI*THF
      C
      C EFFECT OF TIP CLEARANCE
      C *****
      * B=0.5 FOR PLAIN TIP CLEARANCE B=0.25 FOR SHROUDED
      * for plain only
      C
      C B=0.5
1061      YK=B*TCCL*WU/BDMT
1062      *****
      C IF YS GT 0.31 YS=0.3
1063

```

```

1064      RETURN
1065      END

C
C-----
C SUBROUTINE PILOSS
C
C-----
C INCLUDE SEVEN BLK
C * initialize variables from block seven (pi loss)
1067      INTEGER KLOSS,KDE
1068      REAL VRATD,BETA1,BETA2,GM1,RMDZAR,WUD,YSD,
1      YPD,EPFX,ZETA,YTA,YTS,YTC
C
C-----
1069      COMMON/PILOSS/KLOSS,VRATD,BETA1,BETA2,GM1,RMDZAR,WUD,YSD,
1      YPD,EPFX,ZETA,YTA,YTS,YTC,KDE
C
C THIS SUBROUTINE CALCULATES THE DESIGN LOSS COEFFICIENTS
C
C KLOSS=0 INPUT LOSS COEFFICIENT
C KLOSS=01 ANLEY & MATHIESON'S LOSS CORRELATION
C KLOSS=02 SODERBERG'S LOSS CORRELATION
C KLOSS=03 A F CARTER'S LOSS CORRELATION
C-----
1070      REAL PI
C-----
1071      PI=3.141592654
C-----
1072      BTM=(TAN(BETA2)-TAN(BETA1))/2
1073      BTM=ATAN(BTM)
1074      WUD=4*(TAN(BETA1)+TAN(BETA2))*2*COS(BETA2)**2/COS(BTM)
C-----
C ANLEY & MATHIESON LOSS CORRELATION
C
C
C YSD=0.0334*WUD*COS(BETA2)/AR*COS(BETA1))
B=BETA2*180/PI
YPN=87241E-01-.3067E-02*B+.33799E-04*B**2
YPI=.16031E+00-.53802E-02*B+.70465E-04*B**2
YPD=YPN+YPI*(BETA1/BETA2)**2*(YPI-YPN)
C TIP CLEARANCE OF 1% BLADE HEIGHT - B=0.5
YKA=.005*WUD

```

```

1081      IF(KDE EQ 2)YKA=0.0
1082      YTA=YPD+YSD+YKA
C-----
C SODERBERG LOSS CORRELATION
C
C (P98-100 Fluid Mechanics, Thermodynamics of Turbomachinery
C S L Dixon (ed))
C EFX=epsion.ZET-sets*ZETA-sets
C-----
1083      EFX=BETA1*180/PI+B
1084      ZET=.46416E-01-.22734E-03*EPFX+.82142E-05*EPX**2
1085      ZETA=1+ZET*(0.975+.075/AR)**1.0
C * convert from enthalpy loss coefficient to pressure loss coef
C * set pA3 "The design and performance prediction of axial flow
C * turbines" Naga.
1086      CON1=GM1/(GM1-1.0)
1087      DPPI=1-ZETA*(GM1-1.0)*RMDZ**2/2.0*CON1
1088      TRAT=1-(GM1-1.0)*RMDZ**2/2.0*CON1
1089      YTS=(1-DPPI/DPPI)*(TRAT/TRAT-1.0)
C-----
C A F CARTER LOSS CORRELATION
C-----
1090      IF(VRATD GT 0.54) GO TO 20
1091      YTC=WUD*0.0135*(0.64-0.8*COS(BETA2))
1092      GO TO 111
1093 20      YTC=WUD*(0.0135+0.091*(VRATD-0.54)/
1      (0.64-B*COS(BETA2)))
1094 111      CONTINUE
1095      IF(YTC GT 0.3) YTC=0.3
1096      RETURN
1097      END
C-----
C CONCLUDE SLUNE FOR
1098      FUNCTION SLUNE(XN,XS,YS)
C-----
C * This function finds the position of a number X relative to a set of
C * numbers XS such that (XS(L1)-X < XS(L2)), then tests linear
C * interpolation to find the corresponding value Y from the matrix YS
C * using the position from XS. The form of the equation is
C * Y=Y1+(X-X1)*(X2-X1)/(Y2-Y1)

```

```

*****
****This file was last edited Mar 16, '91
*****
1099  REAL X(XS(NX),YS(NX))
1100  INTEGER J,N1,L1,L2
*****

```

```

C
C  FIND THE BOUNDING X-VALUES.
1101  IF(XS(1)GT XS(NX))THEN
1102    DO 30 J=2,NX
1103      JN=J
1104      IF(X GT XS(J)) GO TO 40
1105 30  CONTINUE
1106  ELSE
1107    DO 31 J=2,NX
1108      JN=J
1109      IF(X LT XS(J)) GO TO 40
1110 31  CONTINUE
1111  ENDIF
1112 40  L1=JN-1
1113  L2=JN
1114  DENUM=XS(L2)-XS(L1)
1115  PCTX=X-XS(L1)/DENUM
1116  IF(ABS(DENUM)LT 1.0E-3) PCTX=0.0
1117  SLNE=YS(L1)+PCTX*(YS(L2)-YS(L1))
1118  RETURN
1119  END

```

```

*****
*****
C
CENCLUDE WRITE FOR
*
* Subroutine ROUTE edited by Wendy Kiern, June 1990.

```

```

*
* last updated July 8, '92 by Wendy Kiern
*
1120  SUBROUTINE WRITE
C*****COMMON STATEMENTS*****
CENCLUDE ONE BLK
*1 initialize variables from block one
1121  INTEGER NTYPE
1122  REAL DN,VN,VT,PST,IST,DELN,R,Z,TER1,FMN,PHALEN,BLCK,AREA,
1 ROTV,DELPO,DSM,SHF,DSPT,DELT,ARA,RHZHRT,ZT
*****METHOD
*****
*****init 11, ngrd 50, ngrd+1 51
1123  COMMON ACB/DN(11,51)
1 VN(11,50)/VT(11,50)/PST(11,50)/TER1(11,50)/DELN(11,50)/
1 R(11,50)/Z(11,50)/TER1(11,50)/FMN(11,50)/PHI(11,50)/
1 ALEN(11,50)/CK(11,50)/AREA(11,50)/NTYPE(11,50)/ROTV(11,
1 DELPO(11,50)/DSM(11,50)/SHF(11,2)/DSPT(11,2)/DELT(11,2)/
1 ARA(11,50)/RHZHRT(11,2)/ZT(11,
*****METHOD(11,
CENCLUDE TWO BLK
*2 initialize variables from block two
1124  REAL TM1,TM2,FOR2,TOR2,QALP,DUMH,CFFOC,CTOC,FVT,CFAL,YQ
* *****
*****ngrd - 50, ngrd+1 - 51
1125  COMMON ACB/TM1(50),TM2(50),FOR2(50),TOR2(50),QALP(50),DUMH(50),
1 DUMH(50),YQ(50),
2 CFFOC(51),CTOC(51),CFVT(51),CFAL(51)
CENCLUDE THREE BLK
*3 initialize variables from block three
1126  INTEGER NT,KODE,NBNDX,NFDES,NFBL,NST,KBL,ABORT,NT,KALK,VT
1127  REAL OMEG,OMA,OK
* *****
1128  COMMON ACB/NT,KODE,NBNDX,NFDES,NFBL,NST,KBL,ABORT,NT,
CENCLUDE FOUR BLK
*4 initialize variables from block four
1129  INTEGER NSTAT,NGRID,NTU,BE,NORD1,NPTS,IRD,INT
1130  REAL PO,TO,HO,DESM,GAMA,IRGAS,CP,G0,PLA,TONS,TOLM,WGHT
* *****
1131  COMMON/BLK1/NSTAT,NGRID,NTU,BE,NORD1,PO,TO,HO,DESM,GAMA,IRGAS,CP,
CENCLUDE SIX BLK
*11 initialize variables from block six (old)
1132  INTEGER NPMNT,NROT,NSTOR,KB,NBLAD,NST,KBST
1133  REAL ODD,DLD,ODD,PROL,DEOF,DFAC,SHL,ODL,DEGM,DEVM
* *****init 11 ngrd 50

```



```

1134 COMMON /BLADNPRINT,NIROT,NSTOR,KB,KBLAD(11),NSCT(11),KBST(11),
1 CDD(11,50),DK(11,50),DL(11,50),ODD(11,50),PROL(11,50),
2 DQQR(11,50),DFAC(11,50),SHEL(11,50),ODL(11,50),
3 DQOM(11,50),DEVN(11,50)

C$INCLUDE EIGHT BLK
*9 initialize variables from block 8 (DESL)
1135 REAL VRTIO,DEF,SODL,ANI,CARLASL,APL,FACL
* *****
1136 COMMON /DESL,VRTIO(12,50),DER(12,50),SODL(12,50),ANIL(12,50),
C$INCLUDE TEN BLK
*10 initialize variable from block 10 (POS)
1137 REAL AMCAL
* *****
1138 COMMON /POS,AMCAL(20)
* *****
C$INCLUDE TWONE BLK
1139 INTEGER TPMTHD,TPCNT
1140 REAL X1,Y1,X2,Y2,X3,Y3,A,MY1,DAMP,AGREE,Y2NTL,LOSREQ
1 LOSCUR,TRPGAP,AMFLW,RD12,YTIP
* *****
1141 COMMON /TWO,EX1,X2,X3,Y1,Y2,Y3,A,MY1(12),DAMP(5),AGREE,Y2NTL,
LOSREQ,LOSCUR,TRPGAP,TPCNT,TPMTHD,
2 RD12(50),YTIP(11,50),AMFLW(11,50)

*****DIMENSION STATEMENTS*****
*dimension for agrid
1142 REAL TA(50),PA(50),AMA(50),WTU(50),TRU(50),PRU(50)
1143 REAL RAD(50),AMU(50),UU(50),UD(50),T,4r(50),FLU(50),
1 FLD(50)
1144 REAL TRD(50),PRD(50),AMD(50),WTD(50)
1145 REAL PRAT(50),TRAT(50)
1146 REAL VTAM(50),VTRLU(50),VTRLD(50)
1.47 REAL PSTA(50),TSTA(50)
1148 REAL WORK(50),REAC(50),WKC(50),FLOW(50)
*dimension for act=3
1149 REAL POWER(3),PR(3),TR(3),EFF(3),TRIS(3)
*
1150 REAL ANX
*****
C
C COMPUTE THE ABSOLUTE CONDITIONS
1151 DO 783 LK=1,NGRID
1152 DELPO(1,LK)=0.0
1153 783 CONTINUE

```

```

C *****COMPUTE AND PRINT THE VARIABLES AT EACH STATION
1154 NIROT=0
1155 KPG=0
1156 DO 100 I=1,NSTAT
1157 IJ=0
1158 NPLG=0
1159 WRITE(NWT,2)
1160 DO 110 J=1,NGRID
1161 V2=VM(LJ)**2,V7,V7_LJ**2
1162 VTAB(J)=SQRT(V2)
1163 AO2= GAMA*GOPRGAS*TST(LJ)
1164 CON1=GAMA-1
1165 CON2=1-CON1*V2/2*AO2
1166 PRAT(IJ)= (PST(LJ)/PST(LJ))**(CON1/GAMA+1.0)
1167 TRAT(IJ)=(TST(LJ)/TST(LJ))-1.0
1168 P=PST(LJ)*CON2**(GAMACON1)
1169 T=TST(LJ)*CON2
1170 PSTA(IJ)=P/144
1171 TSTA(IJ)=T
1172 TA(IJ)=TST(LJ)
1173 PA(IJ)=PST(LJ)/144
1174 A=SQRT(GAMA*GOPRGAS*T)
1175 AMA(IJ)=SQRT(V2)/A
1176 RODM=PST(LJ)/WPGAS*TST(LJ)
1177 RO=RODM*(1-(GAMA-1)*AMA(IJ)**2)**(1/CON1)
1178 YQ(IJ)=RO*VM(LJ)*R(LJ)
1179 FLA(IJ)=ATAN(VT(LJ)/VM(LJ))*180/PI

C
C COMPUTE CONDITIONS RELATIVE TO THE UPSTREAM ROW
IF(LEQ.1) GO TO 20
1180 WTU(IJ)= VT(LJ)/ROTV(1-I)*R(LJ)
1181 W2=WTU(IJ)**2+VM(LJ)**2
1182 VTRLU(IJ)=SQRT(W2)
1183 TOR=T+W2/2.0*GOPAJ*CP
1184 POR=PST(LJ)*TOR/TST(LJ)**(GAMACON1)
1185 TRU(IJ)=TOR
1186 PRU(IJ)=POR/144
1187 AMU(IJ)=SQRT(W2)/A
1188 UU(IJ)=ROTV(1-I)*R(LJ)
1189 FLU(IJ)=ATAN(WTU(IJ)/VM(LJ))*180/PI

C
C COMPUTE CONDITIONS RELATIVE TO THE DOWNSTREAM ROW
IF(1EQ,NSTAT) GO TO 30
1191 20 WTD(IJ)=VT(LJ)/ROTV(1)*R(LJ)
1192 W2=WTD(IJ)**2+VM(LJ)**2
1193 VTRLD(IJ)=SQRT(W2)
1194

```

```

1195 TOR=T*W/21*GO*AP*CT)
1196 FOR=FT(LJ)*TOR/ST(LJ)**(GAMMA*CON1)
1197 TRD(J)=TOR
1198 PRD(J)=FOR/144
1199 AMD(J)=SQRT(W/2*VA
1200 UD(J)=ROTV(0)*R(LJ)
1201 FLX(J)=ATAN(WTDX(J)*VM(LJ))*180/PI
1202 30 CONTINUE
1203 RAD(J)=R(LJ)*12
1204 110 CONTINUE
1205 JTOT=J
C
1206 ANX=AREA(J)*144
*added
1207 IF (NIT EQ 1) THEN
1208 AREA(J)=AREA(J)
1209 ENDDIF
1210 PAB=(1.0-ARA(J)/AREA(J))*100
1211 WRITE(IWT,120) I,PAB,ANX
C
1212 WRITE(IWT,130)
1213 WRITE(IWT,140) (RAD(L),FLA(L),VM(L),VT(L),VTAB(L),AMA(L),
1 PA(L),PSTAILX,TAL,TSTA(L),L=NGRID,1.-1)
1214 IF (EQ 1) GO TO 7
1215 NC=NTYPE(J)
1216 GOTO (149,149,7)NC
1217 149 WRITE(IWT,150)
1218 GO TO (204,205,7)NC
1219 204 WRITE(IWT,214)ROTV(J)
1220 DO 160 I=1,NGRID
1221 WT(I)=VT(I-L,J)-ROTV(I-1)*R(I-1,J)
1222 W1=WTU1**2+VMA1-L,J**2
1223 WORK(J)=ROTV(I-1)*R(I-1,J)*VT(I-L,J)-ROTV(I-1)*R(LJ)
*VT(LJ)
1224 RSP=ROTV(I-1)*R(I-L,J)*R(LJ)/2.0
1225 WK(CJ)=WORK(J)/RSP**2
1226 FLOW(J)=VM(L-L,J)/ROTV(I-1)*R(I-1,J)
1227 160 REAC(J)=VTRLU(J)**2-W1/2.0*WORK(J)
1228 RMEAN=(RM(J)-RT(B)-RH(J)-1)*RT(I-1)/4
1229 UMEAN=ROTV(I-1)*RMEAN
1230 ACX=0.0
1231 WKM=0.0
1232 DO 165 I=2,NGRID-1
1233 ACX=ACX+VM(I-L,J)
1234 WKM=WKM+WORK(I-L)*VM(I-L,NGRID)/2.0*NGRID-1)
1235 ACX=(ACX+VM(I-L,1)+VM(I-L,NGRID)/2.0*NGRID-1)
1236

```

```

1237 COBFL=ACX/UMEAN
1238 COEPW=WKM/UMEAN**2
1239 UMH=ROTV(I-1)*RM(I-1)+RH(I)/2.0
1240 COEPWH=WORK(1)/UMH**2
1241 COEPFH=VM(I-1,1)/UMH
1242 GO TO 230
1243 205 WRITE(IWT,215)
1244 DO 161 J=1,NGRID
1245 WK(CJ)=0.0
1246 FLOW(J)=0.0
1247 161 REAC(J)=0.0
1248 230 CONTINUE
1249 WRITE(IWT,232)
1250 WRITE(IWT,233) (DELPO(J),FLU(J),WTU(J),VTRLU(J),UU(J),AMLU(J),
1 PRU(J),TRU(J),REAC(J),WK(CJ),FLOW(I,J)=NGRID,1.-1)
1251 KB=KBST(I-1)
C
C PRINT OUT BLADE ELEMENT DATA FOR THIS BLADE ROW
1252 WRITE(IWT,1)
1253 KPG=KPG+1
1254 WRITE(IWT,201) I,NIT
1255 IF(NIDES NE 1) GO TO 9
1256 WRITE(IWT,203)
1257 WRITE(IWT,202)KOD(KB,J),DK(KB,J),DEQ(KB,J),ODDKB,J),DL(KB,J),
1 DEQMI(KB,J),DEVMI(KB,J),PROU(KB,J),DFAC(KB,J),SHL(KB,J),ODU(KB,J),
2 J=NGRID,1.-1)
1258 GO TO 10
1259 9 WRITE(IWT,208)
1260 WRITE(IWT,207)DEH(J),SODU(LJ),FAC(LJ),AS(LJ),
1 APL(LJ),AUN(LJ),VRTIC(LJ),CARU(LJ),J=NGRID,1.-1)
1261 10 CONTINUE
1262 IF(KPG EQ 2) KPG=0
1263 7 CONTINUE
1264 IF (EQ NSTAT) GO TO 8
1265 IF (NTYPE(I) NE 1) GO TO 8
C
1266 WRITE(IWT,151)
1267 WRITE(IWT,214)ROTV(I)
1268 WRITE(IWT,234)
1269 WRITE(IWT,235) (RAD(J),FLD(J),WTD(J),VTRLD(J),UD(J),AMD(J),
1 PRD(J),TRD(J),J=NGRID,1.-1)
1270 8 CONTINUE
1271 45 CONTINUE
C
C NCT=1 FOR CUMULATIVE P.R.T.R

```

```

1272 IF(LE 3) GO TO 100
1273 NCT=0
1274 420 NCT=NCT+1
1275 NC1=NTYPE(1-1)
1276 NC2=NTYPE(1-2)
1277 NPAC=0
1278 IF(NCT.EQ.1) GO TO 421
1279 IF(NC1.NE.1) GO TO 100
1280 IF(NCT.EQ.3) GO TO 23
1281 NROT=NROT+1
1282 NSI=4-1
1283 GO TO 22
1284 23 NSI=2
1285 22 DO 25 J=1,NGRID
1286 PRAT(J)=PST(NSLJ)/PST(LJ)**(CON1/GAMA)-1.0
1287 TRAT(J)=TST(NSLJ)/TST(LJ)-1.0
1288 25 CONTINUE
1289 421 CONTINUE
C
C COMPUTE MASS AVERAGED PROPERTIES
1290 SUMT=0.0
1291 SUMP=0.0
1292 DO 410 J=2,NGRID-1
1293 SUMP=SUMP+PRAT(J)
1294 410 SUMT=SUMP+PRAT(J)
1295 SUMP=SUMP+PRAT(1)+PRAT(NGRID)/2. W(NGRID-1)
1296 SUMT=SUMT+TRAT(1)+TRAT(NGRID)/2. W(NGRID-1)
1297 PR(NCT)=1.0+SUMP***(GAMACON1)
1298 TR(NCT)=1.0+SUMT
1299 EFF(NCT)=(1.0-1.0/TR(NCT))/(1.0-1.0/PR(NCT))**(CON1/GAMA)
1300 EFF(NCT)=EFF(NCT)*100.0
1301 TRIS(NCT)=TST(1.1)**(1.0-1.0/TR(NCT))
1302 POWER(NCT)=DESM*CP*A*TRIS(NCT)/550.
1303 IF (NCT.EQ.1) THEN
1304 GO TO 620
1305 ELSE IF (NCT.EQ.3) THEN
1306 GO TO 630
1307 ELSE
1308 WRITE(NWT,635) NROT,PR(3),TR(3),TR(2),LEFF(2)
1309 GO TO 620
1310 ENDEF
1311 630 WRITE(NWT,642) NROT,PR(3),PR(1),TR(3),TR(1),EFF(3),LEFF(1)
1312 100 CONTINUE
1313 WRITE(NWT,499)
1314 WRITE(NWT,500) PR(1),TR(1),TRIS(1),EFF(1),DESM,POWER(1)
1315 WRITE(NWT,550) COEFF,COEFW,COEFFH,COEFVW
C
1316 WRITE(NWT,575)
1317 DO 540 I=1,NSTAT
1318 NSN=I
1319 560 WRITE(NWT,585) NSN, AMCAL(I)
*****
C
C PRINT OUT THE B.L. CALCULATIONS
* IF boundary layers calculated print the results
*
1320 IF(NFBL.NE.0) THEN
1321 WRITE(NWT,4)
1322 4 FORMAT(44X,'BOUNDARY LAYER CALCULATIONS =')
1323 IF (NFBL.EQ.1) THEN
1324 WRITE(NWT,605)
1325 605 FORMAT(60X,9H**NOVAK** )
1326 ELSE
1327 WRITE(NWT,603)
1328 603 FORMAT(60X,13H**STRATFORD** )
1329 END IF
1330 WRITE(NWT,604)
1331 604 FORMAT(2X,'STATION',5X,'MOMENTUM THICKNESS',5X,
1 1 'SHAPE FACTOR',10X,26HDISPLACEMENT THICKNESS(DN),
2 2 10X,7HPERCENT,7.96X,4HAREA,17X,3HHUB,6X,6HSHROUD,
3 3 7X,3HHUB,3X,6HSHROUD,15X,3HHUB,8X,6HSHROUD 13X,
4 4 8HBLOCKAGE//)
1332 DO 5 I=1,NSTAT
1333 PAB=(1.0-ARA(0)/AREAL)*100
1334 WRITE(NWT,6) LDSPT(L1),DSPT(L2),SHR(L1),SHR(L2),
1 DELT(L1),DELT(L2),PAB
1335 5 CONTINUE
1336 ENDEF
*****
**print out the mass flow rate between each streamline (grdpoint)
**added July 10, '91 by Wendy Klein
**
1337 WRITE (NWT,900)
1338 900 FORMAT(//10X,'MASS FLOW RATE BETWEEN EACH STREAMLINE'//
1 'GRID POINT STATION #71')
1339 WRITE (NWT,902) (LI=1,NSTAT)
1340 902 FORMAT(136/80X,' ')
1341 DO 900 J=2,NGRID
1342 WRITE (NWT,901) (AMFLW(LJ-1),LJ=1,NSTAT)
1343 WRITE (NWT,903) J
* the following format statement requires (asat)
* real numbers (asat <=13)
1344 901 FORMAT(13F6.2)
1345 903 FORMAT(12)

```

B-26


```

1471 DO 510 I=1,NSTAT
1472 A02=CON1*TS(T(LJS))
1473 V2=VMI(LJS)**2+VT(LJS)**2
1474 T=TS(T(LJS))*(1-(GAMMA-1)*V2/L2**A02))
1475 A2=CON1*T
1476 ROA=PS(T(LJS)*(ROAS*TS(T(LJS)))
1477 AMAB=V2/A2
1478 ROS(T)=RODM*(1+.2*AMAB)**2.5
1479 ANU(I)=VISCOS*SQRT(T*AU778.2*(1+.1804*(AU778.2)))*COS(ROS(I))
1480 TS(TC(I))=T
1481 AMA(I)=SQRT(AMAB)
1482 VFIC(I)=VMI(LJS)
1483 IF(I.EQ.1) GO TO 510
1484 DX(I)=DSM(LJS)-DSM(I-1,J5)
1485 IF(NTYPE(I).NE.2) GO TO 510
1486 IF(DLFC(LJS).LT.0.2) GO TO 510
1487 PS=PS(T(LJS)*T/TS(T(LJS)))**2.86
1488 AMA(I)=SQRT(((PS(T(I-1,J5)/PS)**2.86-1.0)*AMA)**2)**0.5
1489 VFIC(I)=SQRT(AMA(I)**2*A2)
1490 510 CONTINUE
C
C USE STRATFORDS TECHNIQUE
1491 DISP(I)=DISP(IKS)
1492 AMAY=AMA(2)*AMA(I)/2.
1493 H=1.28*(1+.8*AMAV**2)**0.44*(1.0+.1*AMAV**2)**0.7
1494 SHPT(L5)=H
1495 DELT(L5)=DISP(I)
1496 DSP(T(L5))=DISP(I)*H
DO 530 I=2,NSTAT
1497 ITR=0
1498 DISP2=DISP(I-1)
1499 VMA=VFIC(I)*VMI(LJS)/2.
1500 VISA=(ANU(I)*ANU(I-1))/2.
1501 ROA=ROS(I)*ROS(I-1)/2.
1502 IF(NT.CE.8) GO TO 1
1504 PH=0.07
GO TO 212
1505 DM1=1.0
1507 BTK(I)=0
1508 AMQ(I)=AMA(I)
1509 AMH(I)=AMA(I)
1510 WQ(I)=SQRT(VFIC(I)**2+VT(LJS)**2)
1511 IF(NTYPE(I).NE.1) GO TO 651
1512 DM1=1.04
1513 WTI=VT(I-1,J5)-ROTV(I-1)*R(I-1,J5)
1514 WTO=VT(LJS)-ROTV(I)*R(LJS)
1515 A2=CON1*TS(TC(I))
1516 AMH(I)=SQRT(WTI**2+VMI(I-1,J5)**2+VA2)
1517 WQ(I)=SQRT(WTO**2+VFIC(I)**2)
1518 AMQ(I)=WQ(I)/SQRT(A2)
1519 BTK(I)=ATAN(WTI/VMI(I-1,J5))
1520 651 CONTINUE
1521 AMA2=((AMQ(I)*AMH(I))/2)**2
1522 PH=0.08*DM1/COS(BTK(I-1))**0.8
C COMPUTE THE SHAPE FACTOR
1523 H=1.28*(1+.8*AMA2)**0.44*(1+.1*AMA2)**0.7
C COMPUTE THE MOMENTUM THICKNESS
1524 212 CONTINUE
1525 C1=ROS(I)*VMI(I-1,J5)
1526 C2=ROS(I)*VFIC(I)
1527 DPM=2.*C1*C2*(VFIC(I)-VMI(I-1,J5)*(C1+C2))
1528 C3=C2*VFIC(I)-DPM**H/2)*R(I-1,J5)
1529 C4=C1*VMI(I-1,J5)+DPM**H/2)*R(I-1,J5)
1530 C5=DX(I)*(R(LJS)+R(I-1,J5))/2.
C
C ITERATE TO FIND THE MOMENTUM THICKNESS
1531 210 CONTINUE
1532 DSPA=DISP2+DISP(I-1)/2.
1533 REYS=VMA*DISPA/VISA
1534 SKF=PH*ROA*VMA**2*REYS**(-0.2)
1535 DISP3=(SKF**C3+C4*DISP(I-1))/C3
1536 IF(DISP3.GT.0.0) GO TO 652
1537 DISP3=0.*DISP(I-1)
GO TO 200
1538 652 CONTINUE
1539 IF(ABS(DISP2-DISP3).LE.(.04*DISP(I-1))) GO TO 200
1540 DISP2=DISP3
1541 ITR=ITR+1
1542 IF(ITR.LT.10) GO TO 210
1543 WRITE(TWT,220) I
1544 220 FORMAT(' CASE NOT CONVERGED IN BLCAL AT STATION',J3)
1545 200 DISP(I)=DISP3
1547 IF(DISP3.GT.3*DISP(I-1)) DISP(I)=3*DISP(I-1)
1548 530 CONTINUE
C
C IMPROVE THE H CALCULATION
1549 DO 300 I=2,NSTAT
1550 IF(NT.LT.8) GO TO 213
C COMPUTE DVM/DOM
1551 V1=VFIC(I)-VMI(I-1,J5)
1552 DH1=DX(I)
1553 IF(1.NE.NSTAT) GO TO 2
1554 DVM=V1/DH1

```


1676 ENDP

```

*****
1654 IF (TPCNT.EQ.1) THEN
  *   for first run using tip curve loss method set up max changing
  *   values and guess initial maximum pressure loss
  *
  *   function parameters which may be adjusted
1655 MY(1)=0.0
1656 MY(2)=0.5
  *
  *   initialize known points
1657 X1=0.0
1658 Y3=0.0
  *
  *   calculate the width at zero pressure loss coefficient,
  *   along the blade span of the parabola (X3)
  *   based on the pitch-chord and tip-pitch chord ratios
1659 X3=WIDTH/2*(SOL.TCL.CORD)
  *
  *   guess the maximum pressure loss coefficient (Y2) (tip of
  *   parabola) based on the current mass averaged pressure
  *   loss coefficient
1660 Y1=MY(1)+MY(2)*Y2INTL
1661 QA=Y1
1662 QB=2*(Y2INTL-Y1)*X3
1663 QC=Y1-Y2INTL)*X3**2
1664 X3*(QB-QA)*JBT(QB**2-4*QA*QC)/(2*QA)
1665 A=Y1-Y2INTL)*X3**2)
1666 LOSCURB=A*X3**3/3-A*X2*X3**2/(Y2INTL+A*X2**2)*X3
1667 Y2=DAMP(3)*(LOSREQ+LOSCUR)*X3/2)*Y2INTL
  *
1668 WRITE(*,900) Y2,DAMP(1)
1669 900 FORMAT('The total guess for the maximum tip loss pressure'
  * coefficient is: ',F10.6)
  *
1670 WRITE(*,901)
1671 901 FORMAT(5X,'Max Y      Ytot calc      Ytot desired')
  *
1672 ELSE
  *   For subsequent runs using the tip curve loss method
  *   calculate new maximum pressure loss coefficient guess from
  *   old guess and mass averaged loss calculated from Ytip and
  *   Y parabola
1673 Y2=DAMP(1)*(LOSREQ+LOSCUR)*X3/2)*Y2
1674 WRITE(*,902) Y2,LOSCUR,LOSREQ
1675 902 FORMAT(3X,F10.6)

```



```

1711      COMMON /TWONE/K1,X2,X3,Y1,Y2,Y3,ALMY(12),DAMP(5),AGREE,Y2NTL,
1       1  LOSREQ,LOSCUR,TEGAP,TPONT,TPMTHD,
2       2  RD1(50),YTIR(11,50),AMFLW(11,50)

*****
*   initialize variables exclusive to TPIRY FOR
1712   INTEGER I,K
1713   REAL RMAX,DIFF
*dimension for (min,grid)
1714   REAL TIPPY(15,50)
*dimension for (grid)
1715   REAL P(50),X(50),XX(50)
*
*NOTE: K is used to indicate position at center of streamtube
*      J is used to indicate position at grid points
*****
*   CLEAR SCREEN
1716   WRITE(*,900)
1717   900  FORMAT(1H1)
*****
1718   RMAX=ALEN(NST)
1719   LOSREQ=0
1720   DO 100 K=1,NGRID-1
1721     J=K+1
*   calculate average loss (VK), between streamlines
1722     P(K)=(DFAC(KB,J-1)+DFAC(KB,J))/2
*   multiply average loss by mass flow between streamlines
*   and add to previous losses
1723     LOSREQ=LOSREQ+AMFLW(NST,K)*P(K)
*   distance set as average of adjacent streamlines (normalized
*   with respect to area
1724     X(K)=RMAX*(DELN(NST,J-1)+DELN(NST,J))*ALEN(NST)/2
1725     WRITE(*,910) K,X(K)
1726 100  CONTINUE
1727   TPONT=0
*****
1728 300  CONTINUE
1729   TPONT=TPONT+1
*calculate a parabola
*****
*
1730   CALL TPCRV
*
*****
* Calculate the loss coef at the center of each streamtube and add the
* losses to get the total loss
1731   LOSQV(R)=0

```

```

1732   DO 110 K=1,NGRID-1
1733     IF (X(K).GE. X3) THEN
1734       TIPPY(KB,K)=0.0
1735     ELSE
1736       TIPPY(KB,K)=Y2+A*(X(K)-X2)**2
1737     ENDDIF
1738     LOSCUR=LOSCUR+AMFLW(NST,K)*TIPPY(KB,K)
1739 110  CONTINUE
*
*compare required loss to current loss and if equal within tolerance
*continue
1740   DIFF=ABS(LOSREQ-LOSCUR)/LOSREQ*100.0
1741   IF (DIFF.GT. AGREE.AND. TPONT.LE. 30) GOTO 300
*****
* Field loss at grid points by taking an average of loss at center of
* adjacent stream tubes, assuming the loss at the hub is 0.0
1742   DO 120, J=1,NGRID
1743     XX(J)=RMAX-DELN(NST,J)*ALEN(NST)
1744     IF (XX(J).GE. X3) THEN
1745       YTIR(KB,J)=0
1746     ELSE
1747       YTIR(KB,J)=Y2+A*(XX(J)-X2)**2
1748     ENDDIF
1749 120  CONTINUE
*****
1750   WRITE(*,902) Y2,LOSCUR,LOSREQ
1751   902  FORMAT(/X5X,1F10.6))
1752   WRITE(*,901) AGREE,TPONT
1753 901  FORMAT(/THE NUMBER OF ITERATIONS REQUIRED FOR '1F7.3,
1       1  '%/AGREEMENT WITH REQUIRED AREA WAS',1I3)
1754   WRITE(*,903) A,X2,X3
1755 903  FORMAT(/'A = ',1F10.6,'X2 = ',1F10.6,'X3 = ',1F10.6,'R')
1756   WRITE(*,911) X2*X3*12,ALEN(NST)**2
1757 911  FORMAT('X2 = ',1F10.6,'X3 = ',1F10.6,'m',
1       1  'ANNULUS WIDTH',1F10.6,'m'/)
*
1758   WRITE(*,904)K,X(K)*12.0,TIPPY(KB,K),K=NGRID-1,1-1)
1759 904  FORMAT(/'K  X(K) inches  TIP LOSS COEF'/N(3,2F10.6))
1760   WRITE(*,912)
1       1  (J,DELN(NST,J)*12*(P(ALEN(NST),YTIR(KB,J),J=NGRID,1-1)
1       1  /N(3,2(10X,F10.6)))
*****
*****multiply used format statements
1762 910  FORMAT('X(K), K= ',12,' X= ',F10.5)
*****
1763   RETURN

```

```

1764      END

      SUBROUTINE TIPWRT FOR
      C$INCLUDE TIPWRT.FOR
1765      SUBROUTINE TIPWRT
      ..... Subroutine to write the results of the curve method for
      ..... calculating the tip loss (TIPLOSS) FOR .....
      .....
1766      IMPLICIT LOGICAL(A-Z)
      .....
      *Add common statements and their initializations
      C$INCLUDE ONE.BLK
      *1 initialize variables from block one
1767      INTEGER NTYPE
1768      REAL DN,VM,VT,PST,TST,DELN,R,Z,TER1,FAN,PHI,ALEN,BLCK,AREA,
      1 ROTV,DELPO,DSM,SHR,DSPT,DELT,ARA,RHZ,HRT,ZT
      ....._METHOD
      .....
      *.....*init 11, ngrd=50, ngrd+1=51
1769      COMMON ACB/DN(11,51),
      1 VM(11,50),VT(11,50),PST(11,50),TST(11,50),DELN(11,50),
      1 R(11,50),Z(11,50),TER1(11,50),FAN(11,50),PHI(11,50),
      1 ALEN(11,50),BLCK(11,50),AREA(11,50),NTYPE(11,50),ROTV(11,50),
      1 DELPO(11,50),DSM(11,50),SHR(11,50),DSPT(11,50),DELT(11,50),
      1 ARA(11,50),RHZ(11,50),HRT(11,50),ZT(11,50)
      ....._METHOD(11,50)
      C$INCLUDE THREE.BLK
      *3 initialize variables from block three
1770      INTEGER NT,KODE,NRDKM,NFDES,NFBL,NST,KBL,ABORT,NIT,KAL,KVT
1771      REAL OMEG,OMEGA,OK
      .....
1772      COMMON ACB3/NT,KODE,NRDKM,NFDES,NFBL,NST,KBL,ABORT,NIT,
      1 KAL,KVT,OMEGA,OMEGA,OK
      C$INCLUDE FOUR.BLK
      *4 initialize variables from block four
1773      INTEGER NSTAT,NGRID,NTUBE,NORD1,NPTS,IRD,IWT
1774      REAL PO,TO,HO,DESM,GAMA,RGAS,CP,GO,PLAJ,TOLS,TOLM,WGHT
      .....
1775      COMMON/BLK1/NSTAT,NGRID,NTUBE,NORD1,PO,TO,HO,DESM,GAMA,RGAS,CP,
      1 GO,PLAJ,TOLS,TOLM,WGHT,NPTS,IRD,IWT
      C$INCLUDE FIVE.BLK
      *5 initialize variables from block five (CSD)
1776      INTEGER KSER,KOD,KBL,NGRJNQN
1777      REAL KAP1,KAP2,BET1,BET2,DEV,BDHT,VRAI,TRAT,ET1,ET2,

```



```

1868      CALL TLINK
1869      CONTINUE
1870      NIT=NIT+1
1871      IF(NIT.EQ.100)GO TO 134
1872      IF(NIT.EQ.1)OR(NIT.EQ.NTD)/THEN
1873 135      WRITE(NIT,137) NIT
1874 137      FORMAT(1H1,14HITERATION NO. 12)
1875      CALL WRITE
1876      ENDIF
1877 136      CONTINUE
C
C REPOSITION STREAMLINES AND CHECK FOR CONVERGENCE
1878      OK=0
1879      CALL 4EPOS
1880      CALL 8LCAL
1881      K0 L=1
1882      IF (NIT.EQ.1)THEN
1883          OK=1
1884      ELSEIF (OK.EQ.0)THEN
1885          GO TO 20
1886      ENDIF
1887      IF (NIT.LT.NT)GO TO 30
1888 21      WRITE(NIT,40) NIT
1889 40      FORMAT(///,10X,'CASE HAS NOT CONVERGED IN',
1890          1      13.2X,'ITERATIONS')
1891      GO TO 70
1892 20      WRITE(NIT,50) NIT
1893 50      FORMAT(///3X,'Y
1      1      10X,'CASE HAS CONVERGED IN'13.2X,'ITERATIONS')
1894      IF (TPATHD.EQ.1) THEN
1895          CALL WRITE
1896          TPATHD=2
1897          OK=1
1898          GOTO 30
1899      ELSEIF (TPATHD.EQ.2) THEN
1900          TPATHD=3
1901          OK=1
1902          GOTO 30
1903      ELSEIF (TPATHD.EQ.3) THEN

```

```

1903      CALL WRITE
1904      CALL TFWRT
1905      GOTO 675
1906      ENDIF
1907 70      CALL WRITE
1908      continue from here for ignored =3
1909 675      CONTINUE
1910      GOTO 670
1911 480      CONTINUE
1912      CLOSE (TRD)
1913      CLOSE (TWT)
1914      repeat program for analysis mode if not done yet
1915      IF(ANLYSS)GO TO 500
1916      ***** FORMAT STATEMENTS *****
1917 31      FORMAT(3A1,'DESIGN MODE')
1918 32      FORMAT(3X,'ANALYSIS MODE')
1919      *****
1920      16      STOP
1921      17      END

```

Compile time:	06:54 19	50.15	Execution time:
Size of object code:	0	51340	Number of extensions:
Size of local data area(s):	0	31312	Number of warnings:
Size of global data area:	0	121976	Number of errors:
Object/dynamic bytes free:	182072/10586	2715894	Statements Executed:

Appendix C

Sample simulations using the streamline curvature program

This appendix contains three input data files, with one complete output file and two partial output files. Because the tip loss is concentrated in a small region of the annulus a large number of grid points, about 50, is required to obtain enough grid points in the loss region to accurately define the loss. The resulting output files are very long. For this reason only the output data of most interest are listed for the simulations discussed in Chapter 3. That is, the parameters at exit of the rotor and the overall turbine performance. Also listed, in order to show a full output file, is a data file for the high pressure turbine, and its output, which uses 10 grid points. The only difference between this data file and the data file for the 50 grid point case is that it uses 10 grid points instead of 50.

Contents	Page
Data File For High Pressure Turbine Simulation (50 grid points)	C-2
Abbreviated Output For High Pressure Turbine Simulation	C-2
Data File For Low Pressure Turbine Simulation (50 grid points)	C-6
Abbreviated Output For Low Pressure Turbine Simulation	C-6
Data File For High Pressure Turbine Simulation (10 grid points)	C-10
Output For High Pressure Turbine Simulation	C-10

LOSS	FLOW	TANGENT	VELOCITY	WHEEL	MACH	TOTAL	TOTAL	REAC	WORK	FLOW
COEF	ANGLE		TOTAL		NO	PRESS	TEMP		COEF	COEF
10.054	-8.5	715.11	-106.57	723.0	0.310	139.343130	9231368.69	1348.84		
10.012	-8.6	712.72	-107.48	720.8	0.309	139.285110	9231368.79	1349.06		
9.971	-8.7	710.33	-108.39	718.5	0.308	139.227110	9231368.88	1349.28		
9.929	-8.8	707.94	-109.30	716.3	0.307	139.168110	9231368.96	1349.50		
9.887	-8.9	705.55	-110.21	714.0	0.306	139.109110	9231368.98	1349.72		
9.846	-9.0	703.16	-111.12	711.7	0.305	139.052110	9231368.18	1349.94		
CONDITIONS RELATIVE TO UPSTREAM ROW										
(ROTOR WITH ANGULAR VELOCITY OF 1696.46)										
0.222	-64.8	-1725.2	1906.12	1643.4	0.820	198.99	1476.8	0.463	1.286	0.316
0.225	-64.8	-1721.1	1901.6	1639.0	0.818	198.50	1476.4	0.459	1.292	0.319
0.227	-64.8	-1716.9	1897.0	1634.5	0.816	198.20	1476.0	0.455	1.298	0.321
0.230	-64.8	-1712.8	1892.4	1630.1	0.814	197.80	1475.5	0.451	1.304	0.324
0.233	-64.8	-1708.6	1887.8	1625.5	0.812	197.41	1475.1	0.447	1.310	0.326
0.236	-64.8	-1704.4	1883.1	1621.0	0.810	197.02	1474.7	0.443	1.316	0.329
0.239	-64.8	-1700.2	1878.4	1616.5	0.808	196.62	1474.3	0.439	1.322	0.332
0.242	-64.8	-1696.0	1873.7	1611.9	0.806	196.23	1473.8	0.435	1.328	0.334
0.245	-64.8	-1691.8	1869.0	1607.3	0.803	195.83	1473.4	0.431	1.334	0.337
0.248	-64.8	-1687.5	1864.3	1602.6	0.801	195.44	1472.9	0.427	1.340	0.340
0.251	-64.8	-1683.2	1859.6	1598.0	0.799	195.05	1472.5	0.423	1.346	0.342
0.254	-64.8	-1678.9	1854.8	1593.3	0.797	194.65	1472.0	0.418	1.352	0.345
0.257	-64.8	-1674.6	1850.0	1588.6	0.795	194.26	1471.6	0.414	1.358	0.348
0.260	-64.8	-1670.3	1845.2	1583.8	0.793	193.87	1471.2	0.410	1.379	0.351
0.263	-64.8	-1666.0	1840.4	1579.1	0.791	193.47	1470.7	0.405	1.379	0.351
0.267	-64.8	-1661.6	1835.5	1574.3	0.788	193.08	1470.3	0.401	1.395	0.356
0.270	-64.8	-1657.2	1830.7	1569.5	0.786	192.69	1469.8	0.396	1.413	0.363
0.273	-64.8	-1652.8	1825.8	1564.6	0.784	192.29	1469.4	0.392	1.431	0.369
0.277	-64.8	-1648.4	1820.9	1559.7	0.782	191.90	1468.9	0.387	1.449	0.375
0.280	-64.8	-1644.0	1816.0	1554.8	0.780	191.51	1468.5	0.383	1.468	0.381
0.283	-64.8	-1639.5	1811.1	1549.9	0.778	191.12	1468.0	0.378	1.486	0.386
0.287	-64.8	-1635.0	1806.1	1544.9	0.775	190.72	1467.6	0.373	1.485	0.374
0.290	-64.8	-1630.5	1801.6	1539.9	0.773	190.33	1467.1	0.368	1.483	0.377
0.293	-64.8	-1626.0	1796.0	1534.9	0.771	189.94	1466.7	0.364	1.482	0.380
0.297	-64.8	-1621.5	1791.0	1529.8	0.769	189.54	1466.2	0.359	1.471	0.383
0.300	-64.8	-1616.9	1785.9	1524.7	0.766	189.15	1465.8	0.354	1.480	0.390
0.304	-64.8	-1612.4	1780.9	1519.4	0.764	188.77	1465.3	0.349	1.489	0.397
0.307	-64.8	-1607.9	1775.9	1514.5	0.762	188.38	1464.9	0.344	1.498	0.393
0.311	-64.8	-1603.4	1770.9	1509.3	0.760	188.00	1464.4	0.339	1.508	0.397
0.314	-64.8	-1598.8	1765.8	1504.1	0.758	187.61	1463.9	0.334	1.517	0.400
0.318	-64.8	-1594.3	1760.7	1498.8	0.755	187.23	1463.5	0.328	1.527	0.403
0.321	-64.8	-1589.7	1755.6	1493.5	0.753	186.84	1463.0	0.323	1.537	0.407
0.325	-64.8	-1585.1	1750.5	1488.2	0.751	186.46	1462.6	0.318	1.547	0.410
0.329	-64.8	-1580.4	1745.3	1482.8	0.749	186.07	1462.1	0.312	1.557	0.414
0.332	-64.8	-1575.8	1740.2	1477.4	0.746	185.69	1461.6	0.307	1.578	0.417
0.336	-64.8	-1571.1	1735.0	1472.0	0.744	185.30	1461.2	0.301	1.578	0.421
0.340	-64.8	-1566.4	1729.7	1466.5	0.742	184.92	1460.7	0.294	1.588	0.425
0.344	-64.8	-1561.7	1724.5	1461.0	0.739	184.53	1460.2	0.289	1.599	0.428
0.347	-64.8	-1556.9	1719.2	1455.5	0.737	184.15	1459.8	0.284	1.610	0.432
0.351	-64.8	-1552.1	1713.9	1449.9	0.735	183.76	1459.3	0.279	1.621	0.436
0.355	-64.8	-1547.3	1708.6	1444.2	0.732	183.38	1458.8	0.273	1.632	0.440
0.359	-64.8	-1542.5	1703.2	1438.5	0.730	182.99	1458.3	0.267	1.644	0.444
0.363	-64.8	-1537.7	1697.8	1432.9	0.728	182.61	1457.8	0.261	1.655	0.448
0.367	-64.8	-1532.8	1692.4	1427.1	0.725	182.22	1457.4	0.255	1.679	0.452
0.372	-64.8	-1527.9	1687.0	1421.3	0.723	181.83	1456.9	0.249	1.691	0.456
0.376	-64.8	-1522.9	1681.5	1415.5	0.720	181.45	1456.4	0.243	1.703	0.460
0.380	-64.8	-1518.0	1676.0	1409.6	0.718	181.06	1455.9	0.236	1.716	0.464
0.384	-64.8	-1513.0	1670.4	1403.7	0.716	180.67	1455.5	0.230	1.731	0.468
0.389	-64.8	-1508.0	1664.8	1397.7	0.713	180.28	1455.0	0.224	1.749	0.472
0.393	-64.8	-1502.9	1659.2	1391.7	0.711	179.90	1454.5	0.217	1.762	0.476

STATION NO. 4
ITERATION NO. 32

ROTOR --- 1
PRESSURE RATIO = 2.3996
TEMPERATURE RATIO = 1.1910
EFFICIENCY = 90.3591

STAGE --- 1
PRESSURE RATIO = 2.3994
TEMPERATURE RATIO = 1.1910
EFFICIENCY = 86.3911

ACCUMULATIVE
PRESSURE RATIO = 2.3994
TEMPERATURE RATIO = 1.1910
EFFICIENCY = 86.3911

OVERALL PERFORMANCE BASED ON MASS-AVERAGED PROPERTIES
PRESSURE RATIO = 2.3994
TEMPERATURE RATIO = 1.1910
EFFICIENCY = 86.3911

TOTAL PRESSURE RATIO = 2.399
 TOTAL TEMPERATURE RATIO = 1.191
 TOTAL TEMPERATURE DROP = 261.11K
 TOTAL-TEMPERATURE EFFICIENCY = 86.394
 MASS FLOW RATE = 92.30
 POWER OUTPUT = 17929.16 HP
 AVERAGE FLOW COEFFICIENT = 0.388
 AVERAGE WORK COEFFICIENT = 1.486
 RUB FLOW COEFFICIENT = 0.479
 RUB WORK COEFFICIENT = 1.742
 CALCULATED MASS FLOW RATE (lbm/s)
 STATION 1 92.29897
 2 92.29897
 3 92.29401
 4 92.29501
 5 92.29706

CASE HAS CONVERGED IN 64 ITERATIONS
 STREAMLINE CURVATURE COMPUTATION
 STATION NO 4
 BLACKAGE = 0.0008
 AREA = 120.20in²
 ABSOLUTE CONDITIONS
 RADIUS FLOW VELOCITY MACH PRESSURE TEMPERATURE
 inches deg ft/s ft/s ft/s psi psi K K
 11.625 0 0 775.94 -0.15 332.142 813132 7741374 25 1451.39
 11.592 1.8 762.45 23.65 326.142 125132 6601377 33 1355.24
 11.559 3.3 750.91 43.23 321.141 859132 6801379 88 1358.39
 11.524 4.4 741.91 57.34 317.141 57132 6901381 73 1360.21
 11.490 5.2 735.19 66.56 315.141 509132 7001382 97 1362.28
 11.455 5.6 730.60 71.20 312.141 407132 7081383 65 1363.45
 11.419 5.6 728.05 71.47 311.6 312.141 345132 7091383 65 1363.45
 11.384 5.3 727.53 67.44 310.6 311.141 344132 7091383 65 1363.45
 11.348 4.6 729.03 59.09 313.4 312.141 344132 7091383 65 1363.45
 11.313 3.6 732.66 48.26 331.6 316.141 336132 6841378 99 1358.25
 11.278 2.2 746.87 28.68 339.1 319.141 336132 6671376 36 1355.18
 11.242 0.5 766.87 5.92 348.9 325.142 325132 6441373 95 1351.21
 11.208 -1.2 785.96 -22.63 358.3 332.142 325132 6441373 95 1351.21
 11.174 -4.2 802.42 -58.22 366.9 339.143 325132 6441373 95 1351.21
 11.140 -6.5 816.55 -88.82 374.9 343.143 325132 6441373 95 1351.21
 11.102 -7.5 828.61 -100.12 379.9 344.143 325132 6441373 95 1351.21
 11.074 -7.3 835.58 -100.67 380.9 344.143 325132 6441373 95 1351.21

LOSS	FLOW	TANGENT	VELOCITY	WHEEL	MACH	TOTAL	TOTAL	REAC	WORK	FLOW
COEF.	ANGLE				NO	PRESS	TEMP		COEF	COEF
0.332	-64.7	-1649.6	1817.5	1643.4	0.778	193.82	1476.8	0.412	1.236	0.316
0.389	-64.7	-1615.2	1786.1	1638.8	0.764	191.06	1476.4	0.410	1.228	0.319
0.435	-64.7	-1590.8	1759.1	1634.1	0.751	188.96	1475.9	0.406	1.223	0.321
0.471	-64.7	-1571.9	1738.2	1629.2	0.742	187.35	1475.4	0.396	1.221	0.324
0.498	-64.7	-1557.8	1722.5	1624.3	0.734	186.19	1475.0	0.388	1.222	0.326
0.514	-64.7	-1548.2	1711.9	1619.4	0.730	185.41	1474.5	0.382	1.226	0.329
0.519	-64.7	-1542.9	1706.1	1614.4	0.727	184.99	1474.0	0.377	1.233	0.332
0.515	-64.7	-1541.9	1704.9	1609.4	0.729	185.21	1473.0	0.373	1.255	0.337
0.501	-64.7	-1545.3	1708.6	1604.3	0.733	185.86	1472.5	0.373	1.270	0.342
0.476	-64.7	-1553.1	1717.2	1599.1	0.739	186.94	1472.0	0.376	1.288	0.342
0.441	-64.7	-1566.6	1731.1	1594.3	0.748	188.47	1471.0	0.382	1.310	0.345
0.395	-64.7	-1592.4	1750.2	1589.5	0.761	190.55	1470.0	0.392	1.355	0.351
0.340	-64.7	-1637.9	1819.3	1579.9	0.792	197.06	1469.0	0.404	1.407	0.358
0.274	-64.8	-1693.9	1897.9	1569.9	0.794	198.70	1469.0	0.406	1.415	0.359
0.196	-64.8	-1670.4	1846.1	1560.2	0.792	196.50	1468.5	0.396	1.423	0.359
0.201	-64.8	-1666.2	1842.1	1560.5	0.790	195.92	1468.5	0.391	1.431	0.365
0.204	-64.8	-1661.9	1837.3	1556.0	0.788	195.52	1468.5	0.387	1.439	0.368
0.206	-64.8	-1657.8	1832.6	1551.2	0.785	195.13	1468.5	0.382	1.448	0.371
0.209	-64.8	-1653.3	1827.8	1546.4	0.781	194.74	1468.5	0.377	1.456	0.374
0.215	-64.8	-1649.0	1823.1	1541.6	0.777	194.34	1468.5	0.373	1.465	0.377
0.218	-64.8	-1644.8	1818.1	1536.6	0.773	193.94	1468.5	0.369	1.474	0.381
0.221	-64.8	-1640.5	1813.2	1531.6	0.770	193.55	1468.5	0.365	1.482	0.384
0.223	-64.8	-1636.3	1808.3	1526.8	0.767	193.15	1468.5	0.361	1.491	0.387
0.228	-64.8	-1632.1	1803.4	1522.0	0.764	192.76	1468.5	0.357	1.500	0.390

INCIDENCE	STALLING	LOADING	DEV.	ANGLE	YS	YP	YPT	YK	REYN	CP
0.231	-64.8	-1622.5	1793.5	1516.8	0.770	192.37	1465.0	0.353	1.500	0.390
0.234	-64.8	-1618.1	1788.6	1511.7	0.768	191.98	1464.5	0.348	1.510	0.393
0.237	-64.8	-1613.6	1783.7	1506.7	0.766	191.59	1464.1	0.343	1.519	0.397
0.240	-64.8	-1609.2	1778.7	1501.6	0.764	191.20	1463.7	0.338	1.529	0.400
0.243	-64.8	-1604.7	1773.7	1496.4	0.762	190.82	1463.2	0.333	1.539	0.403
0.246	-64.8	-1600.2	1768.7	1491.2	0.759	190.43	1462.8	0.328	1.548	0.407
0.250	-64.8	-1595.7	1763.7	1486.0	0.755	189.65	1462.3	0.323	1.558	0.410
0.253	-64.8	-1591.1	1758.6	1480.8	0.753	189.26	1461.9	0.317	1.568	0.413
0.256	-64.8	-1586.5	1753.5	1475.5	0.750	188.87	1461.4	0.312	1.578	0.416
0.260	-64.8	-1577.3	1743.2	1464.6	0.746	188.08	1460.5	0.306	1.588	0.421
0.263	-64.8	-1572.6	1738.1	1459.5	0.744	188.09	1460.1	0.299	1.599	0.425
0.266	-64.8	-1568.0	1732.9	1454.0	0.743	187.69	1459.6	0.290	1.609	0.429
0.270	-64.8	-1563.3	1727.6	1448.6	0.741	187.30	1459.1	0.284	1.620	0.432
0.273	-64.8	-1558.5	1722.3	1443.1	0.739	186.91	1458.6	0.278	1.631	0.436
0.277	-64.8	-1553.7	1717.0	1437.5	0.736	186.52	1458.2	0.272	1.642	0.440
0.281	-64.8	-1549.0	1711.7	1431.9	0.734	186.12	1457.8	0.267	1.653	0.444
0.284	-64.8	-1544.1	1706.3	1426.3	0.732	185.73	1457.3	0.261	1.665	0.448
0.288	-64.8	-1539.3	1700.9	1420.6	0.729	185.34	1456.8	0.255	1.676	0.452
0.292	-64.8	-1534.4	1695.5	1414.9	0.727	184.94	1456.4	0.248	1.688	0.456
0.296	-64.8	-1529.4	1690.6	1409.2	0.725	184.54	1455.9	0.242	1.700	0.460
0.300	-64.8	-1524.5	1685.5	1403.4	0.722	184.15	1455.4	0.236	1.712	0.464
0.304	-64.8	-1519.5	1680.5	1397.5	0.720	183.75	1455.0	0.230	1.724	0.468
0.308	-64.8	-1514.4	1675.3	1391.7	0.717	183.35	1454.5	0.223	1.737	0.472
0.312	-64.8	-1514.4	1673.3	1391.7	0.717	183.35	1454.5	0.223	1.750	0.476

STATION NO. 4
ITERATION NO. 44

OFF-DESIGN	STALLING	LOADING	DEV.	ANGLE	YS	YP	YPT	YK	REYN	CP
-7.269	22.129	7.254	0.121	0.111	0.046	0.073	0.076	0.172	9.962	0.852
-7.042	21.850	7.254	0.120	0.113	0.047	0.074	0.078	0.226	9.711	0.854
-6.827	21.575	7.355	0.118	0.114	0.049	0.076	0.079	0.270	9.505	0.856
-6.624	21.303	7.406	0.116	0.115	0.070	0.077	0.081	0.303	9.342	0.857
-6.433	21.035	7.456	0.114	0.117	0.072	0.079	0.082	0.327	9.215	0.858
-6.252	20.770	7.505	0.112	0.118	0.073	0.080	0.084	0.340	9.123	0.859
-6.083	20.509	7.555	0.111	0.119	0.075	0.082	0.085	0.344	9.064	0.860
-5.924	20.251	7.604	0.109	0.120	0.076	0.083	0.087	0.337	9.039	0.860
-5.776	19.997	7.652	0.107	0.122	0.078	0.085	0.089	0.319	9.039	0.860
-5.638	19.746	7.701	0.105	0.123	0.079	0.086	0.091	0.292	9.074	0.860
-5.510	19.499	7.749	0.103	0.124	0.081	0.088	0.092	0.255	9.145	0.859
-5.392	19.255	7.797	0.101	0.126	0.083	0.090	0.094	0.207	9.254	0.858
-5.283	19.015	7.844	0.099	0.127	0.084	0.091	0.096	0.149	9.407	0.857
-5.184	18.778	7.891	0.098	0.128	0.086	0.093	0.098	0.081	9.612	0.855
-5.094	18.544	7.938	0.096	0.129	0.088	0.095	0.100	0.003	9.852	0.853
-5.013	18.313	7.985	0.094	0.131	0.089	0.097	0.101	0.000	9.828	0.853
-4.940	18.086	8.031	0.092	0.132	0.091	0.098	0.103	0.000	9.773	0.853
-4.875	17.862	8.077	0.091	0.133	0.093	0.100	0.105	0.000	9.717	0.854
-4.819	17.642	8.123	0.089	0.134	0.094	0.102	0.107	0.000	9.661	0.854
-4.771	17.424	8.169	0.087	0.136	0.096	0.104	0.109	0.000	9.605	0.855
-4.730	17.210	8.214	0.085	0.137	0.098	0.106	0.111	0.000	9.549	0.855
-4.697	17.000	8.260	0.084	0.138	0.099	0.108	0.114	0.000	9.493	0.856
-4.672	16.792	8.305	0.082	0.139	0.101	0.110	0.116	0.000	9.437	0.856
-4.653	16.588	8.349	0.080	0.140	0.103	0.112	0.118	0.000	9.381	0.857
-4.642	16.387	8.394	0.078	0.142	0.105	0.114	0.120	0.000	9.324	0.857
-4.631	16.188	8.438	0.076	0.143	0.107	0.116	0.122	0.000	9.268	0.858
-4.624	15.990	8.481	0.074	0.144	0.108	0.118	0.125	0.000	9.212	0.858
-4.618	15.810	8.524	0.072	0.145	0.110	0.120	0.127	0.000	9.157	0.859
-4.614	15.626	8.567	0.070	0.146	0.112	0.122	0.129	0.000	9.101	0.859
-4.610	15.444	8.610	0.067	0.147	0.114	0.124	0.132	0.000	9.045	0.860
-4.608	15.264	8.652	0.065	0.149	0.116	0.126	0.134	0.000	8.989	0.860
-4.612	15.090	8.694	0.063	0.150	0.118	0.129	0.136	0.000	8.933	0.861
-4.624	14.918	8.736	0.061	0.151	0.120	0.131	0.139	0.000	8.877	0.862
-4.638	14.748	8.778	0.058	0.152	0.122	0.133	0.142	0.000	8.821	0.862
-4.658	14.582	8.819	0.056	0.153	0.124	0.135	0.144	0.000	8.766	0.863
-4.680	14.418	8.860	0.054	0.154	0.126	0.138	0.147	0.000	8.710	0.863

-4.144	14.258	8.902	0.051	0.155	0.128	0.140	0.149	0.000	8.654	0.864
-4.134	14.100	8.942	0.049	0.156	0.130	0.143	0.152	0.000	8.598	0.864
-4.130	13.946	8.983	0.047	0.157	0.133	0.145	0.155	0.000	8.542	0.865
-4.130	13.794	9.024	0.046	0.158	0.135	0.148	0.158	0.000	8.486	0.865
-4.135	13.646	9.064	0.042	0.159	0.137	0.150	0.161	0.000	8.430	0.866
-4.145	13.501	9.104	0.039	0.160	0.139	0.153	0.164	0.000	8.374	0.867
-4.158	13.358	9.144	0.037	0.161	0.141	0.155	0.167	0.000	8.319	0.867
-4.170	13.219	9.184	0.035	0.162	0.143	0.158	0.170	0.000	8.263	0.868
-4.202	12.983	9.223	0.032	0.163	0.145	0.161	0.173	0.000	8.207	0.869
-4.229	12.951	9.263	0.030	0.164	0.148	0.164	0.176	0.000	8.152	0.869
-4.261	12.821	9.302	0.027	0.165	0.150	0.167	0.180	0.000	8.096	0.870
-4.297	12.695	9.341	0.025	0.166	0.152	0.170	0.183	0.000	8.041	0.870
-4.337	12.573	9.380	0.022	0.167	0.154	0.173	0.186	0.000	7.985	0.871
-4.381	12.454	9.419	0.019	0.168	0.156	0.176	0.190	0.000	7.930	0.871

ROTOR -- 1
PRESSURE RATIO = 2.2711
TEMPERATURE RATIO = 1.1885
EFFICIENCY = 90.4738

STAGE -- 1
PRESSURE RATIO = 2.3717
TEMPERATURE RATIO = 1.1885
EFFICIENCY = 86.4415
ACCUMULATIVE
PRESSURE RATIO = 2.3717
TEMPERATURE RATIO = 1.1885
EFFICIENCY = 86.4415

OVERALL PERFORMANCE BASED ON MASS-AVERAGED PROPERTIES

TOTAL PRESSURE RATIO = 2.372
TOTAL TEMPERATURE RATIO = 1.188
TOTAL TEMPERATURE DROP = 258.13K
TOTAL-TOTAL EFFICIENCY = 86.4415
MASS FLOW RATE= 92.30
POWER OUTPUT = 17725.16 HP
AVERAGE FLOW COEFFICIENT = 0.388
AVERAGE WORK COEFFICIENT = 1.469
HUB FLOW COEFFICIENT = 0.479
HUB WORK COEFFICIENT = 1.750

CALCULATED MASS FLOW RATE (lbm/s)

STATION	1	2	3	4	5
	92.29899	92.29899	92.29553	92.29501	92.30299

LOSS	FLOW	ANGLE	TANGENT	VELOCITY	WHEEL	MACH	TOTAL	TOTAL	REAC	MORK	FLOW
COEF.	ANGLE	ANGLE	ANGLE	ANGLE	ANGLE	NO	MASS	TEMP	COEF	COEF	COEF
0.075	-62.4	-683.1	771.0	724.3	0.659	22.01	344.4	0.592	0.701	0.540	
0.075	-62.3	-680.0	768.2	721.1	0.656	21.96	344.2	0.588	0.706	0.542	
0.075	-62.2	-676.8	765.5	717.9	0.654	21.92	344.0	0.584	0.712	0.544	
0.075	-62.0	-673.7	762.7	714.6	0.652	21.88	343.8	0.579	0.718	0.547	
0.076	-61.9	-670.6	759.0	711.4	0.649	21.83	343.6	0.575	0.724	0.550	
0.076	-61.8	-667.5	755.2	708.1	0.647	21.79	343.4	0.570	0.730	0.552	
0.076	-61.7	-664.4	751.9	704.9	0.645	21.75	343.2	0.566	0.737	0.555	
0.077	-61.6	-661.2	748.6	701.6	0.642	21.70	343.0	0.561	0.743	0.557	
0.077	-61.5	-658.1	745.3	698.3	0.640	21.66	342.8	0.556	0.750	0.560	
0.077	-61.4	-655.0	742.0	695.0	0.637	21.62	342.6	0.552	0.756	0.563	
0.077	-61.3	-651.9	738.7	691.7	0.635	21.58	342.4	0.547	0.763	0.565	
0.078	-61.2	-648.6	735.4	688.4	0.633	21.53	342.2	0.542	0.770	0.568	
0.078	-61.0	-645.4	732.1	685.1	0.630	21.49	342.0	0.537	0.776	0.571	
0.078	-60.9	-642.2	728.8	681.8	0.628	21.45	341.8	0.532	0.783	0.574	
0.079	-60.8	-639.0	725.5	678.5	0.625	21.41	341.6	0.527	0.789	0.577	
0.079	-60.7	-635.8	722.2	675.2	0.623	21.36	341.4	0.522	0.795	0.580	
0.079	-60.6	-632.6	718.9	671.9	0.621	21.32	341.2	0.517	0.806	0.583	
0.079	-60.3	-629.3	715.6	668.6	0.618	21.28	341.0	0.512	0.814	0.586	
0.080	-60.0	-626.1	712.3	665.3	0.616	21.24	340.8	0.507	0.822	0.589	
0.080	-60.1	-622.9	709.0	662.0	0.613	21.20	340.6	0.502	0.830	0.592	
0.081	-59.9	-619.7	705.7	658.7	0.611	21.15	340.4	0.496	0.838	0.595	
0.081	-59.7	-616.5	702.4	655.4	0.608	21.11	340.2	0.490	0.847	0.599	
0.081	-59.6	-613.3	699.1	652.1	0.606	21.07	340.0	0.485	0.855	0.602	
0.081	-59.5	-610.1	695.8	648.8	0.603	21.03	339.8	0.479	0.864	0.605	
0.082	-59.4	-606.9	692.5	645.5	0.601	20.99	339.6	0.474	0.873	0.609	
0.082	-59.3	-603.7	689.2	642.2	0.598	20.94	339.4	0.468	0.882	0.612	
0.083	-59.2	-599.8	685.9	638.9	0.596	20.90	339.2	0.462	0.891	0.616	
0.083	-59.0	-596.1	682.6	635.6	0.593	20.86	339.0	0.456	0.901	0.619	
0.084	-58.9	-592.2	679.3	632.3	0.590	20.81	338.8	0.450	0.910	0.622	
0.084	-58.7	-588.4	676.0	629.0	0.587	20.77	338.6	0.444	0.920	0.625	
0.084	-58.6	-584.6	672.7	625.7	0.584	20.72	338.4	0.438	0.930	0.628	
0.085	-58.5	-580.8	669.4	622.4	0.582	20.68	338.2	0.432	0.940	0.631	
0.085	-58.4	-576.9	666.1	619.1	0.579	20.63	338.0	0.425	0.951	0.634	
0.086	-58.2	-573.1	662.8	615.8	0.576	20.59	337.8	0.419	0.962	0.637	
0.086	-58.1	-569.3	659.5	612.5	0.573	20.55	337.6	0.412	0.973	0.640	
0.086	-57.9	-565.4	656.2	609.2	0.570	20.50	337.4	0.406	0.984	0.644	
0.087	-57.7	-561.5	652.9	605.9	0.567	20.46	337.2	0.399	0.995	0.647	
0.087	-57.5	-557.6	649.6	602.6	0.565	20.41	337.0	0.392	1.007	0.650	
0.088	-57.4	-553.6	646.3	599.3	0.562	20.37	336.8	0.385	1.019	0.654	
0.089	-57.2	-549.6	643.0	596.0	0.559	20.32	336.6	0.378	1.032	0.657	
0.089	-57.0	-545.5	639.7	592.7	0.556	20.28	336.4	0.371	1.046	0.661	
0.090	-56.8	-541.5	636.4	589.4	0.553	20.23	336.2	0.364	1.057	0.665	
0.091	-56.7	-537.4	633.1	586.1	0.550	20.19	336.0	0.356	1.071	0.669	
0.092	-56.5	-533.2	629.8	582.8	0.546	20.14	335.8	0.348	1.084	0.672	
0.093	-56.3	-529.0	626.5	579.5	0.543	20.10	335.6	0.340	1.098	0.676	
0.094	-56.1	-524.8	623.2	576.2	0.540	20.05	335.4	0.332	1.113	0.680	
0.094	-55.9	-520.5	620.0	572.9	0.537	20.01	335.2	0.323	1.128	0.685	
0.097	-55.7	-516.2	616.7	569.6	0.534	19.96	335.0	0.315	1.143	0.689	
0.099	-55.5	-511.9	613.4	566.3	0.530	19.91	334.8	0.306	1.159	0.693	
0.100	-55.3	-507.5	610.1	563.0	0.527	19.87	334.6	0.297	1.175	0.698	

STATION NO. 4
ITERATION NO. 39

OFF-DESIGN STALLING LOADING DEV.
INCIDENCE INCIDENCE FACTOR ANGLE VS YP YPI YPT YK REYN CF

CONDITIONS RELATIVE TO UPSTREAM ROW
(NOTOR WITH ANGULAR VELOCITY OF 1353.46)

OVERALL PERFORMANCE BASED ON MASS-AVERAGED PROPERTIES

TOTAL PRESSURE RATIO: 1.454
TOTAL TEMPERATURE RATIO: 1.103

STAGE -- 1
PRESSURE RATIO = 1.4539
TEMPERATURE RATIO = 1.1027
EFFICIENCY = 92.0324

ROTOR -- 1
PRESSURE RATIO = 1.4340
TEMPERATURE RATIO = 1.1027
EFFICIENCY = 95.3606

ACCUMULATIVE
PRESSURE RATIO = 1.4539
TEMPERATURE RATIO = 1.1027
EFFICIENCY = 92.0324

TOTAL TEMPERATURE DROP = 33.15K		TOTAL-TEMPERATURE EFFICIENCY = 92.030		MASS FLOW RATE= 10.81		POWER OUTPUT = 219.50 HP	
AVERAGE FLOW COEFFICIENT = 0.612		AVERAGE WORK COEFFICIENT = 0.893		HUB FLOW COEFFICIENT = 0.709		HUB WORK COEFFICIENT = 1.177	
CALCULATED MASS FLOW RATE (lbm/s)							
STATION	1	2	3	4	5	6	
	10.81000	10.81000	10.80998	10.81004	10.81002	10.81002	
	5.884	5.7	5.853	5.7	5.822	5.7	5.853
	5.853	5.7	5.822	5.7	5.791	5.6	5.760
	5.791	5.6	5.760	5.5	5.728	5.3	5.696
	5.728	5.3	5.696	5.3	5.664	5.4	5.632
	5.664	5.4	5.632	5.4	5.600	5.4	5.567
	5.600	5.4	5.567	5.4	5.534	5.4	5.501
	5.534	5.4	5.501	5.3	5.468	5.3	5.435
	5.468	5.3	5.435	5.3	5.401	5.3	5.367
	5.401	5.3	5.367	5.3	5.333	5.3	5.300
	5.333	5.3	5.300	5.3	5.265	5.3	5.230
	5.265	5.3	5.230	5.3	5.195	5.3	5.160
	5.160	5.3	5.124	5.3	5.088	5.3	5.052
	5.088	5.3	5.052	5.3	5.016	5.3	4.979
	5.016	5.3	4.979	5.3	4.942	5.3	4.905
	4.942	5.3	4.905	5.3	4.868	5.3	4.830
	4.830	5.3	4.800	5.3	4.765	5.3	4.730

CASE HAS CONVERGED IN 82 ITERATIONS

STREAMLINE CURVATURE COMPUTATION									
STATION NO. 4									
BLOCKAGE = 0.5000									
AREA = 56.55in ²									
ABSOLUTE CONDITIONS									
RADIUS	FLOW	VELOCITY	MACH	TEMPERATURE	TEMPERATURE	TEMPERATURE	TEMPERATURE	TEMPERATURE	TEMPERATURE
inches	deg	ft/s	ft/s	total	static	total	static	total	static
6.421	8.0	353.52	49.42	357.0	0.305	17.555	16.461	223.49	317.61
6.393	8.6	351.62	52.90	355.6	0.303	17.541	16.457	223.72	317.89
6.364	9.0	350.09	55.42	354.5	0.302	17.533	16.457	223.90	318.11
6.334	9.3	349.08	57.33	353.8	0.302	17.528	16.457	224.02	318.25
6.305	9.5	348.57	58.06	353.4	0.301	17.525	16.457	224.07	318.31
6.275	9.4	348.57	57.81	353.3	0.301	17.525	16.456	224.05	318.29
6.245	9.2	349.07	56.60	353.6	0.302	17.527	16.456	223.97	318.21
6.215	8.8	349.10	54.40	354.3	0.302	17.531	16.456	223.63	318.04
6.185	8.3	351.68	51.20	355.4	0.302	17.538	16.456	223.36	317.80
6.155	7.7	353.84	48.94	356.9	0.305	17.548	16.455	223.36	317.48
6.126	7.1	356.32	42.11	358.8	0.308	17.569	16.462	223.06	317.12
6.096	6.4	358.40	37.38	360.5	0.308	17.577	16.458	222.77	316.86
6.066	5.9	359.53	34.18	360.5	0.308	17.577	16.458	222.77	316.78
6.036	5.4	358.45	30.97	360.4	0.308	17.576	16.458	222.76	316.77
6.006	4.9	358.45	26.75	360.3	0.308	17.575	16.458	222.76	316.77
5.976	4.4	358.45	22.53	360.3	0.308	17.575	16.458	222.76	316.77
5.945	3.8	358.45	18.31	360.3	0.308	17.575	16.458	222.76	316.77
5.915	3.3	358.45	14.09	360.3	0.308	17.575	16.458	222.76	316.77

0.070	-59.2	-597.8	696.2	631.6	0.595	20.90	339.1	0.459	0.905	0.619
0.071	-59.0	-594.0	692.9	627.9	0.592	20.86	338.9	0.453	0.915	0.622
0.072	-58.8	-590.2	689.7	624.2	0.589	20.81	338.7	0.447	0.924	0.625
0.073	-58.6	-586.4	686.4	620.5	0.587	20.77	338.5	0.441	0.934	0.628
0.074	-58.4	-582.5	683.1	616.7	0.584	20.72	338.3	0.434	0.944	0.631
0.075	-58.2	-578.7	679.8	613.0	0.581	20.68	338.1	0.428	0.955	0.634
0.076	-58.0	-574.9	676.5	609.2	0.578	20.64	337.9	0.422	0.966	0.637
0.077	-57.8	-571.1	673.3	605.4	0.575	20.59	337.7	0.416	0.977	0.640
0.078	-57.6	-567.3	670.0	601.5	0.573	20.55	337.5	0.409	0.988	0.644
0.079	-57.4	-563.4	666.7	597.7	0.570	20.50	337.3	0.402	0.998	0.647
0.080	-57.2	-559.5	663.3	593.8	0.567	20.46	337.1	0.396	1.008	0.650
0.081	-57.0	-555.5	659.9	589.9	0.564	20.42	336.8	0.389	1.018	0.654
0.082	-56.8	-551.6	656.5	585.9	0.561	20.37	336.6	0.381	1.028	0.657
0.083	-56.6	-547.6	653.0	581.9	0.558	20.33	336.4	0.374	1.038	0.661
0.084	-56.4	-543.5	649.5	577.9	0.555	20.28	336.2	0.367	1.048	0.665
0.085	-56.2	-539.4	645.9	573.9	0.552	20.24	336.0	0.359	1.058	0.669
0.086	-56.0	-535.3	642.3	569.8	0.549	20.19	335.8	0.351	1.069	0.672
0.087	-55.8	-531.2	638.7	565.7	0.546	20.15	335.6	0.343	1.079	0.676
0.088	-55.6	-527.0	635.1	561.6	0.543	20.10	335.4	0.335	1.089	0.680
0.089	-55.4	-522.7	631.4	557.4	0.540	20.06	335.2	0.327	1.099	0.684
0.090	-55.2	-518.5	627.6	553.2	0.536	20.01	335.0	0.319	1.109	0.688
0.091	-55.0	-514.2	623.8	549.0	0.533	19.96	334.8	0.311	1.119	0.692
0.092	-54.8	-509.8	620.0	544.8	0.530	19.92	334.6	0.303	1.129	0.696

STATION NO. 4
ITERATION NO. 82

OFF-DESIGN INCIDENCE	STALLING INCIDENCE	LOADING FACTOR	DEV. ANGLE	YS	YP	YPI	YPT	YK	REYN	CF
-6.722	30.243	2.960	0.812	0.036	0.033	0.034	0.033	0.039	4.005	0.933
-6.037	30.319	2.979	0.820	0.036	0.033	0.035	0.033	0.054	3.936	0.935
-6.946	30.193	2.979	0.820	0.036	0.033	0.035	0.033	0.066	3.874	0.936
-7.050	30.465	3.016	0.836	0.036	0.033	0.035	0.033	0.073	3.809	0.937
-7.149	30.536	3.055	0.845	0.036	0.033	0.035	0.034	0.077	3.753	0.938
-7.243	30.605	3.095	0.853	0.036	0.033	0.035	0.034	0.077	3.704	0.939
-7.332	30.672	3.074	0.862	0.036	0.033	0.035	0.034	0.073	3.652	0.940
-7.415	30.739	3.095	0.870	0.036	0.033	0.035	0.034	0.065	3.678	0.941
-7.494	30.805	3.116	0.879	0.036	0.033	0.035	0.034	0.053	3.661	0.941
-7.567	30.870	3.137	0.888	0.036	0.033	0.035	0.034	0.036	3.652	0.942
-7.635	30.935	3.159	0.896	0.036	0.033	0.035	0.034	0.016	3.650	0.942
-7.698	30.999	3.181	0.905	0.036	0.033	0.035	0.034	0.000	3.639	0.942
-7.757	31.061	3.204	0.914	0.036	0.033	0.035	0.035	0.000	3.605	0.943
-7.810	31.121	3.228	0.922	0.036	0.033	0.035	0.035	0.000	3.568	0.944
-7.859	31.179	3.251	0.931	0.036	0.033	0.035	0.035	0.000	3.532	0.945
-7.903	31.233	3.276	0.940	0.036	0.033	0.035	0.035	0.000	3.495	0.946
-7.942	31.285	3.300	0.949	0.036	0.033	0.035	0.035	0.000	3.459	0.947
-7.977	31.334	3.326	0.958	0.036	0.033	0.035	0.035	0.000	3.423	0.948
-8.007	31.380	3.351	0.967	0.037	0.033	0.035	0.035	0.000	3.387	0.949
-8.033	31.422	3.377	0.976	0.037	0.033	0.035	0.035	0.000	3.351	0.950
-8.055	31.461	3.404	0.985	0.037	0.033	0.035	0.035	0.000	3.316	0.951
-8.073	31.496	3.431	0.994	0.037	0.033	0.035	0.035	0.000	3.281	0.952
-8.087	31.528	3.458	1.003	0.037	0.033	0.035	0.035	0.000	3.246	0.953
-8.098	31.556	3.486	1.013	0.037	0.033	0.035	0.035	0.000	3.211	0.954
-8.105	31.580	3.515	1.022	0.037	0.033	0.035	0.035	0.000	3.177	0.955
-8.108	31.600	3.544	1.031	0.037	0.033	0.035	0.036	0.000	3.143	0.956
-8.134	31.611	3.572	1.041	0.038	0.033	0.035	0.036	0.000	3.109	0.957
-8.100	31.601	3.603	1.044	0.038	0.033	0.035	0.036	0.000	3.073	0.958
-8.021	31.575	3.632	1.046	0.038	0.033	0.035	0.036	0.000	3.037	0.959
-8.059	31.544	3.662	1.047	0.038	0.033	0.035	0.036	0.000	3.001	0.960
-8.033	31.509	3.692	1.049	0.038	0.033	0.035	0.036	0.000	2.966	0.961
-8.003	31.460	3.724	1.049	0.039	0.033	0.035	0.036	0.000	2.931	0.963
-7.968	31.311	3.751	1.051	0.039	0.033	0.035	0.036	0.000	2.896	0.964
-7.931	30.997	3.790	1.052	0.039	0.032	0.035	0.036	0.000	2.862	0.965
-7.890	30.675	3.825	1.054	0.039	0.032	0.035	0.036	0.000	2.828	0.966
-7.846	30.343	3.861	1.055	0.040	0.032	0.034	0.036	0.000	2.794	0.967
-7.799	30.003	3.898	1.057	0.040	0.032	0.034	0.035	0.000	2.760	0.968

-7.751	29.654	3.934	1.058	0.040	0.032	0.034	0.035	0.000	2.724	0.969
-7.701	29.285	3.975	1.060	0.041	0.032	0.034	0.035	0.000	2.693	0.971
-7.649	28.921	4.015	1.062	0.041	0.032	0.034	0.036	0.000	2.659	0.972
-7.597	28.551	4.057	1.064	0.042	0.032	0.034	0.036	0.000	2.626	0.973
-7.544	28.186	4.100	1.066	0.042	0.032	0.034	0.036	0.000	2.593	0.974
-7.491	27.822	4.144	1.068	0.042	0.032	0.034	0.036	0.000	2.559	0.976
-7.439	27.457	4.190	1.070	0.043	0.032	0.035	0.036	0.000	2.526	0.977
-7.388	27.092	4.238	1.072	0.043	0.032	0.035	0.037	0.000	2.493	0.978
-7.339	26.727	4.286	1.075	0.044	0.033	0.036	0.038	0.000	2.460	0.979
-7.291	26.356	4.337	1.077	0.044	0.033	0.036	0.038	0.000	2.428	0.981
-7.247	25.971	4.389	1.079	0.045	0.033	0.036	0.039	0.000	2.395	0.982
-7.206	25.571	4.443	1.082	0.046	0.033	0.036	0.039	0.000	2.362	0.983
-7.169	24.774	4.498	1.085	0.046	0.034	0.037	0.040	0.000	2.330	0.985

ROTOR -- 1
PRESSURE RATIO = 1.4332
TEMPERATURE RATIO = 1.1024
EFFICIENCY = 95.2938

STAGE -- 1
PRESSURE RATIO = 1.4530
TEMPERATURE RATIO = 1.1024
EFFICIENCY = 91.9623

OVERALL PERFORMANCE BASED ON MASS-AVERAGED PROPERTIES
TOTAL PRESSURE RATIO = 1.453
TOTAL TEMPERATURE RATIO = 1.102
TOTAL TEMPERATURE DROP = 33.07K
TOTAL-TEMPERATURE EFFICIENCY = 91.963
MASS FLOW RATE = 10.81
POWER OUTPUT = 219.00 HP
AVERAGE FLOW COEFFICIENT = 0.612
AVERAGE WORK COEFFICIENT = 0.891
HUB FLOW COEFFICIENT = 0.709
HUB WORK COEFFICIENT = 1.181

CALCULATED MASS FLOW RATE (lbm/s)

STATION	1	2	3	4	5	6
	10.81000	10.81000	10.80998	10.80997	10.81001	10.81001

DATA FILE FOR HIGH PRESSURE TURBINE SIMULATION (10 GRID POINTS)

```

05100301
990000
02010000
0.100 0.0002 0.005
1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00 1.00
0302010003
9.969 0.000 11.563 0.000
9.969 0.250 11.563 0.250
9.938 2.438 11.625 2.500
9.844 3.813 11.625 3.875
9.656 5.438 12.000 5.625
337.0 1627.0 0.2921 1400.79
1627.0 337.0 0.000 0.000
1627.0 337.0 0.000 0.797
1627.0 337.0 0.000 1.594
92.30 16200.00 1.000 10.00
0.101 102.102 103.104 105.106 106.107 108.110 102.103 104.105 106.104
010303
4.000 0.292 0.289 0.659 2.159 0.140 0.022 0.000
4.000 0.278 0.299 0.882 2.254 0.130 0.020 0.000
4.000 0.265 0.308 0.703 2.350 0.121 0.019 0.000
9.969 10.766 11.563
.312 .283 .257 .233 211 192 .275 .208 .312 .283 .257 .233 .211 .192 .275 .208
020303
58.000 0.425 0.356 0.791 1.294 0.166 0.031 0.03
52.000 0.425 0.280 0.795 1.396 0.153 0.028 0.03
44.000 0.425 0.214 0.799 1.498 0.142 0.026 0.03
9.938 10.781 11.625
999999

```

OUTPUT FILE FOR HIGH PRESSURE TURBINE SIMULATION (10 GRID POINTS)

ANALYSIS MODE

STREAMLINE CURVATURE COMPUTATION

No of stations, NSTAT = 5
 No of grid points, MGRID = 10
 No of points at which inlet prop. are given, NPTS = 3
 Order of polynomial fit to inlet properties, NORD1 = 1

PROPERTY GRADIENTS AT INPUT (prior to curve fit)

(Distance measured from hub or stated as percent of inlet length)

DISTANCE (inches)	TEMP (TOTAL)	PRES (TOTAL)	DISTANCE (%)	STAN IT/S	FLOW ANGLE (DEG)
0.000	1627.0	337.0	0.00	0.00	0.00
0.797	1627.0	337.0	50.00	0.00	0.00
1.594	1627.0	337.0	100.00	0.00	0.00

TEMPERATURE IN DEG K

337.00 1627.00
 (P.S.I.) (DEG.K)

SPECIFIC HEAT : constant pressure (Cp) = 0.292
 RATIO (Cp/Cv) = 1.31

DUCT GEOMETRY (inches)

HUB DISTANCE (Z)	RADIUS (R)	SURROUND DISTANCE (Z)	RADIUS (R)
0.000	9.969	0.000	11.563
0.250	9.969	0.250	11.563
2.438	9.938	2.500	11.625
3.813	9.844	3.875	11.625
5.438	9.656	5.625	12.000

NO OF GRID POINTS

(MGRID) = 10

TOLERANCE (MASS)

(TOLM) = 0.00500

TOLERANCE (DIST)

(TOLDS) = 0.00020

WEIGHTING FACTOR

(WGTFT) = 0.10

CURVATURES ARE SET TO ZERO, (MGRID) = 2

BLOCKAGE FACTORS ARE READ IN, (MFBAL) = 0

MASS FLOW RATE, DESN = 92.30 lbs/sec

SPEED, ONA = 16200.00 rpm

% DESIGN SPEED, PCTN*1000 = 100.0 %

WORK OUTPUT, AVN = 10.00 chp/lbm

NON DIMENSIONAL FLOW AND SPEED

MASS FLOW PARAMETER DESN*(To)^.5/Pc = 11.05

SPEED PARAMETER ONA/(To)^.5 = 401.5

AM = 0.2186E-01

ROJ = 0.2955E+00

TOJ = 1603

POJ = 0.4549E-05

TIPLESS CURVE METHOD IS USED AFTER THE PROGRAM HAS CALLED
 TPRMID = 1

STATOR NO. 1

BLADE GEOMETRY

RADIUS BLADE INLET BLADE OPENING THICKNESS S/C ON ED C/E TET C TOL
 ANGLE PITCH S/S RATIO

α_1
 α_2
 α
 i
 δ
 ζ

blade inlet angle
 blade outlet angle
 blade "opening" or "throat"
 blade maximum thickness
 pitch (spacing)
 stagger angle

c
 i
 δ
 ζ

chord
 incidence angle
 blade back curvature, $j^2/8z$
 trailing edge thickness
 deviation angle

Figure D-1 Blade Geometry Nomenclature

3 of/de 3

PM-1 3½"x4" PHOTOGRAPHIC MICROCOPY TARGET
NBS 1010a ANSI/ISO #2 EQUIVALENT

PRECISIONSM RESOLUTION TARGETS

4 92.29567
5 92.29408

.....
CASE WAS COMPILED IN 47 ITERATIONS
.....
CASE WAS COMPILED IN 95 ITERATIONS
.....

STREAMLINE CURVATURE COMPUTATION

STATION NO. 1
AREA = 107.81in²

ABSOLUTE CONDITIONS

RADIUS	FLOW	ANGLE	MEASUREMENTAL	VELOCITY	TEMPERATURE	MECH	PRESSURE	TEMPERATURE
inches	deg		ft/s	ft/s	°F	NO.	PSI	°F
11.425	0.0	401.95	0.00	402.0	0.157	337.000331	6211627.80	1623.46
11.397	0.0	401.95	0.00	402.0	0.157	337.000331	6211627.80	1623.46
11.226	0.0	401.95	0.00	402.0	0.157	337.000331	6211627.80	1623.46
11.057	0.0	401.95	0.00	401.9	0.157	337.000331	6211627.80	1623.46
10.883	0.0	401.95	0.00	401.9	0.157	337.000331	6211627.80	1623.46
10.707	0.0	401.95	0.00	402.0	0.157	337.000331	6211627.80	1623.46
10.527	0.0	401.95	0.00	402.0	0.157	337.000331	6211627.80	1623.46
10.346	0.0	401.95	0.00	402.0	0.157	337.000331	6211627.80	1623.46
10.158	0.0	401.95	0.00	402.0	0.157	337.000331	6211627.80	1623.46
9.969	0.0	401.95	0.00	402.0	0.157	337.000331	6211627.80	1623.46

1

STREAMLINE CURVATURE COMPUTATION

STATION NO. 2
AREA = 107.81in²

ABSOLUTE CONDITIONS

RADIUS	FLOW	ANGLE	MEASUREMENTAL	VELOCITY	TEMPERATURE	MECH	PRESSURE	TEMPERATURE
inches	deg		ft/s	ft/s	°F	NO.	PSI	°F
11.425	0.0	401.95	0.00	402.0	0.157	337.000331	6211627.80	1623.46
11.397	0.0	401.95	0.00	402.0	0.157	337.000331	6211627.80	1623.46
11.226	0.0	401.95	0.00	402.0	0.157	337.000331	6211627.80	1623.46
11.057	0.0	401.95	0.00	401.9	0.157	337.000331	6211627.80	1623.46
10.883	0.0	401.95	0.00	401.9	0.157	337.000331	6211627.80	1623.46
10.707	0.0	401.95	0.00	402.0	0.157	337.000331	6211627.80	1623.46
10.527	0.0	401.95	0.00	402.0	0.157	337.000331	6211627.80	1623.46
10.346	0.0	401.95	0.00	402.0	0.157	337.000331	6211627.80	1623.46
10.158	0.0	401.95	0.00	402.0	0.157	337.000331	6211627.80	1623.46
9.969	0.0	401.95	0.00	402.0	0.157	337.000331	6211627.80	1623.46

STREAMLINE CURVATURE COMPUTATION

STATION NO. 3
AREA = 110.36in²

ABSOLUTE CONDITIONS

RADIUS	FLOW	ANGLE	MEASUREMENTAL	VELOCITY	TEMPERATURE	MECH	PRESSURE	TEMPERATURE
inches	deg		ft/s	ft/s	°F	NO.	PSI	°F
11.425	75.5	519.93	2022.0	2027.5	0.864	224.073204	2391637.00	1460.73
11.419	75.5	524.16	2059.36	2127.4	0.879	223.045201	2461637.00	1455.92
11.254	75.5	548.82	2067.55	2150.5	0.892	223.022100	2461637.00	1450.87
11.048	75.5	563.97	2116.70	2190.5	0.907	223.044195	2461637.00	1445.58
10.883	74.9	579.47	2147.91	2221.9	0.922	223.149181	2461637.00	1439.99
10.694	74.7	594.12	2178.22	2258.3	0.939	223.093108	2461637.00	1434.13
10.507	74.5	611.38	2210.66	2291.6	0.955	223.025104	2461637.00	1428.93
10.318	74.3	631.39	2243.39	2316.6	0.973	223.040100	2461637.00	1423.54
10.129	74.1	654.11	2278.07	2349.0	0.991	223.051177	2461637.00	1418.48
9.938	73.9	680.43	2318.39	2389.3	1.011	223.145173	2461637.00	1413.35

CONDITIONS RELATIVE TO UPSTREAM ROW (STATION)

LOSS	FLOW	ANGLE	TANGENT	VELOCITY	MECH	PRESS	TEMP	MECH	TEMP	MECH	TEMP
COEF.					NO.			NO.		COEF.	
0.108	75.6	2022.1	2097.5	0.0	0.864	226.08	142.0	0.000	0.000	0.000	0.000
0.107	75.5	2059.3	2127.4	0.0	0.879	223.86	142.0	0.000	0.000	0.000	0.000
0.106	75.3	2106.7	2190.5	0.0	0.892	223.42	142.0	0.000	0.000	0.000	0.000
0.105	74.9	2147.9	2221.9	0.0	0.907	223.40	142.0	0.000	0.000	0.000	0.000
0.104	74.5	2178.2	2258.3	0.0	0.922	223.15	142.0	0.000	0.000	0.000	0.000
0.104	74.5	2190.6	2291.6	0.0	0.939	222.82	142.0	0.000	0.000	0.000	0.000
0.104	74.3	2243.4	2316.6	0.0	0.955	222.46	142.0	0.000	0.000	0.000	0.000
0.103	74.1	2278.1	2349.0	0.0	0.973	222.34	142.0	0.000	0.000	0.000	0.000
0.103	73.9	2318.4	2389.3	0.0	0.991	222.05	142.0	0.000	0.000	0.000	0.000

STATION NO. 3
ITERATION NO. 95

OFF-DESIGN STALLING

INCIDENCE	LOADING	ANGLE	VS	VP	VPT	TR	MECH	CP
-4.000	45.521	8.241	-0.955	0.038	0.040	0.041	0.0024	596.0778
-4.000	45.457	8.119	-0.946	0.037	0.040	0.041	0.0024	464.0778
-4.000	45.394	8.019	-0.937	0.036	0.040	0.041	0.0024	343.0778
-4.000	45.331	7.942	-0.928	0.035	0.040	0.041	0.0024	238.0778
-4.000	45.274	7.887	-0.919	0.034	0.040	0.041	0.0024	153.0780
-4.000	45.214	7.841	-0.910	0.034	0.040	0.041	0.0024	95.0780
-4.000	45.153	7.812	-0.901	0.033	0.040	0.041	0.0024	60.0781
-4.000	45.092	7.784	-0.892	0.032	0.040	0.041	0.0024	33.0781
-4.000	45.032	7.756	-0.882	0.031	0.040	0.041	0.0024	16.0782
-4.000	44.974	7.737	-0.872	0.030	0.040	0.041	0.0024	2.0782

CONDITIONS RELATIVE TO DOWNSTREAM ROW (ROW WITH ANGLE VELOCITY OF 1596.48)

RADIUS	FLOW	ANGLE	TANGENTIAL	VELOCITY	WHEEL	MACH	TOTAL	TOTAL
inches	deg					NO.	PRESSURE	TEMP
11.425	34.6	388.61	449.11	1540.41	0.267	212.995	1470.77	1470.77
11.419	39.6	402.10	457.70	1541.21	0.284	212.584	1470.54	1470.54
11.254	42.1	424.59	460.57	1540.57	0.300	212.601	1471.64	1471.64

TOTAL-TOTAL EFFICIENCY = 86.418
 RADP PUMP RATE. 92.39
 POWER OUTPUT = 17935.29 HP
 ANTIDROP PUMP COEFFICIENT = 0.300
 ANTIDROP MAIN COEFFICIENT = 1.470
 RAD PUMP COEFFICIENT = 0.079
 RAD MAIN COEFFICIENT = 1.749

STATION	CALCULATED RADP PUMP RATE (lbn/s)
1	92.29892
2	92.29892
3	92.29466
4	92.29966
5	92.34437

Appendix D

Turbine Blade Data

The following pages contain the turbine duct and blade geometry estimated from measurements taken of turbine blades from a turbine of current design and supplemented with measurements taken from drawings of blades for the same turbine. Figure D-1 illustrates the blade geometry nomenclature.

α_1'	blade inlet angle	c	chord
α_2'	blade outlet angle	i	incidence angle
o	blade "opening" or "throat"	e	blade back curvature, $j^2/8z$
t	blade maximum thickness	t_c	trailing edge thickness
s	pitch (spacing)	δ	deviation angle
ζ	stagger angle

Figure D-1 Blade Geometry Nomenclature

Geometry at Three Radii for the Four Blade Rows

row	mean radius	high pressure nozzle and rotor		inlet metal angle	tangential curvature	maximum pitch thickness (0.001 in)		chord	blade camber	trailing tip camber		loading radius	trailing edge radius	stagger angle	outlet metal angle	outlet flow angle
		nozzle	rotor			a	b			c	d					
row 04	10.766 LPM	9.949	4.000	0.416	0.426	1.426	2.16	10.144	0.031	0.000	0.203	0.016	0.023	67.5	73.0	
		10.766	4.000	0.427	0.074	1.517	2.25	11.053	0.031	0.000	0.195	0.016	0.023	69.75	73.9	
		11.563	4.000	0.438	0.724	1.651	2.35	12.694	0.031	0.000	0.188	0.016	0.023	64	74.6	
row 05	10.781 LPM	9.938	58.000	0.435	0.461	1.026	1.294	6.154	0.031	0.063	0.070	0.066	0.013	60	64.9	
		10.781	52.000	0.472	0.391	1.111	1.394	7.243	0.031	0.063	0.069	0.066	0.013	61	64.9	
		11.625	46.000	0.509	0.320	1.197	1.496	8.421	0.031	0.063	0.067	0.066	0.013	62	64.9	
row 06	10.997 LPM	9.656	37.000	0.47	0.362	1.213	1.95	3.665	0.000	0.000	0.063	0.024	0.034	61	67.2	
		10.997	37	0.508	0.412	1.382	2.14	5.951	0.039	0.000	0.070	0.019	0.034	60.5	67.0	
		11.85	37	0.583	0.444	1.489	2.27	7.692	0.032	0.000	0.077	0.016	0.034	60	67.0	
row 07	10.949 LPM	9.188	46.000	0.451	0.273	0.731	1.233	1.332	0.047	0.094	0.039	0.023	0.027	54	51.9	
		10.949	35.500	0.458	0.207	0.820	1.292	1.947	0.019	0.094	0.035	0.020	0.027	55.5	56.1	
		12.750	25.000	0.464	0.140	0.908	1.350	2.670	0.031	0.094	0.031	0.016	0.027	57	59.2	

Geometry Required by the Streamline Curvature Program Listed in Appendix B

radius	mean	al	0/a	t/a	a/a	a	0/a	t/a	a/a	a
9.949	4.000	0.292	0.289	0.659	2.16	0.140	0.022	0.000	0.000	0.000
10.766	4.000	0.278	0.299	0.682	2.25	0.130	0.020	0.000	0.000	0.000
11.563	4.000	0.265	0.300	0.703	2.35	0.121	0.019	0.000	0.000	0.000
9.938	58.000	0.425	0.356	0.731	1.294	0.166	0.021	0.063	0.063	0.063
10.781	52.000	0.423	0.280	0.795	1.394	0.153	0.028	0.063	0.063	0.063
11.625	46.000	0.425	0.214	0.799	1.496	0.142	0.026	0.063	0.063	0.063
9.656	37.000	0.387	0.186	0.623	1.95	0.331	0.040	0.000	0.000	0.000
10.997	37.000	0.391	0.192	0.645	2.14	0.232	0.028	0.000	0.000	0.000
11.85	37.000	0.392	0.196	0.657	2.27	0.194	0.022	0.000	0.000	0.000
9.188	46.000	0.417	0.222	0.593	1.233	0.549	0.044	0.044	0.044	0.044
10.949	35.500	0.458	0.140	0.635	1.292	0.421	0.040	0.040	0.040	0.040
12.750	25.000	0.511	0.104	0.673	1.350	0.339	0.034	0.034	0.034	0.034

Appendix E

Drawings for Mould Box

The following seven pages contain the drawings used to make the mould boxes. They are listed below.

Drawing name	Description	Page
MOLD-BOX	Assembly drawing for box to cast blade CC3	E-2
MOLD-BOX TOP	Top of box to cast blade CC3	E-3
MOLD-BOX BOTTOM	Bottom of box to cast blade CC3	E-4
B MOLD-BOX	Assembly drawing for box to cast blade CC1	E-5
B MOLD-BOX TOP	Top of box to cast blade CC1	E-6
B MOLD-BOX BOTTOM	Bottom of box to cast blade CC1	E-7
HOLE PLATE	Plate used in both MOLD-BOX and B MOLD-BOX	E-8

NO	REQD	STEEL PLATE
		PART NAME OR MATERIAL

NOTES:

1. WELD BEFORE FINAL MACHINING.
2. GRIND MARKED SURFACES TO 63 RMS
3. CLEAN AND DEBUR ALL SURFACES
4. ALL WELDS 1/4" MAX.

NOT TO SCALE

B HOLD-BOX TOP	TOLERANCES UNLESS OTHERWISE SPECIFIED
BY: VEDDY KLEIN	FRACTIONAL: 1/16
DATE: 17/01/91	ALL DIMENSIONS IN INCHES
SCALE: 1=2	SHEET 1 OF 1 SHEETS

1	1	1/4" STEEL PLATE
NO	REQD	PART NAME OR MATERIAL

NOTES:
1. CLEAN AND DEBUR ALL SURFACES

HOLE PLATE	TOLERANCES UNLESS OTHERWISE SPECIFIED:
BY: VENDY KLEIN	FRACTIONAL: +/- 1/64
DATE: 29/01/91	ALL DIMENSIONS IN INCHES
SCALE: 1=1	SHEET 1 OF 1 SHEETS

NOT TO SCALE

Appendix F

Moulding and Casting materials

Material	Use
Devcon Flexane 94 liquid Urethane. Stock no's. 15250,15260.	used to make the mould box (referred to as moulding material)
Devcon Plastic Steel Liquid epoxy. Stock no's. 10210,10220,10230.	used to cast the blades (referred to as casting material)
Devcon Paste release agent. Stock no. 19650	used to prevent casting and moulding materials from adhering to surfaces
Canadian Tire Plastic Metal. Stock no. 4756456	Used to fill scratches and holes in epoxy blades.

Appendix G

Equipment Required to Cast Blades

Materials required for casting blades			
Required Item	Quantity Required	Purpose	Previously obtained from
Flat head screw drivers-5"long, 1/4" to 3/16"	2	prying open box prying open other containers	Mechanical shop
7/16" wrenches	2	tightening and loosening hex head screws and nuts	Mechanical shop
Sea clamp	1	clamp centre of box	Mechanical shop
PVC pipe Small (1/2") diameter: 3" long 4" long 6" long Large (1-1/2") diameter: 4" long	(not re-usable) 2 1 1 1	For increasing hydraulic pressure small air holes 1/4" air hole pour hole (final) pour hole (start)	Home Hardware and plumbing store sizes and lengths approximate
Plasticine (does not have to be brand name)		To attach pipes to mold-box. (Window putties do	Mrs. Tiggy Winkles
Piece of wire	1	Clearing holes and checking fluid levels	Thermo lab
Exacto knife	1	Incase its needed	Thermo lab

Materials required for casting blades			
Required Item	Quantity Required	Purpose	Previously obtained from
Rubber gloves	2 pr/ person	protective wear	grocery store and thermo lab
Ventilator mask	1/person	Protective wear (this item should be cleaned before use)	Thermo lab or Mechanical shop
Eye protection		Protective wear	
Mixing containers	2 or 3 (not re-usable)	For measuring and mixing. Large ice cream and juice cans work well.	From homes
Drill and mixing attachment	1	To mix the liquid steel and resin together	Thermo lab
Acetone		To clean up liquid steel	

Materials required to cast blade CC1			
Required Item	Quantity Required	Purpose	Previously obtained from
3/4" diameter rod partly threaded	1	mounting blade and giving inner support	turned the end off a long bolt
Allen keys	1 or 2	tighten collar around rod	Machine shop
Rubber pieces to fit set screw holes (not yet added to box)	2 and extra	Plug inside of set screw hole	Machine shop. Used leather punch and available rubber
Liquid steel	1025 ml approx.	casting material	Mix appropriate amount

Materials required to cast blade CC3			
Required Item	Quantity Required	Purpose	Previously obtained from
3/8" UNC threaded rod, 7" long and nuts	2 2	mounting blade and giving inner support	Cut from threaded rod in machine shop
Wrench (9/16")	1	Tighten external nuts on threaded rod	Machine shop
Rubber pieces to fit set screw holes	2 and extra	Plug inside of set screw hole	Machine shop. Used leather punch and available rubber
Liquid steel	900 ml approx.	casting material	Mix appropriate amount

Appendix H

Detailed Moulding and Casting Procedures

Making the mould

The blade to be used for the mould was coated with release agent. Parts of the mould box where mould material was not desired were also coated with release agent.

A dam was machined, coated with release agent and attached to the end of the blade. This prevented moulding material from flowing over the top of the blade at the non mounting end.

Blade CC3 was screwed into the bottom of the empty box. The moulding material was mixed as per the directions on the box and poured quickly into the bottom of the mould box until reaching the leading and trailing edges of the blade. Air bubbles rose to the top but many were trapped at or near the top in the quickly hardening rubber. This resulted in pockmarks in the mould on the suction side of the blade. The blades cast in this mould box require sanding to remove the bumps which result from these marks. Once the bottom is cast it is coated with release agent. The top of the box is screwed on tightly and moulding material is mixed and poured into one of the holes until it comes out the other three. This required some tipping and shaking of the mould box. Since air bubbles rise there was no problem with air bubbles in this pour.

Blade CC1 is made of acrylic. In order to prevent air bubbles in this box, the package suggestion of using a hot air blower was employed. This helped with the air bubbles however the acrylic blade expanded when heated thus producing an imperfect mould of the original blade. The top half was made the same as the other blade.

Casting the blades

The mould box is cleaned and freed of debris. Old casting material or dried release agent, especially in inside metal corners, can prevent the box from closing properly. The pour hole and all air holes are drilled out.

Once the box is clean, exposed screw holes are taped on the inside (except holes for threaded rods). Short set screws are inserted in holes in bottom of box, recessed from the inside of the mould. Small rubber circles, cut easily with a large leather punch, are inserted above the set screws, to prevent the casting material from flowing into the set screw. These are set flush or recessed with the inside surface. If recessed, extra casting material will need to be sanded off the blades. However, the blade gets scratched around these areas during de-moulding and requires some filling material anyway. If some mould material is removed from the mould in the area the blade gets scratched, then no filling would be required. Alternatively it may be possible to glue a non scratching material such as teflon to the ends of the setscrews.

The mould box is coated with release agent 2 or 3 times as per instructions on the can, the outside where casting material may spill is also coated. Gloves are worn and fume hood used for this procedure. Before putting the box together air holes and pour holes must be cleared of any dried release agent. This can come loose and fall into the box, causing unhardened spots on the blade surface, or it can block off air holes.

Threaded rods should be inserted in their holes with loosely tightened nuts on either side. The top of the box is now put on and all bolts tightened. If it does not fit together it may be necessary to loosen the nuts on the threaded rod. If it does not fit together snugly all around the edges there is probably debris between the two halves of the mould (especially old casting material inside or dirt in the corners of the metal box. A C clamp should be placed and tightened around the centre of the box. Tubing (pvc works very well and is easy to cut) should be placed over air holes and secured with plasticine. A large diameter tube should be placed over the pour hole and

secured with plasticine. A long small tube should be readied for later use in the pour hole by placing plasticine around it. Protective gear should be put on, gloves, smock, safety glasses, respirator. The author and Abbott (1993) found the respirator prevented coughing and headaches otherwise experienced. Mix the material in the container using an electric mixer. Mix well including sides and bottom. Material not mixed will leave soft holes in the blade. Pour into the large pipe until mould box is full. Remove the large pipe and replace it with the small pipe. Pour until the pipe over the large air hole is full, wait for settling, and pour some more, repeat once or twice. Wait two days to remove the blade from the mould. One day may be sufficient since there was something wrong with the first drum of mould material used and the number of days required for curing was not checked with the second drum.

All screws and nuts are removed from the box as well as the small side plate. Air holes are drilled out with the appropriate drills. The top of the box is removed using flat screwdrivers to pry it off, there are indents for these on the sides of the clamping bars. The set screws are turned into the box to push the blade out. Short set screws may have been used during casting to allow the box to be set flat on its bottom. If this is the case they need to be replaced with long set screws which will engage the metal box at all times, since threads in the rubber are stripped.

Appendix I

Control Surface Settings

An iterative procedure is required to determine the control surface settings required to produce flow with uniform inlet conditions and periodic outlet conditions. The experiments discussed in this thesis used the following final settings. Figure I.1 illustrates the nomenclature used below.

Top Flap (tf)	46.0 deg
Bottom Flap (bf)	19.5 deg
Top Tail Board (ttb)	83.5 deg
Bottom Tail Board (btb)	83.0 deg
Bypass 1 (bp1)	35 mm
Bypass 2 (bp2)	29 mm
Floating Wall (fw)	2.5 deg
End Plate Back 1	30 mm
End Plate Back 2	145 mm
End Plate Front 1	34 mm
End Plate Front 2	137 mm
Probe at inlet	0 deg
Probe at outlet	-80 deg

Figure I.1 Control Surface Nomenclature (reproduced from Rodger (1992))

END

1 6-1 1-9 5

FIN