INFORMATION TO USERS

This manuscript has been reproduced from the microfilm master. UMI films the text directly from the original or copy submitted. Thus, some thesis and dissertation copies are in typewriter face, while others may be from any type of computer printer.

The quality of this reproduction is dependent upon the quality of the copy submitted. Broken or indistinct print, colored or poor quality illustrations and photographs, print bleedthrough, substandard margins, and improper alignment can adversely affect reproduction.

In the unlikely event that the author did not send UMI a complete manuscript and there are missing pages, these will be noted. Also, if unauthorized copyright material had to be removed, a note will indicate the deletion.

Oversize materials (e.g., maps, drawings, charts) are reproduced by sectioning the original, beginning at the upper left-hand corner and continuing from left to right in equal sections with small overlaps.

Photographs included in the original manuscript have been reproduced xerographically in this copy. Higher quality 6" x 9" black and white photographic prints are available for any photographs or illustrations appearing in this copy for an additional charge. Contact UMI directly to order.

**ProQuest Information and Learning
300 North Zeeb Road, Ann Arbor, MI 48106-1346 USA
800-521-0600**

UMI[®]

**Physical and Numerical Modelling
of an
In-pit Tailings Management Facility**

by

Anthony C. F. West, B.A.Sc.

**A thesis submitted to the School of Graduate Studies
in partial fulfilment of the requirements for
the degree of Master of Engineering***

**Department of Civil and Environmental Engineering
Carleton University
Ottawa, Ontario, Canada**

*** The Master of Engineering program is a joint program with the University of
Ottawa, administered by the Ottawa-Carleton Institute for Civil Engineering**

Copyright © Anthony C. F. West, 2000

**National Library
of Canada**

**Acquisitions and
Bibliographic Services**

**385 Wellington Street
Ottawa ON K1A 0N4
Canada**

**Bibliothèque nationale
du Canada**

**Acquisitions et
services bibliographiques**

**385, rue Wellington
Ottawa ON K1A 0N4
Canada**

Your file Votre référence

Our file Notre référence

The author has granted a non-exclusive licence allowing the National Library of Canada to reproduce, loan, distribute or sell copies of this thesis in microform, paper or electronic formats.

The author retains ownership of the copyright in this thesis. Neither the thesis nor substantial extracts from it may be printed or otherwise reproduced without the author's permission.

L'auteur a accordé une licence non exclusive permettant à la Bibliothèque nationale du Canada de reproduire, prêter, distribuer ou vendre des copies de cette thèse sous la forme de microfiche/film, de reproduction sur papier ou sur format électronique.

L'auteur conserve la propriété du droit d'auteur qui protège cette thèse. Ni la thèse ni des extraits substantiels de celle-ci ne doivent être imprimés ou autrement reproduits sans son autorisation.

0-612-61028-4

Canada

The undersigned recommend to
the Faculty of Graduate Studies and Research
acceptance of the thesis

**Physical and Numerical Modelling
of an
In-Pit Tailings Management Facility**

submitted by **Anthony C.F. West, B.A.Sc.**
in partial fulfilment of the requirements for
the degree of Master of Engineering

Chair, Department of Civil and Environmental Engineering

Thesis Supervisor

CARLETON UNIVERSITY
February 5, 2001

ABSTRACT

Physical models were constructed of groundwater flowing past a decommissioned in-pit tailings management facility (TMF). A series of experiments was conducted to characterize the rate of solute release from the tailings and the concentrations generated within the down-gradient solute plume. Numerical simulations were carried out to attempt to match these phenomenon.

Solute release was found to decline from a rate controlled by diffusion at the tailings' outside edge towards a rate controlled by advection through their centre. A mixed analytical/numerical model was developed to predict the magnitude of these rates for an idealized full-sized facility with and without a "pervious surround". The pervious surround was shown to result in superior performance after approximately two to 180 years, depending on tailings permeability.

The numerical model was reasonably able to match the observed behaviour. Discrepancies were attributed to inadequate discretization, and difficulties in simulating groundwater flow and solute transport adjacent to the tailings.

ACKNOWLEDGEMENTS

I would like to thank Mr. Ken Raven (Duke Engineering and Services (Canada) Inc.) for his support both of this research and of me. I would also like to express great thanks to Dr. Paul Van Geel (Department of Civil and Environmental Engineering, Carleton University) for his helpful supervision.

I would like to thank Mr. Pierre Trudel (Department of Civil and Environmental Engineering, Carleton University) for his excellent work in the laboratory, as well as for his friendship. Pierre is an artisan of the highest order. Thanks also to Mr. Rob MacLaren (Department of Earth Science, University of Waterloo) for his excellent support of FRAC3DVS.

I would like to thank Dr. Son Nguyen and Dr. Ben Belfadhel (Canadian Nuclear Safety Commission) for their financial support of this project. Also, Mr. Dave Lee (Atomic Energy of Canada Limited) and Dr. Kent Novakowski (Department of Civil Engineering, Queen's University) for their thorough review of the draft report.

I would like to thank Sara Ryan for her help and wisdom in every aspect of life. I would also like to thank my parents for their moral and financial support.

TABLE OF CONTENTS

ABSTRACT	ii
ACKNOWLEDGEMENTS	iii
TABLE OF CONTENTS	iv
LIST OF FIGURES	ix
LIST OF TABLES	xi
LIST OF SYMBOLS	xii
1. INTRODUCTION	1
1.1 In-Pit Disposal of Uranium Mine Tailings	1
1.2 Previous Modelling	5
1.2.1 Rabbit Lake In-Pit TMF	5
1.2.2 Deillmann In-Pit TMF	7
1.2.3 JEB In-Pit TMF	10
1.2.4 Other Modelling	11
1.3 Purpose of the Current Work	12

2. GROUNDWATER FLOW AND SOLUTE TRANSPORT	13
2.1 Porosity and Permeability	13
2.2 Steady-State Groundwater Flow	15
2.2.1 Darcy's Law	15
2.2.2 Parallel Plate Model of Fluid Flow in a Fracture	16
2.2.3 Hydraulic Head	16
2.2.4 Laplace's Equation	17
2.3 Solute Transport	20
2.3.1 Seepage Velocity	20
2.3.2 Advection	22
2.3.3 Dispersion	23
2.3.4 Advection/Dispersion Equation	26
2.3.5 Dispersivity Tensor	33
3. CONCEPTUAL MODEL	37
3.1 Groundwater Flow Model	37
3.2 Solute Transport Model	41
4. PHYSICAL MODEL APPARATUS AND METHODS	44
4.1 Containers and Constant-Head Reservoirs	44
4.2 Materials Testing and Emplacement	47

4.2.1	EPM Model - Host Rock	47
4.2.2	Discrete Fracture Model - Host Rock	53
4.2.2.1	Hydraulic and Tracer Experiments on the Bottom Fracture	55
4.2.2.2	Hydraulic and Tracer Experiments on the Upper Two Fractures	61
4.2.3	Surround	64
4.2.4	Tailings	64
4.3	Instrumentation	66
4.3.1	Manometers	66
4.3.2	Sample Ports	67
4.4	Water Supply	73
4.5	Experiment Operation	74
5.	PHYSICAL MODEL RESULTS	78
5.1	Hydraulic Heads and Specific Discharges	78
5.2	Solute Concentrations in the Surround and Host Rock	83
5.3	Solute Mass Flux Across the Down-Gradient Boundary	94
5.4	Initial and Final Tailings Solute Concentrations	98
5.5	Mass Balance	98
6.	INTERPRETATION OF PHYSICAL MODEL RESULTS	102
6.1	EPM Experiments	102

6.2	DF Experiments	107
6.3	Evaluation of the Transient Conditions Associated with Model Saturation	110
7.	NUMERICAL SIMULATION OF THE EXPERIMENTS	112
7.1	Numerical Model Selection	112
7.2	Numerical Model Construction and Operation	113
7.3	Results	117
7.3.1	Calibration Results	117
7.3.2	Hydraulic Heads, Flow Rates, and Specific Discharges	120
7.3.3	Solute Concentrations in the Surround and Host Rock	126
7.3.4	Solute Mass Flux Across the Down-Gradient Boundary	134
7.4	Full-Pit Simulations	137
7.4.1	Methods	137
7.4.2	Results	137
8.	DISCUSSION AND APPLICATION TO A FULL-SCALE PROBLEM	142
8.1	Discussion	142
8.2	Analysis of the Full-Scale Problem	144
9.	CONCLUSIONS	150
9.1	General Conclusions	150

9.2	Evaluation of Physical Models	151
9.3	Evaluation of Numerical Model	152
10.	RECOMMENDATIONS	154
11.	REFERENCES	156
Appendix A -	Ex-Situ Materials Testing Data	159
Appendix B -	In-Situ Materials Testing Data	163
Appendix C -	Early Time Concentration Data	169
Appendix D -	Monitoring Round Data	173
Appendix E -	Tailings Concentration Data	209
Appendix F -	Selected Photos Showing Physical Model Construction	217

LIST OF FIGURES

Figure 1.1 Phases at an in-pit tailings management facility	4
Figure 1.2 Locations of northern Saskatchewan in-pit TMFs	6
Figure 1.3 Conceptualization of three northern Saskatchewan TMFs	8
Figure 2.1 Tangent law for the refraction of groundwater	21
Figure 2.2 One-dimensional advection/dispersion	28
Figure 2.3 One dimensional advection/dispersion of a decaying source	31
Figure 2.4 Graph of dimensionless dispersion coefficient vs. Peclet number	34
Figure 3.1 Schematic of conceptual model	38
Figure 4.1 Equivalent porous medium (EPM) physical model design	45
Figure 4.2 Discrete fracture (DF) physical model design	46
Figure 4.3 EPM host rock tracer experiment results	52
Figure 4.4 Bottom fracture sample port and manometer locations	57
Figure 4.5 DF host rock tracer test results	63
Figure 4.6 Manometer locations - EPM model	68
Figure 4.7 Sample port locations - EPM model	69
Figure 4.8 Sample port locations - DF model	70
Figure 4.9 Sample port hardware	72
Figure 5.1 Equipotential and flow lines - EPM gravel-surround experiment	79
Figure 5.2 Equipotential and flow lines - EPM sand-surround experiment	80
Figure 5.3 Concentration vs. time in port 18B in all four experiments	84

Figure 5.4 Solute concentration at 0.7 days - EPM gravel-surround experiment	85
Figure 5.5 Solute concentration at 8.2 days - EPM gravel surround experiment	86
Figure 5.6 Solute concentrations at 1.5 days - EPM sand-surround experiment	88
Figure 5.7 Solute concentration at 8.3 days - EPM sand-surround experiment	89
Figure 5.8 Solute concentration at 9.3 days - DF gravel-surround experiment	90
Figure 5.9 Solute concentration at 18 days - DF gravel-surround experiment	91
Figure 5.10 Solute concentration at 6.8 days - DF sand-surround experiment	92
Figure 5.11 Solute concentration at 17 days - DF sand-surround experiment	93
Figure 5.12 Solute mass flux across boundary vs. time in all four experiments	96
Figure 5.13 Solute mass flux across boundary vs. time in comparable experiments	97
Figure 5.14 Residual solute concentration in tailings in all four experiments	99
Figure 7.1 EPM and DF numerical model mesh	115
Figure 7.2 Equipotential lines and particle traces in EPM simulations	123
Figure 7.3 Equipotential lines and particle traces in DF gravel-surround simulation ..	125
Figure 7.4 Equipotential lines and particle traces in DF sand-surround simulation ...	127
Figure 7.5 Solute concentrations in EPM gravel-surround simulation	128
Figure 7.6 Solute concentrations in EPM sand-surround simulation	130
Figure 7.7 Solute concentrations in DF gravel-surround simulation	131
Figure 7.8 Solute concentrations in DF sand-surround simulation	132
Figure 7.9 Observed and simulated solute mass flux across boundary vs. time	135
Figure 7.10 Solute concentrations within tailings in the full-pit simulations	138
Figure 7.11 Solute mass flux and cumulative mass loss vs. time in full-pit simulations	

.....	141
Figure 8.1 Conceptualization of solute release vs. time at an in-pit TMF	143
Figure 8.2 Rate of solute release vs. time from the full-scale facility	148

LIST OF TABLES

Table 3.1 Measured hydraulic conductivities - northern Saskatchewan in-pit TMFs ...	40
Table 4.1 Summary of first fracture tracer experiment data	59
Table 4.2 Summary of experiments completed	77
Table 5.1 Estimated specific discharges in EPM experiment	81
Table 5.2 Summary of outflow rates	82
Table 5.3 Mass balance	101
Table 6.1 Peclet numbers in the two EPM experiments	102
Table 7.1 Parameter estimates	117
Table 7.2 Comparison of calculated and observed flow rates and hydraulic heads	121
Table 8.1 Simulated specific discharges at the full-scale site	145
Table 8.2 Maximum advective flux through the tailings at the full-scale site	146
Table 8.3 Maximum diffusive flux out of the tailings at the full-scale site	147

LIST OF SYMBOLS

α_L	Longitudinal dispersivity
θ_1, θ_2	Angles of approach and exit across a hydraulic conductivity discontinuity
μ	Fluid viscosity
ρ	Fluid density
ρ_d	Dry mass bulk density
ρ_s	Particle mass density
τ	Tortuosity
$2b$	Fracture aperture
C	Solute concentration
C_o	Initial solute concentration in pit
d	Mean grain diameter
D	Coefficient of hydrodynamic dispersion
D_d	Coefficient of molecular diffusion
D_m	Coefficient of mechanical dispersion
D_o	Free water diffusion coefficient
g	Acceleration due to gravity
h	Hydraulic head
h	Depth of conical pit
$\overline{J}$	Solute mass flux due to hydrodynamic dispersion
$\overline{J}_a$	Solute mass flux due to advection

$\overline{J}_d$	Solute mass flux due to diffusion
$\overline{J}_m$	Solute mass flux due to mechanical mixing
K	Hydraulic conductivity tensor
K_f	Saturated hydraulic conductivity of a fracture
L	Fracture length
$\overline{M}$	Rate of solute mass flux across down-gradient boundary
$\overline{M}_a$	Rate of solute mass flux due to advection
$\overline{M}_d$	Rate of solute mass flux due to diffusion
n	Porosity
p	Pressure head
Pe	Peclet number
$\bar{q}$	Specific Discharge
Q	Volumetric flow rate
r	Pit radius
t	Time
$\bar{v}$	Seepage velocity
V_T	Total volume of soil
V_v	Volume of voids in a volume of soil V_T
w	Fracture width
x,y,z	Coordinate directions
z	Elevation head

1. INTRODUCTION

1.1 In-Pit Disposal of Uranium Mine Tailings

The best description of uranium mine tailings emerges from a description of the process by which they are created. At a mine site ore is extracted from either an open pit or from an underground cavity. The uranium is extracted from the ore by the process of milling. Milling is accomplished by first crushing and grinding the ore until the appropriate ratio of surface-area to volume has been achieved. The resulting material is saturated with acid and the uranium, which is preferentially dissolved into the acid, is extracted. Once neutralized with lime and mixed with crushed rock, the residue is known as tailings. Tailings contain crushed rock, chemical precipitates, non-targeted metals, and trace amounts of uranium. Depending on the quantities and nature of the remaining metals, it is toxic, radioactive, easily oxidized, and has a tendency to produce acid leachate.

When tailings emerge from the milling plant they are a fine-grained material contained within a slurry containing up to 70% water. The tailings are pumped to their place of disposal, where, if improperly dealt with, they can cause detrimental health effects to humans and other members of the local ecosystem (Frost, 1998). Techniques for the management and minimization of these effects have developed along with the development of the uranium mining industry itself. From the 1950s to the early 1970s, when mined ore grades were typically much less than 1%U, tailings were piped to local depressions or impoundments and

allowed to drain and consolidate. In the 1970s, with mined ore grades climbing above 1%U, complete isolation of tailings in above-ground engineered cells was the preferred tailings management option. These facilities relied on impermeable liners to separate the tailings from the surrounding environment. By their very nature, these liners prevented drainage of the pore water in the tailings, allowed build-up of high pore water pressures, and created a high potential for leakage and failure.

In the 1980s, a shift in tailings management philosophy took place. It was for the first time proposed to place tailings in pits, beneath the water table. It was argued that the benefits of placing the tailings in an isolated, anaerobic, and stable environment outweighed the negative consequences of the slow release of contaminants into the surrounding groundwater. Furthermore, with ore grades of greater than 12%U soon to be mined at the McArthur River site in northern Saskatchewan, the relative volume of tailings produced for each tonne of uranium has been reduced to such an extent that the additional expense of the pit excavation is economically justifiable. Thus, the in-pit Tailings Management Facility (TMF) represents the state-of-the-art in the management and disposal of uranium mine tailings.

The lifespan of an in-pit TMF is closely linked to the life of the mine and milling operation, and can be divided into three phases: the preparatory phase, the operational phase, and the post-decommissioning phase. In the preparatory phase, the pit is mined out of the host rock, and the ore and waste rock are stored on surface. A drift is then excavated away from the bottom of the pit, and connected to the ground surface with a shaft. Drainage of the pit can

subsequently be controlled by pumping water out of the bottom of the pit via the drift and shaft. The preparatory phase is completed by lining the bottom of the pit with a highly permeable material such as waste rock. This material makes up the “bottom drain”, and sump.

The operational phase of the life of an in-pit TMF is shown schematically in the top half of Figure 1.1. During this phase, slurry tailings are piped from the milling plant, deposited on top of the bottom drain, and allowed to consolidate under their own weight. If, during tailings deposition, the sides of the pit are further lined with a coarse material, a “side drain” or “pervious surround” is formed. As the tailings consolidate the released pore water is collected in the drains and pumped to a treatment facility. In this way the tailings are deposited sub-aerially (above the water table) and the degree of consolidation is maximized. The pumping also draws groundwater inward from the host rock, creates a capture zone, and minimizes the migration of solute into the surrounding groundwater.

When the tailings are deposited without lining the sides of the pit, the facility is said to have a “natural surround”. Pumping of the sump can only draw groundwater downwards through the consolidating tailings and they are deposited sub-aqueously (below the water table).

Decommissioning of the facility occurs when the supply of tailings runs out or when the capacity of the pit has been reached. Decommissioning consists of capping the facility, grading and cleaning up the surface, and shutting off the pump. The post-decommissioning

a) Operational Phase

b) Post decommissioning phase

Figure 1.1 Phases at an in-pit tailings management facility

phase of the life of an in-pit TMF is shown schematically in the bottom half of Figure 1.1. During this phase, the groundwater returns to its natural level and the flow direction and velocity is dictated by the regional topography and hydrogeology. Groundwater flowing past and through the submerged tailings becomes contaminated by materials contained within the tailings, and a solute plume will form down-gradient of the facility. Thus, the performance of an in-pit TMF can be expressed in terms of the rate of solute release from the facility and the solute concentrations generated in the down-gradient plume. It is this performance that is the subject of this research.

1.2 Previous Modelling

The in-pit disposal concept for uranium mine tailings is being used at three sites in northern Saskatchewan: the Rabbit Lake In-Pit TMF at Rabbit Lake, the Deillmann In-Pit TMF at Key Lake, and the JEB In-Pit TMF at McClean Lake. The locations of these three facilities are shown in Figure 1.2. Groundwater flow and solute transport modelling has been used as a tool for the prediction of performance at all three sites. In fact, as supporting evidence in the various applications for regulatory approval, modelling has helped to shape the concept from its inception to its current state. A brief history of this modelling is provided below.

1.2.1 Rabbit Lake In-Pit TMF

Groundwater flow modelling was carried out in the early 1980's by Geocon Inc., consultants

Figure 1.2 Locations of northern Saskatchewan in-pit tailings management facilities

to Gulf Minerals. This modelling consisted of two-dimensional steady-state finite-element groundwater flow modelling of the in-pit TMF in plan and section. The modelling was carried out using a heat-analogue code, and only considered the hydraulic conductivity fields (of the host rock, the pervious surround, and the tailings), and the assumed regional gradient. The results of the modelling were used to create flow-net diagrams, and to illustrate the low hydraulic gradient across the tailings that results from the use of a pervious surround.

The Rabbit Lake in-pit TMF is being constructed with a full pervious surround, and the disposal concept is shown schematically in Figure 1.3a.

1.2.2 Deillmann In-Pit TMF

Regional and local scale groundwater flow modelling was carried out using the equivalent porous media (EPM) finite difference model MODFLOW. Solute transport modelling was carried out using a variety of analytical, semi-analytical, and numerical models, as summarized below:

- Solute loadings to the overlying Deillmann Pond were calculated based on the 3-D flow model estimates of advective flux within both the tailings and within the pervious surround (or variations thereof), coupled with a 1-D analytical diffusion model, assuming a concentration of zero in the pervious surround, and a constant source concentration in the tailings.

Figure 1.3 Conceptualization of three northern Saskatchewan tailings management facilities

- 1-D analytic solute transport modelling was carried out for idealized flow-paths within the overburden, sandstone, and basement rock. These models were based on the solution of the advection-dispersion equation, with appropriate velocities (from the 3-D flow modelling), and solute boundary conditions.
- 2-D horizontal flow and transport modelling was carried out for the overburden using the EPM finite-element models AQUIFER and LTGPLAN, respectively. This modelling was carried out to assess the impact of solute transport from the Deillmann Pond through the overburden to neighbouring surface water bodies.

The analytical methods employed at the Deillmann site are sound, in principle, but are based on assumptions that, on close examination, may be difficult to justify. Specifically, diffusion from the tailings into the pervious surround was based on a continuous and very high concentration gradient. This assumption provides a large and continuous solute source into the pervious surround, which under a full-side drain scenario is swept into the overlying Deillmann Pond. This analysis led to the study's conclusion, that a smaller side-drain which is not connected to the overlying Deillmann Pond gives better overall system performance. In reality, the assumption of a continuous very-high concentration gradient may have been an overly-conservative assumption.

The Deillmann in-pit TMF is being constructed with a pervious surround in the lower half of the pit, and a natural surround in the upper half. It is shown schematically in Figure 1.3b.

1.2.3 JEB In-Pit TMF

Regional and local scale groundwater flow modelling was carried out using MODFLOW. Solute transport modelling was carried out using a variety of different analytical, semi-analytical, and numerical models, as summarized below:

- 3-D solute transport modelling was carried out using the local-scale MODFLOW flow model coupled with the advection/dispersion-based solute transport model MT3D.
- 1-D fracture flow and solute transport modelling was carried out for an idealized fracture using the semi-analytical model Pollute v6.0. The purpose of this modelling was to illustrate the effects of matrix-diffusion on solute movement.
- 1-D solute transport modelling through an idealized section of lake-bed sediments was carried out using Pollute v6.0. Source concentrations were taken from the 3-D solute transport model.

The fully-coupled approach used at the JEB site should be a better approach than that used at Deillmann, as the complex 3-D flow-dependent processes should be better simulated. The accuracy of this method is highly dependent on the adequacy of the domain discretization, however, and this critical aspect was not discussed in detail in the modelling reports reviewed.

The JEB in-pit TMF was originally designed with a pervious surround. Subsequent modelling suggested that solute loading to the surrounding environment would be lower without it (Ben Balfadhel, 2000). Thus, the JEB in-pit TMF is being constructed with a natural surround. It is shown schematically in Figure 1.3c.

1.2.4 Other Modelling

A comparison of the relative performance of three tailings containment strategies was performed by an independent contractor (Misfeldt et al., 1999). The three containment strategies were: the pervious surround, the natural surround, and the hydraulic cage (i.e. a permeable trench excavated into the host rock which encircles but is not in contact with the pit). The analysis considered the degree of consolidation afforded by the various strategies, as well as the rate of solute release for different ratios of host to tailings hydraulic conductivity. The latter analysis was performed using coupled two-dimensional groundwater flow (SEEP/W) and solute transport (CTAN/W) codes.

The analysis found that when the hydraulic conductivity of the tailings was five times or more lower than that of the host material the rate of solute release from the tailings was dominated by diffusion. The hydraulic cage was found to provide the lowest overall rate of solute release (for all K ratios), followed by the natural surround, and then the pervious surround. It was suggested that when the host rock hydraulic conductivity is greater than 10 times that of the tailings, a pervious surround is likely not required.

One serious short coming of this modelling was that it considered only steady-state scenarios. The results of the current study show that transience must be incorporated into the analysis of an in-pit TMF.

1.3 Purpose of the Current Work

At present, the Rabbit Lake, Deilmann, and JEB in-pit TMFs are all in the operational phase of their respective lifespans, and no other in-pit TMF has reached the decommissioning phase. The resulting dearth of performance data from an actual decommissioned facility has meant that the uranium mining industry has had to rely on predictive modelling to demonstrate the efficacy of in-pit disposal, and to support individual license applications.

The purpose of the work described in this thesis was twofold:

- to contribute to a better understanding of the fundamental processes and parameters that affect performance of an in-pit TMF, specifically with regards to the pervious vs. the natural surround approach; and
- to evaluate available numerical modelling tools for their ability to simulate the fundamental processes.

2. GROUNDWATER FLOW AND SOLUTE TRANSPORT

This section provides a summary of the physics of groundwater flow and solute transport. It has been included here to provide background to the problem under consideration, as well as to introduce terms and concepts that are important to the discussion in later sections.

2.1 Porosity and Permeability

A typical geologic material contains three phases: the solid phase, the liquid phase, and the gaseous phase. Typically, the solid phase forms a deformable “skeleton”, and it is through the voids in this skeleton that the liquid and gaseous phases may travel. The porosity of a porous medium is defined as the ratio of the volume of the voids to the total volume (Domenico and Schwartz, 1990):

$$n = \frac{V_v}{V_T} \quad (1)$$

where n is the porosity of a volume of soil V_T , and V_v is the volume of the voids contained within it.

While porosity describes the relative abundance of voids in a given material, the term does little to describe the ease with which liquids may flow through it. This characteristic, termed permeability, is dependent more on the microscopic arrangement of the pores than on their

relative abundance. Due to the complexity of quantifying and analysing exactly the microscopic characteristics of the solid phase skeleton, these characteristics are typically replaced with a statistically-based continuum model at the “macroscopic” scale. At this scale, the independent variables in the model (e.g. porosity, permeability) are chosen such that the dependent variables (e.g. fluid velocity, degree of fluid mixing) reflect the average values observed in the real material. So long as the average values are correct at the scale of the study in question, this approach is valid.

A representative elemental volume (REV) is the volume of a given material below which the macroscopic continuum approach is not valid (Bear, 1972). For example, it is unrealistic to use averaged values to meaningfully describe fluid velocity and flow directions past three pea-sized grains of gravel packed into an open-ended cylinder the size of a thimble. On the other hand, average values describe quite adequately flow through the same thimble packed with a fine-grained silt. Thus we say that the thimble is smaller than the REV of the gravel and larger than the REV of the silt.

In a fractured but otherwise relatively impermeable rock groundwater flows primarily through the network of open fractures. The characteristics of the fracture network such as the spacing and connectivity dictate the size of the rock’s REV. When the REV is small compared to the size of the site under consideration, the macroscopic continuum approach is appropriate, and the rock is modelled as an “equivalent porous medium”. When the size of the REV approaches the size of the site, however, the fracture network must be considered

as separate from the intact portion of the rock. The rock is modelled as a system of “discrete fractures”. Both of these techniques for the modelling of groundwater flow and solute transport at an in-pit TMF are considered as part of this research.

2.2 Steady-State Groundwater Flow

2.2.1 Darcy's Law

Specific discharge is the volumetric rate of groundwater flow across a unit cross-sectional area normal to the direction of flow, and is described by Darcy's Law (Bear, 1972):

$$\bar{q} = -K \text{ grad } h \quad (2)$$

where $\bar{q}$ is the specific discharge vector with units of $[LT^{-1}]$, $\text{grad } h$ is the gradient of the hydraulic head with units of $[LL^{-1}]$, and K is the hydraulic conductivity tensor with units of $[LT^{-1}]$. The hydraulic conductivity tensor is a description of the medium's permeability to water with a given density and viscosity.

Darcy's law is an empirical law that relates, via the constant of proportionality, K , the flow rate of water through a volume of porous media to the change in hydraulic head measured across it. Sands and gravels allow a high flow rate through them for a small drop in head, and have a high hydraulic conductivity. Silts and clays, allow very little flow, even with large head drops, and thus have a low hydraulic conductivity.

Darcy's law is also a macroscopic law. For a given cross-sectional area, hydraulic gradient, and hydraulic conductivity, it predicts the macroscopic (average) flow rate of water travelling through the soil, and does not describe the microscopic (actual) velocity of water between the soil grains.

2.2.2 Parallel Plate Model of Fluid Flow in a Fracture

Fluid flow through a fracture has been researched extensively. It has been found that a physically-based estimate of a fracture's hydraulic conductivity can be determined using the Navier-Stokes equations by assuming the fracture to behave as a pair of two-dimensional parallel plates. The saturated hydraulic conductivity of a fracture, K_f , is given by (Bear, 1972):

$$K_f = \frac{\rho g (2b)^2}{12\mu} \quad (3)$$

where $2b$ is the fracture aperture with units of $[L]$, ρ is the fluid density with units of $[ML^{-3}]$, μ is the fluid viscosity with units of $[MLT^{-1}]$, and g is the acceleration due to gravity with units of $[LT^{-2}]$.

2.2.3 Hydraulic Head

Implied but not stated in the previous paragraphs is that groundwater flows from areas of

high to low hydraulic head. Hydraulic head is defined as the height to which water will rise in a manometer relative to an arbitrary datum. More specifically, hydraulic head is defined as the sum of the elevation head and the pressure head (Freeze and Cherry, 1979):

$$h = z + \frac{p}{\rho g} \quad (4)$$

where h is the hydraulic head with units of $[L]$, z is the height above the datum to the point of measurement with units of $[L]$, p is the gauge pressure of water at that point with units of $[ML^{-1}T^{-2}]$, ρ is the density of water with units of $[ML^{-3}]$, and g is the acceleration due to gravity. This definition is recognizable as Bernoulli's "total head" minus the velocity head which, for typical groundwater applications, is considered to be negligible.

2.2.4 Laplace's Equation

Darcy's law describes how groundwater moves ($\bar{q}$) through a medium with a certain ease-of-flow characteristic (K) in response to a driving force ($\text{grad } h$). To obtain a complete description of groundwater flow in a porous medium requires also a description of how groundwater is stored. For saturated steady-state groundwater flow the continuity equation states that the rate of fluid mass into an elemental control volume is equal to the rate of fluid mass out of it. Continuity, when coupled with Darcy's law, and the assumption of a homogeneous and isotropic hydraulic conductivity tensor, provides the following partial differential equation (Bear, 1972):

$$\text{div}(\text{grad } h) = 0 \quad (5)$$

This equation is called Laplace's equation. It is a mathematical description of the spacial change in hydraulic head at any point in a steady-state groundwater flow field through a homogeneous, isotropic porous medium. To find a function $h(x,y,z)$ that satisfies Laplace's equation requires that the domain geometry and boundary conditions be specified. Through this process we are creating a boundary value problem, and the action of solving it is known as mathematical modelling.

Once found, the solution to Laplace's equation can be represented as surfaces of equal head, or equipotential surfaces. Lines orthogonal to these surfaces point in the direction of maximum head change, and thus show the direction of the hydraulic gradient. Since groundwater flows in the direction opposite to the hydraulic gradient (termed the down-gradient direction) these lines also indicate the direction of groundwater flow, and are termed flow lines. The spacing between the equipotential surfaces indicates the spacial rate of change of hydraulic head and thus provide the magnitude of the hydraulic gradient. This hydraulic gradient information, when coupled with Darcy's law provides the specific discharge at every point in the model domain.

When groundwater flow lines do not deviate significantly outside of a plane then groundwater flow can be simplified to a two-dimensional problem. In this case, the intersection of the equipotential surfaces with the plane make equipotential lines, and these

lines, together with the flow lines, define a “flow net”. The graphical construction of a flow net (in compliance with boundary geometry and conditions, and in accordance with several well-established rules) is one of the easiest ways to solve Laplace’s equation.

When groundwater flow lines are everywhere parallel, then groundwater flow can be further simplified to a one-dimensional problem. The classic example of one-dimensional flow is in a permeameter used for testing a soil’s hydraulic conductivity. In mathematical terms, this device is a simple pseudo-one-dimensional model domain whose dimensions are known, and which contains a porous medium. The hydraulic heads at either end are measured in the laboratory, and can be applied to the mathematical model. Laplace’s equation predicts that the hydraulic head will drop linearly across the domain from the specified head at the up-gradient end to the specified head at the down-gradient end, regardless of the hydraulic conductivity of the medium. The hydraulic conductivity of the medium is then determined by finding the one value that makes the model correctly predict the measured flow rate. (Since the model turns out to be a single equation with a single unknown (K), this adjusting procedure is a one-step process.)

In the previous paragraph it was stated that the head distribution in a model domain is completely independent of the hydraulic conductivity. This is true only if the hydraulic conductivity is homogeneous throughout the domain. If this condition is not met Laplace’s equation does not apply, and a flow net cannot, in its most basic form, be constructed. All is not lost, however, because a basic law governing the behaviour of groundwater flow at a

hydraulic conductivity discontinuity can be brought to bear. The tangent law for the refraction of groundwater is illustrated in Figure 2.1 and is stated as follows (Freeze and Cherry, 1979):

$$\frac{K_1}{K_2} = \frac{\tan \theta_1}{\tan \theta_2} \quad (6)$$

where K_1 and K_2 are the values of hydraulic conductivity on the up- and down-stream sides of the discontinuity, respectively, and θ_1 and θ_2 are the angles of incidence and refraction taken with respect to the normal to the boundary at that point. Simply stated, when groundwater crosses from a zone of high hydraulic conductivity to low hydraulic conductivity, the angle it leaves the boundary is more perpendicular to it than the angle at which it approached.

2.3 Solute Transport

2.3.1 Seepage Velocity

Specific discharge is the volumetric flow rate of fluid through a unit area of porous medium, a flux. In the case of a granular material or a fractured rock represented as an equivalent porous medium, the fluid can only travel through the pore space, not through the entire unit area. The average velocity through the porous medium is termed the seepage velocity, and is defined as follows (Freeze and Cherry, 1979):

Figure 2.1 Tangent law for the refraction of groundwater

$$\bar{v} = \frac{\bar{q}}{n} \quad (7)$$

where $\bar{v}$ is the seepage velocity with units of $[LT^{-1}]$, $\bar{q}$ is the specific discharge, and n is the porosity. While this equation is simple enough, the “porosity” of the porous medium can be further broken down into a variety of categories, and choosing a porosity to describe seepage velocity is often a complex proposition (which depends on the choice of REV). If a fractured rock is being represented as an EPM, the porosity that best describes the velocity in the fracture network is the ratio of the fracture aperture to the fracture spacing, or “fracture porosity”. When fractures are represented discretely, fluid is assumed to flow uniformly across the fracture aperture and the seepage velocity is equal to the specific discharge. In the discussions that follow, emphasis has been placed on solute transport in a granular or EPM model. For the most part, the equations presented apply equally to a discrete fracture, with the porosity of unity.

2.3.2 Advection

Advection is the process of solute movement whereby the dissolved mass is transported along with the moving groundwater. To completely describe this movement would require, of course, a description of all the microscopic velocities contained within the flow field. However, the adoption of Darcy’s law leads to a macroscopic description of groundwater flow. As has been shown in previous sections, Darcy’s law, coupled with a sensible choice

of porosity, provides an estimate of the seepage velocity or “average linear velocity”. It follows that the solute contained within the flowing groundwater also travels, on average, at this velocity. Thus the average solute mass flux due to advection can be defined as follows (Gillham and Cherry, 1982):

$$\bar{J}_a = \bar{v}_n C = \bar{q} C \quad (8)$$

where $\bar{J}_a$ is the mass of solute crossing a unit area of porous medium oriented normal to the flow direction per unit time with units of $[ML^{-2}T^{-1}]$, and C is the solute concentration with units of $[ML^{-3}]$.

2.3.3 Dispersion

As was discussed above, the definition of advective flux is an average rate of mass transport. Consider a volume of liquid containing a high concentration of solute relative to the surrounding groundwater. If advection were the only transport mechanism, the volume of water would move along at the seepage velocity, and the concentration contained within it would remain unchanged. In reality, as it flows along, the solute mass in the volume tends to spread outwards into the surrounding, lower concentration, groundwater. This irreversible tendency of solute to move from areas of high concentration to low concentration is the result of molecular diffusion and mechanical mixing, and is termed hydrodynamic dispersion, or simply dispersion (Bear, 1972).

Molecular diffusion is the process whereby solute moves in the direction of lower concentration due to an imbalance in thermal and kinetic energy expressed by the chemical potential (Domenico and Schwartz, 1990). Fick's first law, modified to account for the presence of the solid phase, provides an estimate of the diffusive mass flux, as follows:

$$\bar{J}_d = -nD_d \text{ grad } C \quad (9)$$

where $\bar{J}_d$ is the mass of solute crossing a unit area of porous medium oriented normal to the direction of the concentration gradient per unit time with units of $[ML^{-2}T^{-1}]$, and D_d is the coefficient of molecular diffusion in the porous medium or effective diffusion coefficient with units of $[L^2T^{-1}]$.

Due to the tortuous nature of the diffusion pathway within the porous medium, the effective diffusion coefficient is generally lower than the free water diffusion coefficient, D_o . A coefficient is introduced to express this reduction (Bear, 1972):

$$D_d = \tau D_o \quad (10)$$

where τ is the tortuosity ($0 < \tau < 1$) of the porous medium. A rigorous analysis of dimensions reveals that the units of τ are $[L_t^2 L_w^{-2}]$ where the subscript t indicates total length, or length of the porous medium, and the subscript w indicates length of water. The units of porosity are similarly expressed as $[L_w^3 L_t^{-3}]$.

A group of flowing water molecules initially grouped together quite closely might, as a result

of a microscopically random velocity field, become quite dispersed. A high concentration of solute contained within that water would obviously become diluted in the process. This is referred to as mechanical mixing, and, in the sense that it causes solute to move in the direction of decreasing concentration due to processes at the sub-REV scale, is analogous to molecular diffusion. Researchers have found that the most reasonable way to express mechanical mixing is through a diffusion equation similar to Equation 9:

$$\bar{J}_m = -n D_m \text{ grad } C \quad (11)$$

where $\bar{J}_m$ is the mass of solute crossing a unit area of porous medium oriented normal to the direction of the concentration gradient per unit time with units of $[ML^{-2}T^{-1}]$, and D_m is the coefficient of mechanical dispersion in the porous medium with units of $[L^2T^{-1}]$.

In flowing groundwater, the processes of molecular diffusion and mechanical mixing take place concurrently, and their combined effect is termed hydrodynamic dispersion. Thus, the solute mass flux due to hydrodynamic dispersion is expressed as follows:

$$\bar{J} = -n D \text{ grad } C \quad (12)$$

where D is the coefficient of hydrodynamic dispersion, defined as follows:

$$D = D_d + D_m. \quad (13)$$

As developed, the coefficients of hydrodynamic dispersion and tortuosity are statistically-based second-rank tensors. The dispersion tensor is further discussed in Section 2.3.5. The

tortuosity tensor is assumed to behave as a scalar.

2.3.4 Advection/Dispersion Equation

The equations for advective and dispersive flux together describe the relationship between two dependent variables: the solute mass flux vector, and the concentration (a scalar). In order to determine how these variables distribute themselves in space and time requires the use of another equation of continuity. Neglecting any loss of solute mass due to reactions, the equation of conservation of mass for an elemental control volume can be stated as follows: the net rate of change of solute mass within the element equals the mass flux of solute into the element minus the mass flux of solute out of it. By combining Equations 8 and 12 with the continuity equation, the partial differential equation describing solute transport in a steady-state groundwater flow field in a homogeneous porous medium can be stated as follows:

$$\frac{\partial C}{\partial t} = \text{div}(D \text{ grad } C) - \bar{v} \text{ grad } C . \quad (14)$$

The advection dispersion equation, in this form is only applicable to single porosity materials. In a discrete fracture model, transport of solute can occur between the fracture porosity and the porosity of the intact rock, known as the matrix porosity. In this case two coupled sets of equations are typically used to model solute transport in the two separate media.

The advection/dispersion equation is a mathematical description of the spatial and temporal change in solute concentration at any point in a groundwater flow field. To find a solution $C(x,y,z,t)$ that satisfies the equation requires that the model geometry, boundary conditions, and initial conditions be provided. As with groundwater flow, solute transport has been cast as a boundary value problem.

Just as hydraulic conductivity was found by fitting a simple mathematical model to laboratory measured conditions, the coefficients of the advection/dispersion equation must also be determined by experimentation (Bear, 1972). Figure 2.2a shows a typical apparatus useful for that purpose. The apparatus consists of a column of granular porous medium such as sand with initially solute-free groundwater flowing at steady-state from left to right. Attached to the up-gradient end of the column is a mixing cell into which, to start the experiment, a mass of tracer is added. The volumetric flux of the tracer solution is assumed to be negligible relative to that of the groundwater, and mixing is assumed to be instantaneous. The solute concentration, with units of $[ML^{-3}]$, entering the up-gradient end of the column is thus equal to the mass flux $[MT^{-1}]$ divided by the fluid flux $[L^3T^{-1}]$.

The groundwater containing solute is distinguished from the solute-free groundwater by referring to it as “the plume”. The changing concentration distribution in the column as the plume travels through it is determined through the extraction of samples at various times and locations. The coefficients of porosity and dispersion are then determined by fitting concentrations calculated by a one-dimensional advection/dispersion model of the

b) Concentration vs. distance profile at $t=X/\bar{v}$ from start of a continuous mass addition.

c) Concentration vs. distance profile at $t=X/\bar{v}$ from start of a short duration mass addition.

Figure 2.2 One-dimensional advection/dispersion

experiment to those measured in the laboratory. In one dimension, the advection/dispersion equation is as follows:

$$\frac{\partial C}{\partial t} = D_L \frac{\partial^2 C}{\partial x^2} - \bar{v} \frac{\partial C}{\partial x} \quad (15)$$

where D_L is the dispersion coefficient in the longitudinal direction, i.e. along the column, $\partial C/\partial x$ is the slope of the concentration with respect to the positive x-direction, and $\partial^2 C/\partial x^2$ is the concentration curvature.

Typical results of two commonly executed advection/dispersion experiments are illustrated in Figures 2.2b and 2.2c. Figure 2.2b shows the distribution of solute in the sand column at some time t after the introduction of a continuous flux of tracer. The dotted line shows the solute distribution predicted by an advection-only model. In this case, the plume front would move forward at the seepage velocity to point X, which is equal to $\bar{v}$ times t . The concentration immediately ahead of point X would be zero, and immediately behind it would be M_{in}/Q_{in} .

There are two reasons why the above-described advection-only scenario is impossible. First, molecular diffusion at the plume front will cause some solute to move ahead of point X in the direction of lower concentration. Second, since the seepage velocity is only an average velocity, water travelling faster than average will bring solute ahead of point X. The solid line shows how the solute would be distributed as predicted by the advection/dispersion

model. In short, this model calculates the correct location for the plume front (point X) as well as a statistically-based distribution of solute concentrations centred about that point.

Figure 2.2c shows the distribution of solute in the sand column at time t after the introduction of a short duration pulse of tracer mass. As before, the dotted line illustrates the solute distribution predicted by an advection-only model, and the solid line by advection/dispersion. In this case, a concentration gradient exists both ahead and behind the plume and, to an observer moving along at the seepage velocity, mass transport appears to occur in both these directions. Again, the advection/dispersion model calculates the appropriate location of the centroid of the plume, as well as a distribution of solute about that point.

Figure 2.3 shows a plume in a 1-D sand column at time t after the introduction of a mass flux that declines asymptotically from an initial high rate to a steady-state lower rate. This scenario has been included here in order to shed further light on the advection/dispersion equation, to define certain terms, and because this type of source is important in the study of in-pit TMFs.

As before the dotted and solid lines show the solute distribution as predicted by an advection-only and an advection/dispersion model, respectively. Above the concentration profile the sign of the concentration slope is indicated. Inspection of Equation 15 indicates that at the plume front, where the slope is negative, and assuming the seepage velocity is positive in the positive x -direction, advection would tend to increase the concentration with time (i.e. $\partial C/\partial t$

Figure 2.3 1-D advection/dispersion of a decaying source

is positive). Behind the plume front, where the slope is positive, advection would tend to decrease the concentration with time. Below the concentration profile, the sign of the concentration curvature is indicated. Inspection of Equation 15 indicates that near the peak concentration, where the curvature is negative, hydrodynamic dispersion would tend to decrease the concentration with time. Similarly, ahead and behind the peak concentration, where the curvature is positive, hydrodynamic dispersion would tend increase the concentration with time.

The bottom of Figure 2.3 shows the combined effect of advection and dispersion on $\partial C/\partial t$ at every point in the domain. At the extreme front of the plume, where $\partial C/\partial x$ is negative and $\partial^2 C/\partial x^2$ is positive, $\partial C/\partial t$ must be positive. Similarly, immediately behind the peak concentration, where both signs are reversed, $\partial C/\partial t$ must be negative. Elsewhere, where the signs of the concentration slope and curvature are the same, the effects on $\partial C/\partial t$ are offsetting. In these zones, the sign and magnitude of $\partial C/\partial t$ are dependent on the relative magnitudes of $\bar{v} \partial C/\partial x$ and $D_L \partial^2 C/\partial x^2$, two possible combinations of which are shown in Figure 2.3.

Finally, it is possible to define the portion of the plume that is transient as that portion where concentration changes rapidly with time, i.e. where $|\partial C/\partial t|$ is large. The portion of the plume where concentration changes slowly with time is termed the pseudo-steady-state portion. Where the concentration gradient and curvature are both zero, the concentration remains stable with time, and this portion is said to be at steady-state.

2.3.5 Dispersivity Tensor

Earlier it was stated that the coefficient of hydrodynamic dispersion is a second-rank tensor, the effect of which is to smear sharp plume fronts according to some statistical model. Being an empirical coefficient, many experiments have been conducted in an effort to shed light on its physical basis. The research has shown that, in general, the dispersion coefficient is strongly dependent on the seepage velocity, and, more specifically, on the dimensionless Peclet number, Pe , defined as $\bar{v}d/D_0$, where d is a characteristic length of the medium, generally taken to be the mean grain diameter.

Figure 2.4 is a graph of dimensionless dispersion coefficient D_L/D_0 versus Peclet number (after Perkins and Johnson, 1963 in Gillham and Cherry, 1982). The figure shows that for low Peclet numbers dispersion is dominated by molecular diffusion, and the dispersion coefficient is equal to the effective diffusion coefficient. As the Peclet number increases the dispersion coefficient also increases. Above Peclet numbers of approximately 1.0 the dispersion coefficient increases linearly with Peclet number, quickly becoming much greater than the diffusion coefficient. In this zone the high groundwater velocities cause mechanical mixing to dominate over diffusive processes, and, the higher the velocity, the higher the degree of mechanical mixing.

A transition zone exists between those zones where dispersion is dominated, at low Peclet numbers, by diffusion, and at high Peclet numbers, by mechanical mixing. In this transition

Figure 2.4 Graph of dimensionless dispersion coefficient vs. Peclet number (after Perkins and Johnston, 1963)

zone fluid velocities are slow enough that dispersion by these two processes are of the same order of magnitude. It has been suggested that closer to the lower end of the transition zone diffusion and mechanical mixing are additive processes, while closer to the upper end of the zone they are not. At the upper end of the transition zone dispersion is dominated by mechanical mixing combined with transversal molecular diffusion, and the validity of Equation 13 becomes questionable (Bear, 1972). The above-noted research has led to the development of physically-based estimates of the dispersion coefficient. The most simple of these in common usage relates the dispersivity to the seepage velocity, as follows:

$$D_L = D_d + \alpha_L |\bar{v}| \quad (16)$$

where D_L is the component of the dispersion coefficient in the longitudinal direction (i.e. in the direction of groundwater flow) and α_L is a fitting coefficient termed the longitudinal dispersivity with units of [L].

Longitudinal dispersivity has been found to be strongly dependent on the mean grain size as well as the grain size distribution, and Equation 16 has been found to be valid so long as dispersion was dominated by mechanical mixing (Klotz and Moser, 1974, in Gillham and Cherry, 1982). Longitudinal dispersivity has been found to be scale dependent (Gillham and Cherry, 1982, and Gelhar et al., 1985, in Domineco and Schwartz, 1990). At the laboratory scale, where homogeneous materials are usually used, dispersivities of 10^{-4} to 10^{-2} m were reported. At the field scale, dispersivities in the order of 10's of metres were reported.

As suggested by the use of the term “longitudinal dispersivity”, an assumption has been made about the direction dependent nature of dispersivity. It is generally assumed that the dispersivity tensor is symmetrical, that it is independent of the directional properties of the porous medium, and that the principal direction of the tensor is aligned with the velocity vector (Gillham and Cherry, 1982). This results in a tensor with only three components: the longitudinal dispersivity and the two mutually perpendicular components transverse to the flow direction. The “transverse” dispersivity has been found to be lower than the longitudinal dispersivity by a factor of approximately 10 to 30 (Fried, 1972, in Gillham and Cherry, 1982). At low velocities the transverse dispersion has been shown to be more dependent on diffusion than is the longitudinal dispersion (Gillham and Cherry, 1982).

3. CONCEPTUAL MODEL

Construction of an exact miniature version of an in-pit TMF with all the implied complexity and uncertainty was impossible. For this reason, a conceptual model was developed of the features and processes that were judged to be important. This conceptual model is shown schematically in Figure 3.1. In short, the conceptual model consists of steady-state groundwater flow through and past the facility, as well as solute transport within and out of the facility. Interest in both of these processes was confined to the saturated zone within the bedrock. Groundwater interaction between the bedrock, the overburden, and surface water, was considered to have a minor affect on the fundamental performance of an in-pit TMF and were thus omitted from the conceptual model. The conceptual model is discussed in more detail below.

3.1 Groundwater Flow Model

The groundwater flow model consists of the following features:

- a flat, horizontal, fully-saturated permeable host rock of infinite extent, bounded on top by overburden, and below by impermeable basement rock;
- a pit excavated into the host rock, filled to the top with a surround and tailings;
- steady-state groundwater flow across the domain subject to a regional hydraulic gradient.

Figure 3.1 Schematic of conceptual model

The host rock for the three northern Saskatchewan sites is Athabasca Sandstone (present at all three sites), Regolith (JEB only), and Precambrian “basement rock”. The conceptual model included only the upper few hundred metres of host rock, where, it was assumed, the solute plume would reside. Within the host rock, the bulk of groundwater flow was assumed to occur within a fracture network. As noted in the previous section, this fracture network may be conceptualized as an equivalent porous medium, or a network of discrete fractures.

When the host rock is conceptualized as an EPM, the correct specification of hydraulic conductivity is all that is necessary in order to model groundwater flow. The hydraulic conductivity of the host rock was assumed to be 1×10^{-6} m/s, and this value was chosen as the geometric mean of hydraulic conductivities measured at the three northern Saskatchewan sites, as shown in Table 3.1.

When the host rock is conceptualized as a network of discrete fractures the properties of the network must be determined from field characterization and mapping. Little information was available on the fracture networks within the Athabasca sandstone. In this study, however, no attempt was made to model a realistic discrete fracture network, and thus fracture data was not required. As will be seen in Section 4, a simplified network of horizontal fractures was chosen as a starting point for discrete fracture modelling.

The geometry of the pit was assumed to be an open cone with a top diameter of one kilometre, and a side slope of 70° from vertical. At the three northern Saskatchewan sites the

pits are roughly circular or elliptical with terraced side slopes ranging from 60° to 80° from vertical. Pit-top diameters range from approximately 500 m to 1000 m.

Table 3.1 Measured hydraulic conductivities - northern Saskatchewan in-pit TMFs

Unit	Rabbit Lake (m/s) ¹			JEB (m/s) ²			Deillmann (m/s) ³		
	Min	Max	Mean	Min	Max	Mean	Min	Max	Mean
Athabasca sandstone	1×10^{-8}	5×10^{-6}	5×10^{-7}	1×10^{-8}	2×10^{-5}	8×10^{-7}	1×10^{-7}	1×10^{-5}	4×10^{-6}
Regolith	-	-	-	3×10^{-8}	6×10^{-6}	4×10^{-7}	-	-	-
Basement rock	3×10^{-10}	2×10^{-4}	7×10^{-7}	-	-	-	-	-	6×10^{-8}
Pervious surround	-	-	1×10^{-1}	-	-	-	-	-	1×10^{-2}
Tailings	-	-	1×10^{-6}	-	-	5×10^{-9}	-	-	1×10^{-7}

Notes: 1) Gulf Minerals, 1981, Cameco, 1998

2) Cogema Resources Inc., 1997

3) Cameco Corporation, 1994

The thickness of the surround was assumed to be approximately 3% of the pit-top diameter.

The thickness of the surround at the three northern Saskatchewan sites ranges from 0 to 8 m.

The hydraulic conductivity of a “pervious” surround was assumed to be 1×10^{-2} m/s. The

hydraulic conductivity of the tailings were assumed to range from 1×10^{-7} to 1×10^{-8} m/s.

The regional hydraulic gradient was assumed to range from 0.1 to 2%. This range corresponds to that measured at the three northern Saskatchewan sites.

3.2 Solute Transport Model

The solute transport model consists of the following features:

- a specific discharge vector field of infinite extent, determined from the groundwater flow model;
- in the case of an EPM flow model, a specified fracture porosity;
- advection/dispersion based solute transport;
- when an EPM representation of the host rock was used, matrix diffusion was neglected, when a DF representation of the host rock was used, matrix diffusion was included;
- a conservative solute initially present in the tailings and absent elsewhere.

When an EPM representation of the host rock is adopted, the porosity that is most appropriate to use in the estimation of seepage velocity is the fracture porosity. As noted earlier, little information on fractures and fracture porosity was available, but because no attempt was made to model specific conditions at an actual site this data was not needed.

Diffusion of solute from the fracture into the intact rock matrix requires the specification of the matrix porosity. The matrix porosity of the Athabasca Sandstone at JEB has been measured with the radial diffusion method, and ranges from 6.5 to 11.5 %. Estimates of Athabasca Sandstone matrix porosity at Deillmann range from 1% to 5%. Since no attempt

was made to accurately model fracture flow at an actual site, it follows that no attempt was made to realistically model matrix diffusion. As will be seen in Section 4, matrix diffusion was neglected where an EPM host rock was assumed, while it was considered for the simplified network of horizontal fractures chosen for the DF network.

The free-water diffusivity of the solute is assumed to be $5 \times 10^{-10} \text{ m}^2/\text{s}$. This value corresponds to the free-water diffusivity of Arsenic and Radium 226, two contaminants of concern at the northern Saskatchewan in-pit TMFs.

Dispersivities are only important when mechanical mixing dominates the dispersive process. As noted in Section 2, dispersivities are generally scale-dependent. Since no attempt was made to model plume development at the full-scale in this study, a full-scale dispersivity was not required. Dispersivities used to simulate laboratory-scale processes were determined experimentally or were used as a tool for numerical model calibration.

Tortuosity is an important factor only where diffusion dominates solute transport. The tortuosity in the tailings is assumed to be 0.4. This is a reasonable number for a fine grained material such as tailings (Gillham et al. 1984). Tortuosity in the matrix of the host rock is assumed to be 0.5. For all other materials, a tortuosity of 0.7 is assumed (Bear, 1972).

Other than the rock matrix as a sink to solute in a discrete fracture, no solute sinks or reactions were included in the conceptual model. This assumption was made because it is

conservative in relation to mass fluxes and plume concentrations. Reactions that were neglected include solution/dissolution, radioactive decay, sorption, mobilization due to acid leaching, and chelation.

The primary contaminants of concern at the northern Saskatchewan in-pit TMFs are Arsenic and Radium 226. Source concentrations of As and Ra226 are in the order of 1-10 mg/L and 10-50 Bq/L, respectively. Saskatchewan drinking water guidelines for these two contaminants are 0.5 µg/L and 1 Bq/L respectively, indicating that the solution to the conceptual model must be capable of accurately modelling solute over a range of concentration of 4 to 5 orders of magnitude.

4. PHYSICAL MODEL APPARATUS AND METHODS

Two physical models were constructed, each representing a different conceptualization of the host rock. In one model the host rock was conceptualized as an equivalent porous medium and was represented with a mortar sand. Its design is shown in Figure 4.1. This model represents the most simple case of an in-pit TMF as conceptualized in the previous section. By definition, the host rock was a single porosity medium, and as such, matrix diffusion was not considered. In the second physical model the host rock was conceptualized as a simple network of discrete fractures, and these fractures were represented as spaces between slabs of Indiana limestone. By definition, the host rock is a dual porosity medium (fracture and matrix), and matrix diffusion will occur. The chosen fracture network was considered to be a good starting point for investigation of discrete fractures. Its design is shown in Figure 4.2.

The construction and testing of the apparatus and materials is presented in further detail below. Also presented is a description of the methods used to conduct the physical model experiments. Selected photos of the physical models are included in Appendix F.

4.1 Containers and Constant-Head Reservoirs

Each of the two physical models was contained within a separate container. The containers were constructed of 10 mm thick steel plates welded together to form an open-topped box.

a) Plan view at 0.6 m above datum

b) Centerline section

↑ (0,0,0) Location of Coordinate System
Origin
(distances in mm)

Figure 4.1 Equivalent porous medium (EPM) physical model design

The inside dimensions of these boxes were 2.7 m x 1.45 m x 1.0 m. These dimensions allowed for a 2.3 m x 1.35 m x 0.9 m physical model, with a 0.2 m wide reservoir at each end, a 0.05 m wide seal (or extra sand in the EPM model) at each side, and 0.1 m freeboard at the top of the model. All steel was painted with epoxy primer and two coats of epoxy paint.

A 50 mm diameter hole was drilled through the steel wall into the reservoir portion at either end of the containers. A bulkhead fitting was installed in each hole, and an adjustable overflow was attached to the fitting. The two reservoirs were separated from the host rock portion of the EPM model with a 10 mm thick perforated steel plate lined with permeable geotextile material. These reservoirs contained 240 L of water when filled to the 0.9 m height of the host rock. The reservoirs in the DF model did not need to be physically separated from the host rock, and contained 259 L of water, when full.

4.2 Materials Testing and Emplacement

4.2.1 EPM Model - Host Rock

A screened, washed mortar sand from a local sand pit was chosen as the EPM host rock. Sieve analysis indicated it to be a uniform medium sand, with a mean grain size of approximately 0.3 mm. Sieve analysis results are included in Appendix A.

Several samples of the mortar sand were tested for hydraulic conductivity using a constant-head permeameter. Densely packed sand was found to have a hydraulic conductivity of 6×10^{-5} m/s, while loosely packed sand was found to have a hydraulic conductivity of 3×10^{-4} m/s. Testing data is included in Appendix A.

The sand was packed moist, in 50 mm lifts. The procedure for each lift was to dump the total volume of sand for the lift into the model using a loader. The sand was then spread evenly throughout the box. The new lift and one to two previous lifts were then disturbed by raking to a depth of approximately 150 mm. It was hoped that the raking would eliminate bedding planes resulting from compaction of the sand in lifts. Following the raking, the sand was compacted with a 200 mm x 200 mm five kilogram plate tamper lifted and dropped from approximately 300 mm height. The compaction step was repeated three times.

The pit in the EPM model was held open by a 900 mm diameter welded-wire-mesh drum, lined with geotextile. After 450 mm of sand had been packed into the box, the drum was placed in its correct location. Sand was then compacted around the drum, leaving a hole (or pit) inside it. The size of the pit was designed to be as large as possible without incurring unduly large boundary effects from the walls of the container. That this criterion was met was confirmed via numerical simulation.

The in-situ porosity of the mortar sand was determined at four locations in the EPM model. Data is included in Appendix B. The porosity was determined by excavating a small hole

in the sand. The dry weight of the sand excavated from this hole was determined by oven-drying and weighing it. The volume of the hole was determined by lining it with plastic wrap, and filling it to the top with water. The quantity of water used to fill the hole was measured to determine the hole volume. The porosity of the sand was then calculated using the following equation (Vomocil, 1965, in Freeze and Cherry, 1978):

$$n = 1 - \frac{\rho_d}{\rho_s} \quad (17)$$

where n is the porosity, ρ_d is the dry mass bulk density with units of $[\text{ML}^{-3}]$, and ρ_s is the particle mass density with units of $[\text{ML}^{-3}]$. The dry mass density was found by dividing the oven-dried mass of the soil by the volume of the hole. The particle mass density was assumed to be $2,650 \text{ kg/m}^3$ (Freeze and Cherry, 1979). In the upper 100 mm of sand, the porosity was found to be approximately 0.38, while 300 mm below the surface the porosity was found to be 0.33.

Following emplacement of the mortar sand, and prior to emplacement of the surround or tailings, the pit was filled with mortar sand using the 50 mm lift procedure. Hydraulic and tracer experiments were then carried out in an intact block of the host material without the complication of having different materials within the pit.

The purpose of the hydraulic experiments was to determine the in-situ hydraulic conductivity of the host material, and to determine if it varied with depth within the model. Data is included in Appendix B. The experiments were carried out by using the model as a type of

large permeameter, with a specified head drop, a cross-sectional area, and a measured flow rate. The difference between the model apparatus and a true permeameter, however, was that the upper surface of the sand in the model apparatus was exposed to atmospheric pressure. This upper boundary condition led to an unsaturated zone above the “water table” as set by the elevation of the up and down-gradient reservoirs. The consequence of the unsaturated zone was that the effective cross-sectional area of the test was not known, and could only be estimated by application of unsaturated flow theory. The experiments consisted of the measurement of flow rates for 4 sets of reservoir levels. The four up-gradient reservoir levels were 900, 700, 500, and 300 mm above the bottom of the box, and the head drop was kept constant at 50 mm. Flow rates were monitored after each reservoir level change, and the steady-state value recorded.

The results were analysed by modelling the hydraulic experiments with an unsaturated/saturated finite-difference flow model (FRAC3DVS). The domain of the finite difference model was divided into horizontal layers, and a hydraulic conductivity profile was determined that would supply best-fit flow rates for the different boundary conditions implemented in the physical model. Typical Van-Genuchten parameters for a medium sand were used for the unsaturated parameters (Van Geel and Sykes, 1997). It was found that the hydraulic conductivity likely varied, due to differential compaction, from $1\text{--}2 \times 10^{-4}$ m/s or greater in the upper few centimetres to as low as 6×10^{-5} m/s at depth.

A tracer experiment was conducted in the fully-saturated model using a 50 mm head drop.

One millilitre of 10,000 ppb Uranine ($D_0 = 4.5 \times 10^{-10} \text{ m}^2/\text{s}$ (Skagius and Neretnieks, 1986)) solution was injected into a sample port in the centre of the model. Samples were collected at regular intervals in four downstream sample ports (described in Section 4.3), and this data is included in Appendix B. The sample ports were located along the same groundwater flow line as the injection port, and were spaced 200 mm apart from each other. The samples were analysed for fluorescence.

The results were analysed by fitting the collected concentration vs. time data to that produced from an analytical solution of the advection-dispersion equation in three-dimensions in a homogeneous isotropic porous medium, assuming an instantaneous point source was released at $x=0$, $y=0$, and $z=0$ (modified from Freeze and Cherry, 1979):

$$C(x, y, z, t) = \frac{M / n}{8(\pi t)^{3/2} \sqrt{D_x D_y D_z}} \exp\left(-\frac{(x - \bar{v}t)^2}{4D_x t} - \frac{y^2}{4D_y t} - \frac{z^2}{4D_z t}\right) \quad (18)$$

where $C(x, y, z, t)$ is the concentration at a given location, and given time, M is the mass of tracer introduced at the point source, t is time from the release, D_x is the coefficient of hydrodynamic dispersion in the stated direction, and $\bar{v}$ is the seepage velocity.

The measured and calculated concentrations vs. time for all four down-gradient sample points are shown in Figure 4.3. A porosity of 0.36 was found to best fit the measured times to peak concentration. Longitudinal and transverse dispersities of approximately 1 mm and

Figure 4.3 EPM host rock tracer experiment results

0.1 mm were found to best fit the magnitude of the measured peak concentrations. These results are consistent with those reported in Section 2.

4.2.2 Discrete Fracture Model - Host Rock

Five slabs of Indiana Limestone were chosen for the discrete fracture model host rock. The design, as shown in Figure 4.2, required the five slabs to be lain one on top of another inside the box. The four gaps between the five slabs, shimmed or otherwise, formed a conduit for groundwater flow between the two end reservoirs. These conduits represent horizontal fractures or fracture zones, and will be referred to as fractures throughout the rest of this thesis.

Indiana Limestone is a calcite cemented grainstone formed from fossil fragments and oolites (Churcher et al, 1991). It is a massive and homogeneous rock that has enjoyed longstanding popularity as a building material. The rock specimens used for this study were a standard grade of buff coloured limestone. They were quarried in Indiana, and cut to shape in Montreal, Quebec. Literature values for the hydraulic conductivity of buff Indiana limestone range from 3.5×10^{-8} m/s to 5.0×10^{-7} m/s (Churcher et al, 1991).

Upon delivery, the rock slabs were measured, and found to be 2.3 m x 1.35 m x 0.18 m in size, as shown in Figure 4.2. A 900 mm diameter hole had been drilled through two of the five slabs, and through one half of a third. Inspection of the rock slabs revealed that these

dimensions were accurate to approximately 5 mm in the x and y direction, and about 3 mm in the z direction. When stacked up, curvature in the top and bottom surfaces of the slabs resulted in apertures ranging from 0 to 4 mm. To alleviate this problem, each pair of rock surfaces (together forming a fracture) was ground together longitudinally under the influence of gravity. The grinding was accomplished by securing the lower slab to the laboratory floor, attaching the upper slab to a hydraulic jack, and cycling the jack back and forth. The amplitude of the motion was approximately 30 mm, and the period approximately 3 seconds. A carbide grinding powder was placed between the surfaces and replaced regularly. In this way, the two surfaces were made to fit together, until no gap was apparent to the naked eye.

The grinding procedure resulted in scoring of the surface. The scoring was characterized by shallow (less than 0.5 mm) longitudinal grooves which were especially pronounced close to the edges of the rock, where the carbide grinding powder had been released. The two upper fractures, both with a 900 mm diameter internal hole, had a higher degree of scoring than the lower two fractures. Following grinding, the rock slabs were found to be, on average, 3 mm thinner than at the start of the procedure.

Each rock slab weighed 950-1200 kg, depending on the geometry. The slabs were moved using an overhead crane and a steel “grappling” device. The device was constructed on-site, and used a system of wedges to achieve a firm grip on the rock slab from the longitudinal ends. This device made it possible to place a slab onto a flat surface without holding it from beneath, and without any damage to the rock.

The slabs were placed one on top of another in the box, leaving 50 mm on each side for a seal, and 200 mm on each end for a reservoir. The 900 mm diameter hole in the upper three slabs was aligned, and once all the slabs were in place, the overall geometry of the host rock and pit were very close to the design. The slabs were separated from each other (in the z-direction) by nine evenly-spaced 10 mm x 10 mm x 100 micron aluminum shims. Each rock slab was saturated immediately following its placement in the box. Saturation was accomplished under the influence of capillary forces and gravity. The rock slab was immersed in water up to, but not covering, its top, and saturation proceeded from the sides and bottom of the slab. Air was released upwards. Saturation could be observed through a darkening of the rock, and occurred at a uniform rate throughout the slab. Following saturation, bentonite clay was placed in a 10 mm thick layer beneath the bottom slab, and in the two 50 mm wide gaps at the sides of the model. The bentonite was held in place in the 50 mm gap by use of plastic retainers at each end of the seal.

Hydraulic and tracer experiments were carried out on the fractured rock system. The purpose of the experiments was to determine the capacity of each of the four fractures to conduct water, and the degree of dispersion experienced by a tracer moving through the aperture. These experiments are described below, and the data is included in Appendix B.

4.2.2.1 Hydraulic and Tracer Experiments on the Bottom Fracture

Following placement of the bottom two rock slabs, a series of hydraulic and tracer

experiments were performed on the bottom fracture. The hydraulic experiments consisted of the measurement of flow rates for three different gradients set across the model. By assuming the fracture to behave as two parallel plates, a rearranged version of Equation 3 was used to calculate the fracture aperture, as follows:

$$2b = \left(\frac{12\mu LQ}{w\rho g\Delta h} \right)^{1/3} \quad (19)$$

Where $2b$ is the fracture aperture, μ is the liquid viscosity, L is the fracture length, Q is the volumetric flow rate, w is the fracture width, g is acceleration due to gravity, and Δh is the head drop over the fracture length.

Based on flow rates of 98, 40, and 22 mL/minute with head drops of 60, 14, and 8 mm, respectively over the 2.3 m length of the fracture, the fracture aperture was determined to be 400, 480, and 475 microns, respectively. These apertures are more accurately referred to as “equivalent fracture apertures”, since the scoring in the rock surface resulted in flow that occurred in a series of small channels rather than in a single sheet. Considering that the spacers placed between the rock surfaces were 100 microns in thickness, and considering the nature of the scoring, the observed equivalent fracture apertures seem reasonable.

Twelve sample ports and three manometers were installed into the bottom fracture in the pattern shown in Figure 4.4. A series of tracer experiments were performed by injecting a tracer solution into the upstream ports, and observing its passage through the model by

Figure 4.4 Bottom fracture sample port and manometer locations

sampling at the middle and downstream ports. All together, seven tracer experiments were performed, three with a 14 mm head drop, and four with an 8 mm head drop. Table 4.1 provides a summary of the experiments performed. Included in the table, for each experiment, are the identification of the injection port number, the volume and concentration of dye injected, as well as the maximum concentrations measured in the middle and downstream ports. The reported concentrations are segregated on the basis of the relative location of the port where dye was detected in relation to the injection port. Ports identified as “in line” are located on the same y-coordinate as the injection port, and are therefore in theory, on the same groundwater flow line. For this reason, concentrations in the in-line sample ports should be the highest measured. Ports identified as Lateral 1 and Lateral 2 are ports that are not on the same groundwater flow line, but are lateral to it. The lateral port with the highest measured concentration is identified as Lateral 1, and the port with the second highest measured concentration is identified as Lateral 2. For all maximum measured concentrations, the table provides identification of the port number, the concentration, and the time from the start of the experiment that the concentration was measured. Finally, in the left hand column, for the two different flow regimes, estimates of average groundwater velocity have been provided based on the flow rate and the equivalent fracture aperture. These velocities have also been provided as the expected time for the tracer to travel the 767 mm between the sets of sample ports (e.g. between the injection and middle ports).

In five of the seven experiments only 1 mL of tracer was injected. In four of these experiments the tracer was detected in in-line ports, though never in both (i.e. never in the

Table 4.1 Summary of first fracture tracer test data

Flow conditions, Estimated aperture, and Velocity	Injection Port	Volume Injected	Middle ports (Port number, Peak conc., Time to peak)		End ports (Port number, Peak conc., Time to peak)		
			In line	Lateral 1	In line	Lateral 1	Lateral 2
Head Drop = 14 mm Flow = 40 mL/min Aperture= 480 micron Velocity = 1.1x10 ⁻³ m/s (12 min. between ports)	2	1 mL of 1000 ppb	ND	ND	10 22.1, 20 mins	ND	ND
	3	1 mL of 1000 ppb	7 21.6, 25 mins	ND	ND	ND	ND
	4	1 mL of 1000 ppb	ND	6 12.1, 18 mins	12 2.7, 30 mins	ND	ND
	2	1 mL of 10000 ppb	ND	ND	ND	ND	ND
Head Drop = 8 mm Flow = 22 mL/min Aperture= 475 micron Velocity = 5.8x10 ⁻⁴ m/s (22 min. between ports)	3	1 mL of 10000 ppb	7 34.4, 33 mins	8 1.1, 22 mins	ND	ND	ND
	2	10 mL of 1000 ppb	ND	ND	10 270.8, 42 mins	11 14.0, 42 mins	12 3.5, 42 mins
	4	10 mL of 1000 ppb	8 373.7, 17 mins	ND	12 149.3, 47 mins	ND	ND

middle in-line port as well as the downstream in-line port), and not necessarily in the first of the in-line ports encountered. In one of these four experiments, the tracer was also detected in a port 405 mm off the theoretical stream line. In another of these four, the tracer was detected in a port 270 mm off the flow line. In the fifth of the 1 mL injection tests, the tracer was not detected at all. All concentrations measured in the 1 mL injection experiments were very low relative to the injected concentration (0.01% to 2%). These results indicate that the small quantities of dye were channelled through the fracture in a relatively tortuous path.

In two of the seven experiments, 10 mL of tracer was injected. In the first of these experiments, the dye was not detected in any of the middle ports, but was detected in three of the downstream ports. The highest concentration was detected in the in-line port, while the concentration dropped off in the two lateral ports with distance off the stream line. In the second 10 mL injection experiment, the highest concentration was detected in the middle in-line port, while a lower concentration was detected in the downstream in-line port. The concentrations measured in the 10 mL injection experiments were high relative to the injected concentration (0.4% to 37%). These results show that, on average, groundwater flowed in the direction of the theoretical flow line, and dispersion occurred laterally as would be expected. At this scale, however, some channelling was still observed.

4.2.2.2 Hydraulic and Tracer Experiments on the Upper Two Fractures

Hydraulic experiments were carried out to determine an equivalent fracture aperture for each of the upper two fractures. The experiments consisted of the measurement of flow rates across the host rock with an open pit for three sets of reservoir levels. In this case the levels were chosen such that, in turn, all four, the lower three, and the lower two fractures contributed to the total flow, and a constant head drop of 10 mm was applied. The total flow rate for the system was found to be 240 mL/min, 65 of which was supplied by the upper fracture, 95 of which was supplied by the second fracture, and 80 of which was supplied by the lower two fractures combined.

The low flow rate measured through the lower two fractures was attributed to three factors: 1) smaller apertures due to the weight of the slabs above them; 2) lower degree of scoring; and 3) these fractures were not intersected by a large open hole like the upper two.

The equivalent fracture apertures were determined to be 560 microns and 640 microns for the upper and second fracture, respectively. These values were determined by fitting flow rates calculated by FRAC3DVS to those measured in the laboratory. The use of the numerical model, with the open water-filled pit modelled as a zone of extremely high hydraulic conductivity, was necessary because a direct solution was unavailable. The equivalent hydraulic conductivity for the upper and second fracture, as determined from Equation 3, was 0.23 m/s and 0.30 m/s, respectively.

A tracer experiment was carried out in each of the upper two fractures by injecting 5 mL of 1000 ppb tracer solution into a port located on the centerline down-gradient of the open hole. In the upper fracture samples were extracted from monitoring ports located 400, 600, and 1000 mm down-gradient of the injection port. In the second fracture, the monitoring ports were located 400 and 800 mm down-gradient of the injection port. The tracer experiment was conducted with a 5 mm head drop across the model.

The concentrations measured during the tracer experiments are shown in Figure 4.5. In the three monitoring ports in the upper fracture, in order of increasing distance from the injection point, peak concentrations of 98, 61, and 67 ppb were recorded at 8.5, 13.5 and 22.5 (average of two points) minutes from the time of injection. Assuming advection/dispersion theory applies, these results translate to seepage velocities of 7.8×10^{-4} , 7.4×10^{-4} , and 7.4×10^{-4} m/s, with an average value of 7.6×10^{-4} m/s. This agrees well with the seepage velocity calculated by the numerical model of 7.5×10^{-4} m/s. In the second fracture the average seepage velocity was determined to be 8.3×10^{-4} m/s. This shows reasonable agreement with the model calculated value of 9.0×10^{-4} m/s.

Examination of Figure 4.5 indicates that the measured peak concentrations do not necessarily decrease with distance from the source. This result shows that different portions of the plume were sampled, not the plume centre. This result, and the low measured values relative to the source concentration, suggests a moderate degree of dispersion and channelling rather than pure advection/dispersion between two parallel plates..

a) Upper fracture

b) Second fracture

Figure 4.5 DF host rock tracer experiment results

4.2.3 Surround

Two materials were used for the surround, depending on the experiment design. These two materials were a 3 mm to 6 mm filter gravel, and the earlier-described mortar sand. Testing of the mortar sand has already been described. A sample of the filter gravel was tested for hydraulic conductivity using a constant-head permeameter. The gravel was found to have a hydraulic conductivity of 0.06 m/s. Data is included in Appendix B.

The surround was placed into the model in stages. First, a 20 mm lift of material was compacted into the bottom of the pit. Second, an 860 mm diameter steel mesh drum (lined at the sides and bottom with geotextile) was placed on top of the compacted material, concentric to the pit wall. Finally, the remainder of the surround was compacted in lifts between the mesh drum and the pit wall. In this way, the pit was lined with a surround of uniform 20 mm thickness.

4.2.4 Tailings

The tailings were represented by a ground silica the size of a medium-grained silt. The material was mined in West Virginia, by U.S. Silica, and is identified as Sil-Co-Sil 90. The product name implies that ninety-eight percent of this material would pass through a 90 micron screen. Samples of the silica were tested for hydraulic conductivity at different compaction densities. The data is included in Appendix A. The hydraulic conductivity was

found to range from approximately 1×10^{-6} m/s for a loosely compacted material to 1×10^{-7} m/s for tightly compacted material. The porosity of moderately compacted tailings was determined to be approximately 0.4.

A known mass of silica was partially saturated with a solution containing a known mass of sodium fluorescein dye (trade name Uranine). Uranine was chosen because of its low detection limit and its conservativeness in silica and limestone media (Worthington and Ford, 1997). The ratio of dye to silica was chosen to achieve the design source concentration, based on an assumed porosity of 0.4. The ratio of water to silica was chosen to maximize water content while allowing the material to be handled and compacted without its liquefaction. The silica (126.4 kg), dye (356 mg for 10,000 ppb), and water (26.25 L) were mixed in two equal-sized batches in a cement mixer.

Like the surround, the tailings were placed into the model in stages. First, a 50 mm lift of silica was compacted into the bottom of the surround-lined pit. Second, an open-topped 760 mm diameter steel drum was placed on top, concentric to the pit wall. Finally, the remainder of the tailings was compacted into the 50 mm annulus between the steel drum and the surround.

The use of the steel drum to occupy the centre of the pit was motivated by the significant labour and materials savings afforded by this method. A second motivation for its use was that the 50 mm thick tailings source reached 100% liquid saturation much more quickly than

would have a full pit of tailings. A further justification for the use of the steel drum was that data from the experiments, as conducted, provided an equivalent test of the numerical model as that provided had the pit been full of tailings. It is important to note that the steel drum prevented groundwater from flowing across the diameter of the pit, and that this is not a realistic representation of actual conditions. The use of the steel drum significantly altered the behaviour of the experiments relative to how they would have performed had the pit been full of tailings. This issue is addressed in Sections 6 and 7.

An approximate estimate of tailings porosity, and by extension hydraulic conductivity and source concentration, was determined by using Equation 17. In this case, the bulk mass density was determined by dividing the mass of emplaced silica by the volume of the tailings portion of the model. The mass of emplaced silica was determined by subtracting the air-dried mass of the left-over silica from the mass of the silica used in the batch. The particle mass density was assumed to be $2,650 \text{ kg/m}^3$ (Freeze and Cherry, 1979).

4.3 Instrumentation

4.3.1 Manometers

Manometers were installed in both models, though the 1mm accuracy was sufficient to characterize heads only within the EPM model whose 50 mm total range in hydraulic head was ten times greater than that within the DF model. Manometer coordinates in the EPM

model are provided in Appendix D, and the locations are shown in plan-view and section in Figure 4.6. In total, 19 manometers were installed in the EPM model, with five of these being multi-levels.

EPM model manometers consisted of 5 mm ID flexible plastic tubing, arranged with one end emplaced at the appropriate location in the model, and the other end pointing upwards on a manometer board, above the top of the model. The emplaced end of the tubing was capped with a piece of geotextile to prevent suction of soil into the manometer during priming. The manometers were primed by pumping water out of the open end of the tube until all the air was released from the tube. The elevation of the inside floor of each container was established as the datum for each model, and a reference line exactly one metre above the datum was marked on the manometer board. In this way, hydraulic heads could be measured in the model by measuring downwards from the 1 m elevation line to the water level in the manometer tubing.

4.3.2 Sample Ports

Thirty-nine sample ports were installed in the EPM model, and 36 were installed in the DF model. The port coordinates for both models are included in Appendix D. The locations are shown in plan and section in Figure 4.7 for the EPM model and Figure 4.8 for the DF model. In the EPM model, the majority of the sample ports in the host rock were distributed in a

a) Plan view at 0.6 m above datum

b) Centerline section

Figure 4.6 Manometer locations - EPM model

a) Plan view at 0.6 m above datum

b) Centerline section

Figure 4.7 Sample port locations - EPM model

a) Plan view at 0.6 m above datum

b) Centerline section

Figure 4.8 Sample port locations - DF model

horizontal plane 0.6 m above the datum, and in a vertical plane along the centerline of the model. In the DF model, the majority of the host rock sample ports were distributed within the upper fracture. Only five sample ports were installed in the second fracture.

Each sample port in the EPM model consisted of a piece of 0.5 mm ID plastic tubing, with a 23 gauge needle inserted at both ends. The luer adaptor of the needle at the emplaced end was filled with filter sand, and covered with a piece of geotextile (acting as a well-screen). The needle at the other end was affixed to a plexiglass sample panel and labelled appropriately. The purge volume (with a 2 m length of tubing) was 0.5 mL. A sketch of this sampling hardware is included in Figure 4.9.

Sample ports were only installed in the upper two fractures of the DF model. The fractures were accessed by holes drilled through the rock slab from above. Where the second fracture was to be instrumented, aligned 12 mm diameter holes were drilled through both of the upper two slabs. Where only the upper fracture was to be instrumented, a 6 mm diameter hole was drilled only through the upper slab. Each sample port consisted of two pieces of 0.33 mm ID stainless steel tubing and a 23 gauge needle, connected together with short pieces of flexible tubing. The first length of stainless steel tubing was given a small bend at the bottom, inserted into the drilled hole, and hooked into either the upper or second fracture. The second length of tubing connected the first length to the needle at the sample panel. The purge volume (with a 2 m length of tubing) was 0.2 mL. A sketch of this sampling hardware is also included in Figure 4.9.

Equivalent Porous Media Model

Figure 4.9 Sample port hardware

Solute concentrations were determined by analysis of the samples for fluorescence using a Turner Designs TD-700 fluorometer. The fluorometer was calibrated to provide concentrations in parts per billion. Calibration standards for the range of expected concentrations were prepared by successive dilution of a calibration standard prepared prior to the experiment. The calibration standards ranged in concentration from 0.05 ppb to 500 ppb. The background fluorescence of tap water extracted from an uncontaminated portion of the model was found to be approximately 0.1 ppb. Instrument drift between calibrations resulted in an effective detection limit of approximately 0.5 ppb.

4.4 Water Supply

Tap water was used for the water supply. Water for use in the EPM experiments was piped into a 200 L storage reservoir, with an overflow. Water in the storage reservoir was then gravity fed into the up-gradient reservoir of the model. This arrangement allowed control of the flow rate into the model, and allowed for some acclimatization of the tap water prior to its use. The flow rate into the up-gradient reservoir was adjusted such that sufficient water was available to satisfy the flow rate dictated by the difference in head across the model, as well as to ensure that the reservoir was constantly overflowing. The flow rate through the model was determined by measuring the volume of water that overflowed the down-gradient reservoir during a known period of time.

Following the completion of the EPM experiments, the model was flushed thoroughly with

clean water. The apparatus, minus a solute source, was then used as an acclimatization tank for water used in the DF experiments. This arrangement was found to prevent air-bubbles from forming in the fractures of this model, and flow remained very steady.

4.5 Experiment Operation

The EPM gravel-surround and sand-surround experiments were each repeated once, for a total of four EPM experiments. The DF gravel-surround experiment was repeated once, and the DF sand-surround experiment was not repeated, for a total of three DF experiments.

The host rock was flushed with clean water prior to the start of each experiment. Following the flushing period, the water levels in the reservoirs were lowered, and the surround and tailings portions of the model were constructed. The reservoir levels were then raised to the full height of the host rock, and saturation began. Within an hour in the EPM experiments, and within a few minutes in the DF experiments, the host rock and surround were observed to be fully saturated. The overflow in the down-gradient reservoir was then lowered by 50 mm in the EPM experiments and 5 mm in the DF experiments, and the start time of the experiment was noted. This process was intended to represent instantaneous saturation, as stipulated in the conceptual model. In reality, the steady-state groundwater flow field was not truly established until full saturation of the tailings was complete. Based on visual inspection, this process was estimated to have occurred during the first few hours of the experiment.

An approximate estimate of the initial tailings concentration was determined following full saturation of the tailings. Samples of the tailings were extracted from the model and the pore-water concentration was determined by dilution, mixing, settling, and analysis of the supernatant. Samples were extracted by pushing a miniature shelly-tube into the saturated tailings, or by suction using a syringe with a large-diameter needle. The action of collecting the samples caused significant disturbance of the tailings, and only a limited number of samples could be taken. The analysis suggested that the actual average initial concentration was close to the design concentration in all experiments. The design initial concentration was 10,000 ppb in all experiments but the DF sand-surround experiment, in which it was 1,000 ppb.

Conditions within the experiments were monitored in rounds. The frequency of the monitoring rounds was commensurate with the concentration changes occurring within the model, and varied from a few minutes to over a week. Each round consisted of the measurement of water levels (in the EPM experiments only), measurement of overflow rate in the down-gradient reservoir, collection and analysis of a water sample in the down-gradient reservoir, and collection and analysis of a water sample from each of the sample ports.

Air bubbles that generated at the up-gradient perforated steel plate in the EPM experiments caused a slight blockage of flow. This blockage was compensated for in the first two experiments by increasing the up-gradient reservoir level by a few millimeters. In the second

half of the third experiment the blockage was removed by occasionally knocking the steel plate with a hammer. The blockage did not occur in the fourth experiment. Air bubbles did not occur in the DF model because of the use of the water acclimatization process described earlier.

Eight to ten days after the start of all but the first two experiments the overflow in the down-gradient reservoir was adjusted and the gradient across the model was reduced by a factor of two. From the time of the gradient change to the end of the experiment, monitoring was carried out as before.

To end the experiments, four sets of five radially-arranged tailings samples were extracted using the same procedure as described earlier. In some cases the reservoir levels were lowered before the samples were extracted while in other cases, they were not.

The duration of the seven experiments and the time of the gradient changes are summarized in Table 4.2. Repeated experiments are distinguished from one another in the table by the order in which they were completed. The number of monitoring rounds conducted in each experiment is also included in the table.

Table 4.2 Summary of experiments completed

Host rock type	Surround type	Duration of experiment (days)	Time to gradient change (days)	Number of monitoring rounds
EPM	Gravel (1)	12.8	no change	31
	Sand (1)	15.8	no change	26
	Gravel (2)	22.9	8.1	42
	Sand (2)	26	8.2	39
DF	Gravel (1)	6.9	3	18
	Sand (1)	16.9	6.8	23
	Gravel (2)	55	9.3	28

5. PHYSICAL MODEL RESULTS

As noted in Section 4, three of the four scenarios were repeated, for a total of seven experiments. In this section comparisons are made between the repeated experiments in order to assess the quality of the data. On the whole, however, the second of each repeated experiment produced the most complete set of data and it is these experiments that are presented in the most detail. Thus, unless otherwise stated, the four scenarios are presented through the data of the four “best” experiments.

5.1 Hydraulic Heads and Specific Discharges

Hydraulic heads measured in the 19 manometers in the four EPM experiments are presented in tabular form in Appendix D. The average of the values measured in each manometer in each of the separate steady-state flow fields (i.e. two each for the experiments with a gradient change) is also provided in the appendix. Comparison of the average values of hydraulic head between repeated experiments shows that they were virtually indistinguishable from one another. For this reason only the second set of data will be discussed further.

Figures 5.1 and 5.2 show schematically the average measured hydraulic heads prior to the gradient change in the EPM gravel-surround and sand-surround experiments, respectively. Both figures show interpreted flow lines indicating the average direction of groundwater flow in the horizontal plane 0.6 m above the datum, and in the vertical plane along the

a) Plan view at 600mm elevation

b) Centerline section view

Figure 5.1 Equipotential and flow lines
EPM gravel-surround experiment

a) Plan view at 600mm elevation

b) Centerline section view

**Figure 5.2 Equipotential and flow lines
EPM sand-surround experiment**

longitudinal centerline. Where the flow lines travel significantly out of these planes, they are represented as dashed lines with question marks. Because of the limited number of manometers and their limited accuracy, the illustrated flow lines, particularly those in and beneath the surround, were interpreted from solute transport results and from flow net theory. It is important to note that, according to the interpretation shown in Figures 5.1 and 5.2, groundwater at 0.6 m above datum did not deviate significantly out of the horizontal plane.

Estimates of specific discharge in the surround, tailings, and down-gradient host rock in the EPM experiments are provided in Table 5.1. These values were estimated with Darcy's law by multiplying hydraulic gradients extracted from Figures 5.1 and 5.2 with estimates of hydraulic conductivity. Since no head drop could be measured across the gravel surround a maximum possible head drop of 0.5 mm was assumed. Thus, the specific discharges in the surround and tailings for this experiment are presented as maximum possible values.

Table 5.1 Estimated specific discharges in EPM experiment

	Gradient across pit()	Specific ¹ discharge in surround (m/s)	Specific discharge in tailings (m/s)	Gradient down- gradient of pit ()	Specific discharge in down-gradient host rock (m/s)
Gravel- surround	$<3.5 \times 10^{-4}$	$<2.1 \times 10^{-5}$	$<2.1 \times 10^{-10}$	0.0375	3.8×10^{-6}
Sand- surround	0.016	8.0×10^{-6}	9.0×10^{-9}	0.0225	2.3×10^{-6}

Notes: 1) Based on maximum possible head drop of 0.5 mm

Because no hydraulic head data was available for the interior of the DF model, estimates of specific discharge in the fractures of the DF host rock were made based on the results of the tracer experiments and on the observed solute transport. Specific discharge in the two upper fractures was assumed to be approximately 8×10^{-4} m/s in the gravel-surround experiment and 5×10^{-4} m/s in the sand-surround experiment.

Outflow rates in the seven experiments are presented in tabular form in Appendix D. The average of the values measured in each of the steady-state flow fields is provided in Table 5.2. The standard deviations of the measured flow rates used to determine these averages are also presented in the table.

Table 5.2 Summary of outflow rates

		Initial gradient		Half gradient	
		Flow rate (mL/min)	Std. deviation (mL/min)	Flow rate (mL/min)	Std. deviation (mL/min)
EPM	Gravel (1)	223	12.8 (n=31)	na	na
	Sand (1)	170	8.4 (n=26)	na	na
	Gravel (2)	238	7.5 (n=24)	123	3.8 (n=18)
	Sand (2)	190	3.1 (n=21)	95	5.1 (n=18)
DF	Gravel (1)	144	1.9 (n=8)	68	2.2 (n=10)
	Sand (1)	98	8.4 (n=13)	52	6.7 (n=10)
	Gravel (2)	125	4.1 (n=12)	66	4.4 (n=16)

Notes: na = not applicable

5.2 Solute Concentrations in the Surround and Host Rock

Solute concentrations measured in the seven experiments are presented in tabular form in Appendix C (for very early time) and Appendix D (for monitoring rounds). As noted in Section 4, the EPM and DF models were equipped with 39 and 36 sample ports, respectively. Since each port was sampled during each monitoring round, the total number of solute concentration data points ranged from 648 to 1640, depending on the experiment. Since these data points were distributed over space and time, they capture quite well the changing concentration distribution in the surround and host rock. Comparison of the concentration data from the repeated experiments showed that similar trends in plume development occurred in both experiments. For this reason, and because the second set of data is the most complete, the first set of solute concentration data from each repeated experiment will not be presented in this section.

Figure 5.3a and 5.3b shows solute concentrations measured in port 18B vs. time, in the two best EPM and DF experiments, respectively. This data has been singled out from the wealth of data to show how the solute concentration changed with time, down-gradient of the tailings source.

Figures 5.4 and 5.5 show the measured solute concentrations 0.7 days and 8.2 days after the start of the EPM gravel-surround experiment, respectively. In both figures solute concentration contours have been interpreted in the horizontal plane 0.6 m above the datum,

a) Concentration in port 18B vs. time in EPM experiments

b) Concentration in port 18B vs. time in DF experiments

Figure 5.3 Concentration vs. time in port 18B in all four experiments

a) Plan view at 600mm elevation

b) Centerline section view

Figure 5.5 Solute concentration at 8.2 days
EPM gravel-surround experiment

and in the vertical plane along the longitudinal centerline. The two times were chosen to show the plume in a transient state at early time, and at pseudo-steady-state at the time of the gradient change. The solute concentration contour lines were interpreted from an analysis of spatial and temporal trends contained within the large quantity of solute concentration data.

Figures 5.6 and 5.7 show the measured solute concentrations and interpreted concentration contours 1.5 days and 8.3 days after the start of the EPM sand-surround experiment, respectively. These times were equivalent in terms of plume development to those chosen for the gravel-surround experiment.

Figures 5.8 and 5.9 show the measured solute concentrations 9.3 days and 18 days after the start of the DF gravel-surround experiment, respectively. In both figures, solute concentration contours have been interpreted at the elevation of the upper and second planar fracture. Two difficulties were encountered in interpretation. First the lack of instrumentation, particularly in the second fracture, meant that data was scarce. Second, the irregular fracture surface meant that plumes were irregular in shape. For this reason the number of concentration contours drawn was kept to the absolute minimum, and second, these contours were marked to indicate the uncertainty in their location. The two times were chosen to show the plume at pseudo-steady-state both at the time of the gradient change, and later in the experiment.

Figures 5.10 and 5.11 show measured solute concentrations multiplied by ten and interpreted

a) Plan view at 600mm elevation

b) Centerline section view

Figure 5.6 Solute concentration at 1.5 days
EPM sand-surround experiment

a) Plan view at 600mm elevation

b) Centerline section view

Figure 5.7 Solute concentration at 8.3 days
EPM sand-surround experiment

a) Upper fracture elevation

b) Second fracture elevation

Figure 5.8 Solute concentration at 9.3 days
DF gravel-surround experiment

a) Upper fracture elevation

b) Second fracture elevation

Figure 5.9 Solute concentration at 18 days
DF gravel-surround experiment

a) Upper fracture elevation

b) Second fracture elevation

Figure 5.11 Solute concentration at 17 days
DF sand-surround experiment

concentration contours 6.8 days and 17 days after the start of the DF sand-surround experiment, respectively. The concentrations were multiplied by ten in order to normalize them to a 10,000 ppb source concentration. Again, these figures were prepared in deference to the lack of data and the irregular shape of the plumes. The figures show the plume at the time of the gradient change, and at the end of the experiment.

5.3 Solute Mass Flux Across the Down-Gradient Boundary

Solute concentrations measured in the down-gradient reservoir in the seven experiments are presented in tabular form in Appendix D. The solute mass flux across the down-gradient boundary, $\bar{M}$, was determined from this and the flow rate data using the following equation, developed from a consideration of mass balance in the reservoir:

$$\bar{M} = \frac{(C_2 - C_1)V + \left(\frac{C_2 + C_1}{2}\right)Q\Delta t}{\Delta t} \quad (20)$$

where V is the volume of the reservoir, C_1 and C_2 are the first and second of a pair of solute concentrations measured in the down-gradient reservoir over a time period Δt , and Q is the experiment outflow rate during that time period. This equation assumes that a linear change in concentration occurred in the reservoir during the time period, and the calculated solute mass flux represents an average rate for the time period. It also assumes complete and instantaneous mixing of solute within the reservoir such that the concentration of the effluent was always equal to the concentration within the reservoir. Mass loss from the host rock

during the time period was determined by multiplying the rate by the length of the time period. Cumulative mass loss vs. time was determined by adding the mass losses for each consecutive time period.

Figures 5.12a and 5.12b show graphs of solute mass flux across the down-gradient boundary vs. time in the two best EPM and DF experiments, respectively. The figure indicates that, with the exception of the DF sand-surround experiment, the solute mass flux data was relatively smooth. The large fluctuations in early-time mass flux observed for the DF sand-surround experiment reflect the fact that the early-time concentrations used to calculate mass flux were close to the detection limit of the instrument.

Figure 5.13 shows the solute mass flux across the down-gradient boundary in the three sets of repeated experiments. The figure indicates that the two EPM gravel-surround experiments compare reasonably well. Both show a similar peak solute flux, at a similar time, followed by a similar decline. The figure indicates that the two EPM sand-surround experiments compare rather poorly. While the time-to-peak compares well, the first of the two experiments produced a much higher solute mass flux than the second. Finally, the figure indicates that the two DF gravel-surround experiments also compared rather poorly. The first of these experiments produced a much lower solute mass flux than the second, especially at early time. In all three cases, the comparison between experiments is better at later time. The poor comparisons are assumed to reflect variations in diffusive solute release from the tailings resulting from variations in compaction density, or in air entrapment.

Figure 5.12 Solute mass flux across boundary vs. time in all four experiments

● Approximate Time of Gradient Change

Figure 5.13 Solute mass flux across boundary vs. time in comparable experiments

5.4 Initial and Final Tailings Solute Concentrations

Initial and final solute concentrations measured in the tailings in the seven experiments are presented in tabular format in Appendix E. Examination of the initial tailings concentrations shows that solute concentrations varied greatly. As noted in Section 4 sampling of the tailings was difficult to do without significantly disturbing them. The sampling technique was improved with each experiment, however, and data from the last two DF experiments is considered to be the most accurate. These results suggest that the actual average initial concentration was quite close to the design concentration. Comparison of the final tailings concentration data from the repeated experiments showed similar spatial patterns in both experiments. For this reason, the first set of data will not be presented in this section.

Figure 5.14a, 5.14b, 5.14c, and 5.14d shows the tailings solute concentrations following the the EPM gravel-surround, EPM sand-surround, DF gravel-surround, and DF sand-surround experiments, respectively. Each figure shows the concentration profile in the four sets of five radially-arranged samples.

5.5 Mass Balance

A mass balance was performed on each of the experiments by comparing the mass of emplaced dye to the sum of the cumulative mass loss and the mass of dye left in the tailings at the end of the experiment. The mass of dye remaining in the surround and host rock as

Legend for all four graphs

Figure 5.14 Residual solute concentration in tailings in all four experiments
(initial concentration approx. 10,000 ppb)

well as that remaining in the tank was not accounted for because it was negligible. The mass of the emplaced dye was determined by multiplying the known mass of the dye in the batch by the ratio of the mass of emplaced silica to the total mass of silica in the batch (not all the silica in a batch would be emplaced). The mass of dye left in the tailings was determined by multiplying the average final tailings solute concentration by the 0.078 m^3 volume of the tailings portion of the model and by the assumed tailings porosity of 0.4.

The mass balance results, and some of the data necessary to calculate the balance, are included in Table 5.3. The table indicates that the discrepancy between the emplaced mass and the accounted for mass at the end of the experiment was generally smaller for the EPM experiments than for the DF experiments. For the EPM experiments the discrepancy ranged from 26% missing to 17% in excess. For the DF experiments the discrepancy ranged from 54% to 33% missing. The discrepancies in the mass balance are attributed to two problems associated with the method used to determine the mass of dye left in the tailings. The first and most important problem was that the average solute concentration in the twenty collected samples may not be a good estimate of the actual average final solute concentration. This is because the samples were extracted from a narrow band close to the upper surface of the tailings source, which, especially in the case of the DF model, may not be representative of the remainder of the tailings. It may also be due to errors associated with the sampling methodology. The second problem may be that the assumed tailings porosity was not correct.

Table 5.3 Mass balance

	EPM host rock				DF host rock		
	Gravel	Sand	Gravel	Sand	Gravel	Sand	Gravel
	(1)	(1)	(2)	(2)	(1)	(1)	(2)
Mass of emplaced tracer (mg)	324	314	305	344	260	27.8	278
Estimated final tailings concentration (ppb)	6375	5709	4846	4380	3220	420	726
Residual mass in tailings (mg)	199	178	151	137	100	13.1	23
Cumulative mass loss (mg)	125	190	138	117	20	3.6	162
Residual + mass lost (mg)	324	368	289	254	120	16.7	185
Percentage of initial	100	117	95	74	46	60	67

It should be noted that the mass balances for the DF experiments do not consider mass diffused into the rock matrix. However, diffusion calculations and the results of the numerical modelling suggest that this mass was negligible relative to the cumulative mass loss at the down-gradient boundary.

6. INTERPRETATION OF PHYSICAL MODEL RESULTS

Interpretation of the physical model results is aided by an analysis of Peclet numbers. Peclet numbers for the host rock, surround and tailings for the two EPM experiments are summarized in Table 6.1. These numbers were calculated based on the specific discharges presented in Table 5.1, on assumed porosities for the tailings of 0.4 and for the granular materials of 0.33-0.35, on assumed characteristic lengths for the mortar sand, filter gravel, and crushed silica of 0.3, 6, and 0.09 mm, respectively, and on a free-water diffusivity of $4.5 \times 10^{-10} \text{ m}^2/\text{s}$. A comparison of the Peclet numbers in Table 6.1 to the graph in Figure 2.4 indicates that hydrodynamic dispersion in the tailings was dominated by diffusion, while in the surround and host rock it was dominated by mechanical mixing.

Table 6.1 Peclet numbers in the two EPM experiments

	Host rock	Surround	Tailings
EPM gravel surround	6.7	2667	0.002
EPM sand surround	4	33	0.01

The Peclet numbers for the surround and tailings in the EPM experiments are assumed to apply equally well to those materials within the DF experiments.

6.1 EPM Experiments

Examination of Figures 5.1 and 5.2 and Table 5.1 clearly show the effect of the gravel

surround on steady-state groundwater flow, relative to the sand surround. The gravel surround caused a greater than 40 fold decrease in hydraulic gradient across the pit, effectively eliminating groundwater flow through the tailings.

Despite the reduced gradient across the pit caused by the gravel surround, the high-hydraulic conductivity of this material allowed five times the flow of groundwater than did the sand surround. To satisfy this increased flow rate, groundwater was drawn inward and upward from the host rock into the up-gradient half of the gravel surround. The path of groundwater through either the gravel or sand surround could not be explicitly determined. Logic dictates that it followed the path of least resistance around the relatively impermeable tailings, and that resistance could be attributed to the length of the path as well as to, it is hypothesized, losses associated with cornering. On the down-gradient side of the pit, groundwater was released outward and downward from the gravel surround at 1.7 times the velocity observed in the sand-surround experiment.

Groundwater flowing through the model picked up solute as it was released from the tailings and carried it towards the down-gradient reservoir. Figure 5.12a shows that the peak rate of solute flux entering the reservoir occurred 2 days after the start of the gravel-surround experiment and 3 days after the start of the sand-surround experiment. Since these times correspond to the groundwater travel-time between the pit and the reservoir, the peak rate of solute release from the tailings must have occurred at the very start of the experiments. Figure 5.12a shows that the gravel-surround experiment produced close to twice the peak

solute mass flux produced by the sand-surround experiment. Following the peak, the solute mass flux decreased asymptotically, and within five days of operation, the two fluxes became virtually identical. When the hydraulic gradient was dropped in half, the solute mass flux showed a corresponding reduction, and, simultaneously, the solute concentrations generated within the surround doubled. When these doubled concentrations reached the down-gradient reservoir, the solute mass flux recovered to its original asymptotically decreasing rate.

Figure 5.12a shows that the rate of solute release from the tailings was essentially independent of the type of surround, as well as the hydraulic gradient. Since this indicates that the rate of solute release from the tailings was independent of the groundwater flow regime, we can conclude that solute release was a diffusion-dominated process, controlled only by the porosity, diffusivity, and concentration gradient at the outer edge of the tailings. The asymptotic decline in solute release rate thus reflects the decline in concentration gradient at the outside edge of the tailings from close to infinity at the start of the experiments towards the lower value measured at the end of the experiments (see Figure 5.14).

The fact that solute release was controlled by diffusion leads us to question the use of the steel drum to occupy the centre of the tailings. Since this drum prevented groundwater flow or solute transport across the centre of the tailings, it also dictated, a priori, that diffusion would control the solute release. This difficulty was addressed by numerically simulating the experiments with a full pit of tailings rather than with the steel drum in place.

It is interesting that the two experiments produced, on the whole, the same rate of solute release even though the concentrations in the gravel surround were five times lower than in the sand surround. Similarly, the rate of solute release did not change significantly when the concentrations in the surround doubled as a result of the gradient change. Both these observations show that the concentration within the tailings was high compared to that in the surround, and that the magnitude of the concentration gradient was insensitive to the solute concentration in the surround.

The movement of solute from its point of release from the tailings to the down-gradient reservoir can be interpreted from the solute concentrations measured in the surround and host rock. Figure 5.3a shows how the concentration changed with time at an observation point down-gradient of the pit. Initially, the concentration at the observation point was zero, but, as the plume front arrived, the concentration increased rapidly to its peak value. Once the plume front had passed the observation point the concentrations decreased asymptotically with time. The temporal behaviour at the observation point is consistent with the rate of solute release from the tailings, as described earlier.

It is interesting to note that the concentrations generated down-gradient of the source were, after the passing of the plume front, approximately five times lower in the gravel-surround experiment than the sand-surround experiment. Given that the specific discharges in the gravel surround were five times higher than in the sand surround, and given that the flux of solute out of the tailings in both experiments was approximately equal, this observation leads

us to the conclusion that the surround acted like a mixing cell. The concentration released from the cell was proportional to the instantaneous mass flux released from the tailings and inversely proportional to the groundwater flow through it.

Examination of Figures 5.4, 5.5, 5.6 and 5.7 shows how the moving groundwater carried the solute away from the pit and towards the down-gradient reservoir. In the gravel-surround experiment, where groundwater was directed outwards and downwards from the pit, solute was distributed widely throughout the down-gradient host rock. In the sand-surround experiment, where groundwater flowed inwards and upwards around the tailings, the solute was concentrated in a narrow zone along the longitudinal centerline.

The high concentrations at the plume front in Figure 5.4 reflects the high rate of solute release from the tailings at the start of the gravel-surround experiment. The released mass was transported quickly around the tailings circumference and radially outwards across the surround to the exit points along the down-gradient half of the pit, leading to the arc-shaped plume front shown in the figure. Looking backwards along the flow lines from the plume front towards the pit shows that as time proceeded the concentrations generated in the surround decreased. As this occurred proportionally more of the solute was transported around the outside edge of the tailings towards the centerline. The pseudo-steady-state distribution, as indicated in Figure 5.5, shows that the vast majority of the solute was concentrated in a narrow band along the centerline of the model.

6.2 DF Experiments

Given the low permeability of the rock matrix, groundwater flow in the DF model was conceptualized as being contained within two separate horizontal two-dimensional domains (the two upper fractures) intersected by a cylindrical three-dimensional domain (the pit). It follows from this analysis that groundwater which entered the pit from the fractures on the up-gradient side must have spread out through the three-dimensional domain, before reconverging towards the fractures on the down-gradient side. Given the low permeability of the tailings, it is also true that the vast majority of this spreading and reconverging flow must have occurred in the surround rather than in the tailings. For the purposes of this discussion, the time that groundwater spent travelling through the surround is referred to as the “residence time”. The actual path that groundwater took during its residence in the pit is not known with any certainty.

Figure 5.12b shows that solute mass flux across the down-gradient boundary increased almost immediately after the start of the experiments, and achieved a peak value after less than one day in the gravel-surround experiment and after six days in the sand-surround experiment. The delay between the start of the experiment and the measurement of peak solute mass flux is attributed to the residence time within the surround materials, rather than the less than one hour fracture-flow travel time between the pit and the reservoir. Following the peak, the solute mass flux declined asymptotically with time, as was observed in the EPM experiments.

Examination of Figure 5.12b shows two distinguishing features of the DF sand-surround experiment. First, the solute mass flux did not recover following the gradient change, and second, the solute mass flux produced in this experiment was generally lower than in any of the three other experiments. These observations indicate that the solute concentrations that existed in the DF sand surround were high enough to modulate the concentration gradient at the outer edge of the tailings, and, by extension, the rate of solute release. Given that concentrations in the DF sand surround doubled following the gradient change from approximately 1000 ppb to 2000 ppb (see Figures 5.10 and 5.11), and that these concentrations were significantly higher than the surround concentrations measured in the other experiments, this result is not surprising.

Figure 5.3b shows the temporal changes in concentration at an observation point down-gradient of the pit, in the second fracture. The figure shows that the concentration increased almost immediately after the start of the experiments, and reached a peak after less than one day in the gravel-surround experiment, and after six days in the sand-surround experiment. Again, these times-to-peak must approximately reflect the residence time within the surround, and that groundwater with the highest concentration must be that which entered the up-gradient side of the pit at the start of the experiments. Following the peak, the concentrations decreased asymptotically with time.

It is interesting to note that the concentrations generated in the gravel-surround experiment were approximately ten times lower than those in the sand-surround experiment. Returning

to the mixing cell analogy, this result suggests that the specific discharge in the gravel surround was ten times higher than in the sand surround. The relative difference in specific discharge between the two experiments agrees with the relative differences in residence time through the surround, as discussed above.

Figures 5.8, 5.9, 5.10, and 5.11 show the solute plumes in the gravel-surround and sand-surround experiments at two different times. As noted previously, the lack of data and the irregularity of the solute plumes resulted in difficulty in interpreting the results. The first observation drawn from the figures, however, is that the plumes in the gravel-surround experiment were wider and contained lower peak concentrations, than those in the sand-surround experiment. This result suggests that the two surround materials had a similar impact on horizontal flow directions in the host rock as was observed in the EPM experiments. Secondly, the concentrations in the lower fracture were higher than in the upper fracture. This suggests that, on average, groundwater that entered (and exited) the surround from the second fracture travelled more slowly through it, than that which entered (and exited) the surround from the upper fracture. It makes sense to suggest that the bulk of this groundwater flowed beneath rather than around the tailings, and the required cornering resulted in lower velocities.

It should be noted that the shape of the plumes was very similar at the two different times, and only the magnitude of the concentrations changed. This results from the fact that the seepage velocities in the fractures of the host rock were high in relation to those in the

surround. In essence, the plume distribution changed instantaneously with the changing concentration at the pit/fracture intersections. In this sense, the plume in the DF experiments reached a pseudo-steady-state condition within an hour after their start.

6.3 Evaluation of the Transient Conditions Associated with Model Saturation

An important question that arose during interpretation of the physical model results was whether or not the transient conditions that existed during model saturation had an impact on the results of the experiments. It was concluded that the transient conditions had very little impact on the results, and that no consideration of these conditions needed to be incorporated into the data interpretation. This statement is based on the analysis presented below.

First, the tailings were placed at an initial saturation of approximately 75-100%, and are believed, based on visual inspection, to have become fully saturated within a few hours of the start of the experiments. During that time, it is felt that the effective diffusivity, which likely controlled solute release from the tailings at early time, would not have been significantly different from the fully saturated value. In fact, it might have been slightly lower due to the presence of air in the pore space.

Second, the interpretation given in this section is born out by the results of numerical simulations. The early time and pseudo steady state solute distributions at 0.6 m elevation illustrated in Figures 5.4, 5.5, 5.6, and 5.7 could be matched very closely with two

dimensional simulations of a planar section through the model domain. As will be shown in the next section, however, matching of the plumes in three-dimensions was made difficult by the requirement to model groundwater flow around 90 degree corners at the bottom of the cylindrical tailings.

7. NUMERICAL SIMULATION OF THE EXPERIMENTS

In this section, the numerical simulation of the four best physical model experiments is described. It is important to note that the geometry, boundary conditions, and initial conditions of the physical model experiments were chosen so as to be reasonably represented by a coupled groundwater flow and solute transport boundary value problem. For this reason, these aspects of the numerical solution were considered to be known. The coefficients contained within the governing equations were known with much less certainty. They were determined through a combination of testing, as described in Section 4, and by adjustment to achieve good agreement between experimental and simulated results. Meeting this goal with values of the coefficients that make physical sense provided confidence in the validity of the numerical solution.

7.1 Numerical Model Selection

Numerical simulation of the physical model experiments was carried out using FRAC3DVS. This code was chosen for its ability to model groundwater flow and solute transport in both a three-dimensional porous matrix, and in a network of two-dimensional fractures. Capabilities available but not used in this project include simulation of variably-saturated transient groundwater flow, as well as sorption and radioactive decay of solute. The governing equations, numerical formulation, and verification of FRAC3DVS is documented in a paper by R. Therrien and E. A. Sudicky (1996).

FRAC3DVS uses a control volume finite element technique for the solution of the groundwater flow equation, and a time-marching Galerkin finite element technique for the solution of the solute transport equation. The equations can be discretized using either a 6-node triangular prism element or an 8-node hexahedral block. If the latter of these element types is chosen, a finite difference solution to both the flow and transport equations is available.

7.2 Numerical Model Construction and Operation

The geometry of the EPM model domain and the distribution of the four media contained within it was the same as the physical model design, as presented in Figure 4.1. The geometry of the DF model was the same as the upper 0.54 m of the physical model design, as presented in Figure 4.2. The upper 0.54 m includes the upper three slabs, and upper two fractures. Since symmetry was assumed to exist along the longitudinal centerline of the model, only one half of the physical system was simulated.

The porous media were discretized into hexahedral blocks, and the fractures were represented by square or rectangular surfaces. The sizing of the blocks was chosen to allow adequate representation of the curved sides of the pit, to meet numerical constraints vis à vis Peclet and Courant numbers, and to allow for the proper development of concentration gradients at diffusion surfaces.

Plan and section views of the EPM and DF model meshes are shown in Figure 7.1. In the longitudinal direction the 204 blocks varied in length from 7.5 mm in the vicinity of the pit to 35 mm at the up-gradient end of the domain. The longest block length in the down-gradient direction was 20 mm. In the transverse direction the 76 (75 in the DF model) blocks varied in length from 7.5 mm in the vicinity of the pit to 50 mm at the lateral extremity. In the vertical direction the 17 (25 in the DF model) blocks varied from 7.5 mm at the fracture surface in the DF model to 150 mm. This discretization resulted in a total of 263,568 blocks in the EPM model, and 382,500 blocks in the DF model. This discretization was as fine as memory constraints allowed.

One of four sets of properties was assigned to every block in the model, depending on the location of its centroid with respect to the surfaces separating the host rock, surround, tailings, and void space (i.e. the space inside the steel drum). These surfaces are shown in plan and section in Figure 7.1. For the porous media, the values of hydraulic conductivity, porosity, longitudinal and transverse dispersivity, and tortuosity for each of these zones were chosen based on the results of the materials testing described in Section 4, and through a calibration exercise. The goal of the calibration exercise was to match calculated model results with those observed in the laboratory. Calibration was carried out manually by adjusting the elemental properties within some reasonable range, running the numerical model, and evaluating the results of the adjustment. This type of calibration is entirely appropriate to estimate in-situ properties that would, in any case, be determined through fitting of a mathematical model to observed results. It should be cautioned, however, that given the large

7.5 mm square blocks

a) Plan view of EPM and DF mesh
(EPM includes top 50 mm block in Y-direction)

b) Section view of EPM mesh

c) Section view of DF mesh

Figure 7.1 EPM and DF numerical model mesh

number of parameters, the solution is not necessarily unique. Calibration results are presented in Section 7.3. The void space was assigned such a very low hydraulic conductivity and tortuosity that neither solute nor groundwater was transported within it.

Hydraulic heads equal to the reservoir levels were applied at the up and down-gradient ends of the model. All other boundaries were impermeable. An initial solute concentration of 10,000 ppb was applied at all nodes contained within those blocks representing tailings. At all other nodes the concentration was initially zero. All boundaries for solute transport were zero dispersive flux. Since the only boundary across which solute moved was the down-gradient end of the host rock, and since very low concentration gradients existed in the direction of groundwater flow across this boundary, the zero dispersive flux assumption is reasonable.

The code was compiled using a Compaq™ Fortran 90/95 compiler. Simulations were run on a PC with a 200 MHz Intel Pentium II processor, and 256 Mbyte of RAM. Extensive testing of both available solution techniques revealed that the block-based finite difference solution was quicker and provided a far more stable solution to the transport problem. For each experiment, the steady-state groundwater flow solution for the initial gradient was found. A variable time-stepping procedure was then used to march the transport solution from the initial condition to the time of the gradient change. At that point the solution was stopped, restarted with the adjusted flow boundary conditions, and marched forward to the end-time of the simulation.

7.3 Results

7.3.1 Calibration Results

The properties determined to fit the numerical model results to those measured in the laboratory are summarized in Table 7.1.

Table 7.1 Parameter estimates

	EPM host rock	DF host rock	Surround	Tailings
Hydraulic conductivity (m/s)	1×10^{-4}	1×10^{-7} Upper fracture $2b=560 \mu\text{m}$ Second fracture $2b=640 \mu\text{m}$	6×10^{-2} - Gravel 5×10^{-4} - EPM sand 1×10^{-4} - DF sand	6×10^{-7}
Porosity ()	0.33	0.2	0.35	0.4
Longitudinal dispersivity (m)	0.02	0.001 0.02 - Fractures	0.1 - EPM model 0.001 - DF model	0.001
Transverse dispersivity (m)	0.002	0.001 0.002 - Fractures	0.1 - EPM model 0.001 - DF model	0.001
Tortuosity ()	0.7	0.15	0.7	0.4

The hydraulic conductivity of the EPM host rock was adjusted to match the overall flow rate through the model, and the value chosen was consistent with the results of the permeameter testing for a moderately compacted material. The porosity of the EPM host rock was chosen to match the seepage velocities as manifested by the velocity of the plume front and is at the

lower end of the range determined from the in-situ testing. The tortuosity was taken from the literature. Longitudinal and transverse dispersivities were taken to be as low as possible while meeting numerical constraints related to discretization. The chosen values are approximately 20 times those suggested by the tracer experiments.

The hydraulic conductivity of the DF host rock was taken from the literature, and the fracture apertures of the upper and second fracture were taken directly from the results of the hydraulic and tracer experiments. The longitudinal and transverse dispersivities were taken to be as low as the discretization allowed. The results of the tracer experiments suggested that channelling did occur in the fracture that would, in any case, be difficult to model using a symmetric dispersivity tensor. The porosity and the tortuosity of the DF host rock matrix were taken from the literature (Zanini et al., 1997), and the dispersivities were taken to be very low.

The tailings hydraulic conductivity was chosen from the results of the permeameter testing and represents a moderately compacted material. The porosity was assumed to be equal to the design value. The tortuosity was adjusted to fit the rate of solute release from the tailings to the measured rate. The value chosen is consistent with the literature for a fine grained material (Gillham et al., 1984). The dispersivities in the tailings were taken to be very low.

The hydraulic conductivity of the gravel surround was taken directly from the permeameter test. The hydraulic conductivity of the sand surround was chosen to match heads in the EPM

model, and seepage velocities in the DF model. The porosity and tortuosity were taken from the literature. Artificially high longitudinal and transverse dispersivities were assigned to the surround in the EPM simulations in order to compensate for errors in the simulated groundwater flow field. Realistic dispersivities were assigned to the surround in the DF simulations because the use of artificially high values did not improve the calibration.

It should be noted that significantly more simulations were conducted than can reasonably be described in this thesis. Simulations that were useful in the interpretation of the physical model results but will not be discussed in detail were two-dimensional simulations of the EPM experiments in the horizontal plane at 0.6 m elevation and in the vertical plane along the longitudinal centerline. The same parameters were used in the 2D simulations as were used in the 3D simulations except that realistic 1 mm longitudinal and 0.1 mm transverse dispersivities were assigned to the surround. The 2D plan view simulations were able to match very closely the plumes observed in the experiments, indicating that the model was quite capable of simulating advection/dispersion that occurred within the surround and host rock. On the other hand, the 2D section view simulations were not able to match the observed plumes, and consistently overestimated solute concentrations along the upper surface of the model domain between the pit and the down-gradient boundary. This tendency to concentrate mass along the upper surface of the model domain was also observed in the 3D simulations. It was hypothesized that the error stemmed from the fact that the numerical model did not consider head losses at the 90 degree corner at the base of the tailings. Consequently, the numerical model consistently overestimated groundwater flow beneath,

rather than around, the tailings and thus overestimated upward flow within the down-gradient half of the surround. To compensate for this error, high dispersivities were assigned to the surround which ensured that solute was expelled into the host rock before it could be erroneously transported through the surround to the upper edge of the model. As noted above, this manipulation was not utilized in the DF simulations.

Numerical model results presented in the remainder of this section are from the three-dimensional simulations.

7.3.2 Hydraulic Heads, Flow Rates, and Specific Discharges

A comparison of simulated to observed flow rates and hydraulic heads is summarized in Table 7.2. The table indicates that the numerical model underestimated the flow rate by approximately 10% in both the EPM experiments. Similarly, the hydraulic heads in the EPM simulations were approximately 2 mm lower than those observed in the experiments. The discrepancies are attributed to two factors. First the perforated steel plate at the up-gradient end of the EPM host rock likely had some impact on the flow field that was not included in the simulations. Second, it is likely that the hydraulic conductivity of the upper few centimetres of the mortar sand was significantly higher than the average value used in the simulations, causing a higher observed flow rate than the simulated value.

Examination of Table 7.2 indicates that the numerical model underestimated the flow rate

through the DF model by 30-40%. This discrepancy is attributed to the use of a fracture aperture that was too low. If the chosen fracture aperture was correct, however, it might simply indicate that the proportion of the total measured flow rate attributed to the upper two fractures was too high.

Table 7.2 Comparison of calculated and observed flow rates and hydraulic heads

	Calculated flow rate (mL/min) (fraction of observed)	Hydraulic head difference (mm)	Typical calculated specific discharge (m/s)		
			Host Rock	Surround	Tailings
EPM-Gravel(2)	219 (0.92)	1 - min. 4- max. 2 - ave.	3.3×10^{-6}	7×10^{-5}	4×10^{-10}
EPM-Sand(2)	164 (0.86)	0 - min. 4 - max. 2 - ave.	2×10^{-6}	1.8×10^{-5}	1.7×10^{-8}
DF-Gravel(2)	59 (0.69)	na	7×10^{-4}	2.3×10^{-5}	2.4×10^{-10}
DF-Sand(1)	35 (0.60)	na	4×10^{-4}	1.8×10^{-6}	2.8×10^{-9}

Notes: na = not applicable

Typical specific discharges in the down-gradient host rock, surround and tailings as determined from the four simulations are also summarized in Table 7.2. Comparison of the specific discharges determined from the EPM simulations to those summarized in Table 5.1 shows a reasonable agreement.

The specific discharge estimates for the DF simulations indicate that the gravel surround

caused a 12 fold decrease in specific discharge through the tailings, a 13 fold increase in specific discharge through the surround, as well as a 1.7 fold increase in specific discharge in the down-gradient host rock, all relative to the sand-surround simulation.

Figures 7.2a and 7.2b show equipotential lines in plan view at 0.6 m above the datum and in cross-section view along the longitudinal centerline, respectively, as determined from the results of the EPM gravel-surround simulation. Also shown on the figures are horizontal and vertical projections of particle traces released within these two planes at the left hand boundary. The equipotential lines and particle traces in the host rock agree well with those in Figure 5.1 and this makes sense given the general agreement in hydraulic heads between the experiments and simulations. It is interesting to note that particle traces that approached the pit at 0.6 m elevation and within 0.2 m of the centerline travelled vertically in the surround so as to take a path beneath the tailings. The experimental results suggested, however, that strong vertical flow in the surround did not exist, and thus a discrepancy is implied between the physical and numerical groundwater flow fields. It was hypothesized that, in the physical models, groundwater tended to flow around rather than below the tailings because this route was smoother and less tortuous. The error in the numerical model was thus attributed to its inability to account for head losses (inertial or turbulent, for example) at the ninety degree corners at the base of the tailings.

Figures 7.2c and 7.2d show the same equipotential lines and particle traces as described above, as determined from the results of the EPM sand-surround simulation. Again, the

a) Gravel
surround
simulation
- plan view

b) Gravel
surround
simulation
- centerline
section

c) Sand
surround
simulation
- plan view

d) Sand
surround
simulation
- centerline
section

Plan - equipotentials at $z = 600$ mm
 - particles released at $x = 0$, $y = \text{various}$, $z = 600$
Section - equipotentials at $y = 0$ mm
 - particles released at $x = 0$, $y = 0$, $z = \text{various}$

Figure 7.2 Equipotential lines and particle traces in EPM simulations

equipotential lines and particle traces in the host rock agree well with the physical model results shown in Figure 5.2. The path of the particles skirting around the tailings is not significantly different from those shown in the previous figure. This is because the shortest route around the tailings did not change from simulation to simulation.

Figure 7.3a shows equipotential lines at the elevation of the upper fracture as determined from the results of the DF gravel-surround simulation. Also shown on the figure are horizontal projections of particles released in the upper fracture at the left hand boundary. Figure 7.3b shows the same type of results but for the second fracture, while Figure 7.3c shows a section view of the equipotential lines and a combined set of particle traces. The plan view figures indicate that the surround had the same influence on horizontal flow directions as was observed in the EPM simulations, causing up-gradient groundwater to be drawn inwards and down-gradient water to be expelled outwards.

Figure 7.3 shows that all the groundwater that entered the pit from the upper fracture skirted around the tailings, while the vast majority of the groundwater that entered the pit from the lower fracture travelled beneath them. This result reflects the fact that from the elevation of the upper fracture, the route around the tailings was shorter than the route below it. From the elevation of the lower fracture the opposite was the case. Again, it was hypothesized that the numerical model's inability to account for head losses due to cornering at the base of the tailings caused an overestimation of the proportion of groundwater travelling beneath rather than around the tailings.

a) Plan view of equipotential lines at upper fracture elevation,
particles released at left hand side in upper fracture

b) Plan view of equipotential lines at second fracture elevation,
particles released at left hand side in second fracture

c) section view of equipotential lines along centerline,
combination of upper and lower fracture particles (as above)

**Figure 7.3 Equipotential lines and particle traces
in DF gravel-surround simulation**

Figures 7.4 a, b, and c show the same equipotential lines and particle traces as described above as determined from the results of the DF sand-surround simulation. The figures show the same basic patterns as were seen for the gravel-surround simulation except that groundwater within the two fractures tended to be diverted around the pit, rather than being focussed towards it. This result is consistent with the EPM results.

7.3.3 Solute Concentrations in the Surround and Host Rock

Figures 7.5a and 7.5b show solute concentrations 0.7 days and 8.2 days after the start of the EPM gravel-surround simulation. Comparison of these figures to Figures 5.4 and 5.5 allows comparison of the simulated solute distributions to those measured within the experiment. The overall shape of the simulated solute plumes agree reasonably well with the observed, but the distribution of solute within the plumes does not generally agree. The simulation underestimated the solute concentration within the center of the plume and overestimated the solute concentration at its extremities. This erroneous distribution can be attributed to the use of the artificially high dispersivities within the surround and to high dispersivities within the host rock. As previously described, the former manipulation was used to prevent mass from concentrating along the upper surface of the model between the pit and the down-gradient boundary. Notwithstanding the use of this manipulation, concentration of mass along the upper surface did occur to some extent and can be observed in both section views of Figure 7.5. The second manipulation was used to prevent numerical dispersion.

a) Plan view of equipotential lines at upper fracture elevation, particles released at left hand side in upper fracture

b) Plan view of equipotential lines at second fracture elevation, particles released at left hand side in second fracture

c) section view of equipotential lines along centerline, combination of upper and lower fracture particles (as above)

Figure 7.4 Equipotential lines and particle traces in DF sand-surround simulation

a) Plan view at 0.6 m above datum and centerline section at 0.7 days

b) Plan view at 0.6 m above datum and centerline section at 8.2 days

Figure 7.5 Solute concentrations in EPM gravel-surround simulation

Figures 7.6a and 7.6b show the solute concentrations 1.5 days and 8.3 days after the start of the EPM sand-surround simulation, respectively, in both plan and section view. The figures again show that the simulation determined the overall shape and size of the solute plume reasonably well, but did not correctly determine concentration distributions within it. All the same discussion that applied to the gravel-surround simulation also applies to this simulation.

Figure 7.7a and 7.7b show solute concentrations 9.3 days and 18 days after the start of the DF gravel-surround simulation, respectively. Both figures show solute concentration contours at the elevation of the upper and second fracture. Comparison of these figures with Figures 5.8 and 5.9 shows that the simulation overestimated the overall width of the plumes, and this is attributed to a combination of an overestimation of hydrodynamic dispersion in the host rock, and possibly, within the surround. Comparison of the simulated and experimental results further indicates that the magnitude of the simulated concentrations along the longitudinal centerline were much closer to the experimental results than they were for the EPM simulations. This positive result reflects the fact that a realistic dispersivity was used to model hydrodynamic dispersion in the surround. It should be noted, however, that the simulation overestimated the concentrations within the upper fracture and underestimated the concentrations in the lower fracture. This discrepancy is again attributed to an overestimation of upwards flow in the down-gradient half of the surround.

Figure 7.8a and 7.8b show solute concentrations 6.8 days and 17 days after the start of the DF sand-surround simulation, respectively, in the upper and second fracture. Comparison

a) Plan view at 0.6 m above datum and centerline section at 1.5 days

b) Plan view at 0.6 m above datum and centerline section at 8.3 days

Figure 7.6 Solute concentrations in EPM sand-surround simulation

a) Upper and second fracture at 9.3 days

b) Upper and second fracture at 18 days

Figure 7.7 Solute concentrations in DF gravel-surround simulation

a) Upper and second fracture at 6.8 days

b) Upper and second fracture at 17 days

Figure 7.8 Solute concentrations in DF sand-surround simulation

of these figures with Figures 5.10 and 5.11 shows that the simulation overestimated the overall width of the plume, generally underestimated concentrations along the centerline, but achieved approximately the correct ratio of peak concentrations in the upper to the second fracture. The latter result indicates that the simulated flow field was likely more accurate than that of the gravel-surround simulation. Since the specific discharge in the surround of the DF sand-surround experiment was quite low, it makes sense that cornering effects were quite minor. Thus, the exclusion of velocity head from the definition of hydraulic head was not a significant problem in this simulation, and the numerical model was reasonably able to simulate the flow field. The fact that the simulated solute concentrations within the plume still did not match the observed concentration indicates a combination of inadequate simulation of hydrodynamic dispersion, or lack thereof, in the surround, and inadequate simulation of the tortuous groundwater flow in the rough-surfaced fractures.

It is unfortunate that the erroneous determination of the groundwater flow fields had such a dramatic impact on the determination of solute distribution within the plumes. The results of the DF sand-surround simulation suggests, however, that the erroneous flow field was not the only cause of the discrepancies. Assuming that the groundwater flow field provided a reasonable match to reality in this simulation, then inadequacies in the three-component dispersivity tensor used to model hydrodynamic dispersion provide the most likely reason for the discrepancies. Section 2.3.5 provides a discussion of the validity of this approach, and it is speculated that conditions existed within the surround that are difficult to model using this approach.

Another reason for the numerical model's relatively poor accuracy in simulating solute distributions may have resulted from small size of the surround portion of the model in relation to the grain size of the materials used to fill it. It is possible that the 2 cm width of the surround was smaller than the REV of these materials. If this was the case then the use of average flow directions rather than intergranular velocities resulted in a simple inability to adequately model solute transport.

7.3.4 Solute Mass Flux Across the Down-Gradient Boundary

Simulated and observed solute mass flux across the down-gradient boundary in both EPM scenarios are shown in Figure 7.9a. The figure shows that the numerical model overestimated solute mass flux in the first few days of the simulations by 100 to 200%. Following this discrepancy, both simulations achieved a very good match to their respective observed results. The initial overestimation is attributed primarily to the use of a too-coarse discretization within the outer few mm of the tailings. The distances across which concentration slopes and curvatures were calculated were too large to adequately simulate the rapidly changing conditions at early time.

Simulated and observed solute mass flux at the down-gradient boundary in both DF scenarios are shown in Figure 7.9b. The figure indicates that the gravel-surround simulation vastly overestimated the solute mass flux for the first day of the simulation, but achieved a very good match after that time. The overestimation is again attributed to inadequate

Figure 7.9 Observed and simulated solute mass flux at boundary vs. time in all four experiments

discretization of the tailings/surround interface. A second likely reason for this overestimation is that hydrodynamic dispersion was not correctly simulated within the surround. The numerical model likely overestimated the flux of solute towards the fractures at early time, and the high specific discharge within the fractures swept this mass out of the model almost instantaneously. Figure 7.9b indicates that a very good match was achieved between the simulated and observed solute mass flux in the sand-surround scenario. Indeed, this simulation was the only simulation that did not overestimate solute mass flux at early time. This fact is attributed to the low specific discharges in the sand surround apparently making the early-time solute transport easier to simulate.

Mass balances performed at the end of the DF simulations showed that the mass transferred to the rock matrix was negligible compared to that which was released out of the down-gradient boundary. For this reason, it was not possible to evaluate the accuracy of this aspect of the numerical simulations.

It is important to note that the numerical model was able to achieve a good later-time match to observed solute mass flux across the down-gradient boundary notwithstanding the discrepancies in simulated plume concentrations. This provides good confidence in the model for predicting solute release from the tailings in the full-pit simulations described below.

7.4 Full-Pit Simulations

7.4.1 Methods

Numerical simulations were conducted in order to predict how the physical models would have performed had the steel drum not been used and had the pits been filled with tailings. To carry out this analysis the EPM gravel-surround and sand-surround simulations were repeated with the void portion of the model implemented as tailings. The solute transport solution was stepped forward from the initial conditions for a total of one year of simulation time, with a constant hydraulic gradient applied across the domain.

7.4.2 Results

The full-pit simulations allowed groundwater to flow across the centre of the tailings, a situation that was disallowed by the steel drum. The simulated specific discharge through the tailings with a gravel surround and sand surround were 8.0×10^{-10} m/s and 1.6×10^{-8} m/s, respectively. Accounting for porosity, it would take groundwater 14 years and 240 days to cross the tailings in the two respective simulations.

Figures 7.10a and 7.10b show solute concentrations in the tailings 91, 182, 274, and 365 days after the start of the gravel-surround and sand-surround simulations, respectively.

a) Full pit, gravel-surround simulation

b) Full-pit, sand-surround simulation

Figure 7.10 Solute concentrations within tailings in the full-pit simulations

The first thing to notice in Figure 7.10 is that concentrations outside the tailings are always much lower than those within. This is because the fast moving groundwater in the surround and host rock provides massive dilution to the released solute. For this reason, the outside edge of the tailings behaves like a first-type, low-concentration boundary condition and ensures that, regardless of the mechanisms of solute transport within, solute is transported out of the tailings by diffusion.

The second thing to notice in Figure 7.10 is that the concentration contours in the gravel-surround simulation are almost concentric circles, while those in the sand-surround simulation are offset towards the down-gradient edge of the tailings. The difference reflects the difference in seepage velocity through the tailings. In the gravel-surround simulation the concentric circles indicate that diffusion was the dominant process of solute transport from the centre of the tailings towards the outside edge. In contrast, the offset circles in the sand-surround simulation mean that the rate of diffusion at the plume front was greater than the rate of diffusion at the plume tail. The difference between these rates is attributed to advection through the centre of the tailings.

The third thing to notice is the persistence of a zone of high concentration within the centre of the tailings in the gravel-surround simulation. This area is far enough from the low-concentration boundary that it is, relatively speaking, unaffected by diffusion at the outside edge. At an actual facility, the area unaffected by diffusion will make up the vast majority of the tailings. This is because actual pit diameters are greater than 500 m, and, even in 1,000

years, diffusion will only penetrate into a narrow 10 m band.

Figures 7.11a and 7.11b show the rate of solute release from the tailings and the cumulative mass loss vs. time, respectively, during the first 100 days of both simulations. These two figures show that the rate of solute release declined from a peak rate after the start of the experiment towards an asymptotic lower rate. The figure indicates that the sand-surround simulation produced a much higher rate of solute release than the gravel-surround simulation. In fact, given that the total mass of solute initially present in the simulations was approximately 1000 mg, the sand-surround simulation released virtually all its mass within the first 100 days. Obviously, the high rate of solute release is attributed to advective solute transport within the tailings towards their down-gradient edge.

a) Solute mass flux across down-gradient boundary vs. time

b) Cumulative mass loss vs. time

Figure 7.11 Solute mass flux and cumulative mass loss vs. time in full-pit simulations

8. DISCUSSION AND APPLICATION TO A FULL-SCALE PROBLEM

8.1 Discussion

Based on the results of the physical and numerical modelling, it is possible to state the following general rule about solute transport within and out of the tailings:

The peak rate of solute release from an in-pit TMF will occur immediately after decommissioning. Solute release will continue to occur via diffusion, and the rate will tend to approach the rate of solute flux due to advection through the centre of the tailings.

This general rule has been applied to the creation of Figure 8.1 which illustrates, conceptually, how the rate of solute release will be affected by the choice of a pervious vs. a natural surround. The figure shows that solute release declines from a peak rate immediately following decommissioning towards some asymptote. The magnitude of the peak rate is controlled by diffusion, and the tendency of the pervious surround to enhance diffusion has been indicated by the higher peak rate assigned to this scenario. The magnitude of the asymptote is controlled by advection, and the tendency of the pervious surround to minimize this process has been indicated by a lower asymptote. Thus it is shown that the rate of solute release from an in-pit TMF with a pervious surround will drop below the rate from a facility with a natural surround. The length of time for this to occur is important to

Figure 8.1 Conceptualization of solute expulsion vs. time at an in-pit TMF

our analysis and has been indicated on the figure as t_a .

It should be the goal of any modelling exercise intended to compare performance of a pervious surround to a natural surround to determine accurate estimates of the two solid lines shown in Figure 8.1. The results would be site specific, as has been shown, and depend principally on the hydraulic conductivity of the host rock, tailings, and surround, the regional hydraulic gradient, and the effective diffusivity of the tailings. In Section 3, these conditions were provided for an idealized full-scale site, and in this section an attempt is made to determine t_a for this site. The analysis focusses on t_a because it is considered to be the most important indicator of the relative performance of the two systems.

8.2 Analysis of the Full-Scale Problem

It was demonstrated in Section 7 that discretization constraints limited our ability to determine accurate predictions of solute release from the lab-scale problem using FRAC3DVS. When the numerical model was applied to a 2D version of the full-scale site, the discretization problem became so acute as to make the results meaningless. For this reason, a simple mixed numerical/analytical model was developed to determine an approximate estimate of t_a , labelled t_b in Figure 8.1. T_b is actually the time required for the total rate of solute release from the pervious surround scenario to drop below the asymptotic advective rate from the natural surround scenario. As shown in Figure 8.1, t_b is actually a conservative estimate of t_a (i.e. t_a will always be shorter than t_b).

In order to determine t_b , it was necessary to estimate specific discharge through the tailings for a range of different tailings hydraulic conductivities, with both a pervious and natural surround. These specific discharges were determined from a two-dimensional groundwater flow model of the horizontal plane at half the total depth of the pit, and are presented in Table 8.1. At this depth the pit was 500 m in diameter, and was either completely filled with tailings ($K = 1 \times 10^{-7}$ and 1×10^{-8} m/s) to represent the natural surround scenario, or lined with an 8 m thick pervious surround ($K = 1 \times 10^{-2}$ m/s). Simulations were completed with all four combinations of hydraulic conductivity using a host rock hydraulic conductivity of 1×10^{-6} m/s, and with a hydraulic gradient of 2% applied at distant boundaries.

Table 8.1 Simulated specific discharges at the full-scale site

	Tailings specific discharge (m/s)	
	Pervious surround	Natural surround
Tailings K 1×10^{-7} m/s	1.3×10^{-11}	3.6×10^{-9}
Tailings K 1×10^{-8} m/s	1.3×10^{-12}	3.9×10^{-10}

The maximum solute mass flux due to advection, M_a , through the centre of the tailings (i.e. immediately after decommissioning) are presented in Table 8.2 for the two values of tailings hydraulic conductivity and two surround scenarios. These estimates were determined using the following equation, which assumes steady state advective flux, (equation 8) across the cross-sectional area of the centre of the conical pit:

$$M_a = rh\bar{q}C_0 \quad (22)$$

where C_0 is the initial tailings concentration (1.0), and $\bar{q}$ is the specific discharge, r is the radius of the top of the pit (500 m) and h is the depth of the pit (182 m).

Table 8.2 Maximum advective flux through the tailings at the full-scale site

	Flux due to advection (% of total mass/year)	
	Pervious surround	Natural surround
Tailings K 1×10^{-7} m/s	2.0×10^{-4}	5.4×10^{-2}
Tailings K 1×10^{-8} m/s	2.0×10^{-5}	5.9×10^{-3}

The maximum rates presented in Table 8.1 were determined assuming that the concentration everywhere within the tailings was equal to the initial concentration. The actual solute mass flux due to advection through the tailings will decrease slightly with time as diffusion removes solute from a narrow band (less than 10 m thick after 1000 years) at the outside edge of the tailings. On the whole, however, the maximum rates presented in Table 8.2 are reasonable estimates of a steady-state advective mass flux through the tailings core.

The maximum possible solute mass flux due to diffusion, M_d , out of the tailings are presented in Table 8.3 for 0.1, 1, 10, 100, and 1000 years after decommissioning. These estimates were determined using the following equation, which assumes diffusive flux (equation 9) across the surface area of the conical pit:

$$M_d = nD_d \frac{dC}{dr}(t) \pi r \sqrt{r^2 + h^2} \quad (21)$$

where $dC/dr(t)$ is the magnitude of the time-dependent concentration gradient at the outside edge of the tailings. The concentration gradients were determined at the above-listed times from a numerical model of diffusion from a column of uniform initial concentration into a first-type boundary condition where the concentration was kept constant at zero.

Table 8.3 Maximum diffusive flux out of the tailings at the full-scale site

Time (years)	dC/dr	Diffusive flux (% of total mass/year)
0.1	22.2	2.5×10^{-1}
1	7.1	7.9×10^{-2}
10	2.25	2.5×10^{-2}
100	0.71	7.9×10^{-3}
1000	0.22	2.4×10^{-3}

Since it is known that groundwater flows through the pervious surround at a very high rate, it is reasonable to assume that the concentration adjacent to the tailings will be negligible relative to the concentration in the tailings themselves. Thus, the assumption of a zero-concentration outer boundary is reasonable, and the maximum diffusive fluxes presented in Table 8.3 are reasonable estimates of the actual flux of solute out of the full-sized facility with a pervious surround.

Figure 8.2 shows the advective solute flux through the centre of the full sized facility for all four tailings hydraulic conductivity/surround type combinations and diffusive flux out of the full-sized facility with a pervious surround, plotted against time for the first 1000 years after

Figure 8.2 Rate of solute release vs. time from the full-scale facility

decommissioning. Both the x and y axes are log-transformed and thus the diffusive solute flux appears to decrease linearly with time.

According to the general rule provided at the start of this section, the total rate of solute release from the full-sized facility with a pervious surround will decrease with time along line A and will eventually approach either line D or E, depending on the tailings hydraulic conductivity. In contrast, the total rate of solute release from the full-sized facility with a natural surround will decrease from some peak value which is not shown towards either line B or C, depending on the tailings hydraulic conductivity. From Figure 8.2 an estimate of t_b can be determined as 2 or 180 years, depending on tailings hydraulic conductivity. Thus we can conclude that for the full-sized facility described in Section 3, the pervious surround will outperform (i.e. release less solute) the natural surround within 2 years for a tailings hydraulic conductivity of 1×10^{-7} m/s and within 180 years for a tailings hydraulic conductivity of 1×10^{-8} m/s.

It should be noted that recharge into the tailings was neglected in the above-described analysis. If significant recharge occurs, the rate of which will depend on the method used to cap the tailings, then the rate of advective mass transport through the tailings will be greater than that attributable solely to the regional hydraulic gradient. Thus, the performance of a facility with a pervious surround, which relies on a very low rate of advective mass transport through the tailings, is sensitive to recharge rate.

9. CONCLUSIONS

9.1 General Conclusions

It was concluded that the peak rate of solute release from an in-pit TMF will occur immediately after decommissioning. Solute release will continue to occur via diffusion, and the rate will tend to approach the rate of solute advection through the centre of the tailings.

It was concluded that a pervious surround enhances groundwater flow adjacent to the tailings relative to a natural surround. For this reason, a facility constructed with a pervious surround would produce a wider and more dilute plume than would the same facility constructed with a natural surround.

It was concluded that the relative merits and detriments of a pervious surround relative to a natural surround must be considered over some specified time-frame. For instance, it was shown that a pervious surround will likely cause a higher initial solute release than a natural surround. Given time, however, the diffusion-limited solute release from the pervious surround facility will drop below the combined diffusion/advection controlled solute release from a natural surround facility.

9.2 Evaluation of Physical Models

The physical models provided invaluable insight into the phenomenon affecting performance of a decommissioned in-pit tailings management facility. In general the data gathered from the experiments was relatively easy to interpret, and there were few significant gaps in understanding. The data proved to be extremely useful for the task of calibrating and testing the numerical model.

Data was lacking in two principal areas. First, there was inadequate data to know precisely the direction and magnitude of groundwater specific discharges within the surround, and within the DF host rock. Second, there was inadequate data with which to precisely determine final solute concentrations within the tailings. For this reason, it was not possible to attain accurate mass balances, especially for the DF experiments.

The steel drum used to occupy the centre of the tailings prevented groundwater flow and advective solute transport across the diameter of the pit. As a result, solute release from the tailings in all the experiments was controlled by diffusion. For this reason, the rate of solute release was similar in all experiments, and advection as a mechanism for solute release could not be evaluated. In the sense that the physical models did not include an important aspect of the system behaviour, it was concluded that models were over constrained by the use of the steel drum.

9.3 Evaluation of Numerical Model

It was concluded that FRAC3DVS was reasonably able to simulate the performance of the physical models. The numerical model provided fair estimates of solute release from the tailings at very early time and good estimates for the remainder of the simulation time. The early time discrepancies were attributed to the use of a too-coarse discretization within the outside few millimeters of the tailings. The numerical model provided fair estimates of plume concentrations in the surround and host rock, and the discrepancies were not so large as to impact the estimates of solute release from the tailings. It was hypothesized that the discrepancies between observed and simulated concentrations were due to the model's inability to simulate head losses at a right-angled turn at the base of the cylindrical tailings source. It was also suggested that the discrepancies were, in part, due to the inadequacy of the symmetrical three-component dispersivity tensor used to model hydrodynamic dispersion at the tailings/surround interface, or to limitations inherent in the macroscopic approach.

It was concluded that the parallel plate model of groundwater flow and advection/dispersion-based solute transport was not able to model accurately the channelled movement of groundwater and solute from the pit towards the down-gradient reservoir. Had all other problems been resolved, however, it is likely the model would have provided reasonable estimates of peak solute concentration within the fractures. It was concluded that the ability of the numerical model to simulate matrix diffusion could not be evaluated because this process was not characterized in the experiments.

It was concluded that numerical modelling using an EPM approach is likely a reasonable method of predicting performance of a full-scale facility. It was concluded, however, that adequate discretization of the diffusion surface at the outside edge of the tailings in three dimensions at the full-scale represents a significant numerical challenge. Finally, it was concluded that if an EPM approach is to be used, matrix diffusion should be evaluated using a dual-porosity formulation.

It was concluded that accurate modelling of diffusion at the outside edge of the tailings is numerically challenging using a traditional discretization scheme. Adequate discretization of this diffusion surface in three dimensions at the full-scale represents a significant challenge.

10. RECOMMENDATIONS

It is recommended that a physical model be constructed that better represents a ubiquitously fractured host rock, as well as the effects of matrix diffusion on plume development. In order to address this issue, the accuracy of the physical model mass balances needs to be improved. It is also recommended that numerical simulations be performed of the conducted experiments using both dual-porosity and discrete fracture representations.

It is recommended that efforts be made to determine more precisely why the numerical model was not able to better simulate plume development. It was postulated that the primary reason for the observed discrepancies was the numerical model's inability to simulate head losses at ninety degree turns. To verify this postulation it is recommended that hydraulic and tracer tests be performed to better characterise groundwater flow adjacent to the tailings, and that this data be used to further evaluate the numerical model's performance. It was also postulated that the three-component dispersivity tensor was not representative of solute mixing adjacent to the tailings. To address this issue, it is recommended that a more thorough literature review of dispersion be conducted, and that the experiments be simulated with numerical models based on alternate dispersion theory.

It is recommended that research be conducted to determine how geochemistry within the tailings and within the host rock would affect in-pit TMF performance. Specifically, it is recommended that research be conducted to determine how geochemical phenomenon affect

the concentration gradient at the tailings/surround interface.

It is recommended that further efforts be made to predict performance at the three northern Saskatchewan in-pit TMFs. Specifically, it is recommended that maximum plume concentrations and solute release from the tailings vs. time be predicted for the duration of the regulatory time frame. This predictive modelling should be carried out using a numerical model with an adequate discretization to accurately simulate early time effects, or with an alternate solution. To this end, it is recommended that analytical and semi-analytical models be developed and that these models be verified using the data collected in this study.

11. REFERENCES

Ben Balfadhel, M., 2000. Methods de Gestion et de Déclassement Des Résidues Miniers D'Uranium au Canada. Proceedings of the 53rd Canadian Geotechnical Conference, Montréal, Québec, 15-18 October, 2000.

Bear, J., 1972. Dynamics of Fluids in Porous Media. Dover Publications Inc. 764 p.

Cameco Corporation, 1994. Key Lake Operation - Deillmann In-Pit Tailings Management Facility, Environmental Impact Statement, February.

Cameco, 1998. Review of Hydrogeology in the Vicinity of the Rabbit Lake In-Pit TMF. March.

Churcher, P.L., P.R. French, J.C. Shaw, and LL. Schramm, 1991. Rock properties of berea sandstone, baker dolomite and indiana limestone. Society of Petroleum Engineers 21044 p. 431-445.

Cogema Resources Inc., 1997. McClean Lake Project JEB Tailings Management Facility, December.

Domenico, P.A. and F.W. Schwartz, 1990. Physical and Chemical Hydrogeology. John

Wiley and Sons 824 p.

Frost, S.E., 1998. Waste Management in the Uranium Mining Industry. The Uranium Institute 23rd Annual Symposium, Sept 10-11, London, p. 1-11.

Freeze, R.A. and J.A. Cherry, 1979. Groundwater. Prentice Hall 604 p.

Gillham, R.W. and J.A. Cherry, 1982. Contaminant migration in saturated unconsolidated geologic deposits. Geological Society of America Special Paper 189, 31-34.

Gillham, R.W., M.J.L. Robin, D.J. Dytynshyn and H.M. Johnston, 1984. Diffusion of nonreactive and reactive solutes through fine-grained barrier materials. Canadian Geotechnical Journal, 21, 541-550.

Gulf Minerals, 1981. Environmental Impact Statement Collins Bay B-Zone Development, Second Addendum, June.

Merriam-Webster Inc., 1990. Webster's Ninth New Collegiate Dictionary, Merriam-Webster 1564 p.

Misfeldt, G.A., J.I. Loi, G.M. Herasymuik and A.W. Clifton, 1999. Comparison of tailings containment strategies for in-pit and above-ground tailings management facilities. In

Proceedings of the 52nd Canadian Geotechnical Conference, October 25-27, Regina, Saskatchewan, p. 279-286.

Skagius, K. and I. Neretnieks, 1986. Porosities and diffusivities of some nonsorbing species in crystalline rocks. *Water Resources Research*, 22-3, 389-398.

Therrien, R. and E.A. Sudicky, 1996. Three-dimensional analysis of variably-saturated flow and solute transport in discretely-fractured porous media. *Journal of Contaminant Hydrology*, 23, 1-44.

Van Geel, P.J. and J.F. Sykes, 1997. The importance of fluid entrapment, saturation hysteresis and residual saturations on the distribution of a lighter-than-water non-aqueous phase liquid in a variably-saturated sand medium. *Journal of Contaminant Hydrology*, 25, 249-270.

Worthington, S.R.H., and D.C. Ford, 1997. Laboratory studies of the suitability of fluorescent dyes for use at Smithville, report for Smithville Phase IV Bedrock Remediation Program, 25p.

Zanini, L., K. Novakowski, and G. Bickerton, 1997. The Radial Diffusion Method Applied to Dolostone Samples from the Lockport Formation, Simthhville, Ontario. *National Water Research Institute* 97-137.

Appendix A - Ex-Situ Materials Testing Data

1) Sieve analysis of mortar sand

2) Permeameter tests

Sieve Analysis on Mortar Sand

Sieve #	Tare Mass (g)	Tare + Sample (g)	Sample (g)	Hole Size (mm)	%Passing
	318.76	598.61	279.85		100
8	108.56	108.75	0.19	2.38	99.93149944
16	106.35	107.85	1.5	1.19	99.39070556
40	129.19	129.23	66.65	0.425	75.36143058
70	119.9	268.26	148.36	0.212	21.87331002
200	127.71	185.03	57.32	0.075	1.207773011
<200	324.43	327.78	3.35		0
			277.37		

Grain Size Analysis - Mortar Sand

Constant Head Test

161

$$L_1 = L_2 = 76 \text{ mm}$$

$$A = 0.00454 \text{ m}^2$$

$$i = \text{average} \left(\frac{\Delta h_1}{L_1}, \frac{\Delta h_2}{L_2} \right)$$

$$K = \frac{Q}{iA}$$

FILTER GRAVEL

Δh_1	Δh_2
8	7
9	10
11	10
10	11
10	10

$$i_{\text{ave}} = \frac{9.6}{76} = 0.126$$

$$Q = 2020 \text{ ml/min}$$

$$K = \underline{\underline{0.06 \text{ m/s}}}$$

DENSELY COMPACTED MORTAR SAND

$$i_{\text{ave}} = \frac{40 \text{ mm}}{76 \text{ mm}} \quad Q = 80 \text{ ml/min} \quad K = \underline{\underline{5.6 \times 10^{-5} \text{ m/s}}}$$

LOOSELY COMPACTED MORTAR SAND

$$i_{\text{ave}} = \frac{230 \text{ mm}}{152 \text{ mm}} \quad Q = 130 \text{ ml/min} \quad K = \underline{\underline{3 \times 10^{-4} \text{ m/s}}}$$

SIL-CO-SIL 90 Falling Head Test.

162

$$K = \frac{r^2 L}{R^2 \Delta t} \ln \left(\frac{h_1}{h_2} \right)$$

$$h_1 = 1.348 \text{ m}$$

$$h_2 = 1.248 \text{ m}$$

$$\Delta t = 62 \text{ s}$$

$$L = 0.083 \text{ m}$$

$$k = 2.4 \times 10^{-7}$$

NOTE: FLOW RATE WAS INITIALLY HIGHER BUT DROPPED DUE TO CONSOLIDATION OF SILICA

$$h_1 = 1.348$$

$$h_2 = 1.248$$

$$\Delta t = 20 \text{ s}$$

$$L = 0.1 \text{ m}$$

$$k = 9 \times 10^{-7}$$

NOTE: SLURRY SAMPLE

Appendix B - In-Situ Materials Testing Data

- 1) EPM host rock porosity
- 2) EPM and DF host rock hydraulic testing
- 3) EPM host rock tracer testing
- 3) DF bottom fracture tracer testing
- 4) DF upper two fractures tracer testing

IN-SITU POROSITY - EPM HOST ROCK

$$n = 1 - \frac{\rho_b}{\rho_s}$$

$$\rho_b = \frac{\text{Mass of dried soil}}{\text{Volume of hole}}$$

Coordinates (cm, cm, cm) DEPTH	Mass of soil	Volume of hole	n
(200, 30, 0-10)	1223g	730ml	0.37
(675, 675, 0-10)	1109g	665ml	0.38
(35, 20, 0-10)	1235g	770ml	0.40
(60, 50, 40-50)	1346g	794ml	0.33

IN-SITU HYDRAULIC TESTING

EPM HOST ROCK

<u>MANOMETER</u>		Q (ml/min)
1A	DOWN	
0.898	0.851	157
0.696	0.650	125
0.504	0.450	100
0.305	0.250	84

DF HOST ROCK

UP	DOWN	Q (ml/min)
0.896	0.886	240
0.716	0.706	175
0.536	0.526	80

EPM Host Rock Tracer Testing

18B		20A	23A	26A
Injected 1 ml 10000 ppb into port 16A at 9:15				
05-17-1999 9:15	0.0	0.0	0.0	0.0
05-17-1999 11:15	0.8	0.6	66.1	1.3
05-17-1999 13:15	1.2	0.6	108.0	29.6
05-17-1999 15:15	0.7	209.6	139.5	62.8
05-17-1999 17:15	0.5	261.7	195.1	114.5
05-17-1999 19:35	1.1	268.7	249.1	135.1
05-17-1999 20:45	57.8	298.9	271.8	158.9
05-17-1999 21:54	197.7	299.0	289.1	179.0
05-17-1999 22:58	195.2	244.0	309.5	193.0
05-17-1999 23:55	80.2	189.5	288.0	188.7
05-18-1999 9:15	7.2	128.0	259.8	145.3
			230.8	117.6
			05-19-1999 0:00	86.8
			05-19-1999 16:00	24.3
			05-20-1999 7:30	4.1
			05-20-1999 8:30	1.9
			05-20-1999 9:40	0.5

Bottom Fracture Tracer Testing

	Port 5	Port 6	Port 7	Port 8	Port 9	Port 10	Port 11	Port 12
Injected 1ml 1000 ppb into port 2 at 9:25, i=14mm/2.3m, Q=40ml/min								
11-23-1999 9:30	0.0							
11-23-1999 9:35	0.0	0.0	0.0					
11-23-1999 9:40	0.0							
11-23-1999 9:45	0.0	0.0	0.0					
11-23-1999 9:50	0.0				0.0	22.1	0.4	
11-23-1999 9:55	0.1	0.0	0.0					
11-23-1999 10:00					0.0	9.3	0.0	
11-23-1999 10:05	0.0	0.0	0.0					
11-23-1999 10:10					0.0	2.5	0.0	
11-23-1999 10:20	0.0	0.0	0.0		0.0	0.6	0.0	
11-23-1999 10:35	0.0	0.0	0.0		0.0	0.2	0.0	
11-23-1999 11:15	0.0	0.0	0.0		0.0	0.0	0.0	
Injected 1ml 1000 ppb into port 3 at 11:25, i=14mm/2.3m, Q=40ml/min								
11-23-1999 11:29	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.9
11-23-1999 11:39	0.0	0.0	15.7	0.0	0.0	0.0	0.0	0.0
11-23-1999 11:50	0.0	0.0	21.6	0.2	0.0	0.0	1.9	0.0
11-23-1999 12:00	0.0	0.0	2.5	0.0	0.0	0.0	0.0	0.0
11-23-1999 12:13	0.0	0.0	0.7	0.0	0.0	0.0	0.0	0.0
11-23-1999 12:30	0.0	0.0	0.2	0.0	0.0	0.0	0.0	0.0
Injected 1ml 1000 ppb into port 4 at 14:05, i=14mm/2.3m, Q=40ml/min								
11-23-1999 14:07	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
11-23-1999 14:15	0.0	0.0	0.0	0.0	0.0	1.8	0.0	0.0
11-23-1999 14:23	0.0	12.1	0.0	0.0	0.0	0.2	0.0	0.2
11-23-1999 14:35	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.7
11-23-1999 14:46	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.3
11-23-1999 15:00	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.7
Injected 1ml 1000 ppb into port 1 at 15:13, i=14mm/2.3m, Q=30ml/min								
11-23-1999 15:15	7.2	0.2	0.0	0.0	0.0	0.0	0.0	0.2
11-23-1999 15:25	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
11-23-1999 15:41	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Injected 1ml 10000 ppb into port 2 at 10:10, i=8mm/2.3m, Q=22ml/min								
11-24-1999 10:12	0.0	0.2	0.0	0.0	0.0	0.0	0.0	0.0
11-24-1999 10:19	0.0	0.0	0.0	0.0	0.0	0.2	0.0	0.0
11-24-1999 10:30	0.0	0.1	0.0	0.2	0.0	0.0	0.0	0.0
11-24-1999 10:41	0.0	0.1	0.0	0.1	0.1	0.1	0.1	0.1
11-24-1999 10:52	0.0	0.1	0.1	0.1	0.2	0.2	0.2	0.2
11-24-1999 11:05	0.0	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Injected 1ml 10000 ppb into port 3 at 11:20, i=8mm/2.3m, Q=22ml/min								
11-24-1999 11:22	0.1	0.2	0.2	0.2	0.3	0.1	0.1	0.3
11-24-1999 11:29	0.1	0.1	0.1	0.4	0.2	0.2	0.2	0.2
11-24-1999 11:42	0.1	0.1	15.5	1.1	0.2	0.3	0.2	0.1
11-24-1999 11:53	0.1	0.1	34.4	0.9	0.4	0.1	0.1	0.1
11-24-1999 12:05	0.0	0.1	13.1	0.5	0.1	0.1	0.1	0.1
11-24-1999 12:20			3.6	0.3	0.3	0.2	0.2	0.2
11-24-1999 12:55			1.2			0.3	0.2	0.2
Injected 10ml 1000 ppb into port 2 at 13:03, i=8mm/2.3m, Q=22ml/min								
11-24-1999 13:04	0.1	0.1	0.7	0.2	0.2	0.2	0.2	0.2
11-24-1999 13:12	0.2	0.1	0.1	0.2	0.2	0.2	0.2	0.3
11-24-1999 13:20	0.4	0.2	0.4	0.2	0.2	0.2	0.2	0.2
11-24-1999 13:30	0.4	0.2	0.5	0.2	0.2	7.4	0.3	0.2
11-24-1999 13:37	0.4	0.2	0.2	0.2	0.2	187.1	5.8	0.6
11-24-1999 13:45					0.2	270.8	14.0	3.5
11-24-1999 13:52					0.6	123.3	11.4	2.1
11-24-1999 14:05					0.3	26.1	3.1	0.5
Injected 10ml 1000 ppb into port 4 at 14:13, i=8mm/2.3m, Q=22ml/min								
11-24-1999 14:15	0.2	0.3	0.4	0.3	0.2	11.9	0.9	0.6
11-24-1999 14:22	0.3	0.2	0.4	1.9	0.2	7.9	1.0	0.4
11-24-1999 14:30	0.3	0.3	0.3	373.7	0.2	3.8	0.7	1.1
11-24-1999 14:39	0.3	0.3	0.3	168.4	0.3	5.6	0.7	0.9
11-24-1999 14:49	0.3	0.3	0.3	25.3	0.3	4.3	0.6	119.3
11-24-1999 15:00	0.2	1.1	0.4	9.5	0.4	2.5	0.5	140.3
11-24-1999 15:10	0.2	1.1	0.4	4.8	0.4	2.5	0.5	40.1

Upper 2 Fractures Tracer Testing

	20A	23A	23B	28A	28B
Injected 0.5 ml 10000 ppb into port 18A at 17:33, i=5mm/2.3m, Q					
03-29-2000 17:34		0.5			
03-29-2000 17:35		0.2			
03-29-2000 17:37		0.0			
03-29-2000 17:38				0.1	
03-29-2000 17:39		0.1			
03-29-2000 17:40				0.1	
03-29-2000 17:41		0.1			
03-29-2000 17:44				3.1	
03-29-2000 17:46				23.7	
03-29-2000 17:48				34.5	
03-29-2000 17:52				1.0	
Injected 0.5 ml 10000 ppb into port 16A at 17:53, i=5mm/2.3m, Q					
03-29-2000 17:55	0.2				
03-29-2000 17:57	0.3	0.2		0.1	
03-29-2000 17:59	44.6	0.4		6.6	
3-29-00 18:01:30	98.0	10.3		6.1	
03-29-2000 18:04	41.8	50.7		4.3	
3-29-00 18:06:30	18.8	61.1		7.0	
3-29-00 18:08:30	9.9	48.0		7.2	
03-29-2000 18:11	4.5	33.0		26.7	
03-29-2000 18:14	3.1	16.6		67.8	
03-29-2000 18:17	5.2	9.7		66.7	
03-29-2000 18:20				46.4	
03-29-2000 18:23				24.5	
Injected 0.5 ml 10000 ppb into port 18B at 18:22, i=5mm/2.3m, Q					
03-29-2000 18:24			1.5		0.4
03-29-2000 18:26			0.9		0.2
03-29-2000 18:28			28.9		0.3
03-29-2000 18:30			48.3		0.6
03-29-2000 18:32			36.5		2.4
03-29-2000 18:34			20.1		21.9
03-29-2000 18:36			9.0		54.7
03-29-2000 18:38			4.9		82.3
03-29-2000 18:40			3.2		59.5
03-29-2000 18:42					35.7
03-29-2000 18:44					21.0

Appendix C -Early Time Concentration Data

1) DF Gravel(1)

2) DF Sand(1)

3) DF Gravel(2)

Early Time Data - DF Gravel(1)

170

	17A		17B		18A		18B		22A
01-07-2000 12:17	1.4	01-07-2000 12:19	1.3	01-07-2000 12:22	1.2	01-07-2000 12:23	2.2	01-07-2000 12:27	5.4
01-07-2000 12:20	0.9	01-07-2000 12:21	1	01-07-2000 12:25	1.7	01-07-2000 12:25	2.7	01-07-2000 12:31	2.1
01-07-2000 12:23	0.9	01-07-2000 12:24	1.1	01-07-2000 12:29	2.9	01-07-2000 12:29	2.9	01-07-2000 12:44	16.2
01-07-2000 12:25	1.1	01-07-2000 12:24	10.3	01-07-2000 12:33	3.2	01-07-2000 12:33	2.3	01-07-2000 12:49	23.2
01-07-2000 12:27	1	01-07-2000 12:26	1.5	01-07-2000 12:39	5.1	01-07-2000 12:45	3.7	01-07-2000 12:54	29.7
01-07-2000 12:29	1	01-07-2000 12:26	16.3	01-07-2000 12:44	6.5	01-07-2000 12:50	5.8	01-07-2000 12:59	34.4
01-07-2000 12:30	1.6	01-07-2000 12:29	2.1	01-07-2000 12:49	7.5	01-07-2000 12:55	8.3	01-07-2000 13:04	36.5
01-07-2000 12:33	1	01-07-2000 12:30	3.6	01-07-2000 12:54	8.4	01-07-2000 13:01	11	01-07-2000 13:09	35.7
01-07-2000 12:35	0.3	01-07-2000 12:32	6.7	01-07-2000 12:59	7.8	01-07-2000 13:04	12.1	01-07-2000 13:19	32.8
01-07-2000 12:37	1.3	01-07-2000 12:41	28.7	01-07-2000 13:04	7.2	01-07-2000 13:09	12.6	01-07-2000 13:24	31.2
01-07-2000 12:39	1.3	01-07-2000 12:43	33.7	01-07-2000 13:09	7	01-07-2000 13:14	12.7	01-07-2000 13:34	28.9
01-07-2000 12:42	1.6	01-07-2000 12:48	39.5	01-07-2000 13:14	7.6	01-07-2000 13:20	12.5	01-07-2000 13:44	26.9
01-07-2000 12:47	1.5	01-07-2000 12:53	45.3	01-07-2000 13:20	6.9	01-07-2000 13:26	13.3	01-07-2000 13:54	25
01-07-2000 12:52	2.2	01-07-2000 12:58	45.6	01-07-2000 13:26	6.3	01-07-2000 13:31	13.5	01-07-2000 14:04	21.7
01-07-2000 12:57	4.1	01-07-2000 13:03	48.7	01-07-2000 13:31	6.7	01-07-2000 13:36	15.3	01-07-2000 14:14	19.3
01-07-2000 13:02	3.9	01-07-2000 13:07	44.4	01-07-2000 13:36	7.8	01-07-2000 13:47	16.5	01-07-2000 14:26	16.9
01-07-2000 13:07	3.6	01-07-2000 13:13	39.3	01-07-2000 13:47	6.5	01-07-2000 13:57	18.5	01-07-2000 14:34	15.4
01-07-2000 13:13	4.2	01-07-2000 13:18	39.1	01-07-2000 13:57	5.8	01-07-2000 14:08	18.8	01-07-2000 14:44	15.1
01-07-2000 13:18	4.6	01-07-2000 13:23	36.8	01-07-2000 14:08	5.8	01-07-2000 14:18	19.5	01-07-2000 14:58	14.5
01-07-2000 13:23	4.7	01-07-2000 13:28	35.1	01-07-2000 14:18	5.5	01-07-2000 14:28	20.3		
01-07-2000 13:28	4.2	01-07-2000 13:33	34.7	01-07-2000 14:28	5.5	01-07-2000 14:39	19		
01-07-2000 13:33	3.5	01-07-2000 13:43	30.5	01-07-2000 14:39	5.4	01-07-2000 14:49	20.5		
01-07-2000 13:43	2.9	01-07-2000 13:53	26.9	01-07-2000 14:49	6.1	01-07-2000 14:57	20.8		
01-07-2000 13:53	3.2	01-07-2000 14:05	24	01-07-2000 14:57	6				
01-07-2000 14:05	4	01-07-2000 14:15	21.5						
01-07-2000 14:15	4.1	01-07-2000 14:25	18.9						
01-07-2000 14:25	3.7	01-07-2000 14:35	17.7						
01-07-2000 14:35	3.2								

	22B		23A		23B		28A		28B
01-07-2000 12:27	1.9	01-07-2000 12:31	1.5	01-07-2000 12:32	2.2	01-07-2000 12:23	1.3	01-07-2000 12:21	2.6
01-07-2000 12:31	3.9	01-07-2000 12:33	1.9	01-07-2000 12:36	2	01-07-2000 12:25	1.3	01-07-2000 12:24	1.7
01-07-2000 12:44	2	01-07-2000 12:35	2.4	01-07-2000 12:38	2	01-07-2000 12:27	1.2	01-07-2000 12:26	1.6
01-07-2000 12:49	2.3	01-07-2000 12:37	2.9	01-07-2000 12:40	2.1	01-07-2000 12:29	1.2	01-07-2000 12:28	1.8
01-07-2000 12:54	3.3	01-07-2000 12:39	3.4	01-07-2000 12:42	2.4	01-07-2000 12:31	1.2	01-07-2000 12:30	2
01-07-2000 12:59	4.2	01-07-2000 12:41	4.3	01-07-2000 12:47	5.1	01-07-2000 12:34	1.2	01-07-2000 12:33	2.2
01-07-2000 13:04	4.8	01-07-2000 12:46	5.1	01-07-2000 12:52	8.4	01-07-2000 12:37	1.4	01-07-2000 12:35	2.3
01-07-2000 13:09	4.7	01-07-2000 12:51	6.4	01-07-2000 13:00	12.8	01-07-2000 12:40	1.6	01-07-2000 12:38	2.1
01-07-2000 13:19	5.2	01-07-2000 13:00	7.5	01-07-2000 13:05	12.7	01-07-2000 12:42	1.8	01-07-2000 12:41	2.3
01-07-2000 13:24	5.4	01-07-2000 13:05	7.3	01-07-2000 13:10	14.5	01-07-2000 12:46	2.2	01-07-2000 12:46	2.2
01-07-2000 13:34	5.4	01-07-2000 13:10	7.6	01-07-2000 13:20	14	01-07-2000 12:51	2.8	01-07-2000 12:53	2.5
01-07-2000 13:44	5.7	01-07-2000 13:20	7.3	01-07-2000 13:25	14.2	01-07-2000 12:56	3.7	01-07-2000 12:58	3.6
01-07-2000 13:54	4.4	01-07-2000 13:25	7.1	01-07-2000 13:34	2	01-07-2000 13:02	5.1	01-07-2000 13:02	5.6
01-07-2000 14:04	4.1	01-07-2000 13:35	7.6	01-07-2000 13:35	14.3	01-07-2000 13:07	5.8	01-07-2000 13:07	7.3
01-07-2000 14:14	4.7	01-07-2000 13:45	7.2	01-07-2000 13:45	13.7	01-07-2000 13:12	6.6	01-07-2000 13:12	9.7
01-07-2000 14:26	5	01-07-2000 13:55	7.4	01-07-2000 13:55	14.5	01-07-2000 13:17	6.2	01-07-2000 13:17	10.9
01-07-2000 14:34	5	01-07-2000 14:05	6.4	01-07-2000 14:05	13.6	01-07-2000 13:23	6.6	01-07-2000 13:23	12.5
01-07-2000 14:44	4.8	01-07-2000 14:15	6.8	01-07-2000 14:15	14.3	01-07-2000 13:29	6.8	01-07-2000 13:29	13.8
01-07-2000 14:58	4	01-07-2000 14:27	6.6	01-07-2000 14:27	12.9	01-07-2000 13:35	6.3	01-07-2000 13:35	13.6
		01-07-2000 14:35	6.6	01-07-2000 14:35	12.7	01-07-2000 13:45	6.3	01-07-2000 13:45	13.4
		01-07-2000 14:45	6.8	01-07-2000 14:45	13.2	01-07-2000 13:55	6.1	01-07-2000 13:55	14.8
		01-07-2000 14:59	7.2	01-07-2000 14:59	14.4	01-07-2000 14:05	6.6	01-07-2000 14:05	14.9
						01-07-2000 14:16	6.3	01-07-2000 14:16	16.9
						01-07-2000 14:28	6.3	01-07-2000 14:28	17.4
						01-07-2000 14:36	6.2	01-07-2000 14:36	18.1
						01-07-2000 14:46	6.7	01-07-2000 14:46	17.8
						01-07-2000 15:01	7.1	01-07-2000 15:01	17.2

Early Time Data - DF Sand(1)

	9A	13A	13B	17A	17B	18A	18B	22A	22B	23A	23B	28A
01-24-2000 12:25				1.4	0.2	0.9	1.3	1	0.8	1.3	0.4	0.2
01-24-2000 12:30				0.6	0.4	0.1	0.3	0.6	0.3	0.2	0.3	0.1
01-24-2000 12:35				0.9	0.2	0.1	0.3	0.1	0.1	0.2	0.3	0.1
01-24-2000 12:40				0.4	0.1	0.1	0.3	0.1	0.1	0.2	0.3	0.2
01-24-2000 12:45				0.2	0.1	0	0.2	0.3	0.5	0.2	0.3	1.5
01-24-2000 12:50				0.1	0	0.1	0.2	0.2	0.2	0.2	0.4	0.3
01-24-2000 13:00	23.0	1.8	2.3	0.1	0.1	0	0.2	0.3	0.4	0.3	0.3	0.3
01-24-2000 13:10	19.2	1.4	3.8	0.1	0.1	0.1	0.2	0.2	0.3	0.3	0.4	0.2
01-24-2000 13:20	19.2	1.3	6.8	0.1	0.1	0.1	0.2	0.3	0.3	0.4	0.3	0.6

Early Time Data - DF Gravel(2)

	17A	17B	18A	18B	22A	22B	23A	23B	28A	28B
03-31-2000 13:10	0.4	0.9	0.6	0.7	0.5	0.3	0.4	0.5	0.7	0.6
01-13-1900 13:15	0.4	3.3	0.7	1.6	0.5	0.6	0.4	0.6	0.8	0.6
01-13-1900 13:20	5.9	1.6	3.7	17.6	0.6	0.6	0.4	0.7	0.5	1
01-13-1900 13:25	4.5	1.3	10.3	34.9	0.8	0.6	1	22.4	0.5	0.4
01-13-1900 13:30	16.5	1.6	16.3	43.1	1.8	6.9	4.6	40.2	0.5	4
01-13-1900 13:35	18	2.1	18.9	51.6	6.9	13.6	11.6	46.1	3	18.1
01-13-1900 13:40	19.1	2.6	17.9	53.3	15.6	15	18.5	51.1	8.7	25.1
01-13-1900 13:45	19.3	3.3	16.9	55.5	13.2	17.5	24.1	61	17	44.3
01-13-1900 13:55	22.3	5.6	20.7	57.8	11.1	17.8	26.4	60.2	20.8	49.9
01-13-1900 14:05	26.2	8.3	14.6	52.2	9.2	21.3	22.8	56.9	18.8	50.3
01-14-1900 14:15	33.3	10.2	14.6	46.4	11.6	26.9	20.5	52	16.6	49.3
01-14-1900 14:35	38.1	14.9	10.6	42.4	16.7	32.6	16.3	41.7	14.5	42.2

Appendix D -Monitoring Round Data

- 1) EPM Gravel(1) - Heads
- 2) EPM Gravel(1) - Concentrations and flow rates
- 3) EPM Sand(1) - Heads
- 4) EPM Sand(1) - Concentrations and flow rates
- 5) EPM Gravel(2) - Heads
- 6) EPM Gravel(2) - Concentrations and flow rates
- 7) EPM Sand(2) - Heads
- 8) EPM Sand(2) - Concentrations and flow rates
- 9) DF Gravel(1) Concentrations and flow rates
- 10) DF Sand(1) Concentrations and flow rates
- 11) DF Gravel(2) Concentrations and flow rates

EPM Gravel(1) Heads

Manometer	UP	1A	2A	2B	3A	3B	4A	4B	5A	5B
x coordinate		0.270	0.235	0.235	0.675	0.675	1.115	1.115	1.125	1.125
y coordinate		0.600	0.000	0.000	0.600	0.600	0.000	0.000	0.300	0.300
z coordinate		0.450	0.600	0.300	0.600	0.300	0.600	0.300	0.600	0.300
Date	water level below 1 m datum									
06-08-1999 22:15	0.094	0	0.105	0.102	0.108	0.109	0.107	0.115	0.112	0.115
06-10-1999 16:15	0.092	0.101	0.115	0.102	0.108	0.107	0.106	0.114	0.111	0.115
06-11-1999 14:10	0.093	0	0.115	0.103	0.109	0.109	0.116	0.116	0.113	0.117
06-14-1999 11:20	0.093	0.107	0.116	0.11	0.114	0.114	0.116	0.119	0.117	0.121
06-15-1999 8:20	0.091	0.102	0.115	0.105	0.111	0.111	0.1155	0.117	0.114	0.118
06-18-1999 9:45	0.089	0.1	0.105	0.104	0.107	0.108	0.105	0.114	0.111	0.115
06-21-1999 8:40	0.089	0.103	0.109	0.102	0.111	0.112	0.111	0.117	0.114	0.118
average hydraulic head	0.908	0.898	0.889	0.896	0.890	0.890	0.889	0.884	0.887	0.883

Manometer	6A	7A	7B	8A	9A	10A	11A	12A	DOWN
x coordinate	1.325	1.325	1.325	1.725	1.725	2.125	0.040	2.260	
y coordinate	0.600	0.000	0.000	0.600	0.000	0.600	-0.625	-0.660	
z coordinate	0.450	0.600	0.300	0.450	0.450	0.450	0.450	0.450	
Date									
06-08-1999 22:15	0.121	0.117	0.12	0.133	0.132	0.144	0.099	0.15	0.15
06-10-1999 16:15	0.121	0.117	0.12	0.133	0.133	0.144	0.098	0.149	0.15
06-11-1999 14:10	0.122	0.118	0.12	0.133	0.133	0.144	0.1	0.149	0.15
06-14-1999 11:20	0.124	0.12	0.123	0.135	0.134	0.145	0.108	0.15	0.15
06-15-1999 8:20	0.122	0.119	0.122	0.134	0.134	0.144	0.104	0.15	0.15
06-18-1999 9:45	0.12	0.107	0.119	0.133	0.132	0.144	0.1	0.15	0.15
06-21-1999 8:40	0.122	0.119	0.12	0.133	0.133	0.144	0.105	0.149	0.149
average hydraulic head	0.878	0.883	0.879	0.867	0.867	0.856	0.898	0.850	0.850

EPM Gravel(1) Concentrations and Flow Rates

Sample port x coordinate y coordinate z coordinate	1A 0.242 0.250 0.600	1B 0.242 0.250 0.300	2A 0.294 0.220 0.600	3A 0.425 0.600 0.600	4A 0.456 0.127 0.460	6A 0.675 0.440 0.675	6B 0.675 0.440 0.460	7A 0.675 0.000 0.460	8A 0.894 0.127 0.460	8B 0.894 0.127 0.300	9A 1.052 0.218 0.600	10A 1.060 0.223 0.600
Date	Time (seconds)	Time (days)	Concentration (ppb)	Concentration (ppb)	Concentration (ppb)	Concentration (ppb)	Concentration (ppb)	Concentration (ppb)	Concentration (ppb)	Concentration (ppb)	Concentration (ppb)	Concentration (ppb)
06-08-1999 13:00	1800	0.02	352.7	2.2	261.3	173.6	309.0	265.9	110.8	0.7	175.1	83.4
06-08-1999 13:30	7500	0.09	310.5	1.7	440.6	151.8	220.6	437.3	352.4	1.3	182.9	135.7
06-08-1999 15:05	12000	0.14	342.8	2.4	599.6	237.9	266.6	611.6	432.0	2.3	309.9	276.1
06-08-1999 16:20	16200	0.19	94.5	4.1	450.0	243.7	364.3	736.3	557.8	7.6	375.0	342.6
06-08-1999 17:30	20700	0.24	9.7	1.7	306.0	239.4	103.9	719.4	655.3	7.6	481.6	425.1
06-08-1999 18:45	24300	0.28	3.8	1.4	83.2	127.4	34.6	352.5	398.0	1.8	404.8	319.9
06-08-1999 19:45	29700	0.34	2.5	1.1	37.0	54.6	14.1	163.7	216.9	1.8	222.9	150.3
06-08-1999 21:15	33300	0.39	1.0	0.2	25.8	35.5	8.1	97.4	131.5	2.3	148.8	84.6
06-08-1999 22:15	36900	0.43	0.7	0.2	22.3	33.9	6.6	105.1	121.3	0.9	127.3	72.3
06-08-1999 23:15	65700	0.76	-0.2	-0.2	16.7	36.8	4.7	86.0	104.2	88.1	108.0	63.8
06-08-1999 7:15	72600	0.84	0.6	0.1	15.8	34.4	4.3	75.5	87.9	120.8	114.0	58.5
06-09-1999 9:10	78600	0.91	0.1	0.0	15.0	31.7	6.7	78.4	87.7	92.8	115.5	61.1
06-09-1999 10:50	87600	1.01	0.9	0.2	15.2	33.3	4.9	78.0	90.7	193.3	113.9	61.2
06-09-1999 13:20	89000	1.15	0.4	0.2	11.0	26.3	4.8	53.9	70.8	230.1	94.5	55.9
06-09-1999 16:30	108300	1.25	0.0	0.0	11.3	25.3	5.0	55.5	68.2	70.3	98.7	53.7
06-09-1999 19:05	114300	1.32	0.2	0.0	10.8	25.2	4.3	52.1	67.7	158.2	91.8	52.7
06-09-1999 20:45	121500	1.41	0.0	0.0	10.4	25.3	4.3	56.2	63.4	107.7	90.4	51.1
06-09-1999 22:45	157200	1.82	0.2	0.0	9.7	27.5	4.9	51.8	60.9	43.8	87.7	48.3
06-10-1999 8:40	174600	2.02	2.5	0.3	7.7	23.6	4.8	51.9	60.5	30.6	89.8	43.8
06-10-1999 13:30	184500	2.14	0.9	0.4	9.1	26.2	4.2	47.1	56.0	23.1	82.0	43.3
06-10-1999 16:15	205800	2.38	1.9	0.3	10.8	26.4	4.6	46.6	59.5	19.9	87.3	44.0
06-10-1999 22:10	243000	2.81	3.6	0.6	9.6	28.1	4.0	42.0	57.2	16.5	79.0	43.8
06-11-1999 6:30	263400	3.05	0.8	0.9	10.4	27.9	4.6	43.7	58.9	16.1	82.7	43.0
06-11-1999 14:10	351000	4.06	1.0	0.2	11.3	38.3	3.7	61.3	72.0	18.2	91.9	55.1
06-12-1999 14:30	446400	5.17	6.5	0.5	10.8	44.0	9.9	58.2	78.4	14.0	92.8	54.2
06-13-1999 17:00	512400	5.93	34.6	3.7	7.4	29.6	2.3	46.3	57.5	8.8	76.0	38.0
06-14-1999 11:20	588000	6.81	-0.5	0.7	5.8	23.2	2.1	36.0	47.7	17.9	67.1	33.9
06-15-1999 8:20	674400	7.81	0.8	0.0	6.4	16.5	4.2	30.8	39.9	15.0	52.9	25.7
06-16-1999 8:20	765600	8.86	0.9	0.2	6.8	22.4	2.5	23.5	46.6	10.4	54.2	30.1
06-17-1999 9:40	852300	9.86	0.6	2.0	5.1	17.9	2.4	27.7	36.2	8.4	46.2	23.6
06-18-1999 9:45	1107600	12.82	2.2	0.6	4.8	16.7	2.2	23.7	34.8	6.9	45.9	24.0

EPM Gravel(1) Concentrations and Flow Rates

Sample port
x coordinate
y coordinate
z coordinate

Date	Time (seconds)	Time (days)	Concentration (ppb)	11A	12A	13A	13B	13C	14A	15A	16A	17A	18A	18B	18C
06-08-1999 13:00	1800	0.02	165.8	9.9	163.0	23.0	0.9	0.9	2.3	5.5	0.7	0.6	0.7	0.6	0.6
06-08-1999 13:30	7500	0.09	150.3	63.5	172.9	164.7	1.2	0.8	3.9	15.6	0.7	0.7	0.7	0.7	0.6
06-08-1999 15:05	12000	0.14	228.2	204.5	217.0	501.5	1.0	1.1	130.6	154.5	1.0	0.4	0.8	0.8	0.6
06-08-1999 16:20	16200	0.19	337.2	377.1	246.8	625.0	3.3	1.4	210.8	267.1	3.1	0.8	0.7	0.6	0.6
06-08-1999 17:30	20700	0.24	377.1	399.1	321.1	785.5	3.4	1.6	376.5	442.5	4.4	0.7	0.7	0.6	0.6
06-08-1999 18:45	24300	0.28	363.4	483.1	341.6	791.2	24.6	1.8	369.6	576.1	4.2	1.3	8.6	9.1	9.1
06-08-1999 19:45	29700	0.34	197.4	172.8	359.8	412.3	93.2	1.6	371.7	540.9	4.7	175.8	175.8	58.3	182.4
06-08-1999 21:15	33300	0.39	114.4	69.5	283.9	225.3	457.2	1.5	167.9	509.7	3.9	146.5	166.0	166.0	458.7
06-08-1999 22:15	36900	0.43	104.4	65.0	241.5	0.2	518.1	0.9	110.6	426.7	25.7	225.1	273.9	641.5	641.5
06-08-1999 23:15	65700	0.76	90.6	46.9	217.1	140.0	194.0	173.9	71.3	272.2	64.9	235.0	314.6	415.0	415.0
06-09-1999 7:15	72600	0.84	83.3	44.8	198.5	137.8	105.2	221.5	63.8	239.4	42.4	215.2	251.5	361.1	361.1
06-09-1999 9:10	78600	0.91	84.3	47.5	203.0	138.9	100.8	202.8	71.9	249.4	47.9	184.4	263.4	320.3	320.3
06-09-1999 10:50	87600	1.01	82.7	47.1	216.2	132.5	103.5	93.4	65.5	241.8	45.7	212.6	265.8	314.3	314.3
06-09-1999 13:20	99000	1.15	73.8	40.7	220.7	115.2	83.0	24.0	25.7	225.8	31.4	187.4	244.1	262.7	262.7
06-09-1999 16:30	108300	1.25	75.0	37.8	219.1	111.5	83.4	15.8	54.0	231.8	33.6	194.6	248.9	263.8	263.8
06-09-1999 19:05	114300	1.32	72.4	37.7	217.3	103.6	78.4	13.8	53.4	253.3	33.3	200.4	242.1	261.2	261.2
06-09-1999 20:45	121500	1.41	76.9	35.6	223.1	106.2	75.9	11.5	49.9	239.2	30.3	199.8	239.8	224.6	224.6
06-09-1999 22:45	157200	1.82	76.6	32.9	50.0	89.1	64.7	8.0	47.3	237.5	30.5	198.3	228.1	179.0	179.0
06-10-1999 8:40	174600	2.02	80.9	33.5	236.9	95.8	60.5	6.6	46.0	217.3	22.1	176.5	233.2	171.7	171.7
06-10-1999 13:30	184500	2.14	71.8	31.8	242.6	89.6	58.6	8.0	44.2	204.9	30.0	199.9	222.3	163.9	163.9
06-10-1999 22:10	205800	2.38	77.4	31.7	264.4	94.6	57.5	7.9	45.0	222.2	23.3	221.0	238.8	179.8	179.8
06-11-1999 8:30	243000	2.81	77.3	29.5	256.1	90.5	55.5	6.7	44.4	193.8	25.1	230.6	240.2	172.0	172.0
06-11-1999 14:10	263400	3.05	77.3	30.4	245.0	94.7	55.6	7.5	42.2	181.1	24.5	234.0	252.8	164.7	164.7
06-12-1999 14:30	351000	4.06	89.8	45.1	239.8	113.5	68.7	6.5	56.9	167.0	33.2	231.7	258.7	183.6	183.6
06-13-1999 17:00	446400	5.17	86.3	41.1	193.0	112.7	68.6	5.5	56.4	140.8	29.0	186.6	239.4	214.6	214.6
06-14-1999 11:20	512400	5.93	68.5	29.9	161.4	90.8	53.2	3.3	39.8	109.5	22.9	151.3	201.3	181.4	181.4
06-15-1999 8:20	588000	6.81	65.6	25.0	162.6	72.1	44.2	6.3	33.1	105.3	18.9	151.8	172.5	148.9	148.9
06-16-1999 8:20	674400	7.81	34.5	18.3	203.0	67.9	36.5	4.1	27.6	143.8	16.5	83.7	93.2	113.2	113.2
06-17-1999 8:40	765600	8.86	51.8	21.5	132.2	63.3	40.8	2.3	29.3	95.1	16.0	137.9	141.5	136.4	136.4
06-18-1999 8:45	852300	9.86	44.8	17.0	109.0	52.8	34.2	1.8	24.5	59.8	18.7	106.4	133.6	110.5	110.5
06-21-1999 8:40	1107600	12.82	45.2	16.5	103.7	51.8	33.7	1.8	24.4	65.9	12.5	95.3	130.6	91.3	91.3

EPM Gravel(1) Concentrations and Flow Rates

Sample port	Time														
x coordinate	Time (seconds)		Time (days)		Concentration (ppb)										
y coordinate	0														
z coordinate															
	Date	18D	18E	19A	19B	20A	20B	21A	22A	23A	24A	25A	26A		
	06-08-1999 13:00	1800	0.02	0.4	0.4	0.7	0.4	0.7	0.5	0.5	0.7	0.6	0.6	0.6	
	06-08-1999 13:30	7500	0.09	0.4	0.4	0.7	0.4	0.7	0.5	0.5	0.7	0.6	0.6	0.6	
	06-08-1999 15:05	12000	0.14	0.4	0.4	0.7	0.4	0.7	0.5	0.7	0.6	0.9	0.6	0.6	
	06-08-1999 16:20	16200	0.19	0.4	0.4	0.7	0.4	0.7	0.5	0.7	0.6	0.9	0.6	0.6	
	06-08-1999 17:30	20700	0.24	0.4	0.4	0.7	0.4	0.7	0.5	0.7	0.6	0.9	0.6	0.6	
	06-08-1999 18:45	24300	0.28	2.8	0.8	0.8	0.8	1.4	0.8	0.9	0.6	0.7	0.6	0.6	
	06-08-1999 19:45	29700	0.34	64.8	1.2	1.0	0.9	0.7	0.7	0.8	0.6	0.7	0.6	0.6	
	06-08-1999 21:15	33300	0.39	354.4	1.1	0.2	0.0	0.4	0.0	0.9	0.6	0.7	0.6	0.6	
	06-08-1999 22:15	36900	0.43	436.9	1.4	0.0	0.0	0.4	0.1	0.9	0.6	0.7	0.6	0.6	
	06-08-1999 23:15	65700	0.76	168.8	0.3	370.5	537.7	494.8	438.5	281.5	0.0	39.4	0.6	0.6	
	06-09-1999 7:15	72600	0.84	142.2	4.1	198.8	612.7	438.0	267.0	319.0	12.0	127.8	2.5	1.0	0.6
	06-09-1999 9:10	78600	0.91	133.9	10.8	104.2	328.3	326.9	182.7	106.7	19.3	256.6	37.9	0.1	0.3
	06-09-1999 10:50	87600	1.01	131.3	6.1	68.0	183.0	281.6	141.6	93.5	42.2	383.3	10.3	1.6	10.3
	06-09-1999 13:20	99000	1.15	112.2	64.3	54.2	129.4	244.2	119.0	70.4	214.2	324.8	9.7	79.2	155.4
	06-09-1999 16:30	108300	1.25	103.3	210.2	57.4	115.6	243.8	113.5	63.4	202.4	253.3	8.7	209.0	317.3
	06-09-1999 20:45	114300	1.32	102.3	285.7	62.6	111.4	241.8	110.3	65.6	100.0	234.0	6.6	251.1	358.2
	06-09-1999 22:45	121500	1.41	98.1	291.2	58.4	101.2	235.6	108.8	63.5	47.5	207.9	8.3	159.1	349.5
	06-10-1999 8:40	157200	1.82	89.4	98.8	55.1	93.6	256.3	90.9	63.8	23.3	219.4	161.0	62.9	219.3
	06-10-1999 13:30	174600	2.02	88.4	75.9	52.1	82.9	261.5	91.0	59.6	21.7	229.3	52.8	50.1	224.5
	06-10-1999 16:15	184500	2.14	75.4	53.9	51.0	81.4	232.8	85.4	59.3	22.4	234.2	25.9	46.7	225.9
	06-10-1999 22:10	205800	2.38	75.5	49.7	51.1	81.6	271.7	80.4	60.0	22.3	269.4	15.4	46.2	264.8
	06-11-1999 8:30	243000	2.81	73.1	40.0	47.9	76.8	276.3	82.5	60.8	21.9	240.3	10.0	49.1	267.5
	06-11-1999 14:10	263400	3.05	72.2	38.2	48.2	74.1	262.7	84.2	57.0	20.9	250.9	12.0	47.4	238.1
	06-12-1999 14:30	351000	4.06	91.4	45.6	64.2	93.5	264.0	92.5	78.2	30.2	229.4	11.3	66.5	261.3
	06-13-1999 17:00	446400	5.17	84.1	42.8	58.2	87.4	231.3	89.8	77.8	29.5	191.9	8.0	63.6	219.7
	06-14-1999 11:20	512400	5.93	62.7	25.9	39.0	68.1	175.8	68.7	56.8	19.8	138.8	5.3	45.1	165.1
	06-15-1999 8:20	588000	6.81	61.9	29.5	40.2	80.4	171.8	66.9	49.5	21.4	87.7	5.8	46.6	212.6
	06-16-1999 8:20	674400	7.81	49.6	34.0	29.1	60.3	72.0	53.4	28.2	119.7	83.7	6.8	47.1	67.9
	06-17-1999 9:40	765600	8.86	52.6	26.8	29.8	53.6	144.9	54.1	34.3	17.5	126.7	5.1	30.7	106.1
	06-18-1999 9:45	852300	9.86	45.2	27.3	23.8	45.7	116.5	47.0	32.1	16.7	101.8	3.9	32.7	110.1
	06-21-1999 8:40	1107600	12.82	39.7	18.4	23.1	42.2	123.8	42.0	34.8	11.4	96.1	1.7	25.3	108.5

EPM Gravel(1) Concentrations and Flow Rates

Sample port	26B	27A	28A	Reservoir				
x coordinate	2.025	2.025	2.225	2.225				
y coordinate	0.000	-0.200	0.000	0.000				
z coordinate	0.300	0.600	0.600	0.600				
Date	Time (seconds)	Time (days)	Concentration (ppb)	Flow rate (ml/min)	Boundary efflux (mg/day)	Cumulative mass loss (mg)		
06-08-1999 13:00	0							
06-08-1999 13:30	1800	0.02	0.5	0.8	0.00	0.00		
06-08-1999 15:05	7500	0.09	0.5	0.8	0.16	0.01		
06-08-1999 16:20	12000	0.14	0.5	0.8	0.16	0.02		
06-08-1999 17:30	16200	0.19	0.5	0.8	0.16	0.03		
06-08-1999 18:45	20700	0.24	0.5	0.8	0.16	0.04		
06-08-1999 19:45	24300	0.28	0.5	0.8	0.16	0.04		
06-08-1999 21:15	29700	0.34	0.5	0.8	0.16	0.05		
06-08-1999 22:15	33300	0.39	0.5	0.8	0.16	0.06		
06-08-1999 23:15	36900	0.43	0.5	0.8	0.16	0.07		
06-09-1999 7:15	65700	0.76	0.5	0.8	0.16	0.12		
06-09-1999 9:10	72600	0.84	0.2	0.4	1.37	0.23		
06-09-1999 10:50	78600	0.91	0.3	2.4	2.36	0.39		
06-09-1999 13:20	87600	1.01	70.4	0.7	1.66	0.56		
06-09-1999 16:30	99000	1.15	403.4	5.2	2.72	0.92		
06-09-1999 19:05	108300	1.25	499.4	7.0	3.51	1.30		
06-09-1999 20:45	114300	1.32	291.7	15.9	-0.03	1.30		
06-09-1999 22:45	121500	1.41	184.8	58.9	2.09	1.47		
06-10-1999 8:40	157200	1.82	122.3	257.1	235.0	12.07		
06-10-1999 13:30	174600	2.02	111.5	188.8	239.0	18.55		
06-10-1999 16:15	184500	2.14	95.5	199.2	235.0	20.53		
06-10-1999 22:10	205800	2.38	275.1	217.5	20.17	25.50		
06-11-1999 8:30	243000	2.81	85.8	250.7	225.0	31.30		
06-11-1999 14:10	263400	3.05	82.8	251.9	13.47	34.48		
06-12-1999 14:30	351000	4.06	94.5	258.2	15.67	50.36		
06-13-1999 17:00	446400	5.17	88.1	229.3	13.39	65.15		
06-14-1999 11:20	512400	5.93	70.5	167.3	8.93	71.97		
06-15-1999 8:20	588000	6.81	79.8	228.8	7.87	78.85		
06-16-1999 8:20	674400	7.81	65.6	184.3	11.41	90.27		
06-17-1999 9:40	765600	8.86	54.0	123.9	6.75	97.39		
06-18-1999 9:45	852300	9.86	58.1	132.4	9.03	106.46		
06-21-1999 8:40	1107600	12.82	44.3	90.0	6.18	124.70		
				16.4	223.3 (average)			

EPM Sand(1) Heads

Manometer	UP	1A	2A	2B	3A	3B	4A	4B	5A	5B
x coordinate	0.270	0.235	0.235	0.675	0.675	0.675	1.115	1.115	1.125	1.125
y coordinate	0.600	0.000	0.000	0.600	0.600	0.600	0.000	0.000	0.300	0.300
z coordinate	0.450	0.600	0.300	0.600	0.600	0.300	0.600	0.300	0.600	0.300
Date	water level below 1 m datum									
06-28-1999 16:15	0.097	0	0.102	0.112	0.114	0.112	0.125	0.125	0.123	0.124
06-29-1999 10:15	0.095	0.1	0.101	0.112	0.112	0.112	0.123	0.123	0.12	0.123
06-29-1999 20:40	0.095	0	0.102	0.111	0.113	0.113	0.124	0.124	0.122	0.124
06-30-1999 13:15	0.093	0.1	0.101	0.11	0.113	0.113	0.122	0.122	0.121	0.123
07-04-1999 17:38	0.09	0.101	0.104	0.111	0.113	0.113	0.124	0.124	0.122	0.124
07-08-1999 11:00	0.088	0.101	0.103	0.111	0.113	0.113	0.123	0.123	0.123	0.123
07-14-1999 9:30	0.087	0.103	0.106	0.113	0.114	0.114	0.124	0.124	0.124	0.125
average hydraulic head	0.908	0.899	0.897	0.889	0.887	0.887	0.876	0.876	0.878	0.876

Manometer	6A	7A	7B	8A	9A	10A	11A	12A	DOWN
x coordinate	1.325	1.325	1.325	1.725	1.725	2.125	0.040	2.260	
y coordinate	0.600	0.000	0.000	0.600	0.000	0.600	-0.625	-0.660	
z coordinate	0.450	0.600	0.300	0.450	0.450	0.450	0.450	0.450	
Date									
06-28-1999 16:15	0.127	0.127	0.128	0.137	0.137	0.145	0.1	0.15	0.15
06-29-1999 10:15	0.126	0.126	0.126	0.134	0.135	0.144	0.1	0.15	0.15
06-29-1999 20:40	0.127	0.127	0.127	0.136	0.136	0.144	0.101	0.149	0.15
06-30-1999 13:15	0.126	0.125	0.126	0.135	0.135	0.144	0.1	0.149	0.15
07-04-1999 17:38	0.127	0.128	0.127	0.136	0.136	0.144	0.102	0.149	0.15
07-08-1999 11:00	0.127	0.127	0.128	0.136	0.136	0.144	0.1	0.149	0.15
07-14-1999 9:30	0.128	0.128	0.128	0.137	0.137	0.144	0.104	0.149	0.15
average hydraulic head	0.873	0.873	0.873	0.864	0.864	0.856	0.899	0.851	0.850

EPM Sand(1) Concentrations and Flow Rates

Sample port
x coordinate
y coordinate
z coordinate

Date	Time (seconds)	Time (days)	1A	1B	2A	3A	4A	6A	6B	7A	8A	8B	9A	10A
06-28-1999 13:50	-2100	-0.02	0.5	0.5	11.5	0.9	3384.0	1000.0	163.5	1850.0	472.8	12.3	3000.0	1000.0
06-28-1999 13:15	3300	0.04	0.3	0.6	3.9	0.7	3384.0	1000.0	189.3	1850.0	683.2	9.4	3000.0	2000.0
06-28-1999 14:45	8700	0.10	7.2	6.6	4.1	0.8	3384.0	673.9	52.6	1850.0	906.0	11.1	2915.0	2681.0
06-28-1999 16:15	16500	0.19	13.6	1.3	1.1	0.7	1627.0	586.4	27.8	1447.0	1126.0	23.6	2760.0	3194.0
06-28-1999 20:08	22680	0.26	1.7	0.5	0.8	0.5	925.0	234.1	19.2	2106.0	1006.0	1.0	2346.0	2550.0
06-28-1999 22:08	29880	0.35	8.2	0.8	0.7	0.5	734.0	106.2	12.2	2396.0	961.0	1.8	2039.0	215.4
06-28-1999 01:05	36900	0.43	3.0	0.7	0.8	0.5	556.0	95.0	10.5	2556.0	1167.0	1.4	1934.0	1730.0
06-28-1999 10:15	73500	0.85	5.0	0.4	0.7	0.0	5390.0	85.0	6.7	1428.0	1452.0	8.1	1658.0	1400.0
06-28-1999 12:15	80700	0.93	0.6	0.3	0.9	0.3	345.0	78.0	8.3	1023.0	1054.0	34.2	1375.0	1123.0
06-28-1999 15:45	93300	1.08	1.4	0.7	1.0	0.5	324.7	63.0	5.3	810.0	768.0	28.8	1263.0	1082.0
06-28-1999 20:40	111000	1.28	0.7	0.6	0.9	0.5	276.4	65.2	4.6	643.6	1127.0	30.6	1118.0	905.0
06-30-1999 0:08	123480	1.43	1.1	0.6	1.3	0.5	252.4	57.1	4.0	547.0	517.0	2.1	1054.0	871.0
06-30-1999 8:30	153600	1.78	0.4	0.0	1.1	0.0	207.5	55.0	4.0	503.0	401.7	18.8	921.0	787.0
06-30-1999 13:15	170700	1.98	0.6	0.0	1.8	0.0	195.2	53.2	2.8	362.4	363.2	16.5	902.0	726.0
06-30-1999 16:13	181380	2.10	1.4	0.5	0.9	0.6	180.3	72.3	3.9	365.8	344.0	4.4	850.0	669.7
06-30-1999 22:25	203700	2.36	0.6	0.5	0.8	0.3	173.8	43.5	2.1	364.8	302.8	2.9	850.0	617.3
07-01-1999 9:10	242400	2.81	1.5	0.6	0.6	0.0	155.6	38.8	10.9	332.8	278.6	5.6	844.0	595.6
07-02-1999 10:38	334080	3.87	8.3	1.2	0.9	0.5	136.3	28.9	1.3	289.5	268.3	6.6	697.2	544.8
07-03-1999 13:10	429600	4.97	2.6	0.9	0.8	0.3	98.1	21.6	1.0	213.5	192.9	5.6	586.5	468.6
07-04-1999 17:38	532080	6.16	2.1	1.5	1.1	0.7	82.5	34.0	1.4	196.0	184.0	4.6	599.6	436.3
07-05-1999 18:08	620280	7.18	2.4	1.3	1.2	1.0	67.3	40.7	1.6	164.8	166.4	16.7	569.8	423.7
07-06-1999 12:39	686940	7.95	1.5	0.4	0.0	0.1	62.2	44.2	1.0	152.0	154.8	2.5	546.3	397.3
07-07-1999 15:28	783480	9.07	1.2	0.0	0.0	0.0	60.0	54.2	0.8	139.0	142.9	2.5	504.4	359.1
07-08-1999 11:00	853800	9.88	0.7	-0.2	-0.2	-0.2	56.9	52.6	0.0	137.4	132.7	3.4	446.2	308.1
07-12-1999 14:45	1212900	14.04	18.3	2.1	0.3	0.2	29.2	25.7	0.9	66.6	64.0	1.7	248.8	177.2
07-14-1999 9:30	1366800	15.82	0.1	-0.2	-0.3	-0.2	23.8	22.2	0.2	63.9	56.9	0.9	237.6	186.0

EPM Sand(1) Concentrations and Flow Rates

Sample port	x coordinate	y coordinate	z coordinate	Date	Time (seconds)	Time (days)	Concentration (ppb)	11A	12A	13A	13B	13C	14A	15A	16A	17A	18A	18B	18C
					0														
				06-28-1999 13:50	-2100	-0.02	1500.0	35.6	2000.0	38.5	1.6	1.0	1.0	0.9	1.0	0.9	0.9	1.1	0.6
				06-28-1999 13:15	3300	0.04	3000.0	57.8	4000.0	114.1	10.7	1.6	1.6	1.0	0.8	1.0	0.8	0.8	0.6
				06-28-1999 14:45	8700	0.10	4382.0	127.5	5864.0	151.0	4.6	1.8	1.8	0.8	0.8	0.8	1.2	0.8	0.7
				06-28-1999 16:15	16500	0.19	4323.0	82.8	7890.0	216.9	15.8	1.3	1.3	0.8	46.3	3.0	0.9	0.7	0.3
				06-28-1999 18:25	22680	0.26	4354.0	136.5	6611.0	140.9	6.2	0.9	0.9	23.6	46.9	2.3	0.7	0.3	0.3
				06-28-1999 20:08	29880	0.35	4273.0	698.6	8086.0	239.9	3.8	0.8	0.8	40.4	92.4	2.6	1.1	0.3	0.3
				06-28-1999 22:08	36900	0.43	3504.0	134.0	7294.0	252.9	14.4	1.7	1.7	313.1	1723.0	51.4	2.5	0.3	0.3
				06-29-1999 0:05	73500	0.85	2837.0	276.3	8112.0	236.6	11.1	0.9	0.9	1000.0	7104.0	73.0	2719.0	1000.0	73.7
				06-29-1999 10:15	80700	0.93	2111.0	314.7	6130.0	542.9	48.7	3.6	3.6	956.0	6596.0	168.2	2926.0	3606.0	144.5
				06-29-1999 12:15	93300	1.08	1904.0	237.0	5366.0	524.0	30.8	2.0	2.0	798.0	6178.0	174.3	2968.0	6116.0	205.9
				06-29-1999 15:45	111000	1.28	1714.0	254.4	4902.0	253.2	13.5	1.1	1.1	638.9	6300.0	238.6	2052.0	6104.0	146.0
				06-29-1999 20:40	123480	1.43	1578.0	207.7	4644.0	264.5	8.6	1.3	1.3	587.3	5156.0	126.0	1722.0	6094.0	220.7
				06-30-1999 0:08	153600	1.78	1587.0	179.9	3946.0	256.6	22.6	1.7	1.7	564.8	4556.0	34.6	1538.0	5882.0	292.8
				06-30-1999 8:30	170700	1.98	1387.0	180.0	3882.0	210.8	18.0	1.5	1.5	336.6	3828.0	131.0	1590.0	5038.0	225.7
				06-30-1999 13:15	181380	2.10	1306.0	165.5	3700.0	198.6	18.0	0.9	0.9	310.5	3592.0	108.8	1301.0	4392.0	61.6
				06-30-1999 16:13	203700	2.36	1111.0	144.4	3203.0	181.6	15.1	1.0	1.0	234.1	2944.0	90.3	1224.0	3464.0	75.9
				06-30-1999 22:25	242400	2.81	1000.0	123.9	3010.0	168.6	17.1	0.6	0.6	195.2	2685.0	57.2	1137.0	3079.0	105.3
				07-01-1999 9:10	334080	3.87	929.0	114.0	3218.0	123.2	5.9	0.8	0.8	145.5	2560.0	72.3	1201.0	2567.0	100.3
				07-02-1999 10:38	429600	4.97	845.0	94.9	2554.0	134.8	8.7	0.6	0.6	101.1	2078.0	40.0	1231.0	2071.0	37.6
				07-03-1999 13:10	532080	6.16	828.0	85.5	2715.0	104.3	5.6	1.1	1.1	83.0	2048.0	44.0	1181.0	1949.0	55.6
				07-04-1999 17:38	620280	7.18	751.2	89.0	2641.0	128.9	6.2	1.2	1.2	76.6	1851.5	26.7	1259.5	1900.0	51.4
				07-05-1999 18:08	686940	7.95	719.7	96.9	2950.0	113.9	5.5	0.6	0.6	73.5	1973.5	37.7	1279.5	1891.0	40.0
				07-06-1999 12:39	783480	9.07	661.9	98.8	2519.5	95.4	9.7	0.2	0.2	72.4	1907.5	54.6	1328.5	1738.0	23.8
				07-07-1999 15:28	853800	9.88	578.1	86.9	2265.5	110.3	2.6	-0.1	-0.1	70.8	1929.5	12.7	1062.0	1670.5	66.3
				07-08-1999 11:00	1212900	14.04	317.5	47.0	1372.0	31.4	1.9	0.3	0.3	33.7	1224.0	14.8	556.5	1113.0	28.9
				07-12-1999 14:45	1366800	15.82	304.2	38.2	1148.5	43.4	1.2	-0.1	-0.1	33.9	1177.0	14.4	520.0	1116.5	12.6

EPM Sand('1) Concentrations and Flow Rates

Sample port x coordinate y coordinate z coordinate	18D 1.425 0.000 0.300	18E 1.425 0.000 0.150	19A 1.625 0.200 0.600	19B 1.625 0.200 0.300	20A 1.625 0.000 0.600	20B 1.625 0.000 0.300	21A 1.825 -0.200 0.600	22A 1.825 0.400 0.600	23A 1.825 0.000 0.600	24A 2.025 0.600 0.600	25A 2.025 0.200 0.600	26A 2.025 0.000 0.600
Date	Time (seconds)	Time (days)	Concentration (ppb)									
06-28-1999 13:50	-2100	-0.02	0.6	0.8	1.0	0.6	1.2	1.4	1.3	1.1	1.4	1.5
06-28-1999 13:15	3300	0.04	0.5	0.7	0.8	0.6	1.0	0.9	1.0	1.0	0.9	1.1
06-28-1999 14:45	8700	0.10	0.6	1.0	0.7	0.6	0.9	0.8	0.9	0.9	0.9	1.6
06-28-1999 16:15	16500	0.19	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
06-28-1999 18:25	22680	0.26	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
06-28-1999 20:08	29880	0.35	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
06-28-1999 22:08	36900	0.43	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
06-28-1999 0:05	73500	0.85	5.6	0.6	0.4	0.4	0.8	0.3	0.3	0.3	0.3	0.3
06-28-1999 10:15	80700	0.93	17.7	2.1	0.8	0.8	2.6	1.1	0.3	0.3	0.3	0.3
06-29-1999 12:15	93300	1.08	16.3	1.4	4.9	0.9	337.0	8.1	2.4	0.3	0.3	0.3
06-29-1999 15:45	111000	1.28	9.2	1.2	520.0	17.4	3280.0	102.9	2.6	1.9	1.0	1.2
06-29-1999 20:40	123480	1.43	13.9	1.5	2020.0	38.5	5522.0	126.5	231.2	7.5	1.7	1.0
06-30-1999 0:08	153600	1.78	25.2	1.9	1370.0	57.5	4566.0	67.0	4304.0	52.6	57.9	22.2
06-30-1999 6:30	170700	1.98	25.0	3.3	1033.0	45.5	5282.0	207.9	4554.0	67.2	1645.0	3774.0
06-30-1999 13:15	181380	2.10	13.2	1.3	921.0	42.0	4622.0	32.5	3916.0	109.4	1525.0	3460.0
06-30-1999 16:13	203700	2.36	4.7	0.8	641.8	14.6	3580.0	55.0	773.0	24.1	863.0	3156.0
06-30-1999 22:25	242400	2.81	6.6	0.8	401.9	8.8	3062.0	79.8	3163.0	81.9	226.8	2336.0
07-01-1999 9:10	334080	3.87	3.6	1.1	187.1	5.0	2233.0	22.0	2090.0	33.3	129.4	1769.0
07-02-1999 10:38	429600	4.97	3.7	0.7	116.5	2.6	1812.0	30.0	1747.0	1.1	84.4	1600.0
07-03-1999 13:10	532080	6.16	4.0	1.1	81.7	2.2	1584.0	16.6	1481.0	17.9	69.6	1431.5
07-04-1999 17:38	620280	7.18	2.6	1.3	66.1	1.9	1551.5	27.6	1309.5	26.6	64.6	1417.5
07-05-1999 18:08	686940	7.95	1.9	0.7	59.5	1.4	1442.5	27.3	1468.0	25.4	62.4	1107.0
07-06-1999 12:39	783480	9.07	1.6	0.4	58.3	1.0	1308.5	25.5	1395.0	23.0	60.1	1088.0
07-07-1999 15:28	853800	9.88	1.2	0.0	52.6	0.0	1204.5	1.4	1076.5	23.2	28.0	839.0
07-08-1999 11:00	1212900	14.04	1.4	0.3	20.9	0.6	821.0	21.8	840.0	19.4	47.8	790.5
07-12-1999 14:45	1366800	15.82	0.4	-0.1	18.9	0.2	917.5	7.7	900.0	0.0	0.0	0.0
07-14-1999 9:30												

EPM Sand(1) Concentrations and Flow Rates

Sample port	26B	27A	28A	Reservoir				
x coordinate	2.025	2.025	2.225					
y coordinate	0.000	-0.200	0.000					
z coordinate	0.300	0.600	0.600					
Date	Time (seconds)	Time (days)	Concentration (ppb)	Flow rate (ml/min)	Boundary efflux (mg/day)	Cumulative mass loss (mg)		
06-28-1999 13:50	0							
06-28-1999 13:15	-2100	-0.02	0.7	150.0	0.00	0.00		
06-28-1999 14:45	3300	0.04	0.8	150.0	0.45	0.03		
06-28-1999 16:15	8700	0.10	0.8	175.0	0.10	0.03		
06-28-1999 18:25	16500	0.19	0.3	185.0	1.95	0.21		
06-28-1999 20:08	22680	0.26	0.3	170.0	-1.72	0.09		
06-28-1999 22:08	29880	0.35	0.3	175.0	-0.45	0.05		
06-29-1999 0:05	36900	0.43	0.3	170.0	2.13	0.22		
06-29-1999 10:15	73500	0.85	0.3	167.5	0.58	0.47		
06-29-1999 12:15	80700	0.93	0.3	165.0	-0.49	0.43		
06-29-1999 15:45	93300	1.08	0.3	157.5	4.85	1.13		
06-29-1999 20:40	111000	1.28	0.8	170.0	-3.25	0.47		
06-30-1999 0:08	123480	1.43	0.9	172.5	0.29	0.51		
06-30-1999 8:30	153600	1.78	1.4	172.5	0.30	0.62		
06-30-1999 13:15	170700	1.98	97.8	172.5	0.96	0.81		
06-30-1999 16:13	181380	2.10	79.4	175.0	21.02	3.40		
06-30-1999 22:25	203700	2.36	94.5	170.0	54.13	17.39		
07-01-1999 9:10	242400	2.81	125.6	160.0	48.92	39.30		
07-02-1999 10:38	334080	3.87	23.4	175.0	21.25	61.85		
07-03-1999 13:10	429600	4.97	31.7	175.0	15.21	78.67		
07-04-1999 17:38	532080	6.16	20.6	175.0	14.92	96.36		
07-05-1999 18:08	620280	7.18	4.3	180.0	16.23	112.93		
07-06-1999 12:39	686940	7.95	30.6	170.0	13.44	123.30		
07-07-1999 15:28	783480	9.07	28.4	177.5	14.57	139.58		
07-08-1999 11:00	853800	9.88	21.2	180.0	10.12	147.81		
07-12-1999 14:45	1212900	14.04	27.6	172.5	7.92	180.31		
07-14-1999 9:30	1366800	15.82	10.0	167.5	5.18	189.53		
				170.4 (average)				

EPM Gravel(2) Heads

Manometer	UP	1A	2A	2B	3A	3B	4A	4B	5A	5B
x coordinate		0.270	0.235	0.235	0.675	0.675	1.115	1.115	1.125	1.125
y coordinate		0.600	0.000	0.000	0.600	0.600	0.000	0.000	0.300	0.300
z coordinate		0.450	0.600	0.300	0.600	0.300	0.600	0.300	0.600	0.300
Date	water level below 1 m datum									
07-26-1999 16:20	0.094	0.1	0.107	0.1	0.105	0.107	0.108	0.113	0.107	0.114
07-27-1999 8:38	0.094	0.101	0.11	0.105	0.109	0.11	0.11	0.116	0.113	0.117
07-27-1999 12:23	0.094	0.102	0.11	0.104	0.109	0.11	0.11	0.116	0.114	0.116
07-27-1999 16:10	0.093	0.1	0.11	0.105	0.11	0.11	0.11	0.116	0.112	0.117
07-30-1999 0:25	0.089	0.104	0.111	0.108	0.111	0.111	0.11	0.117	0.114	0.117
07-31-1999 11:35	0.087	0.103	0.112	0.108	0.111	0.111	0.111	0.118	0.115	0.118
08-03-1999 13:34	0.087	0.103	0.11	0.107	0.11	0.111	0.11	0.117	0.115	0.117
average hydraulic head	0.909	0.898	0.890	0.895	0.891	0.890	0.890	0.884	0.887	0.883
08-03-1999 19:38	0.087	0.098	0.101	0.1	0.101	0.101	0.102	0.104	0.103	0.105
08-04-1999 23:38	0.089	0.1	0.105	0.102	0.103	0.114	0.105	0.108	0.105	0.108
08-06-1999 9:43	0.089	0.101	0.105	0.103	0.104	0.106	0.105	0.109	0.106	0.109
08-09-1999 8:30	0.087	0.1	0.105	0.102	0.104	0.105	0.105	0.11	0.108	0.109
average hydraulic head	0.912	0.900	0.896	0.898	0.897	0.894	0.896	0.892	0.895	0.892
Manometer	6A	7A	7B	8A	9A	10A	11A	12A	DOWN	
x coordinate	1.325	1.325	1.325	1.725	1.725	2.125	0.040	2.260		
y coordinate	0.600	0.000	0.000	0.600	0.000	0.600	-0.625	-0.660		
z coordinate	0.450	0.600	0.300	0.450	0.450	0.450	0.450	0.450		
Date										
07-26-1999 16:20	0.119	0.115	0.119	0.129	0.131	0.144	0.098	0.149	0.15	
07-27-1999 8:38	0.121	0.118	0.121	0.132	0.133	0.143	0.1	0.147	0.15	
07-27-1999 12:23	0.121	0.118	0.121	0.133	0.133	0.144	0.101	0.147	0.15	
07-27-1999 16:10	0.121	0.119	0.121	0.131	0.131	0.144	0.101	0.148	0.15	
07-30-1999 0:25	0.123	0.119	0.122	0.133	0.133	0.143	0.103	0.148	0.15	
07-31-1999 11:35	0.122	0.12	0.122	0.135	0.135	0.145	0.102	0.148	0.15	
08-03-1999 13:34	0.121	0.119	0.121	0.133	0.133	0.143	0.102	0.148	0.15	
average hydraulic head	0.879	0.882	0.879	0.868	0.867	0.856	0.899	0.852	0.850	
08-03-1999 19:38	0.108	0.107	0.108	0.113	0.114	0.119	0.097	0.123	0.123	
08-04-1999 23:38	0.11	0.109	0.11	0.116	0.116	0.121	0.1	0.125	0.125	
08-06-1999 9:43	0.111	0.11	0.11	0.116	0.117	0.122	0.1005	0.125	0.125	
08-09-1999 8:30	0.111	0.11	0.11	0.116	0.117	0.122	0.1	0.124	0.125	
average hydraulic head	0.890	0.891	0.891	0.885	0.884	0.879	0.901	0.876	0.876	

**EPM Grave(2) Concentrations
and Flow Rates**

185

Sample port	1A	1B	2A	3A	4A	6A
x coordinate	0.242	0.242	0.294	0.425	0.456	0.675
y coordinate	0.250	0.250	0.220	0.600	0.127	0.440
z coordinate	0.600	0.300	0.600	0.600	0.460	0.675

Date	Time (seconds)	Time (days)	Concentration (ppb)					
07-26-1999 15:00	0							
07-26-1999 16:20	4800	0.06	1.1	0.6	21.8	1.6	162.8	146.5
07-26-1999 18:05	11100	0.13	0.6	0.5	12.6	0.6	78.4	72.9
07-26-1999 20:14	18840	0.22	0.3	0.5	13.2	0.7	61.2	56.4
07-26-1999 22:08	25680	0.30	0.5	0.4	12.4	0.8	49.7	49.9
07-26-1999 23:38	31080	0.36	0.4	0.4	11.2	0.6	51.3	53.4
07-27-1999 8:38	63480	0.73	0.4	0.3	10.9	0.4	38.8	43.4
07-27-1999 10:35	70500	0.82	0.6	0.3	18.2	0.9	38.1	42.2
07-27-1999 12:23	76980	0.89	0.5	0.5	15.4	0.9	36	42.2
07-27-1999 14:08	83280	0.96	0.6	0.6	12.9	1	32.8	41.5
07-27-1999 16:10	90600	1.05	0.9	1.5	13.2	1	30.8	35.8
07-27-1999 18:10	97800	1.13	0.4	0.1	12.6	0.6	31.4	41.8
07-27-1999 20:10	105000	1.22	0.5	0	12.8	0.1	31.2	38.9
07-27-1999 22:08	112080	1.30	0.3	-0.2	12.6	0	30.2	38.5
07-27-1999 23:10	115800	1.34	1.4	-0.3	12.6	0	28.5	37.3
07-28-1999 8:53	150780	1.75	0.6	0.2	13.1	0.2	28.6	36.7
07-28-1999 13:23	166980	1.93	3.1	0.7	12.4	0.7	30.9	38.6
07-28-1999 16:48	179280	2.07	10.9	2.6	13.3	1	27.7	40.6
07-29-1999 9:05	237900	2.75	3.5	0	11.1	0	25.5	38.5
07-29-1999 15:35	261300	3.02	0.6	2.1	11.8	0.7	25.8	33.1
07-30-1999 0:25	293100	3.39	1.9	0.7	11.2	1.1	24.5	32.5
07-30-1999 12:13	335580	3.88	6.3	1.5	11.3	0.6	22.8	31.2
07-31-1999 11:35	419700	4.86	1.1	0.7	8.7	0.9	22.1	30
08-01-1999 11:55	507300	5.87	1.4	0.5	7.4	0.6	19.6	29
08-03-1999 13:34	686040	7.94	0	0.6	5	-0.2	13.5	24.1
08-03-1999 16:30	696600	8.06						
08-03-1999 19:38	707880	8.19	0	0	7.9	0	19.3	34.2
08-03-1999 21:55	716100	8.29	0	-0.2	9.9	-0.2	23.6	37
08-04-1999 8:52	755520	8.74	-0.2	-0.3	10.4	-0.2	22.6	37.6
08-04-1999 16:08	781680	9.05	-0.3	-0.4	9.4	-0.4	24.3	37.2
08-04-1999 23:38	808680	9.36	-0.2	-0.2	10.3	-0.3	22	37.7
08-05-1999 9:08	842880	9.76	0	0	10.7	0.1	23.2	37.2
08-05-1999 16:08	868080	10.05	0.6	0.4	9.9	0.3	23.1	37.4
08-05-1999 23:53	895980	10.37	0.3	0.2	9	0.2	21.6	35.5
08-06-1999 9:43	931380	10.78	0.1	0	9.4	0	21	33.2
08-06-1999 16:08	954480	11.05	0.2	0.1	8.9	0.2	20.4	33
08-08-1999 11:24	1110240	12.85	0.2	0.2	9	0.3	18.3	33.4
08-09-1999 8:30	1186200	13.73	0.2	0.3	9.4	0.1	16.5	31.1
08-10-1999 14:48	1295280	14.99	0	0.3	10.7	0.2	17.1	34.9
08-11-1999 13:05	1375500	15.92	0.1	0	10.6	0.3	14.8	34.8
08-12-1999 15:40	1471200	17.03	0.8	0.5	11.6	0.4	15.8	33.3
08-13-1999 11:50	1543800	17.87	0.5	0.1	11.2	0	15.5	31.5
08-15-1999 18:40	1741200	20.15	0.5	0.7	9.7	0.6	14	32.3
08-18-1999 13:40	1982400	22.94	0.4	0.6	8.8	0.3	13.6	29

**EPM Grave(2) Concentrations
and Flow Rates**

186

Sample port	6B	7A	8A	8B	9A	10A
x coordinate	0.675	0.675	0.894	0.894	1.052	1.060
y coordinate	0.440	0.000	0.127	0.127	0.218	0.223
z coordinate	0.460	0.460	0.460	0.300	0.600	0.600

Date	Time (seconds)	Time (days)	Concentration (ppb)					
07-26-1999 15:00	0							
07-26-1999 16:20	4800	0.06	163.2	247.2	276.9	1.6	549.2	480.2
07-26-1999 18:05	11100	0.13	69.9	110.1	140.1	2.2	208.2	175.3
07-26-1999 20:14	18840	0.22	53.5	88.8	104.3	5.2	148.4	110.1
07-26-1999 22:08	25680	0.30	47.5	72.7	90.4	1.4	113.3	87.8
07-26-1999 23:38	31080	0.36	33.4	66.3	81	1.9	107.5	78.4
07-27-1999 8:38	63480	0.73	9	56.3	0.4	45.6	78.5	51.9
07-27-1999 10:35	70500	0.82	7.4	51.3	61.6	81.4	77.4	53.7
07-27-1999 12:23	76980	0.89	7.9	45.5	59.7	54.8	70.3	48.3
07-27-1999 14:08	83280	0.96	7.4	47.7	53.2	55.3	72.3	49.7
07-27-1999 16:10	90600	1.05	8	42.3	53.9	36.9	65	44.7
07-27-1999 18:10	97800	1.13	7.9	45.7	61.1	36.4	67	45.7
07-27-1999 20:10	105000	1.22	7.5	46.7	57.4	31.2	69.4	51
07-27-1999 22:08	112080	1.30	8.4	44.6	53.9	31.9	68.9	48.2
07-27-1999 23:10	115800	1.34	7.6	42.1	49.8	29.1	65.2	46.1
07-28-1999 8:53	150780	1.75	7.1	42.7	52.1	25.2	68.3	44.3
07-28-1999 13:23	166980	1.93	7.4	39.6	50.5	24	69.6	44.4
07-28-1999 16:48	179280	2.07	6.9	38.7	48.4	22.3	73.5	47.5
07-29-1999 9:05	237900	2.75	7.5	37.3	47.1	19.9	59.5	41.3
07-29-1999 15:35	261300	3.02	32.9	38.7	44.6	18	62.2	45
07-30-1999 0:25	293100	3.39	6.4	35.4	45.2	17.7	58.7	43.1
07-30-1999 12:13	335580	3.88	6.2	32.3	40.7	16.5	57.1	38.2
07-31-1999 11:35	419700	4.86	8.6	30.5	39.9	15.1	33.4	38.4
08-01-1999 11:55	507300	5.87	4	33.6	31.2	19	46	30.3
08-03-1999 13:34	686040	7.94	2.8	23.4	30	10.3	39.3	28.3
08-03-1999 16:30	696600	8.06						
08-03-1999 19:38	707880	8.19	4.7	31.2	35.6	9.7	57.8	37.1
08-03-1999 21:55	716100	8.29	5.5	37.6	45.1	9	74.1	44.7
08-04-1999 8:52	755520	8.74	6	39.9	48.5	9.4	80.5	49.9
08-04-1999 16:08	781680	9.05	5.5	38.2	47.6	9.1	83	49.6
08-04-1999 23:38	808680	9.36	5.4	38.8	47.4	11.9	80.8	47.5
08-05-1999 9:08	842880	9.76	6.2	39.1	49.5	16.7	71.8	46.7
08-05-1999 16:08	868080	10.05	5.9	36.9	47.7	18.2	70.4	48.3
08-05-1999 23:53	895980	10.37	6.5	37.2	47.8	18.5	72	48.8
08-06-1999 9:43	931380	10.78	6.2	36.7	50.2	18	71.7	46.1
08-06-1999 16:08	954480	11.05	5.5	37.8	46.8	18.4	66.1	45.2
08-08-1999 11:24	1110240	12.85	5.1	35.6	44.9	16.3	63.8	43.4
08-09-1999 8:30	1186200	13.73	4.5	34.5	42.5	15.6	61.1	40.1
08-10-1999 14:48	1295280	14.99	5.3	28.6	38.1	14.8	57.7	41.5
08-11-1999 13:05	1375500	15.92	4.6	27.8	38.9	13.3	53.4	39.8
08-12-1999 15:40	1471200	17.03	5.1	27.8	38.6	11.7	55.7	42.5
08-13-1999 11:50	1543800	17.87	4.8	26.6	38.7	11.7	53.3	39.5
08-15-1999 18:40	1741200	20.15	5.6	26.1	36.8	12	52.1	36.2
08-18-1999 13:40	1982400	22.94	4.9	26.6	34.5	11.7	48.6	34.6

**EPM Grave(2) Concentrations
and Flow Rates**

187

Sample port	11A	12A	13A	13B	13C	14A
x coordinate	1.056	1.108	1.115	1.115	1.115	1.225
y coordinate	-0.220	0.250	0.000	0.000	0.000	0.600
z coordinate	0.600	0.600	0.675	0.460	0.300	0.600

Date	Time (seconds)	Time (days)	Concentration (ppb)				
07-26-1999 15:00	0						
07-26-1999 16:20	4800	0.06	503.3	734.6	726.7	420.7	8.6
07-26-1999 18:05	11100	0.13	214.1	168.5	891.3	202.5	10.8
07-26-1999 20:14	18840	0.22	131.6	69.7	742.4	157.9	152.4
07-26-1999 22:08	25680	0.30	107.6	48.8	565.9	168.5	255.6
07-26-1999 23:38	31080	0.36	96.1	43.4	559.1	120	126.7
07-27-1999 8:38	63480	0.73	68	30	419	98.7	57.7
07-27-1999 10:35	70500	0.82	67.4	29.3	444.4	99.6	50.7
07-27-1999 12:23	76980	0.89	60.6	26.9	428.9	98.8	47.6
07-27-1999 14:08	83280	0.96	62	26.4	391.8	90.6	43.4
07-27-1999 16:10	90600	1.05	55	26.2	348.6	91.2	42.9
07-27-1999 18:10	97800	1.13	61.8	30.4	405	98.8	49.7
07-27-1999 20:10	105000	1.22	64.4	27.4	394.6	97.5	44.9
07-27-1999 22:08	112080	1.30	58.4	27.6	414.4	93.5	42.4
07-27-1999 23:10	115800	1.34	59.8	27.2	388.9	94.2	40.3
07-28-1999 8:53	150780	1.75	59.5	27.9	400.2	94.7	39.5
07-28-1999 13:23	166980	1.93	50.8	25.8	375.6	86.9	41.2
07-28-1999 16:48	179280	2.07	53.8	26.9	390.3	81.8	38.4
07-29-1999 9:05	237900	2.75	48.9	24.8	347.9	70	35.7
07-29-1999 15:35	261300	3.02	48.2	26.1	340.2	64.8	36.7
07-30-1999 0:25	293100	3.39	50.6	22.2	334.7	60	31.8
07-30-1999 12:13	335580	3.88	43.8	23	320.8	57.1	31.2
07-31-1999 11:35	419700	4.86	44.1	23.5	335.5	68.3	11.1
08-01-1999 11:55	507300	5.87	41.2	20.3	309.2	63.8	18.1
08-03-1999 13:34	686040	7.94	35.6	17	236.6	44	22
08-03-1999 16:30	696600	8.06					
08-03-1999 19:38	707880	8.19	43.9	17.7	297.1	50	19
08-03-1999 21:55	716100	8.29	60.4	25.3	353	66	18.9
08-04-1999 8:52	755520	8.74	63.5	30	388.2	75.7	27
08-04-1999 16:08	781680	9.05	65.3	29.7	408.9	75.8	33.5
08-04-1999 23:38	808680	9.36	63	30	413.1	74.7	34.3
08-05-1999 9:08	842880	9.76	61.2	31	320.8	67.7	34.1
08-05-1999 16:08	868080	10.05	60.9	28.1	329.6	70.5	34.7
08-05-1999 23:53	895980	10.37	59.2	27.2	326.5	73.1	33.7
08-06-1999 9:43	931380	10.78	59.9	29	321.3	70.8	33.4
08-06-1999 16:08	954480	11.05	61.2	27.9	298.3	71.3	31.4
08-08-1999 11:24	1110240	12.85	60.8	27.1	312.4	62.9	30.2
08-09-1999 8:30	1186200	13.73	57.6	26	298.8	59.6	29.1
08-10-1999 14:48	1295280	14.99	31.3	25.4	178	32.9	27.1
08-11-1999 13:05	1375500	15.92	45.7	26.4	156	41.2	26.5
08-12-1999 15:40	1471200	17.03	42.4	25.5	150.6	41.6	25.4
08-13-1999 11:50	1543800	17.87	42.5	26	134.2	40.7	24
08-15-1999 18:40	1741200	20.15	39.5	24.1	124.2	40	25
08-18-1999 13:40	1982400	22.94	39.3	22.5	126.1	36.4	25.9

**EPM Gravel(2) Concentrations
and Flow Rates**

188

Sample port	15A	16A	17A	18A	18B	18C
x coordinate	1.225	1.225	1.425	1.425	1.425	1.425
y coordinate	0.200	0.000	0.400	0.000	0.000	0.000
z coordinate	0.600	0.600	0.600	0.750	0.600	0.450

Date	Time (seconds)	Time (days)	Concentration (ppb)					
07-26-1999 15:00	0							
07-26-1999 16:20	4800	0.06	18.9	97	3.1	0.9	0.8	0.3
07-26-1999 18:05	11100	0.13	541	827.7	30.7	4.3	1.2	0.3
07-26-1999 20:14	18840	0.22	146.6	489.8	19.7	3.7	1.5	0.6
07-26-1999 22:08	25680	0.30	87.2	344	15.7	341.7	416.8	212.2
07-26-1999 23:38	31080	0.36	74.6	327.5	297.6	227.4	760.4	726.2
07-27-1999 8:38	63480	0.73	47.8	211.5	50.3	312	453.1	242.6
07-27-1999 10:35	70500	0.82	48.2	191.4	36.8	269.2	397.4	209
07-27-1999 12:23	76980	0.89	41.4	257.6	35.2	252.3	374.1	172
07-27-1999 14:08	83280	0.96	39.9	240.4	30.7	240.9	361.1	158.3
07-27-1999 16:10	90600	1.05	39.4	201.4	32.2	243.3	312.1	161.8
07-27-1999 18:10	97800	1.13	42.8	205.5	29.5	330.4	450.5	188.3
07-27-1999 20:10	105000	1.22	36	195.5	31.6	282.6	398.2	187.4
07-27-1999 22:08	112080	1.30	38.5	185.8	30.3	253.7	367	174.3
07-27-1999 23:10	115800	1.34	38.4	174	27.1	261.3	362.9	171.2
07-28-1999 8:53	150780	1.75	40	190.7	27	262	363.6	156.5
07-28-1999 13:23	166980	1.93	35.5	190.5	173.2	245.4	351.8	135.9
07-28-1999 16:48	179280	2.07	35.8	189.7	27.4	229	327	151.8
07-29-1999 9:05	237900	2.75	35	174.7	25.8	221.3	295.5	128.4
07-29-1999 15:35	261300	3.02	36.7	169.1	24.6	222.5	279.4	120.8
07-30-1999 0:25	293100	3.39	24	156	23.8	236.7	273	111
07-30-1999 12:13	335580	3.88	32.8	152.8	23.3	214.3	250.5	96.8
07-31-1999 11:35	419700	4.86	29.3	127.2	25.2	195	240.6	95.3
08-01-1999 11:55	507300	5.87	29.4	129.7	21.7	158.4	248.1	77.4
08-03-1999 13:34	686040	7.94	24.4	143.8	17	148.5	182.8	72.7
08-03-1999 16:30	696600	8.06						
08-03-1999 19:38	707880	8.19	24.9	145.4	15.4	151.9	171.8	66.3
08-03-1999 21:55	716100	8.29	32.6	157.7	15.5	157	166.9	75.35
08-04-1999 8:52	755520	8.74	42	215.3	16.9	176.9	201.2	84.4
08-04-1999 16:08	781680	9.05	43.9	222.9	22.1	205.7	254.1	170.9
08-04-1999 23:38	808680	9.36	42.1	224.9	27.1	210.2	269.4	186.9
08-05-1999 9:08	842880	9.76	44.4	201.8	26.4	182.9	237.9	157.1
08-05-1999 16:08	868080	10.05	43.6	193.5	27.2	182.2	236.1	150.9
08-05-1999 23:53	895980	10.37	44	182.9	27.5	186.4	246.1	135.2
08-06-1999 9:43	931380	10.78	41.6	183.1	26.5	173.6	239.4	132.6
08-06-1999 16:08	954480	11.05	38.6	189.5	25.6	174	230.8	130.5
08-08-1999 11:24	1110240	12.85	39.3	159.6	24.4	160.7	239	111.6
08-09-1999 8:30	1186200	13.73	38.1	158.7	23.5	159	233.5	108.3
08-10-1999 14:48	1295280	14.99	37.9	262.1	24.3	127.3	140.6	80.3
08-11-1999 13:05	1375500	15.92	38.7	265.3	26.8	124.3	127.3	79
08-12-1999 15:40	1471200	17.03	37.5	252.5	28.2	120.2	119.1	77.9
08-13-1999 11:50	1543800	17.87	36.9	228.6	27.3	109.5	119.9	54.8
08-15-1999 18:40	1741200	20.15	33.9	212.4	23.6	102	111.4	67.6
08-18-1999 13:40	1982400	22.94	32.7	214.4	23.6	96.5	118.6	67.5

**EPM Gravel(2) Concentrations
and Flow Rates**

189

Sample port	18D	18E	19A	19B	20A	20B
x coordinate	1.425	1.425	1.625	1.625	1.625	1.625
y coordinate	0.000	0.000	0.200	0.200	0.000	0.000
z coordinate	0.300	0.150	0.600	0.300	0.600	0.300

Date	Time (seconds)	Time (days)	Concentration (ppb)					
07-26-1999 15:00	0							
07-26-1999 16:20	4800	0.06	0.3	0.3	0.3	0.3	0.3	0.3
07-26-1999 18:05	11100	0.13	0.3	0.3	0.3	0.3	0.3	0.3
07-26-1999 20:14	18840	0.22	0.3	0.3	0.3	0.3	0.3	0.3
07-26-1999 22:08	25680	0.30	375.9	6.3	1	0.5	1	0.6
07-26-1999 23:38	31080	0.36	249.3	9.7	1.6	0.5	0.8	42
07-27-1999 8:38	63480	0.73	82.7	2.3	107.1	163.1	521.5	82.6
07-27-1999 10:35	70500	0.82	65.3	2	93.2	152.8	455.6	79.6
07-27-1999 12:23	76980	0.89	62.9	8.9	77.9	132.4	441.7	72.4
07-27-1999 14:08	83280	0.96	58.4	42.5	73.2	120.3	402.9	66.3
07-27-1999 16:10	90600	1.05	58	138.5	65.8	109.3	342.1	80.4
07-27-1999 18:10	97800	1.13	60	130.4	71.6	127.6	406.8	69.8
07-27-1999 20:10	105000	1.22	62.1	108.8	68.9	118.6	388.1	70.8
07-27-1999 22:08	112080	1.30	56.7	74.7	67.9	113.2	439.5	62.7
07-27-1999 23:10	115800	1.34	55.9	63.9	61.7	104.1	408.3	63.6
07-28-1999 8:53	150780	1.75	49.8	43.9	54.9	91.6	377.7	61.4
07-28-1999 13:23	166980	1.93	48.2	36.5	53.7	89.7	329	60.6
07-28-1999 16:48	179280	2.07	49.4	33.5	49.8	87.1	325.7	53.2
07-29-1999 9:05	237900	2.75	50.5	27.5	45.7	67.8	293.4	50
07-29-1999 15:35	261300	3.02	45.2	25.1	47.5	73	282.5	52.8
07-30-1999 0:25	293100	3.39	41.4	24.1	47.1	63.8	285.2	47.3
07-30-1999 12:13	335580	3.88	40.5	23.1	45.9	62.3	273.6	43.6
07-31-1999 11:35	419700	4.86	41.5	25.9	42.4	51.5	227.9	41.9
08-01-1999 11:55	507300	5.87	37.2	24.4	37	46.9	239	44.3
08-03-1999 13:34	686040	7.94	29.6	14.7	31.9	39.7	203	29.8
08-03-1999 16:30	696600	8.06						
08-03-1999 19:38	707880	8.19	26.9	12.9	32.9	38.8	201	29.6
08-03-1999 21:55	716100	8.29	29.8	12.25	32.05	39	198.35	29.4
08-04-1999 8:52	755520	8.74	32.7	11.6	31.2	39.2	195.7	29.2
08-04-1999 16:08	781680	9.05	43.1	12.3	31.6	36.5	197.8	38
08-04-1999 23:38	808680	9.36	44.3	11.8	49.6	47.3	261.5	44.7
08-05-1999 9:08	842880	9.76	46.7	11.3	55.2	63	238.7	45.8
08-05-1999 16:08	868080	10.05	46.6	13.2	58.6	62.3	243.1	50.1
08-05-1999 23:53	895980	10.37	47.8	18.4	55.9	65.9	252.3	50
08-06-1999 9:43	931380	10.78	46.7	22.5	56.4	68	256.3	47.7
08-06-1999 16:08	954480	11.05	46.9	22.7	53.4	63.5	260.9	48.3
08-08-1999 11:24	1110240	12.85	43.5	22.1	52.1	60	242.6	45.3
08-09-1999 8:30	1186200	13.73	41.5	21	49	55.3	246	45.1
08-10-1999 14:48	1295280	14.99	29.1	20.3	54.3	56.4	168.2	31.4
08-11-1999 13:05	1375500	15.92	30.7	18.2	51.6	52.1	145.7	33.3
08-12-1999 15:40	1471200	17.03	31.1	18.7	50.4	50.3	143.6	35.8
08-13-1999 11:50	1543800	17.87	30.2	17.1	48.5	46.1	134.1	30.6
08-15-1999 18:40	1741200	20.15	30.1	16.5	49.1	43	126.1	32.9
08-18-1999 13:40	1982400	22.94	29.9	16	48.5	43.1	128.9	33.4

**EPM Grave(2) Concentrations
and Flow Rates**

190

Sample port	21A	22A	23A	24A	25A	26A
x coordinate	1.625	1.825	1.825	2.025	2.025	2.025
y coordinate	-0.200	0.400	0.000	0.600	0.200	0.000
z coordinate	0.600	0.600	0.600	0.600	0.600	0.600

Date	Time (seconds)	Time (days)	Concentration (ppb)					
07-26-1999 15:00	0							
07-26-1999 16:20	4800	0.06	0.3	0.3	0.3	0.3	0.3	0.3
07-26-1999 18:05	11100	0.13	0.3	0.3	0.3	0.3	0.3	0.3
07-26-1999 20:14	18840	0.22	0.3	0.3	0.3	0.3	0.3	0.3
07-26-1999 22:08	25680	0.30	0.6	0.3	0.3	0.3	0.3	0.3
07-26-1999 23:38	31080	0.36	1.6	15.2	3	0.9	0.5	1.5
07-27-1999 8:38	63480	0.73	160.4	1.8	324.1	3.7	0.7	0.7
07-27-1999 10:35	70500	0.82	120.2	6	655	13.7	1.2	1.4
07-27-1999 12:23	76980	0.89	99.1	137	566.4	8.5	6.6	14.3
07-27-1999 14:08	83280	0.96	80.9	394.3	483	6.6	211	222.6
07-27-1999 16:10	90600	1.05	71.9	198.1	402.7	3	402.8	598.2
07-27-1999 18:10	97800	1.13	79	93.9	101.5	0.7	246.4	732.5
07-27-1999 20:10	105000	1.22	69.4	66.4	395.4	7.2	157.9	615.6
07-27-1999 22:08	112080	1.30	62.6	57.3	352.3	11.4	120.1	515.3
07-27-1999 23:10	115800	1.34	59.3	47.7	336	42.7	107.5	473.1
07-28-1999 8:53	150780	1.75	56.5	34.8	343.5	167.5	82.6	388.9
07-28-1999 13:23	166980	1.93	67.5	33.9	278.6	49.4	67	372.9
07-28-1999 16:48	179280	2.07	51.1	32.1	276.5	26.8	61.5	328.7
07-29-1999 9:05	237900	2.75	47.5	27.4	256.6	18.7	50.8	257
07-29-1999 15:35	261300	3.02	45	28	239.6	13.3	49.6	261.3
07-30-1999 0:25	293100	3.39	46.2	27.5	225.1	11.8	46.5	258.4
07-30-1999 12:13	335580	3.88	43.5	26.2	210.6	10.2	46.9	227.1
07-31-1999 11:35	419700	4.86	40.6	23.5	183.7	10	17.3	196
08-01-1999 11:55	507300	5.87	39.5	21.4	184.4	28.5	37.2	192.6
08-03-1999 13:34	686040	7.94	30.8	17.5	185.7	5.3	32.5	186.4
08-03-1999 16:30	696600	8.06						
08-03-1999 19:38	707880	8.19	29.9	16.7	185.3	4	31.7	185.3
08-03-1999 21:55	716100	8.29	28.95	16.2	183.6	3.75	32.1	181.45
08-04-1999 8:52	755520	8.74	28	15.7	181.9	3.5	32.5	177.6
08-04-1999 16:08	781680	9.05	28.1	28	176.1	3.6	30.4	182.6
08-04-1999 23:38	808680	9.36	36.4	14.8	177	3.1	28.5	177.8
08-05-1999 9:08	842880	9.76	48.5	14.7	187.7	3.8	31.5	149.8
08-05-1999 16:08	868080	10.05	54.1	19	227.3	2.8	34.3	168.4
08-05-1999 23:53	895980	10.37	53.5	25.4	228.8	3.9	45.5	210.9
08-06-1999 9:43	931380	10.78	0.2	51.8	239.3	4.5	55.3	243.2
08-06-1999 16:08	954480	11.05	53.5	27.9	230.5	2	58.9	243.5
08-08-1999 11:24	1110240	12.85	50.9	25.9	210.6	6.1	54.2	234.5
08-09-1999 8:30	1186200	13.73	50.4	25.5	209	5	50	227.1
08-10-1999 14:48	1295280	14.99	46.8	25.5	220.4	5.2	57	215.1
08-11-1999 13:05	1375500	15.92	41.4	26.9	190.8	5.6	52.9	187
08-12-1999 15:40	1471200	17.03	40.1	27.4	164.2	8.4	50.4	154.9
08-13-1999 11:50	1543800	17.87	37.2	27.2	161.4	6.5	53.8	147.2
08-15-1999 18:40	1741200	20.15	37.8	26	159.3	7.8	47	147.7
08-18-1999 13:40	1982400	22.94	36.3	23	158.9	5.6	45.2	138.7

**EPM Gravel(2) Concentrations
and Flow Rates**

191

Sample port	26B	27A	28A	Reservoir
x coordinate	2.025	2.025	2.225	
y coordinate	0.000	-0.200	0.000	
z coordinate	0.300	0.600	0.600	

Date	Time (seconds)	Time (days)	Concentration (ppb)			
07-26-1999 15:00	0					
07-26-1999 16:20	4800	0.06	0.3	0.3	0.3	0.3
07-26-1999 18:05	11100	0.13	0.3	0.3	0.3	0.5
07-26-1999 20:14	18840	0.22	0.3	0.3	0.3	0.4
07-26-1999 22:08	25680	0.30	0.3	0.3	0.3	0.5
07-26-1999 23:38	31080	0.36	0.4	1	1.4	0.5
07-27-1999 8:38	63480	0.73	0.3	0.4	0.9	0.4
07-27-1999 10:35	70500	0.82	5.7	2.9	1.4	1
07-27-1999 12:23	76980	0.89	206.5	11.8	1.7	1.2
07-27-1999 14:08	83280	0.96	277.4	173.8	6.2	1.5
07-27-1999 16:10	90600	1.05	166.6	372.4	14.6	2.4
07-27-1999 18:10	97800	1.13	120	309.4	9.3	5.6
07-27-1999 20:10	105000	1.22	106.8	164.3	147.4	3
07-27-1999 22:08	112080	1.30	89.8	122.2	520.7	8.7
07-27-1999 23:10	115800	1.34	87.4	105.6	694.4	10.2
07-28-1999 8:53	150780	1.75	74	71.1	425.5	47.1
07-28-1999 13:23	166980	1.93	72.4	64.8	344.4	59.3
07-28-1999 16:48	179280	2.07	60	60	349.5	65.1
07-29-1999 9:05	237900	2.75	51.6	47.7	254.4	55.6
07-29-1999 15:35	261300	3.02	47.5	44.7	256.5	45.5
07-30-1999 0:25	293100	3.39	48.5	45	252.7	40.5
07-30-1999 12:13	335580	3.88	45	44.8	221.1	34.7
07-31-1999 11:35	419700	4.86	41.4	37.5	194.1	27
08-01-1999 11:55	507300	5.87	50.2	36.8	173.1	24.6
08-03-1999 13:34	686040	7.94	32.3	30	173.1	19
08-03-1999 16:30	696600	8.06				
08-03-1999 19:38	707880	8.19	31.2	30.1	162.9	19.2
08-03-1999 21:55	716100	8.29	31.05	29.3	160	19.3
08-04-1999 8:52	755520	8.74	30.9	28.5	157.1	17.6
08-04-1999 16:08	781680	9.05	27	29.5	172.5	17.3
08-04-1999 23:38	808680	9.36	29.4	27.9	155.7	17.9
08-05-1999 9:08	842880	9.76	26.5	27.5	137.8	18.4
08-05-1999 16:08	868080	10.05	34.2	28.1	130.8	16.1
08-05-1999 23:53	895980	10.37	44.5	38.7	135.5	17.3
08-06-1999 9:43	931380	10.78	48	44.5	184.2	15.5
08-06-1999 16:08	954480	11.05	48.8	49.6	188.5	15.9
08-08-1999 11:24	1110240	12.85	43.9	49.6	212.4	22.2
08-09-1999 8:30	1186200	13.73	42.1	49.5	202.5	25.5
08-10-1999 14:48	1295280	14.99	43.8	48.4	207.1	26.3
08-11-1999 13:05	1375500	15.92	38	46.5	205	27.2
08-12-1999 15:40	1471200	17.03	33.6	42.8	173.7	24.7
08-13-1999 11:50	1543800	17.87	31.9	38.1	157.6	22.9
08-15-1999 18:40	1741200	20.15	31.9	25.2	156.1	21.6
08-18-1999 13:40	1982400	22.94	30	34.8	142.5	18.8

EPM Grave(2) Concentrations and Flow Rates

Sample port

x coordinate

y coordinate

z coordinate

Date	Time (seconds)	Time (days)	Flow rate (ml/min)	Boundary efflux (mg/day)	Cumulative mass loss (mg)
07-26-1999 15:00	0				
07-26-1999 16:20	4800	0.06	255.0	0.00	0.00
07-26-1999 18:05	11100	0.13	255.0	0.76	0.06
07-26-1999 20:14	18840	0.22	245.0	-0.10	0.05
07-26-1999 22:08	25680	0.30	245.0	0.44	0.08
07-26-1999 23:38	31080	0.36	250.0	0.17	0.09
07-27-1999 8:38	63480	0.73	232.5	0.09	0.13
07-27-1999 10:35	70500	0.82	230.0	1.93	0.28
07-27-1999 12:23	76980	0.89	235.0	0.99	0.36
07-27-1999 14:08	83280	0.96	235.0	1.40	0.46
07-27-1999 16:10	90600	1.05	240.0	3.09	0.72
07-27-1999 18:10	97800	1.13	240.0	10.14	1.57
07-27-1999 20:10	105000	1.22	235.0	-5.65	1.10
07-27-1999 22:08	112080	1.30	237.5	17.88	2.56
07-27-1999 23:10	115800	1.34	235.0	11.19	3.04
07-28-1999 8:53	150780	1.75	237.5	30.63	15.44
07-28-1999 13:23	166980	1.93	235.0	33.09	21.65
07-28-1999 16:48	179280	2.07	245.0	30.63	26.01
07-29-1999 9:05	237900	2.75	230.0	17.50	37.88
07-29-1999 15:35	261300	3.02	230.0	8.82	40.27
07-30-1999 0:25	293100	3.39	227.5	11.64	44.55
07-30-1999 12:13	335580	3.88	237.5	10.20	49.57
07-31-1999 11:35	419700	4.86	235.0	8.77	58.11
08-01-1999 11:55	507300	5.87	232.5	8.31	66.53
08-03-1999 13:34	686040	7.94	235.0	6.86	80.72
08-03-1999 16:30	696600	8.06	238.1 (average)		
08-03-1999 19:38	707880	8.19	127.5	3.58	81.62
08-03-1999 21:55	716100	8.29	130.0	3.66	81.97
08-04-1999 8:52	755520	8.74	125.0	2.43	83.08
08-04-1999 16:08	781680	9.05	125.0	2.88	83.95
08-04-1999 23:38	808680	9.36	125.0	3.57	85.07
08-05-1999 9:08	842880	9.76	120.0	3.51	86.46
08-05-1999 16:08	868080	10.05	122.5	1.27	86.83
08-05-1999 23:53	895980	10.37	122.5	3.82	88.06
08-06-1999 9:43	931380	10.78	120.0	1.91	88.84
08-06-1999 16:08	954480	11.05	122.5	3.13	89.68
08-08-1999 11:24	1110240	12.85	120.0	4.18	97.22
08-09-1999 8:30	1186200	13.73	120.0	5.10	101.70
08-10-1999 14:48	1295280	14.99	130.0	4.75	107.69
08-11-1999 13:05	1375500	15.92	125.0	4.98	112.31
08-12-1999 15:40	1471200	17.03	122.5	4.10	116.85
08-13-1999 11:50	1543800	17.87	125.0	3.74	119.99
08-15-1999 18:40	1741200	20.15	120.0	3.82	128.73
08-18-1999 13:40	1982400	22.94	115.0	3.36	138.12
			123.2 (average)		

EPM Sand(2) Heads

Manometer	UP	1A	2A	2B	3A	3B	4A	4B	5A	5B
x coordinate		0.270	0.235	0.235	0.675	0.675	1.115	1.115	1.125	1.125
y coordinate		0.600	0.000	0.000	0.600	0.600	0.000	0.000	0.300	0.300
z coordinate		0.450	0.600	0.300	0.600	0.300	0.600	0.300	0.600	0.300
Date	water level below 1 m datum									
08-25-1999 13:09	0.099	0	0.102	0.102	0.111	0.112	0.123	0.124	0.124	0.123
08-26-1999 8:18	0.099	0.101	0.102	0.102	0.112	0.112	0.123	0.123	0.124	0.124
08-27-1999 8:10	0.098	0	0.101	0.102	0.112	0.112	0.124	0.123	0.124	0.124
08-28-1999 8:46	0.098	0.102	0.101	0.102	0.112	0.112	0.123	0.123	0.123	0
08-29-1999 21:30	0.098	0.102	0.101	0.102	0.113	0.112	0.124	0.123	0.124	0.124
08-31-1999 15:03	0.098	0.102	0.101	0.102	0.112	0.112	0.124	0.124	0.123	0.124
09-01-1999 10:58	0.098	0.102	0.101	0.102	0.112	0.112	0.124	0.123	0.124	0.124
average hydraulic head	0.902	0.898	0.899	0.898	0.888	0.888	0.876	0.877	0.876	0.894
09-02-1999 16:50	0.098	0.1	0.1	0.101	0.105	0.106	0.112	0.112	0.113	0.112
09-09-1999 11:22	0.098	0.101	0.1	0.1	0.105	0.106	0.111	0.111	0.112	0.112
09-12-1999 12:17	0.098	0.1	0.1	0.101	0.105	0.106	0.111	0.111	0.112	0.112
09-20-1999 8:15	0.098	0.102	0.1	0.101	0.106	0.106	0.112	0.112	0.113	0.112
average hydraulic head	0.902	0.899	0.900	0.899	0.895	0.894	0.889	0.889	0.888	0.888
Manometer	6A	7A	7B	8A	9A	10A	11A	12A	DOWN	
x coordinate	1.325	1.325	1.325	1.725	1.725	2.125	0.040	2.260		
y coordinate	0.600	0.000	0.000	0.600	0.000	0.600	-0.625	-0.660		
z coordinate	0.450	0.600	0.300	0.450	0.450	0.450	0.450	0.450		
Date										
08-25-1999 13:09	0.126	0.125	0.127	0.136	0.136	0.145	0.1	0.149	0.15	
08-26-1999 8:18	0.127	0.127	0.127	0.135	0.136	0.145	0.1	0.148	0.15	
08-27-1999 8:10	0.126	0.126	0.127	0.136	0.137	0.145	0.1	0.149	0.15	
08-28-1999 8:46	0.126	0.127	0.127	0.136	0.137	0.145	0.1	0.148	0.15	
08-29-1999 21:30	0.127	0.127	0.127	0.136	0.137	0.145	0.1	0.148	0.15	
08-31-1999 15:03	0.126	0.127	0.127	0.135	0.136	0.145	0.1	0.148	0.15	
09-01-1999 10:58	0.127	0.127	0.127	0.135	0.136	0.145	0.1	0.148	0.15	
average hydraulic head	0.874	0.873	0.873	0.864	0.864	0.855	0.900	0.852	0.850	
09-02-1999 16:50	0.114	0.114	0.113	0.118	0.118	0.122	0.1	0.125	0.125	
09-09-1999 11:22	0.113	0.114	0.112	0.118	0.118	0.122	0.1	0.124	0.125	
09-12-1999 12:17	0.113	0.113	0.112	0.117	0.118	0.122	0.1	0.124	0.125	
09-20-1999 8:15	0.114	0.114	0.113	0.118	0.118	0.122	0.101	0.124	0.125	
average hydraulic head	0.887	0.886	0.888	0.882	0.882	0.878	0.900	0.876	0.875	

EPM Sand(2) Concentrations and Flow Rates

Sample port x coordinate y coordinate z coordinate	1A	1B	2A	3A	4A	6A	6B	7A	8A	8B	9A	10A	11A	12A	13A	13C
Time (seconds)	Time (days)	Concentration (ppb)	0	0.10	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0	1.1	1.2	1.3
08-25-1999 8:00	8280	0.242	0.242	0.242	0.242	0.242	0.242	0.242	0.242	0.242	0.242	0.242	0.242	0.242	0.242	0.242
08-25-1999 11:18	14940	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
08-25-1999 13:08	22800	0.300	0.300	0.300	0.300	0.300	0.300	0.300	0.300	0.300	0.300	0.300	0.300	0.300	0.300	0.300
08-25-1999 15:20	30840	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
08-25-1999 17:34	38840	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
08-25-1999 22:07	47220	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
08-26-1999 8:18	63980	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
08-26-1999 12:10	97800	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
08-26-1999 16:08	112080	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
08-26-1999 20:08	128480	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
08-27-1999 0:05	140700	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
08-27-1999 8:10	169800	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
08-27-1999 12:08	184080	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
08-27-1999 16:18	199080	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
08-27-1999 21:18	217080	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
08-28-1999 8:48	253360	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
08-28-1999 17:53	291180	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
08-29-1999 21:30	390600	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
08-30-1999 13:30	448200	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
08-31-1999 15:03	540180	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
09-01-1999 10:58	611880	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
09-02-1999 11:52	701520	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
09-02-1999 14:45	711900	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
09-02-1999 16:50	719400	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
09-02-1999 23:35	743700	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
09-03-1999 9:09	778140	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
09-03-1999 21:40	823200	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
09-04-1999 11:40	873600	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
09-04-1999 21:37	909420	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
09-05-1999 11:02	957720	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
09-05-1999 21:41	996060	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
09-06-1999 10:39	1042740	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
09-06-1999 21:41	1082460	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
09-07-1999 8:20	1120800	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
09-08-1999 8:21	1207260	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
09-08-1999 11:22	1304520	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
09-10-1999 13:33	1393760	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
09-12-1999 12:17	1567020	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
09-14-1999 11:32	1737120	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
09-16-1999 16:20	1927200	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250
09-20-1999 8:15	2243700	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250	0.250

**EPM Sand(2) Concentrations
and Flow Rates**

Sample port x coordinate y coordinate z coordinate	14A 1.225 0.600 0.600	15A 1.225 0.600 0.600	16A 1.225 0.600 0.600	17A 1.425 0.400 0.600	18A 1.425 0.000 0.750	18B 1.425 0.000 0.600	18C 1.425 0.000 0.450	18D 1.425 0.000 0.300	18E 1.425 0.000 0.150	18F 1.625 0.200 0.600	18G 1.625 0.200 0.300	20A 1.625 0.000 0.600	20B 1.625 0.000 0.300	21A 1.625 -0.200 0.600	22A 1.625 0.400 0.600	23A 1.625 0.000 0.600	24A 2.025 0.600 0.600
Date	Time (seconds)	Time (days)	Concentration (ppb)	0	0.10	0.17	0.24	0.3	0.36	0.43	0.5	0.57	0.64	0.71	0.78	0.85	0.92
08-25-1999 8:00	8280	0.10	0.9	0.5	0.6	0.3	0.3	0.3	0.3	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4
08-25-1999 11:16	14940	0.17	3	2.4	1.5	0.9	1.2	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
08-25-1999 13:09	22800	0.26	4.9	3.4	2.4	1.4	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
08-25-1999 15:20	30840	0.36	1.6	1.2	17.5	1	1.1	0.9	0.6	1	0.8	0.3	0.3	0.3	0.3	0.3	0.3
08-25-1999 17:34	47220	0.55	0.9	372.6	411.6	10.8	0.8	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
08-26-1999 8:18	83680	0.97	0.4	130.4	5688	7.5	1.6	0.6	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
08-26-1999 8:18	83680	0.97	0.4	130.4	5688	7.5	1.6	0.6	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
08-26-1999 12:10	87600	1.13	0.8	105.9	4684	0.3	1608	2.2	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
08-26-1999 16:08	112080	1.30	0.7	107.8	3688	0.5	1982	0.6	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
08-26-1999 20:08	128480	1.46	0.1	114.1	3524	0.4	1788	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
08-27-1999 0:05	140700	1.63	1.6	119	5064	0.7	1783	0.2	0	0	0	0	0	0	0	0	0
08-27-1999 8:10	169800	1.97	0.5	124.7	2363	0	1475	0	0	0	0	0	0	0	0	0	0
08-27-1999 12:08	184080	2.13	0	120.1	2206	0	1721	0	0	0	0	0	0	0	0	0	0
08-27-1999 16:18	199080	2.30	0.3	119.9	2000	0.2	1822	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
08-27-1999 21:18	217080	2.51	0.3	119.6	2033	0.2	1869	0.4	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
08-28-1999 8:48	258360	2.89	0	137	2067	0	1680	0	0	0	0	0	0	0	0	0	0
08-28-1999 17:53	291180	3.57	0.3	128.7	1666.5	0.4	1718.5	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
08-29-1999 21:30	390600	4.52	-0.2	116.1	1458.5	-0.1	1379.5	-0.1	-0.2	-0.2	-0.2	-0.2	-0.1	-0.1	-0.1	-0.1	-0.1
08-30-1999 13:30	448200	5.19	-0.3	107.2	1350	-0.3	1267.5	-0.3	-0.3	-0.3	-0.3	-0.3	-0.3	-0.3	-0.3	-0.3	-0.3
08-31-1999 15:03	540180	6.25	-0.2	96.3	1186	-0.2	1167	-0.2	0	0	0	0	-0.2	-0.2	-0.2	-0.2	-0.2
09-01-1999 10:58	611880	7.08	-0.5	89	1175	-0.4	1095	-0.1	-0.3	-0.3	-0.3	-0.3	-0.4	-0.4	-0.4	-0.4	-0.4
09-02-1999 11:52	701520	8.12	-0.2	95.6	1206.5	-0.2	991	-0.2	-0.1	-0.1	-0.1	-0.1	-0.2	-0.2	-0.2	-0.2	-0.2
09-02-1999 14:45	711900	8.24	0	97.2	1115	0	1014	0.2	0	0	0	0	0	0	0	0	0
09-02-1999 16:50	719400	8.33	0	92.4	1090.5	0	970.5	0.2	0	0	0	0	0	0	0	0	0
09-02-1999 23:35	743700	8.61	0	92.1	1175	0.2	1267	0.6	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0.2
09-03-1999 8:09	778140	9.01	0.1	92.1	1175	0.2	1267	0.6	0.1	0.1	0.1	0.1	0.2	0.2	0.2	0.2	0.2
09-03-1999 21:40	823200	9.53	0.6	118.3	1246	0.6	837.5	0.7	0.7	0.7	0.7	0.7	0.6	0.6	0.6	0.6	0.6
09-04-1999 11:40	873600	10.11	0.5	145.8	1510.5	0.5	877.5	0.5	0.4	0.4	0.4	0.4	0.6	0.6	0.6	0.6	0.6
09-04-1999 21:37	909420	10.53	0.6	152.9	1285.5	0.7	1012.5	0.7	0.8	0.8	0.8	0.8	1	1	1	1	1
09-05-1999 11:02	957720	11.08	0.5	154.3	1578.5	0.5	1513.5	0.6	0.5	0.5	0.5	0.5	0.6	0.6	0.6	0.6	0.6
09-05-1999 21:41	998060	11.53	0.7	146.4	1038	0.7	1492.5	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7	0.7
09-06-1999 10:39	1042740	12.07	0.2	149	1549.5	0.2	1602	0.4	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
09-06-1999 21:41	1082460	12.53	0.5	136.8	1603.5	0.5	1663.5	0.5	0.6	0.6	0.6	0.6	0.5	0.5	0.5	0.5	0.5
09-07-1999 8:20	1120800	12.97	1.7	141.4	1485.1	0.3	1523.2	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
09-08-1999 8:21	1207260	13.87	0	136.3	1418.2	0	1395.1	0	0	0	0	0	0	0	0	0	0
09-08-1999 11:22	1304520	15.10	0	125.7	1392.3	0	1428.7	0	0	0	0	0	0	0	0	0	0
09-10-1999 13:33	1398760	16.19	0	155.5	1471.75	-0.3	1477	-0.2	-0.3	-0.3	-0.3	-0.3	-0.3	-0.3	-0.3	-0.3	-0.3
09-12-1999 12:17	1567020	18.14	-0.3	98.1	1317.05	-0.3	1428.35	-0.2	-0.3	-0.3	-0.3	-0.3	-0.3	-0.3	-0.3	-0.3	-0.3
09-14-1999 11:32	1737120	20.11	0	84.2	1185.8	0	1150.45	0	0	0	0	0	0	0	0	0	0
09-16-1999 16:20	1827200	22.31	0	74.6	1172.15	0	1127	0	0	0	0	0	0	0	0	0	0
09-20-1999 8:15	2243700	25.97	0	72.1	1047.9	0	833.45	0	0	0	0	0	0	0	0	0	0

EPM Sand(2) Concentrations and Flow Rates

Sample port	25A	26A	26B	27A	28A	28B	27A	28A	Reservoir	Flow rate	Boundary	Cumulative
x coordinate	2.025	2.025	2.025	2.025	2.025	2.025	2.025	2.025		(ml/min)	efflux	mass loss
y coordinate	0.200	0.000	-0.200	0.000	0.000	0.000	0.600	0.000		(mg/day)	(mg)	
z coordinate	0.600	0.600	0.300	0.600	0.600	0.300	0.600	0.600				
Date	Time	Time	Time	Time	Time	Time	Time	Time	Time	Time	Time	Time
(seconds)	(days)	(days)	(days)	(days)	(days)	(days)	(days)	(days)	(days)	(days)	(days)	(days)
08-25-1999 9:00	0	0.10	0.5	1	0.5	0.5	0.5	0.8	1.8	200.0	0.00	0.00
08-25-1999 11:18	8280	0.17	0.3	0.3	0.3	0.3	0.3	0.3	0.7	180.0	-2.91	-0.22
08-25-1999 13:09	14940	0.26	0.3	0.3	0.3	0.3	0.3	0.3	0.6	190.0	-0.07	-0.23
08-25-1999 15:20	22800	0.36	1.2	1.6	1	1	1	1.8	0.6	190.0	0.16	-0.22
08-25-1999 17:34	30840	0.55	0.3	0.3	0.3	0.3	0.3	0.3	1.2	185.0	0.87	-0.03
08-25-1999 22:07	47220	0.97	0.3	0.6	0.3	0.3	0.3	0.6	0.7	187.5	-0.01	-0.04
08-26-1999 8:18	83880	1.13	0.2	0.6	0.3	0.3	0.3	0.8	0.1	190.0	-0.74	-0.16
08-26-1999 12:10	97800	1.30	0.3	0.7	0.4	0.4	0.5	1	0.3	190.0	0.33	-0.10
08-26-1999 16:08	112080	1.46	0.3	0.6	0.3	0.3	0.3	0.8	1.3	190.0	1.59	0.16
08-26-1999 20:06	128480	1.63	0.7	41.7	0.6	0.6	23.1	0.9	2.5	190.0	2.18	0.52
08-27-1999 0:05	140700	1.87	228.2	2243	1.8	225.9	81.5	61.5	0.2	183.3	-1.19	0.12
08-27-1999 8:10	168800	2.13	284.7	3060	1.3	253.8	1147.5	1.1	1.1	180.0	1.42	0.36
08-27-1999 12:08	184080	2.30	182.6	3050	0.4	245.4	3190	3.8	3.8	190.0	4.22	1.09
08-27-1999 16:18	199080	2.51	163.5	2793	0.4	216.8	3190	11.3	11.3	190.0	10.28	3.23
08-27-1999 21:18	217080	2.89	131.3	2040.5	0	158.8	3532.5	37.8	37.8	190.0	19.38	12.49
08-28-1999 8:48	253360	3.37	117	1484	0.4	144.7	2982	44.1	44.1	190.0	14.99	18.18
08-28-1999 17:53	281180	3.57	114.5	876.5	-0.1	117	1762	37.1	37.1	190.0	9.72	29.37
08-29-1999 21:30	390600	4.52	110.8	608	-0.3	114.1	1278	34.1	34.1	187.5	8.72	35.18
08-30-1999 13:30	448200	5.19	69.2	438.5	-0.3	108.7	1032.5	27.2	27.2	190.0	6.91	42.54
08-31-1999 15:03	540180	6.25	59.6	474.9	-0.2	98.1	871	25.1	25.1	190.0	6.58	48.00
09-01-1999 10:58	611880	7.08	58.75	445.5	0	98.9	675.9	21.6	21.6	187.5	5.62	53.83
09-02-1999 11:52	701520	8.12	58.75	445.5	0	98.9	675.9	21.6	21.6	180.0 (average)	2.86	54.44
09-02-1999 14:45	711900	8.24	58.75	445.5	0	98.9	675.9	21.6	21.6	95.0	2.35	55.10
09-02-1999 16:50	719400	8.33	58.75	445.5	0	98.9	675.9	21.6	21.6	92.5	4.09	56.73
09-02-1999 23:35	743700	8.61	57.9	416.1	0.2	101.7	673.8	22.8	22.8	95.0	1.15	57.33
09-03-1999 8:09	778140	9.01	56.1	359	0.7	98.3	646.5	18.9	18.9	97.5	4.20	59.78
09-03-1999 21:40	823200	9.53	50.7	438.5	0.5	90.1	517.5	22.4	22.4	105.0	2.02	60.62
09-04-1999 11:40	873900	10.11	50.7	438.5	0.5	90.1	517.5	22.4	22.4	101.5	3.75	62.71
09-04-1999 21:37	909420	10.53	52.4	435.5	70	84.8	606	20.7	20.7	102.5	1.70	63.47
09-05-1999 11:02	957720	11.08	50	430.5	1.4	88.2	638	22.6	22.6	98.5	3.28	65.23
09-05-1999 21:41	998060	11.53	52.7	456.5	0.8	88.3	718	20.2	20.2	97.5	2.57	66.41
09-06-1999 10:39	1042740	12.07	57.6	524.5	0.3	99.8	681.5	20.6	20.6	95.0	2.71	67.62
09-06-1999 21:41	1082460	12.53	72.3	542.5	0.6	125.5	681.5	20.6	20.6	95.0	3.18	70.80
09-07-1999 8:20	1120800	12.97	81.1	682.85	0.3	135.7	708.75	20.4	20.4	95.0	3.44	74.67
09-08-1999 8:21	1207260	13.97	85.8	660.45	0	151.7	858.1	23.4	23.4	95.0	4.69	78.78
09-08-1999 11:22	1304520	15.10	89.6	635.95	0	151.7	841.4	28.7	28.7	90.0	4.74	89.01
09-10-1999 13:33	1398780	16.19	87.5	511.7	0	150.5	741.3	33	33	92.5	3.64	96.18
09-12-1999 12:17	1567020	18.14	77.7	380.7	-0.3	127.7	682.5	28.2	28.2	95.0	3.63	104.16
09-14-1999 11:32	1737120	20.11	70	345.9	0	106.2	569.6	26.8	26.8	90.0	82.5	117.39
09-16-1999 16:20	1927200	22.31	61.9	318.1	0	93.7	525.2	26.3	26.3	85.9 (average)		
09-20-1999 8:15	2245700	25.87	47.2	300.7	0	70.4	537.4	26.3	26.3			

DF Grave(1) Concentrations and Flow Rates

Sample port x coordinate y coordinate z coordinate	1A	1B	2A	3A	4A	5A	6A	6B	7A	8A	9A
	0.242	0.242	0.284	0.425	0.456	0.675	0.675	0.675	0.675	0.894	1.052
	0.250	0.250	0.220	0.800	0.127	0.500	0.440	0.440	0.000	0.127	0.218
	0.720	0.540	0.720	0.720	0.480	0.720	0.675	0.480	0.480	0.480	0.720
Date	Time (seconds)	Time (days)	Concentration (ppb)	3A	4A	5A	6A	6B	7A	8A	9A
1-7-00 12:15 PM	0										
1-7-00 4:04 PM	13740	0.16	0.7	0.7	3.8	0.9	1.4	1.8	3.2	3.1	15.4
1-7-00 5:04 PM	17340	0.20	1.5	0.9	4.3	1.5	1.8	1.8	3.3	3.8	14.2
1-7-00 7:08 PM	24780	0.29	1.1	1.1	4.8	1.1	2	1.3	3.9	4.8	11.3
1-7-00 10:35 PM	37200	0.43	0.5	0.5	4.8	0.6	2	1.1	3.8	5.2	12
1-8-00 9:09 AM	75240	0.87	0.4	0.4	7	0.7	2.9	1.1	5.7	7	18.8
1-8-00 6:50 PM	110100	1.27	0.4	0.3	9.8	0.5	3	1.5	8.5	10.2	26.4
1-9-00 2:58 PM	182580	2.11	0.3	0.2	15.6	0.3	3.8	1.7	12.9	15.8	35
1-10-00 8:35 AM	248000	2.85	0.6	0.3	21.1	0.5	5	1.7	19.7	25.5	45.9
01-10-2000 12:15	259200	3.00									
1-10-00 2:38 PM	267780	3.10	0.4	0.6	29.8	0.3	9.3	4.7	26	29.1	65.4
1-10-00 3:45 PM	271800	3.15	0.7	0.2	34.9	0.1	52.6	4.7	29.4	31.7	101.5
1-10-00 5:04 PM	278540	3.20	0.1	0.2	39.2	0.6	39.1	13.4	35.4	36.5	129.6
1-10-00 6:50 PM	290100	3.36	1	0.3	59.8	0.9	26.8	15.9	53.6	50.4	126.1
1-10-00 11:50 PM	300900	3.48	0.5	0.4	64.7	1	21.3	13.4	57	70.3	132.1
1-11-00 9:20 AM	335100	3.88	1.3	0.4	57.8	1.2	18	8.1	54.7	68	126.3
1-11-00 3:00 PM	355500	4.11	0.4	0.4	57	0.8	17.7	8.4	58.1	68.4	118.2
1-12-00 9:08 AM	420680	4.87	0.3	0.3	57.3	1	18	8	62.2	72.2	116.6
1-13-00 8:50 AM	506100	5.86	0.5	0.2	54.5	1.1	16.8	7.6	66	72.3	125
1-14-00 11:00 AM	600300	6.95	0.9	0.4	54.6	0.4	16	7	65.6	76.8	124.7

DF Grave(1) Concentrations and Flow Rates

Sample port	10A	11A	12A	13A	13B	14A	15A	16A	17A	17B	18A
x coordinate	1.060	1.056	1.108	1.115	1.115	1.225	1.225	1.225	1.425	1.425	1.425
y coordinate	0.223	-0.220	0.250	0.000	0.000	0.600	0.200	0.000	0.400	0.400	0.000
z coordinate	0.720	0.720	0.600	0.675	0.460	0.720	0.720	0.720	0.720	0.540	0.720
Date	Time										
	(seconds)	(days)	Concentration (ppb)								
1-7-00 12:15 PM	0										
1-7-00 4:04 PM	19740	0.16	7.9	3.9	3.7	1	9.1	18.3	13.2	2.8	17.1
1-7-00 5:04 PM	17340	0.20	6.7	5.9	4.5	0.8	8.8	23.8	11.5	2	20.5
1-7-00 7:08 PM	24780	0.29	6.3	6.1	3.7	1	7.4	24.1	10	2	24.3
1-7-00 10:35 PM	37200	0.43	5.5	8.2	3.8	0.6	7	24.1	10.7	1.9	29
1-8-00 9:09 AM	75240	0.87	8.3	12.7	5.3	0.4	10.3	18.5	12.5	3.6	20.9
1-8-00 6:50 PM	110100	1.27	10.9	15	7.9	0.4	12.8	18.2	13.9	4.2	17.9
1-8-00 2:58 PM	182580	2.11	14.3	19.9	13.9	0.4	18	20.3	15.1	5.5	18.1
1-10-00 8:35 AM	246000	2.85	18.8	24.5	18.4	0.5	24.3	28.2	16.5	9.9	23.2
01-10-2000 12:15	259200	3.00									
1-10-00 2:38 PM	287780	3.10	29.5	35.1	22.6	0.7	29.7	25.1	24.6	10.3	21.1
1-10-00 3:45 PM	271800	3.15	29.9	56.9	24.8	0.7	39.8	33.4	35.8	13.3	29.6
1-10-00 5:04 PM	276540	3.20	57	146.4	27.2	0.8	61.7	48.5	56	48.7	48.3
1-10-00 8:50 PM	280100	3.36	67.4	154.7	34	0.7	82.6	45.1	75	45.1	43.2
1-10-00 11:50 PM	300900	3.48	68.1	167.2	50	1	78.5	47	66.9	49.1	36.6
1-11-00 9:20 AM	335100	3.88	62.6	150.6	54.1	0.4	65.7	43.8	53.7	30.8	40.2
1-11-00 3:00 PM	355500	4.11	55.6	141.2	54.1	0.8	63.6	40.2	47.4	28	36.9
1-12-00 9:06 AM	420660	4.87	57.7	125.8	61.3	1	68.4	39.9	46.2	26.7	37.3
1-13-00 8:50 AM	506100	5.86	57.6	80.7	65.1	0.7	64.9	41.1	44.5	27.4	38.5
1-14-00 11:00 AM	600300	6.95	58.9	66.2	70.1	0.6	63.8	40.5	40.3	24.9	41.4

DF Grave(1) Concentrations and Flow Rates

Sample port	Time													
	18B	19A	20A	21A	22A	22B	23A	23B	24A	25A	26A			
x coordinate	1.425	1.625	1.625	1.625	1.825	1.825	1.825	1.825	2.025	2.025	2.025			
y coordinate	0.000	0.200	0.000	-0.200	0.400	0.400	0.000	0.000	0.600	0.200	0.000			
z coordinate	0.540	0.720	0.720	0.720	0.720	0.540	0.720	0.540	0.720	0.720	0.720			
Date	Time (seconds)	Time (days)	Concentration (ppb)											
1-7-00 12:15 PM	0													
1-7-00 4:04 PM	13740	0.16	8	11.2	14	8.5	4.5	12.5	15.4	10.2	11.7	1.5	11.7	14.6
1-7-00 5:04 PM	17340	0.20	8.8	12.5	23.7	8.1	2.8	11.3	22.2	11.4	11.8	1.8	11.8	17.3
1-7-00 7:08 PM	24780	0.29	10.3	9.7	24.7	8.3	3.2	10.6	19.5	13.5	9	1.2	9	17
1-7-00 10:35 PM	37200	0.43	12.5	10.5	26.5	7.5	3.1	10.4	20.9	14.3	8	0.6	8	18.1
1-8-00 8:09 AM	75240	0.87	16	12.6	18.9	8.5	5.8	12.2	17	19.9	11.4	0.5	11.4	15.2
1-8-00 8:50 PM	110100	1.27	22.3	14.8	16.7	9.2	6.5	14	17.4	23	14.2	0.4	14.2	14.5
1-9-00 2:58 PM	182580	2.11	30.8	20.1	18.4	11.4	8.6	15.9	19.1	33.1	19.9	0.5	19.9	16.8
1-10-00 8:35 AM	246000	2.85	38.4	26.9	25.1	15.8	11.4	18	25.6	40.2	27.3	0.6	27.3	22.3
01-10-2000 12:15	259200	3.00												
1-10-00 2:38 PM	267780	3.10	47.5	30.2	24.3	19.8	14.6	21.5	25.3	45.8	29.6	0.7	29.6	22.1
1-10-00 3:45 PM	271800	3.15	98	36.6	32	22.7	20.2	30.6	29.7	67.3	31.9	1.1	31.9	23.8
1-10-00 5:04 PM	278540	3.20	121.6	50.6	46.7	27.4	37.2	54.4	46.1	126.2	44.9	0.9	44.9	37.5
1-10-00 8:50 PM	290100	3.36	119.3	63.5	44.4	44.2	61.8	77.1	43.8	121	70	2.2	70	38.9
1-10-00 11:50 PM	300900	3.48	122.8	67.2	39.6	41.7	57.4	62.6	50.1	133.1	66.6	1.7	66.6	45.2
1-11-00 8:20 AM	335100	3.88	117.4	64.3	43	41	44.2	46	44.7	112.7	66.6	1.5	66.6	39
1-11-00 3:00 PM	355500	4.11	120.5	64.5	44.5	39.7	40	47.6	43.9	114.5	69.5	2.4	69.5	39.8
1-12-00 8:06 AM	420660	4.87	121.6	66.1	44.5	41.3	42	43.9	46.1	115.7	63.4	1.1	63.4	39.3
1-13-00 8:50 AM	506100	5.86	114.5	64.4	43.2	42.2	39	43.7	42.5	112.8	63.2	1.1	63.2	39.2
1-14-00 11:00 AM	600300	6.85	113.7	64.6	48.3	43	36.2	37.7	46.4	110.6	63.9	1.2	63.9	39.5

DF Gravel(1) Concentrations and Flow Rates

Sample port	27A	28A	28B	Reservoir				
x coordinate	2.025	2.225	2.225					
y coordinate	-0.200	0.000	0.000					
z coordinate	0.720	0.720	0.540					
Date	Time (seconds)	Time (days)	Concentration (ppb)	Flow rate (ml/min)	Boundary efflux (mg/day)	Cumulative mass loss (mg)		
1-7-00 12:15 PM	0							
1-7-00 4:04 PM	13740	0.16	9	143.3	0.00	0.00		
1-7-00 5:04 PM	17340	0.20	9.2	140.0	3.43	0.14		
1-7-00 7:08 PM	24780	0.29	7	145.0	2.24	0.34		
1-7-00 10:35 PM	37200	0.43	6.5	145.0	0.50	0.41		
1-8-00 9:09 AM	75240	0.87	7	141.7	1.60	1.11		
1-8-00 6:50 PM	110100	1.27	9	145.0	1.50	1.72		
1-8-00 2:58 PM	182580	2.11	11	143.3	2.17	3.54		
1-10-00 8:35 AM	246000	2.85	14.3	145.0	3.10	5.81		
01-10-2000 12:15	259200	3.00		143.5 (average)				
1-10-00 2:38 PM	267780	3.10	17.4	66.0	1.72	6.25		
1-10-00 3:45 PM	271800	3.15	21.1	66.3	-0.56	6.22		
1-10-00 5:04 PM	276540	3.20	25.3	70.0	3.01	6.38		
1-10-00 8:50 PM	290100	3.36	44.3	64.0	4.88	7.15		
1-10-00 11:50 PM	300900	3.48	43.8	65.6	4.86	7.77		
1-11-00 8:20 AM	335100	3.88	39.7	68.3	2.78	8.87		
1-11-00 3:00 PM	355500	4.11	37.6	66.0	5.02	10.06		
1-12-00 8:06 AM	420660	4.87	40.3	70.0	3.94	13.03		
1-13-00 8:50 AM	506100	5.86	40	68.3	2.83	15.92		
1-14-00 11:00 AM	600300	6.95	38.7	70.5	4.01	20.29		
				67.5 (average)				

DF Sand(1) Concentrations and Flow Rates

Sample port x coordinate y coordinate z coordinate	Time												
	Time (seconds)		Concentration (ppb) x 10										
	1A	1B	2A	3A	4A	5A	6A	6B	7A	8A	9A		
	0.242	0.242	0.294	0.425	0.456	0.675	0.675	0.675	0.675	0.894	1.052		
	0.250	0.250	0.220	0.600	0.127	0.500	0.440	0.440	0.440	0.127	0.218		
	0.720	0.540	0.720	0.720	0.460	0.720	0.675	0.460	0.460	0.460	0.720		
Date	Time (days)												
01-24-2000 12:20	4800	0.06	4.0	13.0	14.0	11.0	257.0	10.0	24.0	72.0	36.0	466.0	192.0
01-24-2000 13:40	6600	0.08	7.0	4.0	5.0	4.0	255.0	5.0	56.0	169.0	33.0	585.0	224.0
01-24-2000 14:10	10500	0.12	2.0	4.0	2.0	3.0	221.0	4.0	70.0	218.0	33.0	529.0	262.0
01-24-2000 15:15	14100	0.16	4.0	2.0	2.0	7.0	205.0	2.0	86.0	288.0	24.0	468.0	328.0
01-24-2000 16:15	24000	0.28	0.0	0.0	2.0	1.0	190.0	3.0	61.0	272.0	21.0	328.0	551.0
01-24-2000 19:00	72420	0.84	2.0	2.0	2.0	2.0	382.0	2.0	76.0	129.0	58.0	203.0	1757.0
01-25-2000 8:27	114900	1.33	6.0	4.0	4.0	3.0	771.0	8.0	180.0	73.0	187.0	281.0	2095.0
01-25-2000 20:15	159180	1.84	3.0	3.0	4.0	3.0	1016.0	20.0	254.0	64.0	376.0	393.0	2168.0
01-26-2000 8:33	202320	2.34	3.0	5.0	2.0	3.0	1056.0	7.0	279.0	63.0	621.0	502.0	2135.0
01-26-2000 20:32	245040	2.84	1.0	0.0	2.0	3.0	999.0	5.0	297.0	74.0	763.0	643.0	2138.0
01-27-2000 8:24	341460	3.95	2.0	2.0	3.0	2.0	918.0	3.0	302.0	66.0	937.0	870.0	1920.0
01-28-2000 11:11	445740	5.16	2.0	2.0	3.0	2.0	855.0	7.0	276.0	84.0	1095.0	1052.0	1666.0
01-29-2000 16:09	589200	6.82	3.0	2.0	3.0	3.0	806.0	8.0	241.0	88.0	1170.0	1187.0	1540.0
01-31-2000 8:00	589380	6.82											
01-31-2000 8:03	589380	6.82											
01-31-2000 16:16	618960	7.16	2.0	3.0	4.0	4.0	807.0	6.0	249.0	99.0	1189.0	1350.0	1610.0
02-01-2000 8:37	677820	7.85	4.0	7.0	8.0	3.0	889.0	3.0	266.0	104.0	1194.0	1370.0	1633.0
02-01-2000 18:28	713280	8.26	4.0	4.0	3.0	3.0	925.0	2.0	295.0	117.0	1300.0	1430.0	1586.0
02-02-2000 8:25	763500	8.84	6.0	2.0	3.0	2.0	988.0	2.0	302.0	117.0	1195.0	1475.0	1539.0
02-02-2000 21:21	810060	9.38	3.0	2.0	2.0	5.0	957.0	4.0	329.0	119.0	1271.0	1447.0	1624.0
02-03-2000 13:05	866700	10.03	3.0	0.0	2.0	2.0	1110.0	1.0	393.0	132.0	1399.0	1644.0	1759.0
02-04-2000 8:41	937260	10.85	2.0	0.0	0.0	0.0	1067.0	0.0	485.0	141.0	1460.0	1662.0	1745.0
02-06-2000 20:45	1153500	13.35	3.0	0.0	2.0	0.0	1050.0	0.0	549.0	143.0	1497.0	1660.0	1765.0
02-08-2000 8:30	1282200	14.84	0.0	0.0	0.0	0.0	1105.0	0.0	594.0	161.0	1577.0	1878.0	1765.0
02-10-2000 9:58	1460280	16.90	2.0	4.0	3.0	2.0	1140.0	2.0	546.0	155.0	1618.0	1781.0	1589.0

DF Sand(1) Concentrations and Flow Rates

Sample port x coordinate y coordinate z coordinate	10A	11A	12A	13A	13B	14A	15A	16A	17A	17B	18A
	1.060	1.056	1.108	1.115	1.115	1.225	1.225	1.225	1.425	1.425	1.425
	0.223	-0.220	0.250	0.000	0.000	0.600	0.200	0.000	0.400	0.400	0.000
	0.720	0.720	0.600	0.675	0.460	0.720	0.720	0.720	0.720	0.540	0.720
Date	Time (seconds)										
01-24-2000 12:20	4800	88.0	11.0	17.0	102.0	10.0	8.0	6.0	0.0	1.0	1.0
01-24-2000 13:40	6600	13.0	7.0	30.0	160.0	9.0	4.0	3.0	3.0	3.0	1.0
01-24-2000 14:10	10500	26.0	3.0	25.0	182.0	6.0	4.0	2.0	3.0	2.0	1.0
01-24-2000 15:15	14100	4.0	2.0	31.0	305.0	3.0	3.0	4.0	2.0	2.0	2.0
01-24-2000 16:15	24000	1.0	2.0	29.0	319.0	2.0	1.0	2.0	1.0	0.0	0.0
01-24-2000 19:00	72420	3.0	5.0	19.0	293.0	4.0	2.0	51.0	2.0	2.0	2.0
01-25-2000 8:27	114900	15.0	4.0	40.0	270.0	5.0	8.0	195.0	3.0	3.0	4.0
01-25-2000 20:15	159180	16.0	4.0	68.0	228.0	4.0	3.0	354.0	5.0	7.0	3.0
01-26-2000 8:33	202320	40.0	3.0	131.0	215.0	4.0	5.0	444.0	19.0	4.0	3.0
01-27-2000 8:24	245040	6.0	6.0	263.0	290.0	2.0	4.0	555.0	3.0	1.0	3.0
01-28-2000 11:11	341460	17.0	3.0	493.0	424.0	5.0	2.0	664.0	10.0	2.0	3.0
01-29-2000 16:09	445740	17.0	11.0	606.0	616.0	11.0	7.0	654.0	16.0	2.0	2.0
01-31-2000 8:00	589200	14.0	4.0	616.0	820.0	17.0	3.0	668.0	5.0	4.0	4.0
01-31-2000 8:03	589380	16.0	4.0	570.0	924.0	10.0	4.0	505.0	5.0	4.0	4.0
01-31-2000 16:16	618960	5.0	3.0	586.0	1019.0	5.0	5.0	506.0	6.0	3.0	9.0
02-01-2000 8:37	677820	3.0	2.0	622.0	1023.0	3.0	3.0	539.0	2.0	2.0	4.0
02-01-2000 18:28	713280	3.0	2.0	669.0	1079.0	2.0	2.0	395.0	3.0	2.0	3.0
02-02-2000 8:25	763500	3.0	3.0	668.0	1071.0	3.0	3.0	587.0	4.0	8.0	4.0
02-02-2000 21:21	810060	3.0	1.0	713.0	1355.0	0.0	1.0	610.0	1.0	1.0	3.0
02-03-2000 13:05	866700	2.0	0.0	756.0	1325.0	0.0	0.0	617.0	0.0	0.0	2.0
02-04-2000 8:41	937260	1.0	0.0	868.0	1500.0	0.0	0.0	952.0	1.0	1.0	3.0
02-06-2000 20:45	1153500	2.0	0.0	892.0	1518.0	0.0	0.0	850.0	0.0	0.0	0.0
02-08-2000 8:30	1282200	2.0	0.0	845.0	1573.0	1.0	2.0	891.0	0.0	1.0	3.0
02-10-2000 9:58	1460280	3.0	0.0								

DF Sand(1) Concentrations and Flow Rates

Sample port x coordinate y coordinate z coordinate	18B	19A	20A	21A	22A	22B	23A	23B	24A	25A	26A			
	1.425	1.625	1.625	1.625	1.825	1.825	1.825	1.825	2.025	2.025	2.025			
	0.000	0.200	0.000	-0.200	0.400	0.400	0.000	0.000	0.600	0.200	0.000			
	0.540	0.720	0.720	0.720	0.720	0.540	0.720	0.540	0.720	0.720	0.720			
Date	Time (seconds)	Time (days)	Concentration (ppb) x 10	18B	19A	20A	21A	22A	22B	23A	23B	24A	25A	26A
01-24-2000 12:20	4800	0.06	2.0	2.0	8.0	5.0	10.0	4.0	2.0	2.0	4.0	2.0	5.0	2.0
01-24-2000 13:40	6600	0.08	2.0	2.0	6.0	2.0	1.0	9.0	9.0	1.0	2.0	5.0	2.0	2.0
01-24-2000 14:10	10500	0.12	2.0	2.0	4.0	3.0	3.0	2.0	3.0	2.0	3.0	2.0	3.0	1.0
01-24-2000 15:15	14100	0.16	1.0	2.0	2.0	1.0	1.0	2.0	2.0	1.0	2.0	1.0	2.0	1.0
01-24-2000 16:15	24000	0.28	4.0	5.0	5.0	1.0	2.0	1.0	2.0	1.0	2.0	1.0	2.0	1.0
01-24-2000 19:00	72420	0.84	807.0	5.0	5.0	2.0	2.0	2.0	3.0	7.0	688.0	6.0	3.0	4.0
01-25-2000 8:27	114900	1.33	1282.0	17.0	6.0	6.0	13.0	7.0	49.0	3.0	1013.0	5.0	6.0	5.0
01-25-2000 20:15	159180	1.84	1446.0	16.0	3.0	3.0	58.0	16.0	5.0	3.0	1077.0	6.0	4.0	4.0
01-26-2000 8:33	202320	2.34	1458.0	11.0	8.0	8.0	17.0	5.0	3.0	3.0	1081.0	12.0	3.0	3.0
01-26-2000 20:32	245040	2.84	1581.0	6.0	1.0	1.0	4.0	2.0	3.0	1.0	1114.0	4.0	2.0	1.0
01-27-2000 8:24	341460	3.95	1583.0	2.0	2.0	2.0	6.0	3.0	2.0	2.0	1110.0	10.0	5.0	2.0
01-28-2000 11:11	445740	5.16	1644.0	6.0	2.0	2.0	8.0	2.0	2.0	5.0	1270.0	24.0	7.0	2.0
01-29-2000 16:09	589200	6.82	1539.0	98.0	4.0	4.0	31.0	3.0	5.0	3.0	1242.0	15.0	3.0	3.0
01-31-2000 8:00	589380	7.16	1484.0	15.0	4.0	4.0	3.0	3.0	11.0	3.0	1235.0	8.0	20.0	7.0
01-31-2000 16:16	618960	7.85	1474.0	4.0	3.0	3.0	2.0	3.0	3.0	3.0	1280.0	2.0	3.0	3.0
02-01-2000 8:37	677820	8.26	1665.0	3.0	2.0	2.0	2.0	2.0	2.0	2.0	1274.0	2.0	2.0	2.0
02-01-2000 16:28	713280	8.84	1620.0	2.0	2.0	2.0	2.0	2.0	2.0	2.0	1315.0	2.0	3.0	3.0
02-02-2000 8:25	763500	9.38	1670.0	3.0	3.0	3.0	2.0	2.0	1.0	2.0	1416.0	2.0	2.0	2.0
02-02-2000 21:21	810060	9.38	1670.0	3.0	3.0	3.0	2.0	2.0	1.0	2.0	1416.0	2.0	2.0	2.0
02-03-2000 13:05	866700	10.03	1847.0	1.0	1.0	1.0	1.0	0.0	1.0	1.0	1576.0	0.0	1.0	1.0
02-04-2000 8:41	937260	10.85	1814.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1580.0	0.0	0.0	0.0
02-04-2000 20:45	1153500	13.35	2104.0	1.0	1.0	0.0	1.0	0.0	0.0	0.0	1875.0	0.0	0.0	0.0
02-06-2000 20:45	1282200	14.84	2099.0	2.0	2.0	0.0	0.0	0.0	0.0	0.0	1907.0	0.0	0.0	0.0
02-08-2000 8:30	1460280	16.90	2150.0	2.0	2.0	2.0	0.0	0.0	1.0	2.0	1925.0	0.0	1.0	1.0

DF Sand(1) Concentrations and Flow Rates

Sample port			Reservoir		
x coordinate	y coordinate	z coordinate	27A	28A	28B
2.025	-0.200	0.720	2.225	0.000	2.225
			0.720	0.720	0.540
Date	Time (seconds)	Time (days)	Concentration (ppb) x 10		
01-24-2000 12:20	0				
01-24-2000 13:40	4800	0.06	2.0	4.0	10
01-24-2000 14:10	6600	0.08	1.0	1.0	3
01-24-2000 15:15	10500	0.12	2.0	2.0	2
01-24-2000 16:15	14100	0.16	1.0	0.0	3
01-24-2000 19:00	24000	0.28	1.0	0.0	2
01-25-2000 8:27	72420	0.84	2.0	2.0	219
01-25-2000 20:15	114900	1.33	4.0	3.0	397
01-26-2000 8:33	159180	1.84	11.0	3.0	431
01-26-2000 20:32	202320	2.34	3.0	17.0	509
01-27-2000 8:24	245040	2.84	0.0	4.0	434
01-28-2000 11:11	341460	3.95	3.0	2.0	488
01-29-2000 16:09	445740	5.16	2.0	2.0	452
01-31-2000 8:00	589200	6.82	2.0	7.0	437
01-31-2000 8:03	589380	6.82			
01-31-2000 16:16	618960	7.16	4.0	4.0	504
02-01-2000 8:37	677820	7.85	3.0	2.0	510
02-01-2000 18:28	713280	8.26	2.0	2.0	477
02-02-2000 8:25	763500	8.84	3.0	2.0	466
02-02-2000 21:21	810060	9.38	2.0	5.0	594
02-03-2000 13:05	866700	10.03	0.0	1.0	664
02-04-2000 8:41	937260	10.85	0.0	0.0	698
02-06-2000 20:45	1163500	13.35	0.0	1.4	1029
02-08-2000 8:30	1282200	14.84	0.0	0.0	1018
02-10-2000 9:58	1460280	16.90	1.0	1.0	1040
			Flow rate (ml/min)		
			86.7	0.00	0.00
			85.0	0.04	0.00
			85.0	0.04	0.00
			86.7	0.04	0.00
			100.0	0.04	0.01
			100.0	2.02	1.14
			101.7	1.16	1.71
			103.0	3.01	3.25
			103.6	5.99	6.24
			103.8	-1.18	5.66
			104.3	3.06	9.07
			105.0	3.39	13.17
			105.0	3.27	18.59
			97.7 (average)		
			50.0	1.63	19.15
			49.2	0.79	19.69
			45.5	1.48	20.30
			44.5	1.48	21.16
			68.9	-0.07	21.12
			52.5	2.13	22.52
			50.0	2.12	24.25
			51.7	1.84	28.85
			50.0	1.70	31.39
			52.5	2.03	35.57
			51.5 (average)		

DF Gravel(2) Concentrations and Flow Rates

Sample port	1A	1B	2A	3A	4A	5A	6A	6B	7A	8A	9A
x coordinate	0.242	0.242	0.294	0.425	0.456	0.675	0.675	0.675	0.675	0.894	1.052
y coordinate	0.250	0.250	0.220	0.600	0.127	0.500	0.440	0.440	0.000	0.127	0.218
z coordinate	0.720	0.540	0.720	0.720	0.460	0.720	0.675	0.460	0.460	0.460	0.720
Date	Time (seconds)										
03-31-2000 13:15	0	0.07	0.4	0.4	0.5	31.3	4.9	16	15.4	51.1	56.9
03-31-2000 15:02	6420	0.12	0.3	0.5	0.5	31.7	7.8	18.2	29.4	84.4	77.6
03-31-2000 16:05	10200	0.16	0.2	1.2	0.5	44	13	21.8	27.4	46.7	113.1
03-31-2000 17:04	13740	0.28	0.4	0.6	0.9	66.5	16.6	27.3	51.3	52.9	145
03-31-2000 20:05	24600	0.77	0.3	0.9	0.7	86.4	15.5	27.2	74.4	81.7	170
04-01-2000 7:45	66600	1.18	0.5	0.7	1.6	95	13.5	22.9	82.5	107.2	163.1
04-01-2000 17:35	102000	2.13	0.4	0.6	3.5	87.3	12.5	19.8	100	114.8	137.6
04-02-2000 16:28	184380	3.01	0.6	0.1	0.9	82.3	11.4	18.7	95.5	107.3	120.8
04-03-2000 13:27	259920	4.41	0.8	0.6	0.5	69.5	9.2	14.8	85.4	94.5	104.1
04-04-2000 23:05	381000	5.80	0.4	0.3	0.9	61.7	6.8	11.6	78	80	95.5
04-06-2000 8:32	501420	7.11	0.3	0.2	0.5	54.6	5.5	11.5	67.5	74.6	88.9
04-07-2000 16:00	614700	9.33	0.4	0.2	0.1	51.8	4	11.8	59.2	68.1	80.6
04-09-2000 21:10	806100	9.35	0.5	0.6	0.8	63.4	7.5	22.4	74.9	91	114.3
04-09-2000 21:43	808080	9.81	0.6	0.5	0.6	85.6	7.5	26.2	104.9	114.5	125.3
04-10-2000 8:35	847200	10.28	0.3	0.3	1.3	94.2	7.8	26.8	108	119.4	134.7
04-10-2000 20:05	888600	10.91	0.6	0.3	1.3	95.4	8.1	25	108.8	129.9	128.9
04-11-2000 11:00	942300	11.84	0.6	0.4	0.9	90.8	8.5	23.5	103.6	120.4	120.7
04-12-2000 9:25	1023000	11.84	3.6	0.7	0.5	90	7.3	24	112.6	122.7	129.7
04-13-2000 9:10	1108500	12.83	5.3	0.3	1.4	85.9	8.2	24.1	100.4	115.2	123.4
04-14-2000 9:35	1196400	13.85	0.6	0.3	1.4	85.9	8.2	24.1	100.4	115.2	123.4
04-16-2000 12:57	1381320	15.99	0.5	0.3	0.5	81	5.7	17.4	95.2	103.2	115.2
04-18-2000 12:57	1554120	17.99	0.5	0.3	0.5	81	5.7	17.4	95.2	103.2	115.2
04-20-2000 9:15	1713600	19.83	0	0	0.5	76.8	5.5	17.4	90.7	108.1	104.9
04-22-2000 8:08	1882380	21.79	0.1	0	0.5	76.8	5.5	17.4	90.7	108.1	104.9
04-24-2000 8:15	2055600	23.79	0.3	0.3	0.7	72.8	4.9	15.6	80.7	97.4	99.7
04-27-2000 8:27	2315520	26.80	0	0.4	0.7	57.6	4.6	10.7	66	88.9	86
04-30-2000 16:25	2603400	30.13	0	0.2	0.7	52	4.3	10.1	56.7	79.1	81.2
05-03-2000 14:50	2856900	33.07	0.2	0.2	0.6	45.9	3.5	9.1	53.5	71.7	70.3
05-14-2000 17:00	3815100	44.16	1.2	0.5	0.7	42.6	3.4	7.9	51.1	62.1	60.2
05-25-2000 14:30	4756500	55.05	0.9	0.8	0.9	34	2.9	5.9	47.5	49.9	47

DF Gravel(2) Concentrations and Flow Rates

Sample port x coordinate y coordinate z coordinate	Time (seconds)	Time (days)	Concentration (ppt)	10A	11A	12A	13A	13B	14A	15A	16A	17A	17B	18A
	0													
	6420	0.07	51.5	12.8	19.6	32.8	0.5	26.1	7.1	46	19.8	9.1		
03-31-2000 13:15	10200	0.12	68.4	31.8	63.2	38.4	0.5	36	13.3	45.1	30.2	13		
03-31-2000 16:05	13740	0.16	85.6	42.4	90.1	52.2	0.6	45.3	22	40.8	40.7	22.6		
03-31-2000 17:04	24600	0.28	123.1	63	123.9	83.4	1.2	68.5	40.7	40.4	45.1	44.2		
03-31-2000 20:05	66600	0.77	137.4	76.7	127	91.4	1.3	80.1	62.8	42.6	45.1	62.4		
04-01-2000 7:45	102000	1.18	128.9	72.8	116.6	105.1	0.5	78.1	61.8	44.1	35.9	65.6		
04-01-2000 17:35	184380	2.13	122.2	59.8	103	106.4	0.6	74.6	58	37.9	31.6	65.7		
04-02-2000 16:28	259920	3.01	108.9	57.3	85.3	107.8	0.9	61.1	51.6	33.4	27.7	54.4		
04-03-2000 13:27	381000	4.41	90.1	45.4	67.1	101.8	1.5	55.6	50.3	30	23	53.9		
04-04-2000 23:05	501420	5.80	83.1	38.4	59.1	86.7	0.6	46.3	48.8	24	19.2	49.5		
04-06-2000 8:32	614700	7.11	77.3	34.5	32.2	81	0.8	42	42.7	22.8	17.1	50		
04-07-2000 16:00	806100	9.33	69.3	31.2	28.9	72.2	0.3	36.2	41.5	20.7	14.8	45.6		
04-09-2000 21:10	808080	9.35												
04-09-2000 21:43	847200	9.81	96	50.4	45	91.6	1.3	54.6	50.9	39.3	30.1	50.3		
04-10-2000 8:35	888600	10.28	103.1	56.1	44.2	120.3	2.7	53.2	49	42.3	32.7	46.3		
04-10-2000 20:05	942300	10.91	113.2	56.3	50.3	132.1	0.5	60.2	48.3	38.2	33.6	56.1		
04-11-2000 11:00	1023000	11.84	103.4	52.2	52.4	138.3	1.1	54.5	51.6	37	32	56.3		
04-12-2000 9:25	1108500	12.83	98.3	49.6	34.6	134.8	1.1	53	50.7	39	31.2	54		
04-13-2000 9:10	1196400	13.85	106.9	50.4	52.7	133.3	1.2	51.4	53.4	34.7	32.8	54.1		
04-14-2000 9:35	1381320	15.99	101.7	50.9	51.5	133.1	0.5	55.2	55.3	36.2	32.8	53.3		
04-16-2000 12:57	1554120	17.99	101.7	50.9	51.5	133.1	0.5	55.2	55.3	36.2	32.8	53.3		
04-20-2000 9:15	1713600	19.83	93.7	42.4	47	119.4	1	53	53.4	26.7	25.5	55.4		
04-22-2000 8:08	1882380	21.79	88.2	41	45.8	109.9	1	51.9	51.3	25.1	24.8	55.1		
04-24-2000 8:15	2055600	23.79	83.3	36.4	45.4	109.5	0.5	49.3	58.2	22.9	22.5	57.2		
04-27-2000 8:27	2315520	26.80	71	30.7	35.4	86.7	0.4	42.3	57.1	16	19.4	58.1		
04-30-2000 16:25	2603400	30.13	50.1	28.7	33.5	80.3	0.5	36.7	50.1	0.5	17	49.2		
05-03-2000 14:50	2856900	33.07	55.3	23.1	28	71.8	0.4	35.3	50.6	13.5	15.6	49.4		
05-14-2000 17:00	3815100	44.16	50.3	20.6	23.5	67.9	0.4	29.3	34.3	13.9	11.6	42		
05-25-2000 14:30	4756500	55.05	39.7	16	19.2	62.9	1.2	24.6	28.6	9.2	7.9	36		

DF Gravel(2) Concentrations and Flow Rates

Sample port												
x coordinate	18B	19A	20A	21A	22A	22B	23A	23B	24A	25A	26A	
y coordinate	1.425	1.625	1.625	1.625	1.825	1.825	1.825	1.825	2.025	2.025	2.025	
z coordinate	0.000	0.200	0.000	-0.200	0.400	0.400	0.000	0.000	0.600	0.200	0.000	
	0.540	0.720	0.720	0.720	0.720	0.540	0.720	0.540	0.720	0.720	0.720	
Date	Time (seconds)	Time (days)	Concentration (ppb)									
03-31-2000 13:15	6420	0.07	38.2	12.7	17.6	19.2	39.2	33.9	0.6	24.2	10.4	
03-31-2000 15:02	10200	0.12	46.7	16.2	23	28.9	40.8	51.4	0.4	32.9	12.1	
03-31-2000 16:05	13740	0.16	88	24.8	36.5	39.9	35.6	69.7	1.3	41.6	23.8	
03-31-2000 17:04	24600	0.28	123.7	48.2	51.5	40.9	51.4	70.7	0.8	58.5	42	
03-31-2000 20:05	66600	0.77	153.5	73.1	80.3	57.4	40.5	164.6	1.1	85.5	64.7	
04-01-2000 7:45	102000	1.18	168.3	63	81.9	38.5	38.3	176.8	1.5	71.4	65.6	
04-01-2000 17:35	184380	2.13	149.5	61.8	73.5	41.5	36.3	160.6	1.1	76.5	61.1	
04-02-2000 16:28	259920	3.01	137.3	50.6	63.5	38	31.4	145	1.4	59.9	61.1	
04-03-2000 13:27	381000	4.41	125.5	49.7	55.5	31.3	27.2	124.5	1.6	53.6	53.8	
04-04-2000 23:05	501420	5.80	102.2	43.5	51.2	26.7	22.8	108.1	1.3	48.6	52.9	
04-06-2000 8:32	614700	7.11	100.9	40.1	0.5	23.6	24.6	101.5	0	42.4	44.6	
04-07-2000 16:00	806100	9.33	91.4	34.9	42.7	22.6	18.8	86.2	0.5	41.7	44.4	
04-08-2000 21:10	808080	9.35										
04-09-2000 21:43	847200	9.81	129.6	39.4	58.1	42.8	32.5	123.2	1.5	53.9	51.3	
04-10-2000 8:35	887200	9.81	153.6	39.3	56.6	42.9	36.5	151.7	1.1	51.5	52.1	
04-10-2000 20:05	888600	10.28	159.8	41.2	60.6	46	34	153.3	0.5	57.7	56.7	
04-11-2000 11:00	942300	10.91	158.4	40.8	59.1	50.6	32.5	157.8	1	58.5	53.2	
04-12-2000 9:25	1023000	11.84	164.5	41.5	60.9	46.2	35	168.1	1	53.1	48.6	
04-13-2000 9:10	1108500	12.83	166.7	40.7	56.4	46.4	32	150.3	1.3	55.5	54.2	
04-14-2000 9:35	1196400	13.85	156.5	46.5	51.9	43.3	32.1	164.4	0.7	57	55	
04-16-2000 12:57	1381320	15.89	176.6	46.5	51.9	43.3	32.1	164.4	0.7	57	55	
04-18-2000 12:57	1554120	17.99	176.6	46.5	51.9	43.3	32.1	164.4	0.6	54	49.1	
04-20-2000 9:15	1713600	19.83	146.2	48.4	49.2	38.5	27.7	133.5	0.9	53.1	45.8	
04-22-2000 8:08	1882380	21.79	141.8	50.7	48.6	29.8	25.9	131.6	0.9	59.9	49.2	
04-24-2000 8:15	2055600	23.79	136.7	55	44.3	30.5	23.9	122.9	0.9	59.9	49.2	
04-27-2000 8:27	2315520	26.80	112.7	59.4	39.4	24.9	17.3	113.1	1	51.9	46.8	
04-30-2000 16:25	2603400	30.13	101.7	54.5	34.2	23.3	16.8	105.6	0.7	50.1	43.2	
05-03-2000 14:50	2856900	33.07	93.6	53.6	26.9	20.7	14.3	88.4	0.6	45.2	41.8	
05-14-2000 17:00	3815100	44.16	79.6	45.8	24.5	17	14.5	77.7	0.4	36	30.7	
05-25-2000 14:30	4756500	55.05	65.2	31	19.5	12.8	9.5	63.8	1.1	27.2	26.5	

DF Gravel(2) Concentrations and Flow Rates

[illegible]

Appendix E - Tailings Concentration Data

1) EPM Gravel(1)

2) EPM Sand(1)

3) EPM Gravel(2)

4) EPM Sand(2)

5) DF Gravel(1)

6) DF Sand(1)

7) DF Gravel(2)

EPM Sand(1)

	Mass of			Mass of		Dry Mass		Mass of		Mass of Meas.C		Actual	Dist. From
	Mass of	Sample	Vial +	Sample	Dish Mass	(g)	+Silica (g)	Vial	Silica (g)	Water (g)	Water in	Conc.	Outside
	Vial (g)	(g)	(g)	(g)	(g)	(g)	(g)	(g)	(g)	Sample (g)	onc. (ppb)	(ppb)	Edge (mm)
1A	6.5818	7.2267	0.6449	1.552	2.0726	0.5206	0.1243	2.1243	400.3	6841	36.825		
1B	6.5417	7.1365	0.5948	1.5602	2.0344	0.4742	0.1206	2.1206	370.2	6510	29.475		
1C	6.5349	7.1752	0.6403	1.5522	2.0698	0.5176	0.1227	2.1227	342.3	5922	22.125		
1D	6.5732	7.2076	0.6344	1.5626	2.08	0.5174	0.117	2.117	283.5	5130	14.775		
1E	6.5761	7.2212	0.6451	1.5581	2.0711	0.513	0.1321	2.1321	178.3	2878	5.425		
2A	6.5875	7.1533	0.5658	1.5521	2.0099	0.4578	0.108	2.108	514	10033	41.825		
2B	6.5358	7.062	0.5262	1.5781	1.9866	0.4085	0.1177	2.1177	488.6	8791	33.075		
2C	6.5799	7.0862	0.5063	1.554	1.9569	0.4029	0.1034	2.1034	360.4	7331	24.325		
2D	6.5875	7.0988	0.5113	1.5526	1.9675	0.4149	0.0964	2.0964	272.8	5933	15.575		
2E	6.5417	6.9977	0.456	1.5531	1.9236	0.3705	0.0855	2.0855	146.6	3576	5.325		
3A	11.1393	11.6991	0.5598	1.5584	11.5849	0.4456	0.1142	2.1142	361.3	6689	34.825		
3B	11.2775	11.6766	0.3991	1.5567	11.5943	0.3168	0.0823	2.0823	371	9387	27.475		
3C	11.234	11.7009	0.4669	1.5523	11.61	0.376	0.0909	2.0909	184.3	4239	20.125		
3D	11.1984	11.6599	0.4615	1.5457	11.5691	0.3707	0.0908	2.0908	112.3	2586	12.775		
3E	11.252	11.7875	0.5355	1.556	11.6824	0.4304	0.1051	2.1051	84.7	1696	5.425		
4A	11.214	11.6885	0.4745	1.5472	11.5923	0.3783	0.0962	2.0962	326.5	7114	36.825		
4B	11.1595	11.6132	0.4537	1.5539	11.5208	0.3613	0.0924	2.0924	317.7	7194	28.975		
4C	11.2291	11.6681	0.439	1.5641	11.5817	0.3526	0.0864	2.0864	240.8	5815	21.125		
4D	11.0592	11.4901	0.4309	1.5694	11.4121	0.3529	0.078	2.078	163.2	4348	13.275		
4E	10.7731	11.2481	0.475	1.565	11.1628	0.3897	0.0853	2.0853	88.4	2161	5.425		
										5709 average			

EPM Gravel(2)

	Mass of Vial (g)	Mass of Vial + Sample (g)	Mass of Sample (g)	Dry Mass +Silica (g) Vial	Mass of Silica (g)	Mass of Water (g)	Mass of Water in Sample (g)	Meas. Conc. (ppb)	Actual Conc. (ppb)	Dist. From Outside Edge (mm)
1A	11.0125	11.6105	0.598	11.4845	0.472	0.126	1.126	56.1	501	32.75
1B	10.9238	11.3425	0.4187	11.2563	0.3325	0.0862	1.0862	382.8	4824	25.375
1C	10.8551	11.2887	0.4336	11.1977	0.3426	0.091	1.091	395.7	4744	18
1D	10.8977	11.4268	0.5291	11.3182	0.4205	0.1086	1.1086	378.8	3867	10.625
1E	10.8904	11.3855	0.4951	11.2893	0.3989	0.0962	1.0962	275.9	3144	3.25
2A	10.9227	11.3851	0.4624	11.2958	0.3731	0.0893	1.0893	520.6	6350	37.75
2B	10.8253	11.2917	0.4664	11.2017	0.3764	0.09	1.09	428.7	5192	29.125
2C	10.8914	11.4104	0.519	11.311	0.4196	0.0994	1.0994	369.5	4087	20.5
2D	10.9664	11.5019	0.5355	11.3972	0.4308	0.1047	1.1047	250.5	2643	11.875
2E	10.9494	11.5246	0.5752	11.4106	0.4612	0.114	1.114	103.9	1015	3.25
3E	10.9084	11.4825	0.5741	11.3655	0.4571	0.117	1.117	662.8	6328	34.75
3D	10.7802	11.2749	0.4947	11.1726	0.3924	0.1023	1.1023	623.6	6719	26.875
3C	10.8918	11.3686	0.4768	11.27	0.3782	0.0986	1.0986	452.3	5040	19
3B	10.8164	11.3384	0.522	11.235	0.4186	0.1034	1.1034	391.7	4180	11.125
3A	10.9301	11.4385	0.5084	11.3405	0.4104	0.098	1.098	208.7	2338	3.25
4E	10.8421	11.3287	0.4866	11.2305	0.3884	0.0982	1.0982	759.2	8490	42.75
4D	11.0819	11.5701	0.4882	11.4705	0.3886	0.0996	1.0996	755	8335	32.875
4C	10.9077	11.4007	0.493	11.3006	0.3929	0.1001	1.1001	577.4	6346	23
4B	10.8713	11.3527	0.4814	11.2587	0.3874	0.094	1.094	459.2	5344	13.125
4A	10.8254	11.3235	0.4981	11.2274	0.402	0.0961	1.0961	270	3080	3.25
									4846 average	

DF Gravel(1)

I.D.	Mass of Test Tube + Wet Sample (g)	Mass of Test Tube + Dry Sample (g)	Mass of Test Tube + Sample + Dilutant (g)	Meas. Conc. (ppb)	Actual Conc. (ppb)	Dist. From Outside Edge (mm)
Initial Samples						
	11.2986	11.2003	15.8799	308.9	14705	
	11.908	11.6861	19.3905	403.5	14010	
	12.004	11.6595	18.2002	620.5	11781	
	11.6834	11.4543	18.7802	350.2	11198	
Final Samples						
1A	12.3613	12.0747	19.1979	39.5	9817	50.000
1B	12.4616	12.1379	17.0389	30.8	4663	37.500
1C	12.8007	12.3746	20.0042	14.1	2525	25.000
1D	13.0789	12.5991	19.8703	17.1	2591	12.500
1E	12.6102	12.2283	20.3251	17.2	3647	0.000
2A	12.2326	11.9435	17.4605	48.5	9255	50.000
2B	11.3805	11.2601	15.7758	15.4	5776	37.500
2C	12.7458	12.3587	20.2194	18.3	3716	25.000
2D	12.4978	12.1692	18.2606	13.8	2558	12.500
2E	12.194	11.9191	16.779	7.4	1308	0.000
3A	12.3467	12.0491	18.4676	35.4	7635	50.000
3B	12.1876	11.8999	19.1422	24.3	6117	37.500
3C	12.1857	11.9075	19.556	11.1	3052	25.000
3D	11.874	11.6413	17.9672	5.5	1495	12.500
3E	12.1847	11.8982	19.0589	7.2	1800	0.000
4A	12.5954	12.2079	18.1272	45.1	6889	50.000
4B	12.0632	11.8056	18.0919	18	4393	37.500
4C	12.4366	12.1183	18.665	12.4	2550	25.000
4D	12.065	11.8561	18.4546	8.4	2653	12.500
4E	11.6651	11.4803	18.6225	4	1546	0.000
					4199 average	

DF Sand(1)

215

	Mass of Test Tube + Wet Sample I.D. (g)	Mass of Test Tube + Dry Sample (g)	Mass of Test Tube + Sample + Dilutant (g)	Meas. Conc. (ppb)	Actual Conc. (ppb)	Dist. From Outside Edge (mm)
Final Samples						
1A	12.3613	12.0747	19.1979	39.5	9817	50.000
1B	12.4616	12.1379	17.0389	30.8	4663	37.500
1C	12.8007	12.3746	20.0042	14.1	2525	25.000
1D	13.0789	12.5991	19.8703	17.1	2591	12.500
1E	12.6102	12.2283	20.3251	17.2	3647	0.000
2A	12.2326	11.9435	17.4605	48.5	9255	50.000
2B	11.3805	11.2601	15.7758	15.4	5776	37.500
2C	12.7458	12.3587	20.2194	18.3	3716	25.000
2D	12.4978	12.1692	18.2606	13.8	2558	12.500
2E	12.194	11.9191	16.779	7.4	1308	0.000
3A	12.3467	12.0491	18.4676	35.4	7635	50.000
3B	12.1876	11.8999	19.1422	24.3	6117	37.500
3C	12.1857	11.9075	19.556	11.1	3052	25.000
3D	11.874	11.6413	17.9672	5.5	1495	12.500
3E	12.1847	11.8982	19.0589	7.2	1800	0.000
4A	12.5954	12.2079	18.1272	45.1	6889	50.000
4B	12.0632	11.8056	18.0919	18	4393	37.500
4C	12.4366	12.1183	18.665	12.4	2550	25.000
4D	12.065	11.8561	18.4546	8.4	2653	12.500
4E	11.6651	11.4803	18.6225	4	1546	0.000
					4199 average	

I.D.	Mass of Test Tube + Wet Sample (g)	Mass of Test Tube + Dry Sample (g)	Mass of Test Tube + Sample + Dilutant (g)	Meas. Conc. (ppb)	Actual Conc. (ppb)	Dist. From Outside Edge (mm)
Initial Samples						
A	13.5343	13.0584	22.0472	608.2	11488	
B	12.2857	11.9926	18.9544	409.7	9731	
C	12.5575	12.24	19.1677	470.5	10266	
Final Samples						
1A	14.2341	13.7208	21.6303	66.7	1028	50.000
1B	13.1955	12.7598	21.995	44.2	937	37.500
1C	13.2135	12.7261	20.9665	40.6	686	25.000
1D	13.3223	12.9093	22.5763	7.7	180	12.500
1E	12.5583	12.2919	21.7383	6	213	0.000
2A	14.2098	13.625	23.3088	69.1	1144	50.000
2B	13.4778	12.9731	24.4648	45.3	1031	37.500
2C	13.5489	13.0946	23.8038	40.5	955	25.000
2D	13.9331	13.3958	22.7379	50.4	876	12.500
2E	13.3607	12.9626	22.9907	14.8	373	0.000
3A	13.7132	13.2001	22.0866	86.3	1495	50.000
3B	12.9957	12.6096	22.7637	59.3	1560	37.500
3C	13.3047	12.868	23.1657	31.4	740	25.000
3D	12.8115	12.5018	22.2672	9.5	300	12.500
3E	13.2813	12.8815	23.29	4.8	125	0.000
4A	14.6621	13.8158	24.1282	73.9	900	50.000
4B	13.4519	12.9852	23.29	35.6	786	37.500
4C	13.0265	12.6782	23.3538	18	552	25.000
4D	14.5133	13.8741	23.6406	15.9	243	12.500
4E	13.6806	13.1957	23.6657	18	389	0.000
					726 average	

Appendix F - Selected Photos Showing Physical Model Construction

**Plate 1 Steel Containers.
DF model in foreground, EPM model in background**

Plate 2 Dumping sand into EPM model for 50 mm lift

Plate 3 Raking the upper 150 mm.
The white tube is protection for a sample port.

Plate 4 Compacting the lift

Plate 5 Sand placed halfway up welded wire mesh drum

Plate 6 2 cm of filter gravel placed in bottom of pit.

Plate 7 Overflow in constant head reservoir.

Plate 8 Saturation front across pit filled with mortar sand.

Plate 7 Ground silica, Uranine dye, and water being mixed together to form partially-saturated tailings

Plate 8 From top to bottom: EPM host rock, surround, tailings, and void space.

Plate 11 Extracting 0.5 ml purge volume
and 0.2 ml sample with syringe.

Plate 12 Cuvette containing sample.

Plate 13 Sample adaptor and fluorometer.

Plate 14 Indiana limestone slab with no hole

Plate 15 Grappling device for lifting slabs.

Plate 16 Spreading carbide grit on surface of slab.

Plate 17 Rubbing two surfaces together using a frame and a hydraulic jack (to left)

Plate 18 Scored surface at end of slab following grinding.

Plate 19 Coring 1/2 inch hole
in second slab from bottom.

Plate 20 Bottom slab in various states of saturation.

Plate 21 Open pit in DF model.

Plate 22 DF model after placement of surround and before placement of tailings.